MILITARY SPECIFICATION

RIVETS, BLIND, STRUCTURAL, 100° FLUSH HEAD,
NICKEL-COPPER ALLOY SLEEVE, MECHANICALLY LOCKED 15-7PH CRES SPINDLE
OVERSIZED DIAMETER (TYPE I, STYLE B, CLASS 2)

This amendment forms a part of MIL-R-7885/9B, dated 18 April 1988, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 3

Change the grip limits for the -02 and add a -04-01 grip Also delete the first two footnotes so the Table reads as follows:

TABLE II

Grip Limits		Nominal Sizes								
		4			5			6		
Min	Max	Dash No	L +.000 -.030	K Max	Dash No	L +.000 -.030	K Max	Dash No (a)	L +.000 -.030	K Max
045	062	-01	200	.450						
063	125	-02	238	450	-02	.266	.470	-02	265	480
126	187	-03	301	520	-03	309	530	-03	328	550
188	250	-04	.363	580	-04	.371	600	-04	390	.620
.251	312	-05	426	.650	-05	.434	660	-05	453	680
313	375	-06	488	710	-06	496	720	-06	515	740
376	437	-07	551	780	-07	559	790	-07	578	820
438	500	-08	613	840	-08	621	850	-08	.640	890
501	.562	-09	676	900	-09	684	910	-09	.703	.950
563	625				-10	.746	980	-10	765	1.010
626	.687				-11	809	1.040	-11	828	1.070
.688	750							-12	890	1 140

(a) Do not use part number M7885/9-6-02 below .073 sheet thickness (grip)

DISTRIBUTION STATEMENT A: Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-17T09:27Z
Check the source to verify that this is the current version before use.

Military Interests

Custodians
Army - AR
Navy - AS
Air Force - 99

Review Activities
Army - AV
Navy - MC
Air Force - 82

Preparing Activity
DLA - IS

(Project No 5320-0827)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.