MILITARY SPECIFICATIONS

SPARK PLUG, SHIELDED, AIRCRAFT RECIPROCATING ENGINE, MODEL T28/R1820A

This specification jas been approved by
the Bureau of Naval Weapons, Navy Department.

1. SCOPE

1.1 This specification covers the model T28/R1820A spark plug.

2. APPLICABLE DOCUMENTS

2.3 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-S-7886	Spark Plug, Shielded, Aircraft Reciprocating Engine, General Specification For

(Copies of specifications required by contractors in connection" with specif ic procurement functions should be obtained from the procuring activity or l s directed by the contracting officer).

3. REQUIREMENTS

3.1 Requirements. - The requirements of MIL-S-7886 apply. Design and construction shall be type I specified therein.

3.2 Engine-airframe-flight test. - The spark plugs shall be capable of operating satisfactorily without fouling or other evidence of electrical or mechanical failure for an operational period of 300 hours in the airframe-engine combinations listed herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:30Z
Check the source to verify that this is the current version before use.

Aircraft Model	Engine Models
T-28B/C	R1820-86

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions shall be in accordance with MIL-S-7886 and as specified herein.

4.2 Heat rating. - An acceptable quality level (AQL) of 1 percent for the hot limit (low IMEP rating) and an AQL of 2-1/2 percent for the cold limit (high IMEP rating) shall be applicable to production acceptance testing.

4.3 Engine-airframe flight test. - To demonstrate compliance with 3.2, at least one complete set of plugs for one engine shall be installed in an applicable engine-airframe combination and subjected to 300 hours of operation under typical service conditions. At the end of this period the plugs shall be removed and inspected for cracks, conductive deposits, excessive gap growth, and loss of plug integrity in any other manner. Any plug-caused malfunction of the engine may be considered cause for rejection. Qualified plugs may be retested at any time to assure continued compliance with 3.2. Failure to meet the 300 hours service requirement shal be cause for removal from the QPL

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-S-7886.

6. NOTES

6.1 Spark plugs covered by this specification. are intended for use with the airframe-engine combinations listed in 3.2.

6.2 Ordering data. - Ordering data shall be in accord-cc with MIL-S-7886 with acceptable quality levels as specified In 4.2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:30Z
Check the source to verify that this is the current version before use.