MIL-S-7886/6A(AS)
22 July 1985
SUPERSEDING
MIL-S-7886I/6(WEP)
18 October 1963

MILITARY SPECIFICATION SHEET

SPARK PLUG, SHIELDED AIRCRAFT RECIPROCATING ENGINE, MODEL R1820-82B/C

This specification sheet has been approved by the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the spark plug described herein shall consist of this document and the latest issue of MIL-S-7886.

1. SCOPE

1.1 Scope. This specification covers the model R1820-82B/C spark plug.

2. REQUIREMENTS

2.1 Requirements. Design and construction shall be Type I specified in MIL-S-7886.

2.2 Engine-airframe flight test. The spark plug shall be capable of operating satisfactorily without fouling or any other evidence of electrical or mechanical failure for an operational period of 300 hours in the airframe-engine combinations listed herein.

Aircraft Model	Engine Model
S-2	R1820-82
E-1	R1820-82
C-2	R1820-82

FSC 2925

DISTRIBUTION STATEMENT A.
APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED.

Source: https://assist.dla.mil -- Downloaded: 20261O-17T09:30Z
Check the source to verify that this is the current version before use.

3. QUALITY ASSURANCE PROVISIONS

3.1 Heat rating. An acceptable quality level (AQL) of 1 percent for the hot limit (low IMEP rating) and an AQL of 2-1/2 percent for the cold limit (high IMEP rating) shall be applicable to production acceptance testing.

3.2 Engine-airframe flight testing. To demonstrate compliance with 2.2, at least one complete set of plugs for one engine shall be installed in an applicable engine-airframe combination and subjected to 300 hours of operation under typical service conditions. At the end of this period, the plugs shall be removed and inspected for cracks, conductive deposits, excessive gap growth, and loss of plug integrity in any other manner. Any plug-caused malfunction of the engine may be considered cause for rejection. Qualified plugs may be requested at any time to assure continued compliance with MIL-S-7886. Failure to meet the 300 hours service requirement shall be cause for removal from the QPL.

4. NOTES

4.1 Intended use. Spark plugs covered by this specification are intended for use with the airframe-engine combinations listed in 2.2.

4.2 Ordering data. Ordering data shall be in accordance with MIL-S-7886 with acceptable quality levels as specified herein.

Preparing Activity:
Navy - AS
(Project No. 2925-N022)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:30Z
Check the source to verify that this is the current version before use.