MIL-N-60501C(MU)
AMENDMENT 3
15 February 1973
SUPERSEDING
AMENDMENT 2
15 March 1972

MILITARY SPECIFICATION

NIXIE POWER SUPPLY: 10540716

This amendment forms a part of Military Specification MIL-N-60501C(MU), dated 1 May 1970.

Paragraph 2.1: Add Military Specification "MIL-P-46843 - Printed Circuit Assemblies, Design and Production of".

Paragraph 3.3: Add "and MIL-P-46843".

Paragraph 3.3.1: Add after MIL-F-13926 "and MIL-P-46843".

* Paragraph 4.3.4: Delete paragraph and substitute.- "Certification- Certification shall include test data and results for the characteristics specified below. Certification shall be provided prior to performing final acceptance inspection, and remain in effect throughout the performance of the contract. This does not relieve the contractor from inspection throughout the contract production, including recording data and results therefrom. Recorded data and results shall be made available to the Government upon request. A new certification shall be required whenever any change(s) occur in materials, manufacturing processes and techniques previously certified. Exception to the above may be provided by certificate of compliance (COC) for those items for which the contractor cannot obtain recorded data, i.e., off the shelf items. This exception shall not apply without prior approval by Frankford Arsenal. Request for approval shall include item name, part number, identification of supplier, and justification for exception; and shall be forwarded to Commander, Frankford Arsenal, ATTN: SMUFA-Q4000.

CHARACTERISTIC	TEST DATA TO COMPLY WITH
Cleaning	3.3.1.8
Drying	3.3.1.9
Coating, Insulating Compound	3.3.1.10.2"

Paragraph 4.4.1, TABLE III, NO. 303: Under "Test Procedure" add "MIL-P-46843".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

* Paragraph 4.6.1.- Delete third sentence and substitute: "The vibration equipment shall be capable of providing the conditions of amplitude, frequency and duration specified in 3.4. The vibration test shall be performed in accordance with Figure 514-1, Curve C of MIL-STD-810, except double amplitude shall not exceed .036 inch."

Paragraph 4.6.2.- Delete second sentence and substitute the following:

"The tests shall be performed as specified in Procedure I of MIL-F-13926."

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for an inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A489

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.