MILITARY SPECIFICATION

PERISCOPE, TANK: XM48

1. SCOPE

1.1 This specification covers one type of unity-power infrared binocular periscope. This periscope consists of a separate head assembly and body assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel; Packaging of
MIL-H-60132	Head Assembly, Tank Periscope: 10513625
MIL-B-60135	Body Assembly, Tank Periscope: 10513599

STANDARDS

Military

MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army Munitions Command

F10516700	Periscope, Tank: XM48

PACKAGING DATA SHEET

MIL-P-14232/P10516700	Packaging of Periscope, Tank: XM48

(Copies of specifications, standards, drawings and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 6650

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Fabrication.- The periscope shall be manufactured in accordance with Drawing F10516700 and drawings pertaining thereto.

3.2 Head assembly.- The head assembly shall conform to MIL-H-60132.

3.3 Body assembly.- The body assembly shall conform to MIL-B-60135.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The quality assurance provisions of this specification and of other documents referenced herein form the basis for inspection to be performed by the supplier. Definitions of inspection terms not otherwise defined herein shall be as listed in MIL-STD-109.

4.2 Inspection provisions.

4.2.1 Examination and tests.- Examination and tests related to Section 3 herein shall be performed on a 100 percent basis. Examinations and tests for Packaging, Packing and Marking shall be in accordance with MIL-P-14232 and Section 5 herein. The Government reserves the right to inspect for any applicable requirement, and to reject individual non-conforming items.

4.2.2 Disposition of non-conforming product.- Disposition of rejected items supplied by the Government shall be as specified by the Contracting Officer (see 6.2(f). Disposition of rejected items not supplied by the Government shall be repaired or corrected and resubmitted for inspection with the approval of, and in the manner specified by, the Government Representative.

4.3.1 Fabrication.- The periscope shall be visually examined to determine conformance with 3.1.

4.3.2 Head assembly.- Each head assembly shall show evidence that it has met the requirements of MIL-H-60132 as specified in 3.2. The head assembly shall also be visually examined for defects and physical damage that may have resulted from handling or shipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.

4.3.3 Body assembly.- Each body assembly shall show evidence that it has met the requirements of MIL-B-60135 as specified in 3.3. The body assembly shall also be visually examined for defects and physical damage that may have resulted from handling or shipment.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P10516700. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The Tank Periscope XM48 is primarily intended for use as a tank driver's night viewing instrument in the XM551 Vehicle.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Applicable packaging data sheet number (see 5.1).
(c) Selection of applicable levels of preservation, packaging and packing.
(d) Whether reusable container is required.
(e) Applicable stock number.
(f) Disposition of rejected items (see 4.2.2).

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 6650-A145Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.