MILITARY SPECIFICATION

ROCKET, HE 66mm, ANTITANK
M72A2 W/COUPLER, LOADING, ASSEMBLING
AND PACKING

This amendment forms a part of Military Specification MIL-R-50431A(MI), dated 14 November 1974.

Page 3

3.5.1, delete the second sentence and substitute:

"The nozzle exit cone areas of the motor shall be free from all external and internal cracks and metallic discontinuities where examined by "eddy current" equipment."

3.5.3, line 3: Delete "4.4.2" and substitue "4.4.3".

Page 14

4.4.2.6, under Categories, Critical; delete and substitute:

"Critical 100% Inspection

1. Holes in lid or parts loose to the extent that the explosive charge may leak out or draw moisture ---------- Visual 06001"

Page 20

* 4.4.4.1, delete and substitute:

"4.4.4.1 Test to be performed. For all lots, a sample of fifty weapons shall be randomly selected and tested for compliance with the requirements of section 3. A listing of tests to be performed, the quantities allotted to each type of test and defects considered with each type of test are indicated in Table II. It is required that the 70°F

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

flight test and waterproof/penetration test be performed prior to the 140°F flight test. When the plus 70°F conditioned flight test is conducted using a thirty (30) round sample size, replacements shall be selected from the plus 140°F test sample only if less than 27 sample accuracy results are obtained. Every fifth (5th) lot, the 70°F conditioned flight test shall be conducted using a twenty (20) round sample size and ten (10) rounds used for the waterproof/penetration test. Replacement rounds taken from the 140°F flight test shall assure twenty (20) 70°F sample accuracy results and ten (10) penetration sample results. High temperature (140°F) tests shall be conducted using the balance of the samples available for that test. If a penetration test fails, continue penetration test sampling until two (2) consecutive lots satisfy the penetration requirements."

Page 21

* 4.4.4.3 delete last sentence of paragraph.

Page 22

* Table II, Quantity in Test above Waterproof Penetration Column: Delete "10" and substitute "**".

* Quantity in test above +70°F accuracy column: Delete "20" and substitute "30".

* Defect Code 17007, Waterproof Penetration Column: Delete "X*".

Defect Code 17013, Waterproof Penetration Column: Delete "X**" and substitute "X".

Page 24

4.5.1.4, delete the "Warning" note in its entirety.

Page 26

4.5.2, line 2 after "64.6 mils for the -40°F" (nonvented propellant)".

Add to "Temperature" column: "62.0 mils for the -40°F (vented propellant)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

*NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - MI

Review Activity:
Army - PA

Preparing Activity:
Army - MI

Project No. 1340-A502

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.