MIL-T-62246B(AT)
29 March 1988
SUPERSEDING
MIL-T-62246A(AT)
21 April 1981

MILITARY SPECIFICATION

TRUCKS, DUMP: STREET MAINTENANCE, DIESEL AND GASOLINE ENGINE DRIVEN, 21,000 POUNDS GVW, 4X2, COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear-wheel drive dump trucks equipped with a material sprayer, an auxiliary engine driven air compressor, and a vibrating roller for use in street maintenance. Vehicles shall have a minimum gross vehicle weight (GVW) of 21,000 pounds for normal operating conditions. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS), and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

* FEDERAL

W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
* ZZ-T-381	- Tires, Pneumantic, Vehicular (Highway).

MILITARY

MIL-B-46176	- Brake Fluid, Silicone, Automotive, All Weather, Operational and Preservative.

STANDARDS

FEDERAL

* FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

* MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.
MS51317	- Light, Warning, Vehicular, Rotating, D.C.
MS51335	- Pintle Assembly, Towing - 18,000 Lbs. Capacity, Manual Release.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Applications for copies of DoT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)
Safety and Health Regulations for Construction.

(Application for copies of OSHA publications should reference the Code of Federal Regulations, Title 29, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

(Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DoDISS shall be the issue of the non-Government document which is current on the date of the solicitation.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)
ASME Boiler and Pressure Vessel Code.

(Application for copies of ASME publications should be addressed to the American Society of Mechanical Engineers, 345 East Forty-Seventh Street, New York, NY 10017.)

TRUCK BODY AND EQUIPMENT ASSOCIATION, INC. (TBEA)
Hydraulic Hoist and Dump Body Classification Chart.

* (Sources for copies of TBEA publications are not known. Use alternate publications if copies of TBEA publications are not on hand.)

NATIONAL TRUCK EQUIPMENT ASSOCIATION (NTEA)
Conversion Hoist Chart.
Dump Body Hoist Chart.

(Application for copies of NTEA publications should be addressed to the National Truck Equipment Association, 25900 Greenfield Road, Suite 410, Oak Park, MI 48237.)

SAE, INC.
SAE Standards and Recommended Practices.

*	J318	- Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers-Trucks, Truck-Tractors, and Trailers (DoD adopted).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

*	J350	- Spark Arrester Test Procedure for Medium Size Engines (DoD adopted).
	J537	- Storage Batteries.
*	J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
	J560	- Seven Conductor Electrical Connector for Truck Trailer Jumper Cable.
	J588	- Turn Signal Lamps.
	J589	- Turn Signal Switch.
*	J682	- Rear Wheel Splash and Stone Throw Protection (DoD adopted).
*	J688	- Truck Ability Prediction Procedure (DoD adopted).
*	J704	- Openings for Six- and Eight-Bolt Truck Transmission Mounted Power Take-Offs.
*	J844	- Nonmetallic Air Brake System Tubing (DoD adopted).
*	J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Yearbook.

(Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.8, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

technical data. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of' the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of the invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2). When specified (see 6.2), concealed markings shall be furnished.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.3 Towing devices. Not less than two hooks, loops or pins, for towing the vehicle, shall be furnished on the front of the vehicle.

* 3.1.1.4 Wheel splash and stone throw protection. The vehicle shall have rigid splash shields ahead of the rear wheels and rubber mud flaps to the rear of the rear wheels. All tilt cabs shall have rubber mud flaps to the rear of the front wheels. A metal strip not less than 1/8 inch thick and not less than one inch wide, extending the entire width of the mud flap, shall be installed to prevent the bolt heads or bolt nuts from damaging the mud flap. All splash shield and mud flap installations, front and rear, shall conform to the rear wheel splash and stone throw protection provisions of SAE J682.

* 3.1.1.5 Trailer towing package. A trailer towing package consisting of a pintle, safety chain attachment devices, a lighting receptacle, and associated reinforcements and wiring shall be installed on the rear of the vehicle. The pintle shall be of the rotating type conforming to MS51335-1. The pintle shall be installed on the chassis frame with reinforcements to transfer a vertical tongue load of not less than 1,800 pounds and a horizontal drawbar load of not less than 18,000 pounds directly to the chassis rails. The rearmost portion of the pintle shall be forward,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

but not more than 4 inches forward, of the rearmost part of the vehicle. Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength at least equal to the GVW of the truck furnished. The attachment devices shall be capable of accommodating a standard grab hook (2-3/16 inches wide, 47/64 inch thick and 31/64-inch throat width) for a 3/8-inch chain. The lighting receptacle, conforming to SAE J560 with its conductors connected and color-coded as specified therein, shall be mounted in a readily accessible location near the pintle.

* 3.1.1.6 Drain plugs. Drain plugs installed in the manual transmission and in the rear axle shall be of the permanent magnet type.

* 3.1.1.7 Silicone brake fluid. When specified (see 6.2), and if available as the manufacturer's standard or optional brake fluid, brake fluid conforming to MIL-B-46176 shall be provided in the hydraulic brake system. A tag shall be placed near the master cylinder stating "CAUTION: USE SILICONE BRAKE FLUID ONLY, MIL-B-46176."

* 3.1.1.8 Hydraulic fluid identification plate. A corrosion resistant metal identification plate shall be installed near the dump system hydraulic fluid filler cap and shall identify the type of hydraulic fluid to be used.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with the EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to the EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis and cab, with all attachments, accessories and equipment; the body; and a full complement of fuel, lubricants and coolant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator weight (computed at 175 pounds), and a payload to provide not less than the specified GVW.

3.2.6 Weight distribution. The distribution of GVW for the purpose of establishing suspension, axle and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.2.7 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity. Minimum GVW rating shall be 21,000 pounds.

* 3.2.8 Overall width. The overall width of the vehicle, exclusive of mirrors, lights, reflectors and tires, shall be not more than 96 inches. The width over the tires shall be not more than 100 inches.

* 3.2.9 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.3 Performance.

3.3.1 Speeds. High and low speed requirements shall be met with the truck loaded to specified GVW.

3.3.1.1 High speed gradeability. The vehicle shall ascend a continuous grade of 1.5 percent at 50 miles per hour (mph). Gradeability requirements shall be met with the main transmission in direct drive, and when a multispeed axle is furnished with the axle in high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.3.1.2 Low speed. Low speed for vehicles with a manual transmission shall be calculated with the engine operating at not less than 35 percent of the recommended governed speed, and shall provide a vehicle speed of not more than 3 mph.

* 3.3.1.3 Maximum geared speed. Maximum geared speed at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3).}}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

* 3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than four cylinders. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349.

* 3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. Net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at an engine speed not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual.

3.4.1.3 Oil filter. A full flow type oil filter shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit the engine to the engine manufacturer's maximum recommended operating speed.

* 3.4.1.5 Cooling system. The cooling system shall maintain the engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level, or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F). The cooling system shall include a surge tank or a coolant recovery reservoir of not less than two-quart capacity. A high coolant level alarm buzzer and a red indicator warning light shall be provided on the instrument panel. On tilt cab models, a radiator servicing access door shall be provided to allow verification of the coolant level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

* 3.4.1.6 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters or complete thermostatic control of all coolant flow through the radiator.

* 3.4.1.7 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling.

3.4.1.8 Power plant heaters and fuel warmer. When specified (see 6.2), a coolant heater, an engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 110-volt alternating current (ac), and shall be wired through a junction block to a single three-pronged (male), weatherproof slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof, three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of the connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) A coolant heater, 1500-watt minimum rating, shall be installed in the engine block or lower coolant inlet hose. Engine thermostat with an operating range of 170°F to 195°F shall be installed
(b) An immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening
(c) A battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall include a thermostat to limit the temperature of the electrolyte to not more than 80°F
(d) For diesel engine driven vehicles, a fuel warmer or pre-heater shall be provided to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

* 3.4.2.1 Starting system (diesel engines). For diesel engine driven vehicles, a 12- or 24-volt direct current (dc) starting system, with a 12-volt dc lighting system, and not less than a 60 ampere alternator, shall be furnished. Engine starting equipment shall include an ether starting system or a glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

3.4.2.2 Ignition system (gasoline engines). For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished. An alternator of not less than 40-ampere rated capacity, and which provides not less than 16 amperes dc output at normal engine idle speed, shall be furnished.

* 3.4.2.3 Lighting. All vehicle lights, reflectors and wiring shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.19, 393.20 and 393.22 through 393.26(d). When available as the manufacturer's standard or optional feature, the brake lights shall override the four-way emergency flasher. Lights and reflectors shall not be mounted on vertical surface of rub rails or mounted on vehicle bumpers (unless recessed and fully protected).

3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. The vehicle shall be provided with double-faced front signal units and with single-faced rear signal units. Signal units shall be installed in accordance with SAE J588, except that turn signals shall not be mounted on the engine compartment hood. Turn signal operating units shall be of the self-cancelling type with a visible and audible type flash indicator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

3.4.2.5 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity ratings and the total cold cranking ratings at 0°F, both measured in accordance with SAE J537, shall be not less than specified in table I. The batteries shall be of the maintenance free type having the maintenance-free characteristics listed in W-B-131.

TABLE I. Batteries.

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel	320	1,200
Gasoline	100	450

* 3.4.2.6 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation, except the vibrating roller auxiliary engine (see 3.5.5.3), shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

* 3.4.3.1 Air cleaner. An air cleaner shall be furnished.

* 3.4.3.2 Fuel tanks. The fuel tank(s) shall be the manufacturer's standard for the vehicle specified with not less than 30 gallons total capacity. When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure an equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to the engine fuel intake shall be provided and means shall be provided to monitor the fuel level of either tank from a single fuel gage.

* 3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. If vertical exhaust mufflers are furnished, a heat shield shall be furnished. Vertical exhaust systems shall be provided with a hinged rain cap.

* 3.4.5 Transmission. Unless otherwise specified (see 3.4.5.2), a manually shifted transmission shall be provided. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. The manually shifted transmission shall have not less than five forward and one reverse speed with SAE J704 power takeoff openings on both right and left sides. The transmission shall provide for synchronized shift for at least the three highest forward speeds, or a constant mesh transmission may be provided. The transmission and axle gear ratios shall be selected to provide the performance specified in 3.3.1 through 3.3.1.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

3.4.5.1 Clutch. The clutch shall be the largest capacity clutch offered for the vehicle and engine furnished with the clutch torque capacity exceeding the maximum delivered engine torque.

* 3.4.5.2 Automatic or semiautomatic transmission. When specified (see 6.2), the vehicle shall be provided with an automatic or semiautomatic transmission. The transmission shall include a hydraulic torque converter and not less than four forward gear ratios. Normal driving range selector position shall provide not less than four gear ratios without movement of the selector. The transmission shall be provided with SAE J704 power takeoff openings. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.5.3 Power takeoff. A power takeoff shall be furnished. The power takeoff shall be of a rated capacity to operate powered equipment. Controls to operate the power takeoff shall be located in the truck cab accessible to the seated driver. A caution plate or decal reading "DO NOT OPERATE VEHICLE AT HIGHWAY SPEEDS WITH POWER TAKEOFF ENGAGED" shall be installed so as to be readily visible to the seated driver.

3.4.6 Driveline components. Driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction. The driveline shaft for front mounted winches, when specified in procurement documents, shall have an angle not greater than 16 degrees from the longitudinal plane.

3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the vehicle furnished. The vehicle shall have a frame with reinforcement extending at least from the rear of the front suspension, rear hanger bracket to the front of the rear spring, front hanger bracket. Reinforcement shall provide sufficient structural strength in the chassis frame through increased resisting bending moment to at least equal the load imposed, with the dump body loaded to provide specified GVW. A heavy duty frame with a resisting bending moment of not less than 600,000 inch-pounds may be furnished. Chassis frame rails shall not project beyond the rear end of the body.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to specified GVW. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic, double-acting shock absorbers at the front wheels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

* 3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to specified GVW. Vehicles provided with automatic or semiautomatic transmission shall be equipped with a single-speed axle. Unless a two-speed axle is furnished, a single reduction rear axle shall be provided. When specified (see 6.2), the wheel bearings and axle spindles shall be oil lubricated. The hubcaps shall have a window for visual determination of oil level. Provisions for venting or withstanding internal pressure buildup and for replenishing the oil supply shall be provided.

3.4.9.1 Two-speed axle. Unless an automatic or semiautomatic transmission is furnished, a two-speed axle shall be furnished, equipped with electric, vacuum or air shift and provided with ratios which will permit proper gear splitting. The gear ratios shall provide the performance specified in 3.3.1 through 3.3.1.3.

3.4.9.2 Traction control. When specified (see 6.2), the vehicle shall be furnished with a traction control on the rear axle. The traction control shall actuate automatically to ensure that power is transmitted to the wheel having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

* 3.4.10 Wheels, rims, tires and tubes. Unless wide base tires are specified, the vehicle shall be equipped with single front and dual rear wheels. Except as specified herein, rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Rim and disc wheel sizes shall be the same for all wheels on each vehicle. Tire size and load range (ply rating) shall be the same for all tires on each vehicle. When specified (see 6.2), wide base type tires and wheels for the front and rear axles shall be provided in lieu of conventional front and dual rear wheels and tires. Wide base wheels shall be interchangeable without the use of an adapter. When specified (see 6.2), disc type wheels shall be furnished.

* 3.4.10.1 Tires. Unless otherwise specified (see 6.2), tires shall be steel belted radial tube or tubeless type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to specified GVW. Tires shall conform to Tire and Rim Association recommendations, or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.4.10.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of heavy duty type, and shall be of the proper size for the tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

* 3.4.10.3 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare tire assembly is specified (see 3.4.10.4), a spare tire wheel or rim shall be furnished.

* 3.4.10.4 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished and shall be stowed securely on the vehicle for shipment. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design, and load range (ply rating) as the tires furnished on the vehicle.

* 3.4.11 Brakes. The brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.42 and 393.45 through 393.52. When available as the manufacturer's standard or as an option, brake linings shall be of nonasbestos material.

3.4.11.1 Power-hydraulic brakes. Unless otherwise specified (see 3.4.11.2), the vehicle shall be equipped with power assisted, hydraulically actuated, four-wheel service brakes.

* 3.4.11.1.1 Split hydraulic brake system. The power-hydraulic brake system shall be so arranged as to provide separate systems for at least two wheels and so designed and constructed that rupture or leakage type failure of any single pressure component of the service brake system, except structural failures of the brake master cylinder body, effectiveness indicator body, or other housing common to the divided system, will not result in complete loss of function of the vehicle brakes when force on the brake pedal is continued. “Pressure component” means any internal component of the brake master cylinder or master control unit, wheel brake cylinder, brake line, brake hose, or equivalent, except power assist components.

* 3.4.11.1.2 Indicator light. The split hydraulic brake system shall be equipped with an electrically operated red light mounted on the instrument panel to indicate system effectiveness. The light shall have an area of not less than 0.196 square inch. It shall illuminate before or upon application of the brakes when an actuating-pressure component of the system has sustained a loss of pressure. The indicator light system shall include a means for testing by the vehicle operator to assure that the light bulb is operable.

3.4.11.2 Air brakes. When specified (see 6.2), the vehicle shall be equipped with four-wheel, full air brakes. The braking system, complete with all necessary components, shall include:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

(a) Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7-1/4 cubic feet per minute (cfm)

* (b) Air storage reservoir(s), each tank equipped with drain, and with safety and check valves between the compressor and the last reservoir tank

(c) Foot control, suspended or treadle type

(d) Air control valves

(e) Air pressure gage, visible to the driver

(f) Low air pressure warning, visible and audible

(g) Service brake stop lamp switch

(h) Automatic moisture ejector

(i) Automatic slack adjusters.

* 3.4.11.2.1 Air dryer. A replaceable cartridge desiccant type air dryer shall be installed in the air brake system. The dryer shall have the capability of removing not less than 95 percent of the moisture in the air being dried. The dryer shall have a precooler and a filter to screen out oil and solid contaminants. The dryer shall have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

3.4.11.3 Trailer brake control system. When specified (see 6.2), in addition to the components specified in 3.4.11.2 and 3.4.11.2.1, a trailer brake control system shall be furnished. The trailer brake control system shall include:

(a) Identification of emergency and service lines

(b) Coincident control of trailer brakes with prime mover foot control

(c) Independent hand control for trailer brakes

(d) Prime mover protection valve with dash control and automatic breakaway feature

(e) Trailer stoplight control operable with foot brake and with hand control for trailer brakes

(f) Two SAE J844 coiled air hoses, not less than 110 inches long when fully extended, with SAE J318 gladhand couplers on both ends of hoses. The hoses shall be packaged and stowed in the vehicle tool compartment for shipment

(g) Air connectors for trailers with SAE J318 gladhand couplers mounted at the rear of the vehicle, located to prevent interference with trailer

(h) Dummy gladhand couplers with chains

(i) Prime mover only parking brake valve to permit prime mover parking brakes to be applied while charging the trailer air brake system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

* 3.4.11.4 Brake controls for use from a towing vehicle. When specified for vehicles with air brakes (see 6.2), the vehicle shall be furnished with a system for controlling the brakes from a towing vehicle (wrecker). The installation shall be complete with air brake couplers, relay emergency valve with no-bleed-back feature (except when spring applied emergency brake is furnished), additional air lines and fittings. The service and emergency couplers shall be mounted on the front in a protected position providing for ready attachment of air hoses from a towing vehicle. The service and emergency couplers shall be identified and provided with dummy gladhand couplers with chains. The system shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

* 3.4.12 Cab. Unless otherwise specified, the chassis manufacturer shall furnish any type of his standard or optional full width cab. When specified (see 6.2), a cab with a forward tilting hood and fender assembly, including tilting and locking mechanism, shall be furnished. When specified (see 6.2), a tilt cab with tilting and locking mechanism shall be furnished. Tilt cab features shall be in accordance with the Employee Safety and Health Standards of Federal Motor Carrier Safety Regulation 399, including the first step height which shall be not more than 24 inches. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, with at least the curbside door equipped with external, key-operated lock. Drip rails shall be installed above the cab doors. The cab shall have upholstered, full-width, adjustable seat and back or individual, adjustable driver's seat and individual passenger seat. When specified for vehicles with air brakes (see 6.2), the driver's seat shall be the manufacturer's standard air ride suspension type. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.1.1.1). White upholstery shall not be furnished. Interior lighting shall be provided. Two pairs of seat belts shall be installed. When specified for tilt cabs (see 6.2), vehicles with a height from the ground to the top of the windshield of more than 80 inches shall include provisions to facilitate cleaning the windshield. Provisions shall consist of a bumper step or bumper step cutouts and a grab handle located under the windshield.

3.4.13 Steering. Power steering shall be provided.

3.4.14 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be of the multispeed type and shall be operated by either air or electric motor(s).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

3.4.15 Bumper. Unless the bumper is an integral part of the vehicle cab, a channel type front bumper shall be provided.

* 3.4.16 Tool stowage. Stowage space of sufficient size to accommodate vehicle jack, hand tools, anti-skid chains, warning flares and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished in the cab. When stowage space for these tools is located outside the cab, it shall be weatherproof and shall provide for locking with a padlock.

* 3.4.16.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, a jack handle and a wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.17 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to the floor and to defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

3.4.18 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.4.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch
(b) Ammeter, charging indicator, or voltmeter
(c) Fuel gage
(d) Oil pressure gage or indicator
(e) Engine temperature gage or indicator
(f) Speedometer with recording odometer
(g) Ash receptacle

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

(h) Dual sunvisors
(i) Front door mounted armrest on driver's side
(j) Driver's compartment ventilator other than window
* (k) Tachometer.

3.4.20 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the cab. The mirrors shall be of the combination type having flat and convex areas enclosed in a common housing. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 20 square inches of reflective area. The mirrors shall have not less than two supporting arms.

3.4.21 Horn. The manufacturer's standard electric horn shall be furnished. When specified (see 6.2), in addition, an air operated horn shall be furnished on vehicles equipped with an air brake system.

* 3.4.22 Engine hour meter. An engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

* 3.4.23 Warning light. An amber, rotating, vehicular warning light conforming to MS51317-4 shall be provided. The rotating light shall be mounted with reinforcement at point of attachment on vehicle centerline for 360-degree visibility. The rotating light shall be operated by means of a separate switch with an indicator light located on the instrument panel and marked to indicate the function of the switch.

3.4.24 Back-up alarm. The vehicle shall be provided with an audible, pulsating signaling device (electrical or mechanical) to caution personnel when the vehicle is in reverse gear operation.

3.5 Body. The vehicle shall have a rear-of-cab to rear axle dimension of not less than 100 inches. The vehicle shall be equipped with a hydraulic hoist operated dump body. Maintenance equipment shall include a material sprayer with air compressor, and all accessories including other standard equipment generally furnished, and an asphalt patching vibrating roller.

3.5.1 Dump body. The dump body shall have a water level capacity of not less than 2 cubic yards (minus 5 percent). Inside length shall be not less than 96 inches. Inside width shall be not less than 78 inches. The front head and tailgate shall be not less than 6 inches higher than the sides.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

3.5.1.1 Body construction. Body floor, sides, and front head shall be not less than 10 gage (0.1345 inch) steel. The front head shall be capable of withstanding a horizontal static load equal to half the payload capacity of the vehicle without permanent deformation. When the body floor is constructed in two or more pieces, an automatic seam weld having full penetration without reinforcement is acceptable. When the seam is hand welded, the underside of the joint shall be reinforced with 3-inch wide, 8 gage (0.1644 inch) butt plates, welded between crossmembers. A full-length channel-formed rub rail of minimum width to cover the rear dual tire treads shall be provided. Not less than two triangular or box-section side braces per side, of not less than 12 gage (0.1046 inch) steel, shall be equally spaced between the body front head and the full box type rear corner posts, and welded to side plates. The front head sheet shall be formed or reinforced for rigidity. The body sides shall have pockets provided at each end for insertion of side boards. The interior of the body shell and side reinforcements shall be welded with continuous welds. The rub rail shall be attached using continuous welds, or with intermittent welds for not less than 50 percent of the edge length of contact edges. The body shall have sloping running boards and sloping horizontal tailgate braces to minimize the buildup of dirt.

3.5.1.2 Body location. The forward face of the body front head shall be located immediately to the rear of the material sprayer and air compressor unit (see 3.5.2), and shall be a minimum of 35 inches to the rear of the rear face of the cab.

3.5.1.3 Tailgate. The tailgate panel shall be not less than 10 gage (0.1345 inch) steel. The tailgate shall be double acting, opening from top or bottom. The tailgate shall have support chains and a tailgate latch operable by a control at the left front corner of the vehicle body. The tailgate shall be reinforced to prevent deformation under load.

3.5.1.4 Body understructure. Body longitudinal sills, each having a minimum section modulus equivalent to that provided by a 5-inch by 6.7 pounds per foot channel, shall be provided to support the hoist load. Not less than six crossmembers, each having a minimum section modulus equivalent to that provided by a 3-inch by 4.1 pounds per foot channel, shall be provided to support an evenly distributed load of not less than 10,000 pounds in the body. Crossmembers shall be welded to the body shell with not less than 4-inch lengths of weld, front and rear of both ends of each crossmember, and with staggered intermittent welds of not less than 4-inch lengths, on not more than 12-inch centers. Contact edges of crossmembers with longitudinal sills, and contact edges of welded reinforcements, shall be welded for not less than 50 percent of the edge length.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

* 3.5.1.5 Hydraulic hoist. A double acting hydraulic hoist shall be furnished. The hoist shall be the manufacturer's standard with a minimum lifting capacity rating of class 20 in accordance with the TBEA Hydraulic Hoist and Dump Body Classification Chart or the National Truck Equipment Association Dump Body Hoist Chart. The hoist shall lift the body to a minimum dumping angle of 50 degrees from the top of the truck chassis frame. Power takeoff, pump and valve shall be the manufacturer's standard for the hoist model furnished. Controls and levers shall be located in the cab within easy reach of the operator. In compliance with OSHA Regulation 1926.601(11), title 29, controls for operating hoisting and dumping activities shall be equipped with a latch or other device which will prevent accidental starting or tripping of the mechanism.

3.5.1.6 Safety lock. A mechanical safety lock permanently affixed to the dump body shall be furnished. The safety lock shall provide positive retention of the dump body with the body in the up position for servicing or repair. The safety lock shall not interfere with operation of the body under any operating condition.

3.5.2 Material sprayer and air compressor. An Essick Model TMU 292H or equal material sprayer and air compressor shall be mounted on the truck chassis between the cab and the dump body. The unit shall be located for ready access to and use of filler openings, valves, drain plugs, cleanout ports, and air and material connections.

3.5.2.1 Material tank. A material tank of not less than 200 gallons capacity and constructed to ASME standards for a 125 pounds per square inch (psi) working pressure shall be provided. The tank shall have a filler cap covering a fill opening of not less than 3-3/4 inches in diameter. The cap assembly shall be constructed to provide for the release of air from the material tank before the cap is completely open. Primary means for releasing pressure within the tank shall be by an air exhaust valve located near the filler cap. The valve shall be threaded into the tank with pipe threads not less than 1 inch in size. A warning decal instructing the operator to release all air through the valve before opening the filler cap shall be provided. Drain plugs, not less than 2 inches in diameter, shall be provided and located to completely drain the tank. A 1-1/2 inch fluid filter with a quick cleanout port, mesh screen, and fluid shut-off cock shall be installed. A spare screen shall be provided.

* 3.5.2.2 Air compressor. A Quincy Model 390 or equal air compressor shall be mounted on a base welded to the top of the material tank. The compressor shall have not less than 2 cylinders, a displacement of not less than 92 cfm at 870 revolutions per minute (rpm), pressure type

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

lubrication and shall include an air cleaner. An adjustable, continuous-running type compressor unloader shall be provided.

* 3.5.2.3 Auxiliary engine. An engine to drive the compressor shall be mounted on the base welded to the top of the material tank. When a diesel engine driven truck chassis is provided, the compressor engine shall be a Lister Model TS2 or equal diesel engine with a rating of not less than 35 horsepower. When a gasoline engine driven truck chassis is furnished, the compressor engine shall be a Wisconsin Model VG4D or equal gasoline engine with a rating of not less than 32 horsepower. Both type engines shall have not less than 2 cylinders, a 12-volt dc electric starter connected by a one-piece cable to the truck battery, and an air operated slow-down device to idle the engine when the air compressor is unloaded. Drive belts and pulleys shall be provided with safety guards.

3.5.2.4 Air receiver. An air receiver shall be connected between the compressor and the material tank. The receiver shall be bolted to the truck frame and shall be constructed to ASME standards for a 150 psi working pressure. A safety valve, air pressure gage, air regulating valve, check valve, drain valve, 1/4-inch air cock, 3/4-inch globe valve, and a Dixon quick coupling or equal shall be provided.

3.5.2.5 Spray gun. An Essick Model EG-3000 six-foot, dual control, air atomized or straight pressure emulsion spray gun, or equal, shall be provided. Three spray tips of assorted sizes shall be provided. Two material hoses, each with not less than 3/4 inch inside diameter (id), one not less than 25 feet in length and the other not less than 10-1/2 feet in length shall be provided. Two air hoses, each with not less than 3/8 inch id, one not less than 25 feet in length and the other not less than 11-1/2 feet in length, shall be provided. Fittings for interconnecting the spray gun, hoses, air receiver and material tank to provide dual spray operations shall be attached. Means for securely storing the spray gun and hoses on the exterior of the vehicle shall be provided.

3.5.2.6 Heater. A liquified petroleum gas (LPG) heater with controls for venting the tank during the heating cycle shall be provided. An open-faced storage box to accommodate two 11-kilogram LPG cylinders, each 12 inches in diameter and 24 inches in height, shall be provided. Devices to hold the cylinders securely in place during vehicle transit, but which permit ready removal of the cylinders for filling and testing, shall be provided. A flexible LPG hose with standard fittings shall be provided between the heater and the storage box. Final fittings compatible with the metric fittings on the LPG cylinders are not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

3.5.3 Water tank. A water tank of not less than 60 gallon capacity shall be installed on the side of the truck frame. The tank shall be pressurized from the air receiver and shall be constructed to ASME standards for a pressure of 150 psi. A 1/4-inch air regulator, pressure gage, safety valve, check valve, 2-inch filler cap and 3/4-inch garden hose threaded outlet shall be provided.

3.5.4 Solvent tank. A solvent tank of not less than 5 gallons capacity shall be installed on the side of the truck frame. The tank shall be pressurized from the air receiver and shall be complete with all fittings required for cleaning out the material hoses.

3.5.5 Vibrating roller. An Essick Model V30W2 or equal vibrating roller, suitable for being carried on the rear tailgate of the dump body, shall be furnished and stowed for shipment.

3.5.5.1 Performance. The vibrating frequency shall be not less than 4,500 vibrations per minute with a peak amplitude of not less than 0.046 inch. Centrifugal force developed shall be not less than 2,640 pounds. Maximum ground pressure on roll with vibration shall be not less than 3,640 pounds with a total applied force of not less than 144 tons per second. Speed range shall be 0 to 220 feet per minute.

3.5.5.2 Roll. The roll shall be not less than 22-1/2 inches in diameter by 30 inches wide.

3.5.5.3 Engine. When a diesel engine driven truck chassis is provided, the roller engine shall be a Lister Model LTl or equal diesel with a rating of not less than 8.8 horsepower. When a gasoline engine driven chassis is provided, the roller engine shall be a Wisconsin Rubbin Model W1390 or equa1 with a rating of not less than 11 horsepower. On both, a muffler and air cleaner shall be furnished. The engine shall be in an enclosed compartment with hinged doors. The engine need not be radio interference suppressed.

* 3.5.5.4 Transmission. A hydrostatic transmission providing forward and reverse speeds as specified in 3.5.5.1 shall be furnished.

3.5.5.5 Construction. A gravity sprinkler system with a 9-gallon capacity tank and full width coco mat shall be furnished. Adjustable roll scrapers, front and rear, shall be provided. Stabilizing rolls, front and rear, shall be provided. Independent controls for driving and vibrating shall be provided on the handle of the roller. Brakes with controls on the operating handle shall be furnished. A fuel tank of not less than 1-gallon capacity shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

* 3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle and its mounted equipment for operational use including at least the following: alinement of lights; adjustment of the engine, electrical and brake systems; filling and charging of the battery; alinement of the front wheels; inflation of all tires; complete lubrication of the chassis, engine, and running gear, with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of the cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the specification shall not relieve the contractor of the responsibility for assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and distribution of the curb weight on the front and rear axles. The total imposed loading on front and rear axles will be computed by the contractor and verified by the Government, using the curb weight, the operator weight of 175 pounds, and the payload required to provide the specified GVW. The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle, and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle shall be examined and road tested (less payload) by the contractor. The road test shall be for not less than 10 miles at speeds up to 50 mph.

* 4.3.3 Truck body treatment and painting. The certification regarding the body cleaning, treating, prime painting and salt spray resistance testing, as required by MIL-STD-1223, shall be made to the Government representatives at the first production vehicle inspection.

* 4.3.4 Equipment operation. All equipment on the body shall be functionally tested less material in the material sprayer, to determine conformance to requirements specified herein.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

4.4 Inspection of production vehicles. The contractor's inspection system shall as a minimum assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PREPARATION FOR DELIVERY

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general nontactical use by the Government in the performance of the street maintenance tasks indicated.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Identification of appropriate service for painting and marking (see 3.1.1.1).
(c) Concealed markings, if required (see 3.1.1.1).
(d) Rustproofing, if required (see 3.1.1.2).
(e) Tropical rustproofing, if required (see 3.1.1.2).
(f) Silicone brake fluid, if required (see 3.1.1.7).
(g) Gasoline engine, if required (see 3.4.1.2).
(h) Power plant heaters and a fuel warmer, if required (see 3.4.1.8).
(i) If a battery heater is not required with power plant heaters (see 3.4.1.8).
(j) Special transmission requirements (see 3.4.5.1).
(k) Automatic or semiautomatic transmission, if required (see 3.4.5.2).
(l) Oil lubricated wheel bearings and axle spindles, if required (see 3.4.9).
(m) Traction control, if required (see 3.4.9.2).
(n) Wide base front and rear tires and wheels, if required (see 3.4.10).
(o) Disc type wheels, if required (see 3.4.10).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

(p) Other type tires, if required (see 3.4.10.1).
(q) Spare wheel or rim, if required (see 3.4.10.3).
(r) Spare tire assembly, if required (see 3.4.10.4).
(s) Air brakes, if required (see 3.4.11.2).
(t) Trailer brake control system, if required (see 3.4.11.3).
(u) Brake controls for use from a towing vehicle, if required (see 3.4.11.4).
(v) Tilting hood and fender assembly, if required (see 3.4.12).
(w) Tilt cab, if required (see 3.4.12).
(x) Air ride driver's seat, if required (see 3.4.12).
(y) Tilt cab windshield cleaning step and grab handle, if required (see 3.4.12).
(z) Tools, if required (see 3.4.16.1).
(aa) Air operated horn, in addition, if required (see 3.4.21).

6.3 Performance prediction. SAE Truck Ability Prediction Procedure computations and computations for low speed and maximum geared speed will be required by the contract. The SAE Work Sheet Item 1 should include vehicle model number, engine model number, and vehicle type. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still dry air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Table:

Table 1 - Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2 - Altitude Factor. 1.00
Table 3 - Rolling Factor. 1.613
Table 4 - Area Factor. 0.173
Table 5 - Velocity Factor. 250.0
Table 6 - Altitude Factor. 1.00
Table 7 - Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest l00 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.
Table 8 - Grade Factor. 0.75
Table 8A - Correction Factor. Not required
Table 9 - Road Factor. 0.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.

* 6.4 Subject term (key word) listing.

Air compressor
Auxiliary engine
Dump body
Material sprayer
Truck, commercial
Truck, dump, street maintenance
Truck, nontactical
Vibrating roller.

* 6.5 Identification of changes. The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, regardless of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AT

Preparing Activity:
Army - AT
Project No. 2320-A321

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:26Z
Check the source to verify that this is the current version before use.