MIL-C-12889A
AMENDMENT 3
30 March 1979
SUPERSEDING
AMENDMENT 2
29 AUGUST 1961

MILITARY SPECIFICATION

CAPACITORS, BY-PASS, RADIO-INTERFERENCE
REDUCTION, PAPER DIELECTRIC, AC AND DC,
(HERMETICALLY SEALED IN METALLIC CASES),
GENERAL SPECIFICATION FOR

This amendment forms a part of military specification MIL-C-12889A, dated 30 August 1957, and is approved for use by all Departments and Agencies of the Department of Defense.

*

THIS SPECIFICATION INACTIVE FOR DESIGN AFTER DATE OF THIS AMENDMENT. USE MIL-C-19978.

PAGE 2

Table II, column 1, Ac-Dc capacitors: Following "rating," delete remainder of sentence.

PAGE 3

Paragraph 2.1, list of Military Specifications, Add:

"MIL-C-12889/1 - Capacitors, By-Pass, Radio-Interference Reduction, Paper Dielectric, Ac and Dc, (Hermetically Sealed in Metallic Cases), Styles CA32, CA33, and CA34.

MIL-C-12889/2 - Capacitors, By-Pass, Radio-Interference Reduction, Paper Dielectric, Ac and Dc, (Hermetically Sealed in Metallic Cases), Styles CA36, CA37, and CA38.

MIL-C-12889/3 - Capacitors, By-Pass, Radio-Interference Reduction, Paper Dielectric, Ac and Dc, (Hermetically Sealed in Metallic Cases), Style CA47."

Paragraph 3.1, at end of first sentence, add "listed in section 2."

PAGE 6

Paragraph 3.16, Opposite "Dissipation factor ...," add "Shall not exceed 1.5 percent."

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:39Z
Check the source to verify that this is the current version before use.

PAGE 7

Following paragraph 4.2 insert new paragraph:

4.3 Responsibility for inspection.

"4.3.1 Supplier. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Paragraph 4.3: Delete paragraph designation "4.3" and substitute "4.3.1.1"; in line 5, delete "manufacturer" and substitute "supplier."

PAGE 14

Following paragraph 6.6, add new paragraph:

"6.7 Insertion loss. The insertion loss of a by-pass capacitor when measured in a 50-ohm system in accordance with Standard MIL-STD-220A, dated 15 December 1959, "Method of Insertion-Loss Measurement," is within 6 decibels of the value of an ideal capacitor of the same nominal capacitance value up to 0.7 of the resonant frequency (F_R). From 0.7 F_R to F_R, the insertion loss is at least equal to or better than the insertion loss of an ideal capacitor. From F_R to 1.4 F_R, the insertion loss in most cases is higher than the insertion loss of an ideal capacitor, but in no case 6 decibels below the ideal curve. Beyond 1.4 F_R the useful insertion loss of a by-pass capacitor decays rapidly."

PAGE 16

Table X, column 3, listing: Delete and substitute:

"14
14
14
14."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:39Z
Check the source to verify that this is the current version before use.

for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1297)

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:39Z
Check the source to verify that this is the currentversion before use.