MIL-G-36645A
5 June 1973
SUPERSEDING
MIL-G-36645
18 February 1970

MILITARY SPECIFICATION

GOWN, HOSPITAL, Cotton

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a cotton, patient's, hospital gown, short sleeves, and of universal size.

1.2 Classification. The gown shall be of one style and size as specified.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

| | |
|---|---|
| QQ-S-766 | Steel Plate, Sheet, and Strip-corrosion Resisting. |
| DDD-L-20 | Label, For Clothing, Equipage, and Tentage, (General Use). |
| PPP-B-636 | Box, Fiberboard. |
| PPP-F-320 | Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes. |

FSC 6532

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

Military

| | |
|---|---|
| MIL-F-10884 | Fasteners, Snap. |
| MIL-T-43548 | Thread, Polyester, Cotton-Covered |
| MIL-T-43624 | Thread, Polyester, Spun |

STANDARDS

Federal

| | |
|---|---|
| FED-TEST-METHOD STD No. 191 | Textile Test Methods. |
| FED-STD-No. 751 | Stitches, Seams and Stitching |

Military

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | Marking for Shipment and Storage. |

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials

3.1.1 Fibers

3.1.1.1 Polyester fiber. The fiber shall be polyethylene glycol terephthalate.

3.1.1.2 Cotton. The cotton shall be combed or well carded.

3.1.2 Yarns. The warp and filling yarns shall be a singles blend of 50 ± 3 percent polyester and the remaining percentage cotton, based on the dry weight of the desized and finished cloth.

3.1.3 Cloth.

3.1.3.1 Weave. The weave shall be a plain weave (broadcloth).



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

3.1.3.2 Physical requirements. The finished fabric shall conform to the requirements listed in Table I when tested as specified in Table VI.

Table I. Physical requirements

| Weight oz. sq. yd. | Yarns per inch minimum | | Breaking strength pounds minimum | |
|---|---|---|---|---|
| Minimum | Warp | Filling | Warp | Filling |
| 3.5 | 100 | 60 | 75 | 35 |

3.1.3.3 Color. The finished cloth shall be dyed blue 290.

3.1.3.4 Sulfur content. The use of sulfur dyes or dyes containing elementary sulfur or sulfur compounds capable of oxidation to sulfuric acid is prohibited. The finished cloth shall contain no more than a trace of labile sulfur when tested as specified in Table VI.

3.1.3.5 Matching. The finished cloth shall be a good approximation to the standard sample under (North sky) daylight or artificial daylight, having a color temperature of 7500° Kelvin and shall be a good approximation to the standard sample under incandescent lamplight at 2800° Kelvin.

3.1.3.6 Colorfastness. The finished cloth shall show "fair" fastness to light and "good" fastness to crocking, perspiration and laundering (after 3 cycles). Tests shall be performed or specified in Table VI.

3.1.3.7 Finish. The cloth shall be mercerized and dyed. Following dyeing, the cloth shall be closely singed.

3.1.3.8 pH. The pH value of the water extract of the finished cloth shall be not less than 5.0 nor more than 9.0 when tested as specified in Table VI.

3.1.3.9 Nonfibrous materials. The starch and protein content including chloroform-soluble and water-soluble material of the finished cloth shall not exceed 2% when tested as specified in Table VI.

3.1.3.10 Shrinkage. The finished cloth shall not shrink nor elongate more than 2% in either the warp or filling when tested as specified in Table VI. The pre-shrinking process used shall not be identified by name or trademark; either on the cloth, ticket, or package.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

3.1.4 Bias binding cloth. The cloth used for binding the neck opening shall be of self material (see 3.1.3) and cut on the bias. The width shall be as necessary to comply with the applicable manufacturing operation.

3.1.5 Thread. The thread for seaming and stitching shall be polyester, cotton-covered, ticket Nos. 50, 3 ply, and 70, 2 ply, conforming to MIL-T-43548. Spun polyester thread, ticket Nos. 50, 3 ply, and 70, 2 ply, conforming to class 1 or 2 of MIL-T-43624 may be substituted for the polyester, cotton-covered thread. The thread shall be dyed to match the base fabric.

3.1.6 Snap fasteners. The snap fasteners shall be 16 or 17 lines conforming to style 3 (pronged ring head type) of MIL-F-10884, except the metal shall be stainless steel (Heavy-Duty) in accordance with class 304 of QQ-S-766.

3.1.7 Labels. Each gown shall have an identification label and instruction label conforming to type I of DDD-L-20. The fastness to laundering requirements of DDD-L-20 shall apply.

3.1.7.1 Identification label. The identification label shall conform to class 1.

3.1.7.2 Instruction label. The instruction label shall conform to class 3 and shall contain the following information:

Washing Instructions

Close snap fasteners.
Machine wash, medium set.
Do not use chlorine bleach or starch.
Use fabric softener to whiten and
prevent clinging.
Tumble dry, medium set.
Remove from dryer immediately.
Little or no ironing.
"CAUTION - To comply with NFPA 56A, use
appropriate ionizing (anti-static) agents
in final rinse."

3.1.7.3 Combination label. The identification (class 1) and instruction (class 3) labels may be combined into one label. The content of the identification label shall precede the instruction information. The coating requirements for the class 3 label shall apply.



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

3.1.7.4 Laundering instructions. The following laundering instructions shall be legibly printed on a suitable paper insert that shall be placed in a visible position within the polyethylene bag containing the finished gown (see 5.1). Lettering shall be a minimum 1/8 inch. Size of insert shall be at the option of the supplier.

"Launder with suitable anti-static agent before first use in medical facility"

Laundering Instructions

| Operation | Time (Mins) | Water Level | Temperature °F | Supplies per 100 lbs. |
|---|---|---|---|---|
| Suds | 5 | High | 160 | Synthetic Detergent (1) 4 Ozs by volume Sodium Orthosilicate (2) 4 Ozs by volume |
| Suds(4) | 5 | High | 160 | Synthetic Detergent 4 Ozs by volume |
| Rinse | 3 | High | 150 | None |
| Rinse | 3 | High | 135 | None |
| Sour | 3 | High | 120 | Sour to pH 6.5 |
| Rinse | 3 | High | 105 | None |
| Anti-Stat(3) | 5 | Low | 90 | Anti-static agent 2-1/2 qts per 100 qts of water |

(1) Detergent, Laundry, Type I FSN 7930-929-1220 50 lb drum
(2) Sodium Orthosilicate FSN 6810-264-6523 100 lb drum
(3) Acceptable anti-static agents - Stantex 461 - Standard Chemical Products Co. 131 Jefferson St., Hoboken, N. J.
Aston 456 - Refined Onyx Division, Millmaster Onyx Corporation, Lyndhurst, N.J.

Dilute these products with at least an equal amount of water before adding to the washwheel. Operate the washer at the lowest practical water level, then add the required amount of anti-static agent after determining the amount of water at that level.
(4) If a bleach is required, use at the rate of 2 quarts of 1% chlorine bleach per 100 pounds of garments.

3.2 Design. The gown shall be full length with an open back, closed by means of snap fasteners. The gown shall be collarless with a reinforced neckline, with short raglan styles sleeves. The body of the gown shall be adjustable by means of snap fasteners.



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

3.3 Figure. Figure 1 is furnished for information only. To the extent of any inconsistencies between the written specification and the figure, the specification shall govern.

3.4 Patterns. Standard patterns for use in cutting working patterns will be furnished by the Government. The working patterns shall be identical to the Government patterns which show size, directional lines and notches for correct assembling and shall not be altered in anyway. The pattern provides a 1/2 inch seam allowance for all double-lapped, double-stitched or safety-stitch seams, and 3/8 inch for all other seams unless otherwise indicated in Table III.

3.4.1 List of pattern parts. The component parts of the gown shall be cut from the specified materials in accordance with the number of parts required in Table II.

Table II. List of pattern parts

| Material | Item Identification | Cut parts |
|---|---|---|
| Cloth, polyester/ cotton, broadcloth | Body part | 1 |
| | Sleeve | 4 |
| | Front neck facing | 1 |
| | Back neck facing | 2 |
| | Snap reinforcement, right side | 1 |

3.5 Construction.

3.5.1 Stitches, seams and stitching. The stitch, seam and stitching types specified in Table III shall conform to FED-STD-751. When two or more seam or stitching types are given for the same operation, either one may be used. Where stitch type 401 is used, the looper (underthread) shall be on the inside of the garment. Seam allowances shall be maintained with seams sewn so that no raw edges, runoffs, twists, pleats, puckers or open seams shall result. The gage of stitching shall be 3/16 to 5/16 inch for all double-lapped, double-stitched seams with the outer row of stitching 1/16 inch from the edge on the outside of garment.



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

When safety-stitch construction is used, the width of the overedge stitch shall be 3/16 to 1/4 inch. Unless otherwise specified, raise stitching shall be 1/16 to 3/32 inch from the joining seam.

3.5.2 Stitches per inch. The minimum and maximum number of stitches per inch shall be as specified in Table III.

3.5.3 Thread breaks and ends of seams. The ends of all seams or stitching when not caught in other seams or stitching, shall be back-tacked not less than 1/4 inch. The ends of a continuous line of stitching shall be overlapped not less than 1/2 inch except on labels where the overlap shall be not less than 3 stitches. Thread breaks, all stitch types, shall be secured by stitching back of the break not less than 1/2 inch. Skipped stitches or thread breaks on 401 seaming, may be repaired by using 301 stitch type.

3.6 Manufacturing operation requirements. The gown shall be manufactured in accordance with operation requirements specified in Table III. The supplier is not required to follow the exact sequence of operations listed. Any basting or holding stitching used to facilitate manufacture is permissible provided that the thread is removed or does not show on the finished gown.

3.6.1 Marking. The parts of the gown shall be marked to insure correct size and a uniform shade throughout. Any method of marking may be used except:

(a) Corrosive metal fastening devices.
(b) Sew-on type tickets.
(c) Adhesive type tickets which discolor or adhere to the material upon removal of the tickets.



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the currentversion before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>Table III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 1. | Cutting:<br><br>a. Cut gowns in strict accordance with patterns furnished, which show size, shape, directional lines and notches for proper assembly. Directional lines shall be in the warp direction.<br><br>b. Cut all component parts of the gown out of one piece of material, except front and back facings and reinforcement piece, which may be cut from ends.<br><br>c. Cut binding of sufficient length and width so that the binding on the finished neckline shall finish 5/8 ± 1/16 inch, both sides. | | | | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 2. | Replacement of damaged parts:<br><br>a. Replace at time of cutting any part containing damages such as holes, multiple floats, smashes and slubs.<br><br>b. Replace any part damaged during the manufacturing process by needle chews, cuts, tears, holes, burns or large exposed drill holes. | | | | | |
| 3. | Marking: (see 3.6.1)<br><br>a. Mark or ticket all parts to insure a uniform shade and proper assembly throughout the garment. | | | | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 4. | Attach front and back facings: | | | | | |
| | a. Position the front facing at the top center of front on inside of garment. Turn in bottom raw edge and single stitch 1/16 to 1/8 inch from edge. | 301 | LSd-1 | 8-12 | 50 | 50 |
| | b. Position the back facings (reinforcement pieces) at the top of back on inside of garment, both sides. The folded edge shall face the bottom of the gown. Stitch along folded edge 1/16 to 1/8 inch from edge. | 301 | | 8-12 | 50 | 50 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 5. | Attach lower reinforcement piece to right back: | | | | | |
| | a. Attach lower reinforcement piece to the inside right back as indicated by marks on pattern. Stitch along the three folded sides 1/16 to 1/8 inch from edges. | 301 | LSd-1 | 8-12 | 50 | 50 |
| 6. | Attach label: | | | | | |
| | a. Position identification label on the inside left back so that one end will be caught in the back hem. The label shall be centered on the female fastener (socket) as indicated by marks on pattern. Stitch to gown on three sides. | 301 | LSbj-1 | 8-12 | 50 | 50 |
| | b. Position instruction label below, and in line with the identification label. Stitch on all four sides. | 301 | LSbj-1 | 8-12 | 50 | 50 |
| | c. When combination label is used follow operation 6a above. | | | | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 7. | Hem backs: | | | | | |
| | a. Turn in hem of backs, as indicated by notches on pattern, with the raw edges turned under 5/8 inch. Single stitch 1/16 to 1/8 inch from the folded edge. The hem shall finish 3/4 ± 1/8 inch. | 301 | EFb-1 | 8-12 | 50 | 50 |
| 8. | Make sleeves. | | | | | |
| | a. Join sleeve pieces at the outseam with double-lapped and double-stitched seam. The seams may lap in either direction. | 301 or<br>401 | LSc-2<br>LSc-2 | 8-12<br>8-12 | 50<br>50 | 50<br>70 |
| | or | | | | | |
| | b. Join sleeve pieces by using safety-stitch. | 515 or<br>516 or<br>519 or | SSa-2 | 8-12 | 50<br>(chain stitch)<br>and<br>70<br>(overedging) | 70<br><br><br>70 |
| | | 517 or<br>518 | SSa-2 | 8-12 | 50<br>(lock stitch)<br>70<br>(overedging) | 70<br><br>70 |



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 8. | Make sleeves (cont'd.): | | | | | |
| | c. Hem bottom of sleeves. Turn up bottom of sleeve to the inside, turning in the raw edges, and stitch. The hem shall finish 1/2 ± 1/8 inch. | 301 | EFb-1 | 8-12 | 50 | 50 |
| | d. Join inseam of sleeves with double-lapped and double-stitched seam. The seam may lap in either direction. | 301 or<br>401 | LSc-2<br>LSc-2 | 8-12<br>8-12 | 50<br>50 | 50<br>70 |
| | e. A bartack shall be placed across the lapped seam at the bottom of sleeve. The bartack shall be 3/8 to 1/2 inch long. | Bartack | | 28 per bartack | 50 | 50 |
| | NOTE: As an alternate, the sleeves shall be made by following operations a, and c, in that order, and deleting operation e entirely. | | | | | |
| | or | | | | | |
| | f. Join inseam of sleeves by using safety-stitch. | 515 or<br>516 or<br>519 or | SSa-2 | 8-12 | 50<br>(chain stitch)<br>and<br>70<br>(overedging) | 70<br><br><br>70 |
| | | 517 or<br>518 | SSa-2 | 8-12 | 50<br>(lock stitch)<br>70<br>(overedging) | 70<br><br>70 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 9. | Set sleeves: | | | | | |
| | a. Stitch sleeves to armhole of gown with a double-lapped and double-stitched seam, with the body parts over the sleeve. | 301 or<br>401 | LSc-2<br>LSc-2 | 8-12<br>8-12 | 50<br>50 | 50<br>70 |
| | or | | | | | |
| | b. Set sleeves by using safety-stitch. | 515 or<br>516 or<br>519 or | SSa-2 | 8-12 | 50 (chain stitch) and 70 (overedging) | 70 |
| | | 517 or<br>517<br>518 | SSa-2 | 8-12 | 50 (lockstitch) 70 (overedging) | 70 |
| 10. | Seam binding to neck opening: | | | | | |
| | a. The neck opening shall be bound with the bias cut binding. The binding shall finish 3/8 ± 1/16 inch. | 301 | BSc-1 | 8-12 | 50 | 50 |
| | b. Bartack each end of the bound neck opening across the binding using a bartack 3/8 to 1/2 inch long. | Bartack | | 28 per Bartack | 50 | 50 |
| | c. Trim excess binding even with the finished edges of the garment. | | | | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 11. | Attach fasteners:<br><br>a. Attach 5 socket portions of the fasteners to the left back of gown as indicated by marks on pattern.<br><br>b. Attach 3 stud portions of the fasteners to the right back of gown as indicated by marks on pattern.<br><br>c. The sockets and studs shall be affixed so that the left back shall overlap the right back. The sockets and studs along the back neck area shall be in horizontal alignment to provide a smooth closure. | | | | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| No. | MANUFACTURING OPERATIONS REQUIREMENTS<br>TABLE III | Stitch Type | Seam and Stitching Type | Stitches Per Inch | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | Needle | Bobbin or Looper |
| 12. | Clean gown:<br>a. Remove all spots, stains and shade tickets.<br>b. Trim all thread ends and remove loose threads.<br>c. Shade markings when exposed on the outside of gown shall be removed. | | | | | |
| 13. | Folding:<br>a. Gowns shall be neatly folded. | | | | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

3.7 Measurements. The finished gowns shall conform to the measurements shown in Table IV. All measurements and tolerances are expressed in inches.

Table IV. Table of measurements

| Gown | Back length 1/ | Sleeve length 2/ | 1/2 Chest 3/ |
|---|---|---|---|
| | 44 | 6-1/2 | 31 |
| Tolerance | ± 1/2 | ± 1/4 | ± 1/2 |

1/ Measure from top edge of neck at back, to bottom edge of gown.

2/ Measure inseam of sleeve from the armhole seam to the bottom of finished sleeve.

3/ Measure at base of armhole, from folded edge to folded edge, with the hemmed edges abutting.

3.8 Workmanship. The finished gown shall conform to the quality established by this specification. The occurrence of defects shall not exceed the applicable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except when otherwise indicated herein.



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document. In addition to the quality assurance provisions of the referenced specification, components listed in Table VI shall be tested for the characteristics shown therein. Wherever applicable, tests shall be conducted in accordance with method specified in FED-STD-191 and as listed in Table VI. When the data in the "determinations per sample unit" and "results reported as" columns are not specified in the table, they shall be as required by the referenced test method. All test reports shall contain the individual values utilized in expressing the final results.

4.3.1.1 Sampling for testing. Unless otherwise specified in the subsidiary specifications, sampling shall be in accordance with Table V. The lot shall be unacceptable if one or more sample units fail to meet any test requirements specified. The unit for expressing lot sizes and sample unit for testing each component shall be in accordance with applicable subsidiary specifications and as follows:

| Component | Lot expressed as | Sample unit for testing |
|---|---|---|
| Cloth, polyester/Cotton broadcloth | Yards | 3 Yards (full width) |

Table V. Sample size

| Lot size | Sample size |
|---|---|
| 800 or less | 2 |
| 801 up to and including 22,000 | 3 |
| 22,001 and over | 5 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

Table VI. Test Methods

| Characteristic | Requirement Paragraph | Test Method |
|---|---|---|
| Base cloth: | | |
| Polyester identification | 3.1.1.1 | 1/ |
| Cotton identification | 3.1.1.2 | 1/ |
| Cotton-combed or well carded | 3.1.1.2 | 1/ |
| Fiber content: | | |
| Polyester-percent | 3.1.2 | 4.3.1.2 |
| Weave | 3.1.3.1 | Visual 1/ |
| Nonfibrous materials | 3.1.3.9 | 2611 |
| Yarns per inch: | | |
| Warp | 3.1.3.2 | 5050 |
| Filling | 3.1.3.2 | 5050 |
| Breaking strength | | |
| Warp | 3.1.3.2 | 5100 |
| Filling | 3.1.3.2 | 5100 |
| Shrinkage | 3.1.3.10 | 5550 |
| Weight | 3.1.3.2 | 5041 |
| pH | 3.1.3.8 | 2811 |
| Sulfur content | 3.1.3.4 | 2020 |
| Mercerized and singed | 3.1.3.7 | Microscopic 1/ |
| Colorfastness: | | |
| Laundering (3 cycles) | 3.1.3.6 | 5610 2/ |
| Crocking | 3.1.3.6 | 5651 |
| Perspiration | 3.1.3.6 | 5680 |
| Light | 3.1.3.6 | 5660 |

1/ Unless otherwise specified, a certificate of compliance shall be submitted and will be acceptable for the stated requirement.

2/ For method 5610 - 3 laundering cycles shall be performed with the test specimens dried after each of the 3 laundering cycles. Only the stain on the cotton fiber of the color transfer cloth shall be evaluated.

4.3.1.2 Polyester fiber content.

4.3.1.2.1 Test specimen. - The specimen shall be approximately 2 grams made up of yarns ravelled from the cloth sample and cut into approximately 1/4 inch lengths.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

4.3.1.2.2 Apparatus, reagents, method cited. -
Apparatus as described in Method 2611.
Sintered glass filter crucible of coarse porosity.
Hydrometer.
Sulfuric acid, 74 percent (density 1.67) prepared by pouring 350 cubic centimeters (cc.) of water in a round-bottom glask, then adding 680 cc. of concentrated sulfuric acid slowly, with cooling under the tap. The density of the solution is adjusted to 1.67 using a hydrometer.
Sulfuric acid, dilute (100 cc. of concentrated sulfuric acid added to 1900 cc. of water).

4.3.1.2.3 Procedure. - The nonfibrous material shall be removed as specified in Method 2611. The desized specimen shall be dried to a constant weight, cooled in a desiccator and weighed. The specimen shall then be immersed in 200 cc. of 75 percent solution of sulfuric acid for 1 hour with intermittent stirring. The residual fibers shall be transferred to the glass crucible and the excess acid solution removed by suction. The residual fibers shall be washed on the fiber filter successively with dilute sulfuric acid, water, dilute ammonia solution (soak for ten minutes) and again with water (soak for ten minutes). After each separate washing, the crucible is drained by suction. The residue shall be dried to a constant weight in the air oven at 105° to 110° C. This is the "weight of the dry polyester fiber" in the specimen.

4.3.1.2.4 Result. - The percentage of polyester fiber shall be based on the following equation:

$$\text{Polyester fiber, percent} = \frac{\text{Weight of dry polyester fiber}}{\text{Weight of dry desized specimen}} \times 100$$

4.3.1.2.5 Two specimens shall be tested from each sample unit and the polyester content shall be the average of the results obtained from the specimen tested and shall be reported to the nearest 1.0 percent.

4.3.2 Examination of the end item. The end item shall be examined for the defects listed in 4.3.2.1 through 4.3.2.3. The applicable inspection levels and acceptable quality levels (AQL's) shall be as indicated in 4.3.3. The sample unit shall be one gown. Defects shall be classified as listed.



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

4.3.2.1 General defects.

| Defect | Classification | |
|---|---|---|
| | Major | Minor |
| **Material defects and damages** | | |
| a. Hole, needle chew, scissor or knife cut, tear or mend. | X | |
| b. Any weakening defect such as smash, multiple float or loose slub. | X | |
| **Shaded parts** | | |
| a. Any outside part shaded. | X | |
| **Cleanness** | | |
| a. Spot or stain on outside. | | X |
| b. Thread ends not trimmed or loose threads not removed. | | X |
| c. Two or more shade or size markings not removed. | | X |
| **Component and assembly** | | |
| a. Any component part or operation omitted (unless otherwise classified herein). | X | |



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

| Defect | Classification | |
|---|---|---|
| | Major | Minor |
| Cutting | | |
| a. Any component part not cut in conformance with directional lines on pattern. | X | |
| b. Any component part not as specified. | X | |
| Seams and stitching | | |
| a. General: | | |
| 1. Any part of gown caught in any unrelated operation. | X | |
| 2. Seams twisted, puckered or pleated (unless otherwise classified herein). | | X |
| 3. Wrong shade or varying shades of thread used on outside of same garment. | | X |
| 4. Ends of all stitching, when not caught in other seams or stitching backtacked less than 1/4 inch. | | X |
| 5. Thread breaks (all stitch types) stitches less than 1/2 inch beyond each end of break. | | X |
| 6. Continuous line of stitching overlapped less than 1/2 inch. | | X |



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.

| Defect | Classification Major | Classification Minor |
|---|---|---|
| Seams and stitching (cont'd.) | | |
| b. Gage of stitching: | | |
| 1. Unevenly gaged or various stitching not uniform. | | X |
| 2. Beyond width specified or varies more than 1/16 inch when no range is specified. | | X |
| c. Open seams: | | |
| - up to 1/4 inch inclusive | | X |
| - over 1/4 inch | X | |
| NOTE: One or more broken or two or more continuous skipped or run-off stitches are considered an open seam. Double-stitched seams are considered open when either one or both sides of seams are open. | | |
| d. Raw edges: | | |
| 1. On outside: | | |
| - more than 1/4 inch, but not more than 3/4 inch | | X |
| - more than 3/4 inch. | X | |
| 2. On inside: | | |
| - 3/4 inch to 1 inch inclusive | | X |
| - more than 1 inch. | X | |
| NOTE: Raw edges not securely caught in stitching shall be classified as open seams. | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| Defect | Classification Major | Minor |
|---|---|---|
| Seams and stitching (cont'd.) | | |
| e. Run-offs (see classification of open seams). | | |
| f. Seam and stitch types: | | |
| 1. Not specified seam or stitch type. | X | |
| 2. Looper thread (when stitch type 401 is used) on outside. | X | |
| g. Stitch tension: | | |
| 1. Loose tension on edge or raised stitching, resulting in exposure of bobbin or top thread. | | X |
| 2. Loose tension, resulting in a loose seam. | X | |
| 3. Tight tension (stitches break when normal strain is applied to seam or stitching). | X | |
| NOTE: Puckering is evidence of tight tension. When puckering is evident, seam shall be tested by exerting normal pull in lengthwise direction of seam. | | |
| h. Stitches per inch: | | |
| 1. Less than minimum specified by: | | |
| - one or two stitches | | X |
| - three or more stitches. | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| Defect | Classification Major | Minor |
|---|---|---|
| Seams and stitchings (cont'd.) | | |
| h. Stitches per inch (cont'd.): | | |
| 2. More than maximum specified. | | X |
| i. Stitches skipped or broken: | | |
| 1. On raised or edge stitching 1/2 inch or more. | X | |
| 2. Less than 1/2 inch at two or more places. | | X |
| 3. On all other stitchings: see "Open seams". | | |
| Bartacks | | |
| a. Less than 3/8 inch or more than 1/2 inch long. | | X |
| b. One or more omitted or added, or type not as specified (when applicable). | | X |

4.3.2.2 Detailed defects applicable to specific parts.

| Defect | Classification Major | Minor |
|---|---|---|
| Body piece | | |
| a. Front | | |
| 1. Facing badly twisted or puckered. | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| Defect | Classification Major | Minor |
|---|---|---|
| Body piece (cont'd.) | | |
| a. Front (cont'd.) | | |
| 2. Facing not centered properly. | | X |
| 3. Facing omitted. | X | |
| b. Back hem | | |
| 1. Less than 5/8 inch or more than 7/8 inch wide. | | X |
| c. Back facings (reinforcement piece) | | |
| 1. Omitted. | X | |
| 2. Less than double thickness. | X | |
| d. Back | | |
| 1. Right back overlapping left back. | | X |
| 2. Back not overlapping. | X | |
| e. Snap fasteners | | |
| 1. Studs and sockets not positioned as marked on pattern. | X | |
| 2. Not specified type and size. | | X |
| 3. Missing, broken or otherwise defective, i.e., not functioning properly. | X | |
| 4. Not reinforced as specified. | X | |
| 5. Studs or sockets not clinched. | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

| Defect | Classification Major | Minor |
|---|---|---|
| Body piece (cont'd.) | | |
| f. Neck binding | | |
| 1. Omitted. | | |
| 2. Finished less than 5/16 or more than 7/16 inch wide. | X | X |
| 3. Ends of binding not bartacked. | X | |
| 4. Bartack not across the finished binding. | | X |
| 5. Ends of binding not trimmed as specified. | | X |
| Sleeves | | |
| a. Construction and setting: | | |
| 1. Puckered or pleated at joining to armhole. | | X |
| 2. Seams overlapping body. | | X |
| 3. Hem less than 3/8 inch or more than 5/8 inch wide. | | X |
| 4. Bartack omitted at the end of the inseam. | X | |
| 5. Bartack less than 3/8 inch and more than 1/2 inch long. | | X |
| 6. Seams not lapped as specified. | | X |
| Labels | | |
| a. Label: | | |
| 1. Missing, incorrect, or illegible. | X | |



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the currentversion before use.

| Defects | Classification Major | Minor |
|---|---|---|
| Labels (cont'd.) | | |
| a. Label (cont'd.): | | |
| 2. Not stitched on all three sides. | | X |
| 3. Fourth side not caught in back hem. | | X |

4.3.2.3 Size measurements (see 3.9). Any measurement deviating from dimensions and tolerances specified in Table IV shall be scored as a size measurement defect. Sleeve in-seams uneven in length by more than 1/2 inch shall be scored as a size measurement defect.

4.3.3 Inspection levels and acceptable quality levels. Inspection levels and acceptable quality levels (AQL) expressed in defects per 100 units (DHU) shall be as follows:

| | AQL | Inspection level II |
|---|---|---|
| 4.3.2.1, 4.3.2.2 (combined) | | |
| Major | 2.5 | |
| Total | 10.0 | |
| 4.3.2.3 | | S-2 |
| One class | 4.0 | |

4.3.4 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking comply with requirements of section 5. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The sampling shall be in accordance with MIL-STD-105. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.



Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the currentversion before use.

| Examine | Defects |
|---|---|
| Marking (exterior and interior) | Omitted, incorrect, of improper size, location, sequence or method of application. |
| Materials | Any component missing, damaged or not as specified. |
| Workmanship | Inadequate application of components such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Open and noncontinuous heat sealed seams and closure of polyethylene bags. Omission of air vent hole in polyethylene bags. Bulged or distorted container. |
| Content | Number of packages per shipping container is more or less than required.<br>Number of gowns per package is more or less than required. |

## 5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each gown shall be folded to approximate dimensions of 12 inches in length, by 12 inches in width and placed in a close fitting clear polyethylene film bag of 0.002 inch thickness (± 20 percent tolerance). The bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and the formed edges of the bag. The final closure of the bag shall be heat sealed with the seal made as close as possible to the open end. A 1/4 inch diameter hole shall be made at one corner of the polyethylene bag to allow excess air to escape.

5.1.2 Level C. Gowns shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Forty-eight gowns packaged as specified in 5.1, shall be packed in a fiberboard shipping container of appropriate size conforming to PPP-B-636, style RSC-L, grade V2s. The container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed, waterproofed, and reinforced with strapping in accordance with the appendix of PPP-B-636.

5.2.2 Level B. Forty-eight gowns packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to PPP-B-636, style RSC-L, type CF (variety SW or SF), class domestic, grade 275. The container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each container shall be closed in accordance with the appendix of PPP-B-636, method II.

5.2.2.1 When specified (see 6.2), the shipping container shall be grade V3c or V3s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification. The shipping container material may also be grade V4s of PPP-F-320.

5.2.3 Level C. Gowns, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129. Date of manufacture shall also be shown.

5.3.1 Polyethylene bagged packages. Polyethylene bagged packages shall have the required information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall indicate the following information:

STOCK NUMBER
NOMENCLATURE
CONTRACT OR PURCHASE ORDER NUMBER
QUANTITY
NAME AND ADDRESS OF MANUFACTURER
DATE OF MANUFACTURE



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The gown, is intended for wear by hospitalized patients confined to bed in Military hospitals.

6.2 Ordering data. Procurement document should specify the following:

a. Title, number, and date of this specification.
b. First article. When preproduction samples are required (see 3.2).
c. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
d. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Samples. For access to sample of the gown and shade samples of the material, address the procuring activity issuing the invitation for bids (see 3.1).

6.4 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types, etc. which are normally procured to meet military requirements.

6.5 This specification covers the following item appearing in the Federal Supply Catalog:

| FSN | Item Identification |
|---|---|
| 6532-117-8247 | GOWN, HOSPITAL, Cotton-Polyester, Universal Size |

Custodians:

Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6532-1066

Review activities:

Army - MD
Navy - MS
Air Force - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on information in the current DODISS.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
ATTN: DPSC-ATTS
Philadelphia, PA 19101

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:57Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| | |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:57Z
Check the source to verify that this is the current version before use.