MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLES 30 THRU 110 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.100 SQ. GRID)

This amendment forms a part of Military Specification Sheet MIL-C-55302/27F, dated 24 March 1980, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 13

REQUIREMENTS, *under* "Material", delete the plating requirement and substitute the following:

"Plating (contact):

Types I through IV contacts:
Engagement area: Gold per MIL-G-45204, type II, grade C, class 1, over nickel per QQ-N-290, class 2, 30 to 150 microinches, for .100-inch minimum length.

Termination area: Tin lead per MIL-T-10727, class 1, over nickel per QQ-N-290, class 2, 30 to 150 microinches, for .300-inch minimum length.

Other contact areas: Nickel per QQ-N-290, class 2, 30 to 150 microinches.

Types V and VI contacts: Gold per MIL-G-45204, type II, grade C, class 1, over nickel per QQ-N-290, class 2, 30 to 150 microinches."

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - CR, AR, MI
Navy - SH, AS, OS
Air Force - 11, 99
DLA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3192-3)

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.