INCH-POUND
MIL-PRF-55342/4H
3 July 1997
SUPERSEDING
MIL-R-55342/4G
28 June 1995

PERFORMANCE SPECIFICATION

RESISTORS, FIXED, FILM, CHIP, NONESTABLISHED RELIABILITY, ESTABLISHED RELIABILITY, SPACE LEVEL, STYLE RM1505

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for style RM1505, fixed, film, chip, nonestablished reliability, established reliability, and space level resistors. This style is available in characteristic H, characteristic E, characteristic K, and characteristic M, resistance tolerances .1 percent, 1 percent, 2 percent, 5 percent, and 10 percent, and all termination materials.

1.2 Part or Identifying Number (PIN). Chip resistors covered by this specification must be identified by a PIN which must consist of the basic number of this specification and a coded dash number. The PIN must be in the following form:

M55342H04	B1E00M
* * *	* * *
Performance specification number	Coded dash number

The coded dash number must be derived in accordance with MIL-PRF-55342.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Communications - Electronics Command, ATTN: AMSEL-LC-LEO-E-EP, Fort Monmouth, NJ 07703-5023, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of the basic document or by letter.

AMSC N/A FSC 5905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-55342 - Resistors, Fixed, Film, Chip, Nonestablished Reliability, Established Reliability, Space Level, General Specification for.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Defense Printing Service Detachment Office, Building 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specification, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-55342.

3.2 Interface and physical dimensions. Resistors shall meet the interface and physical dimensions specified on figure 1, as applicable.

3.3. Power rating. The power rating for characteristic H and characteristic E shall be 100 milliwatts. For characteristic K and characteristic M, the power rating shall be 150 milliwatts.

3.4 Voltage rating. The maximum continuous working voltage shall not exceed 40 volts.

3.5 Resistance and resistance tolerance. Minimum and maximum resistance values and associated resistance tolerances shall be as listed in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.

TABLE I. Minimum and maximum resistance values and tolerances.

Resistance tolerance	Minimum resistance	Maximum resistance
percent (±)		
0.1	100 ohms	1,000,000 ohms
1.0	5.62 ohms	1,000,000 ohms
2.0	5.6 ohms	1,000,000 ohms
5.0	5.6 ohms	1,000,000 ohms
10.0	5.6 ohms	1,000,000 ohms

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-PRF-55342.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order. When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Chip resistors are intended to be used in thin or thick film hybrid circuits where micro-circuitry is indicated and in surface mount applications.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, date of this specification, and complete PIN (see 1.2).

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2).

c. Packaging requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.

Configuration A



Configuration B



Configuration	Dimension A inch	Dimension B inch	Dimension C inch	Dimension D inch	Dimension E inch
A	.150 ±.005	.050 ±.005	.012/.030	.015 ±.005	N/A
B	.155 ±.007	.050 ±.005	.015/.033	.015 ±.005	.015 ±.005

FIGURE 1. Style RM1505.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.

Configuration C



Inches	mm
.005	0.13
.007	0.18
.012	0.30
.015	0.38
.020	0.51
.030	0.76
.033	0.84
.050	1.27
.150	3.81
.155	3.94

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ∀.005 (0.13 mm).
4. The pictorial view of the styles above are given as representative of the envelope of the item. Slight deviations from the outline shown, which are contained within the envelope, and do not alter the functional aspects of the device are acceptable.
5. Configuration A covers termination materials D, T, and W.
6. Configuration B covers termination materials B, C, G, and U.
7. Configuration C covers all characteristics and terminal P type units.

FIGURE 1. Style RM1505 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.

6.3 Tolerance for wraparound termination. The added tolerance for the wraparound type termination is intended to apply only to termination, metallization, and pretinning material.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AT, AV, CR4
Navy - AS, CG, MG, OS
Air Force - 17, 19, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5905-1459-04)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.