MIL-R-60176(MU)
AMENDMENT 2
8 August 1967
SUPERSEDING
Amendment 1
19 October 1966

MILITARY SPECIFICATION

RECTIFIER, TRANSISTOR ASSEMBLY: 10525740

This amendment forms a part of Military Specification MIL-R-60176(MU), dated 18 February 1965.

Paragraph 3.3.1, Fourth sentence: Delete "Logic Driver" and substitute "Rectifier Assembly"

Paragraph 3.5.1.1: Add "Volts" between "150" and "Direct-current"

Paragraph 3.5.2.1(b): Delete "9.45ma(min)" and substitute "945ma (min)".

Table V, current supply number 3: Delete ".5amp" and substitute ".25 amp".

Table VI, Lines 8 and 9: Delete "11A" and substitute "10A".

Paragraph 4.5.1.2, Last line: Delete "3.4" and substitute "3.5".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating. - This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour period, and the test shall cease at the end of that period (Method 106 Of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the test of 4.5.2.4, as specified in 3.3.4.1. in order to demonstrate this capability, the tests of 4.5.2.4 shall be performed a minimum of once each 6 hours of the 24-hour period. The final test shall ne conducted during the final portion of the 24-hour period. Between tests, the board shall be electrically energized as described in 4.5.2.2.1, 4.5.2.2.2, 4.5.2.2.5, 4.5.2.2.6 and 4.5.2.3.4.

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray. - This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2.2. and 4.5.2.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-2[illegible]
Check the source to verify that this is the current version before use.

Paragraph 4.5.1.5: Delete "4.5.2.9.1, 4.5.2.9.2, 4.5.2.4 and 4.5.2.5" and substitute "4.5.2.4.1, 4.5.2.4.2, 4.5.2.2 and 4.5.2.3" respectively.

Paragraph 4.5.2.2.3: Delete the third sentence in its entirety and substitute "for each test position, the voltage from test terminal X to test terminal Y shall be less than + 1.5 volts as specified in 3.5.1.3."

Paragraph 4.5.2.2.4: Delete the third sentence in its entirety and substitute "for each position, the voltage from test terminal X to test terminal Y shall be less than + 1.5 volts as specified in 3.5.1.4."

Paragraph 4.5.2.2.5: Delete the second sentence in its entirety and substitute "the voltage from terminal 36B to terminal 41B shall be +6.0 ± 0.36 volts." Delete the fourth sentence in its entirety and substitute "the voltage from terminal 46B to terminal 52B shall be + 6.0 ± 0.36 volts."

Paragraph 4.5.2.2.6: Delete the second sentence in its entirety and substitute "the voltage from 35B to 35A shall be +33 ± 2 volts, as specified in 3.5.1.6."

Table VIII Test Position 3, test terminal X column: Delete "1A,2A" and substitute "1A, 2A, 3A."

Paragraph 4.5.2.3.5: Delete "Table VI" and substitute "Table IX."

Paragraph 4.5.2.4.1.3: Delete "3.5.1.3.3" and substitute "3.5.3.1.3."

Paragraph 4.5.2.4.1.4: Delete "3.5.1.3.4" and substitute "3.5.3.1.4"

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No.1220-A040

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.