MILITARY SPECIFICATION

WRITE SWITCH:10526581

This amendment forms a part of Military Specification MIL-W-60179 (MU) dated 18 February 1965.

Paragraph 3.4.1.2(c): Delete "shall be at least 0.IV, but".

Paragraph 3.4.5: Delete in its entirety and substitute:

"3.4.5 Resistors. - After final assembly into the write switch, the resistor connected between 10B and 13B shall possess characteristics within tolerance limits specified on the appropriate drawings."

Table I, Characteristic 111 : Delete "Thermistor resistance range" and substitute "Resistors."

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.2.1.3.1. In order to demonstrate this capability, the tests of 4.5.2.1.3.1 shall be performed a minimum of once each 6 hours of the 24-hour period."

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray. - This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2."

Table IV, Column 9: Delete "35" and substitute "35A".

Paragraph 4.5.2.1.2(c): Delete "plus 0.65 ± 0.55 volt" and substitute "less than plus 1.2 volts".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T[illegible]
Check the source to verify that this is the current version before use.

Paragraph 4.5.2.4.2, line 5: Delete "from pin 33A to ground" and substitute "at pin 33A with respect to the minus 18 volt supply".

Figure 3: Delete "-0.1 ± 0.1 volt" and substitute "+0.1 ± 0.1 volt".

Paragraph 4.5.2.5: Delete in its entirety and substitute:

"4.5.2.5 Resistors. - The resistance between terminals 10B and 13B shall be 10K ohms ± 5% to determine compliance with 3.4.5".

Figure 4: Delete.

Paragraph 6.1: Delete the first sentence in its entirety and substitute "the write switch module contains 12 separate write switches, write-head, isolation diddes and test diodes". Last sentence: Delete.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A043

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.