INCH-POUND

MIL-W-63441A(AR)
AMENDMENT 9
29 June 2001
SUPERSEDING
AMENDMENT 8
13 November 1996

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, PRACTICE: M267

This amendment forms a part of MIL-W-63441A(AR), dated 17 May 1983, and is approved for use by the U.S. Army Armament Research, Development, and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Paragraph 2.1.1, SPECIFICATIONS, MILITARY, Add:

"QAC-1415 - Rocket, 2.75 Inch/Hydra-70: Assembly, Packing and Testing".

"MIL-B-63469 - Body Assemblies, General Purpose Grenade: M73 and 75 (Practice)."

Bottom of page: Add:

PAGE 2

(a) Paragraph 2.1.2: Delete section from "MISSILE INTERIM ..." to "... Alabama 35898.)".

(b) Delete references to specification MIS-30862 and substitute QAC-1415. Make this substitution wherever it appears in this document.

(c) Paragraph 2.1.2, Product Drawings: Add: "12937865 - Packing and Marking for Container, Metal, for 2.75 Inch Rkt., M261/M267".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

(d) Paragraph 2.1.2: Add:

"PUBLICATIONS

ITOP-1-2-601 -- Laboratory Inspection Schedules, International Test Operations Procedures (ITOP), TECOM".

PAGE 3

(a) Paragraph 3.3: Delete and substitute:

3.3 Grenades.

3.3.1 M75 general purpose practice grenade. The grenade shall comply with MIL-G-63445.

(b) Delete paragraph 3.7 (Reliability).

(c) Paragraph 3.8, line 2: Delete "MK66 Mod 1 motor" and substitute "MK66 Mod 1, Mod 2, and Mod 3 motors".

(d) Paragraph 3.9, line 4: Delete "components" and substitute "major components and subassemblies, such as pusher plate, M75 grenade, simulator grenade, cable, etc.,".

PAGE 4

Paragraph 3.16, line 2:

(a) Delete "4.5.8" and substitute "4.5.6."

(b) Delete "and shall comply with the ballistic test as specified in 4.5.10."

PAGE 7

TABLE I. First Article Inspection:

(a) Delete "102" and substitute "108" (four places).

(b) Note (a): Delete "leakage tests (6)" and substitute "nonenvironmental (6)".

(c) Delete Note (b) and substitute "The first article ballistic sample shall be rejected if two or more payloads fail to eject, or if all the grenades in any warhead fail to function."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 8

Paragraph 4.4.1, last line: Delete “4,000.” and substitute “5,000.”

|Paragraph 4.4.1 (d), change “d” to read:

"d. Metal parts from no more than two lots bearing the same interfix number from one manufacturer, except no more than six lots of warhead cases may be used within each individual warhead case interfix number from one manufacturer.”

PAGE 10

Paragraph 4.4.2.2: Add minor defect 202:

“202. Packing missing 0.65% 3.2 Visual”.

PAGE 11

Paragraph 4.4.2.3:

(a) Major defect 109: Delete and substitute: “Leakage test 6 -- 3.16 4.5.6”.

(b) Add Major defect 110: “Ballistic test 36 -- 3.18 4.5.8”.

PAGE 12

(a) Paragraph 4.5.1, second sentence, Delete and substitute: “Verify that all major components, assemblies, and sub-assemblies, such as pusher plate, M75 grenade, simulator grenade, cable, etc. are present and properly placed; that all grenades are safe; and that no foreign material is present.”

(b) Paragraph 4.5.2: Delete “box” and “boxes” and substitute “box or container” or “boxes or containers” where applicable (8 places).

PAGE 13

Paragraph 4.5.2, 3rd last paragraph, line 3: After “containers” add “(fiber containers are not required if fastpack is used)”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 14

(a) Paragraph 4.5.2, last paragraph, line 3: Delete “intact and securely in place).” and substitute “intact and not manually removable).”

(b) Paragraph 4.5.3, third paragraph: Delete “The packed shipping boxes . . . Resonance testing does not apply.” and substitute “The packed shipping boxes or metal containers shall be subjected to the vibration test in accordance with paragraph 4.1, and with Figures on pages: B-3, B-4, and B-5 (40 min./axis); B-6, B-7, and B-8 (32 min./axis), International Test Operations Procedures (ITOP), 1-2-601, dated 01 March 1988. Resonance testing does not apply.”

PAGE 16

Paragraph 4.5.6:

(a) Line 2 - 3: Delete “for first article testing only.”

(b) End of paragraph, Add: “To inspect the cargo compartment, unthread the base plug in the rear of the warhead, and remove the nose cone and base nose cone assemblies. If one or more warheads fail to meet the requirement, the test shall be considered a failure. This test is to be conducted for first article testing and until two consecutive lots have complied with the acceptance criteria specified. After satisfying this requirement, the leakage test shall be performed on every subsequent third lot only. Should the lot fail the acceptance criteria, the contractor shall be required to return to the two consecutive lot procedures above.”

|Paragraph 4.5.8: Delete and substitute:

“4.5.8 Ballistic test. The requirement for the warhead is to provide a ballistic match with the M261 tactical MPSM warhead, realism, and an indication of ground impact resulting from the proper delivery of M75 grenades into target areas from 1000 to 6000 meters from the launching helicopter. Performance shall be evaluated by ground launching a sample of 36 M267 warheads, assembled with M66 Mod 1, Mod 2, or Mod 3 motors, from any of the compatible launchers per the following matrix:

	CONDITIONING TEMPERATURE		
FUZE SET RANGE	-50° + 5°F	+70° ± 15°F	+150° - 5°F
1 KM	4 each	4 each	4 each
3 KM	4 each	4 each	4 each
6 KM	4 each	4 each	4 each

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

Each rocket shall be temperature conditioned for a minimum of 8 hours and shall be fired within 10 minutes after removal from temperature conditioning chamber. Firing and fuze charging shall be accomplished by a Government-approved ballistic firing set. Grenade functioning and time from launch to cargo ejection shall be detected and recorded. Except with one situation described below, the lot shall be rejected if three or more payloads fail to eject or if all the grenades in any warhead payload fail to function. In the event all three grenades from one warhead failed to function, the lot shall still be acceptable if both of the following conditions are met:

a. One or more grenade duds from the failed warhead show evidence of air collision with the spent rocket casing or another grenade.

b. The total dud count, excluding the grenade(s) that showed evidence of air collision, does not exceed 11."

PAGE 19

Paragraph 6.3: Delete "US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I, Dover, NJ 07801." and substitute "U.S. Army Armament Research, Development, and Engineering Center, Attn: AMSTA-AR-QAC-S, Picatinny Arsenal, NJ 07806-5000."

The margins of this amendment are marked with vertical lines to indicate where changes to the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-1023)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.