MIL-G-8798(ASG)
AMENDMENT-2
5 APRIL 1960

Superseding
Amendment -1
21 December 1959

MILITARY SPECIFICATION

GAGE SYSTEM, FUEL-QUANTITY, CAPACITOR-TYPE, NONVACUUM TUBE, INTEGRALLY LIGHTED, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-G-8798(ASG), 20 December 1956, and has been approved by the Department of the Air Force and by the Navy Bureau of Naval Weapons.

Pages 1 and 2, paragraph 2.1: Delete, and substitute:

"2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

Federal

QQ-P-416	Plating, Cadmium (Electrodeposited)
QQ-Z-325	Zinc Coating, Electrodeposited, Requirements for

Military

MIL-C-17	Cables, Radio Frequency, Coaxial, Dual Coaxial, Twin Conductor, and Twin Lead
MIL-P-116	Preservation, Methods of
MIL-S-3136	Standard Test Fluids Hydrocarbon and Iso-Octance
MIL-T-4687	Tester, Capacitor-Type, Fuel-Quantity-Gage Tank Unit, Type MD-2A
MIL-C-5015	Connectors, Electric, "AN" Type
MIL-E-5272	Environmental Testing, Aeronautical and Associated Equipment, General Specification for
MIL-E-5400	Electronic Equipment, Aircraft, General Specification for
MIL-G-5572	Gasoline, Aviation: Grades 80/87, 91/96, 100/130, 115/145
MIL-J-5624	Jet Fuel, Grades JP-3, JP-4, and JP-5
MIL-I-6181	Interference Control Requirements, Aircraft Equipment
MIL-L-6880	Lubrication of Aircraft, General Specification for
MIL-P-6906	Plates, Information and Identification

FSC 6680

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.

MIL-W-7139	Wire, Electrical, Insulated, Copper, 600-Volt, 400° Fahrenheit
MIL-S-7742	Screw Threads, Standard, Optimum Selected Series: General Specification for
MIL-P-7936	Parts and Equipment, Aeronautical Preparation for Delivery
MIL-G-7940	Gages, Fuel Quantity, Capacitor Type, Installation and Calibration of
MIL-T-8579	Tester, Fuel Quantity Gage, Variable Capacitance, Field, Type MD-1
MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys
MIL-W-16878	Wire, Electrical (Insulated, High Temperature)
MIL-L-25467	Lighting, Integral, Instrument, General Specification for
MIL-C-25516	Connectors, Electrical, Miniature, Shielded or Unshielded, Environmental Resistant Type, General Specification for
MIL-D-70327	Drawings, Engineering and Associated Lists

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property
MIL-STD-704	Electric Power, Aircraft, Characteristics and Utilization of
MS33586	Metals, Definition of Dissimilar
MS33639	Cases, Instrument, Clamp - Mounted, Aircraft

Air Force-Navy Aeronautical

AN4130	Fitting - Synthetic Tank Single Plane Flush and Recessed
AN10412	Case - 2-Inch Size Instrument, Standard Dimensions for

PUBLICATIONS

Air Force-Navy Aeronautical Bulletin

No. 143	Specifications and Standards; Use of

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.

Page 3: Add the following paragraph:

"3.01 Definitions.- For definitions of terms used in this specification see 6.4."

Page 3, paragraph 3.1: Delete, and substitute:

"3.1 Preproduction.- This specification makes provision for preproduction testing. (See 4.1 and 6.2.)"

Page 3, paragraph 3.3.4, line 3: Delete "Drawing AND10398" and substitute "Standard MS33586".

Page 5, paragraph 3.4.7, line 3: Delete "MIL-F-5624" and substitute "MIL-J-5624".

Page 6, paragraph 3.4.8.4.3, line 4: Delete "Drawing" and substitute "Standard".

Page 8, FIGURE 1: Delete "DRAWING" and substitute "STANDARD" in the "case" legend.

Page 9, FIGURE 2: Delete "MS33554" in "case" legend and substitute "MS33639".

Page 10, FIGURE 3: Delete "DRAWINGS" and substitute "STANDARDS" in the "case" legend.

Page 11, FIGURE 4: Delete "MS33516" in "case" legend and substitute "MS33639".

Page 12, FIGURE 5: Delete "MS33516" in "case" legend and substitute "MS33639".

Page 14, paragraph 3.4.8.7, line 3: Delete "type RG-179/u of Specification MIL-C-8721" and substitute "type RG-179A/u of Specification MIL-C-17".

Page 14, paragraph 3.4.8.9, line 2: Delete "Specification MIL-E-7894" and substitute "Standard MIL-STD-704".

Page 15, paragraph 3.5, line 4: Delete "MIL-D-5028" and substitute "MIL-D-70327".

Page 16: Add the following paragraph:

"4.01 Inspection responsibility.- The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 16, paragraph 4.1: Delete, and substitute:

"4.1 Classification of tests.- The inspection and testing of gages shall be classified as follows:

(a) Preproduction tests (4.2)
(b) Acceptance tests (4.3)"

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.

Page 28, paragraph 4.5.17.3, line 2: Delete "Procedure I" and substitute "Procedure XII".

Page 30, paragraph 4.5.23, line 4: Delete "MIL-F-5624" and substitute "MIL-J-5624".

Page 31: Add the following paragraph:

"4.5.30 Inspection of packaging and packing.- The inspector shall ascertain that preparation for delivery conforms to the requirements of section 5."

Page 31, paragraphs 5.1, 5.2, and 5.2.1: Delete, and substitute:

"5.1 Packaging and packing.- The indicator shall be packaged and packed for shipment in accordance with Specification MIL-P-7936."

Page 32, paragraph 5.3.1: Delete.

Page 32, paragraph 6.2: Add the following:

"(d) Where the preproduction test samples should be sent and instructions concerning the submittal of the test reports."

Page 33, paragraphs 6.3 and 6.3.1: Delete.

Page 34: Add the following paragraph:

"6.5 International agreements.- Certain provisions of this specification are the subject of international standardization agreement (ABC Air Std 13/10). When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned."

Custodians:
Navy - Bureau of Naval Weapons
Air Force
International interest (see 6.5)

Preparing activity:
Navy - Bureau of Naval Weapons

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.