INCH–POUND

MIL–S–8802F
AMENDMENT 2
24 March 1992

SUPERSEDING
MIL–S–8802F
AMENDMENT 1
27 March 1991

MILITARY SPECIFICATION

SEALING COMPOUND, TEMPERATURE–RESISTANT, INTEGRAL FUEL TANKS AND FUEL CELL CAVITIES, HIGH ADHESION

This amendment forms a part of MIL–S–8802F, dated 7 March 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

3.4.9, line 2, delete "30" and substitute "35."

PAGE 15

4.4, delete and substitute:

"**4.4 Quality conformance inspection.** Quality conformance inspection requirements can be satisfied by the use of a third party accreditation system in accordance with AS 7001, AS 7002, AS 7003, and AS 7200/1 or by fulfilling the requirements of 4.4.2 and 4.4.3. If the third party system is used, written approval from WL/MLSE, Wright–Patterson AFB OH that the third party system meets the requirements of the above AS documents is required. The sealant manufacturer must be accredited by the third party system and product surveillance must be done on each batch of material by the third party system. All tests specified in 4.4.2 and 4.4.3 must be performed by the manufacturer and/or distributor."

4.4.2, line 6 add: "and air content (Class B only)."

PAGE 16

Paragraph 4.4.2.3: Delete.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.

PAGE 17

Paragraph 4.4.3, 1., (2): Delete.

PAGE 18

4.5, line 3: Delete "prepared and."

4.6.2.2, first line, delete and substitute:

"**4.6.2.2 Special cleaning of graphite epoxy and titanium panels.** The graphite epoxy and titanium panels shall be cleaned by first solvent wiping with MIL–C–38736 cleaner."

PAGE 19

4.6.6.1, delete last sentence.

PAGE 24

4.8.10, line 4, delete "1/8 inch (3 mm)" and substitute "1/4 inch (6 mm)."

PAGE 31

4.8.20, line 5, delete "with 4.8.5, 4.8.6, 4.8.7, and 4.8.8." and substitute "with 4.8.5, 4.8.6, 4.8.7, 4.8.8, and 4.8.9."

4.8.20, line 5, delete "Two QQ–A–250/13 aluminum alloy panels" and substitute "Two QQ–A–250/12, T6 sulfuric acid anodized in accordance with MIL–C–27725 peel panels."

Custodians:
Army – MR
Navy – AS
Air Force – 11

Preparing activity:
Air Force – 11

(Project No. 8030–0635)

Review activities:

Army – MI, AR, AT
Navy – SH, OS
Air Force – 84, 99
DNA – DS

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.