INCH-POUND

MIL-S-8802F
AMENDMENT 3
3 May 1993
SUPERSEDING
AMENDMENT 2
24 MARCH 1992

MILITARY SPECIFICATION

SEALING COMPOUND, TEMPERATURE-RESISTANT, INTEGRAL FUEL TANKS AND FUEL CELL CAVITIES, HIGH ADHESION,

This amendment forms a part of MIL-S-8802F dated 7 March 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.2 a. Types, (1): Delete "Type I – Dichromate cured sealing materials" and substitute "Type I – Cancelled, Type II is authorized for all previous uses of Type I"

PAGE 2

* 1.2.2, delete first sentence.

PAGE 3

* 2.2 Add:

AS 7001	National Aerospace and Defense Contractors Accreditation Program (NADCAP) Program Description
AS 7002	National Aerospace and Defense Contractors Accreditation Program (NADCAP) Rules for Implementation
AS 7003	National Aerospace and Defense Contractors Accreditation Program (NADCAP) Program Operations
AS 7100/1	National Aerospace and Defense Contractors Accreditation Program (NADCAP) Survey Checklist for the NDT Suppliers Accreditation Program
AS 7200/1	National Aerospace and Defense Contractors Accreditation Program (NADCAP) Audit and Inspection Checklists for the Sealant Manufacturers Accreditation Program
AS 7201	National Aerospace and Defense Contractors Accreditation Program (NADCAP) Requirements for Accreditation of Pass-Thru Distributors
AS 7202	National Aerospace and Defense Contractors Accreditation Program (NADCAP) Requirements for Accreditation of Value Added Distributors

(Applications for copies should be addressed to the Society of Automotive Engineers, Inc., 400 commonwealth Drive, Warrendale, PA 15096.)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.

PAGE 6

* 3.4.1, delete and substitute:

"**3.4.1 Specific gravity**: When tested in accordance with 4.8.1, the specific gravity of the cured sealing compound shall not be more than 1.65 for Type II at standard conditions (see 4.5)."

*3.4.2, line 4, delete "Type I – 90 percent by weight."

PAGE 7

3.4.9, line 2, delete "30" and substitute "35."

PAGE 11/12

* Table IV and Table V: Delete Type I portion of tables and substitute "Type II".

PAGE 13

* 4.1.2, delete and substitute:

"**4.1.2 Source inspection.** Materials procured by the Government under this specification shall be third party approved prior to shipment, to assure that the material meets the quality conformance tests (4.4.3). The third party approval shall be by a third party accreditation process in accordance with AS 7001, AS 7002, AS 7003, and AS 7200/1. Sealant manufactured to this specification shall be from a manufacturer that currently holds a third party accreditation and shall be from a batch of material that has been third party sourced inspected in accordance with AS 7200/1. Distributors supplying sealant to this specification shall supply material from an accredited manufacturer and from a batch of material that has been third party source inspected. Distributors shall also be third party accredited in accordance the AS 7201 or AS 7202, whichever is applicable. Note that 4.4.2 requires that the sample for quality conformance tests be packaged and mixed as much as practical in the same containers that are being procured."

PAGE 15

* 4.4, delete and substitute:

"**4.4 Quality conformance inspection.**"

*4.4.2, line 6 add: "and air content (class B only, premixed and frozen material excluded)."

PAGE 16

4.4.2.3: Delete.

PAGE 17

4.4.3, l, (2): Delete.

PAGE 18

* 4.5, delete and substitute:

"**4.5 Test conditions.** Standard laboratory conditions are 77°F ± 2°F (25°C ±1°C) and 50 ±5 percent relative humidity. Unless otherwise specified, all test specimens shall be cured under these condition and all test shall be performed at 77°F ± 2°F (25°C ±1°C)."

4.6.2.2, first line, delete and substitute:

* "**4.6.2.2 Special cleaning of graphite epoxy and titanium panels.** The graphite epoxy and titanium panels shall be cleaned by first solvent wiping with MIL-C-38736 cleaner."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.

PAGE 19

4.6.6.1, delete last sentence.

PAGE 22

* 4.8.5.1 sentence 2 delete; line 13 after "its forward travel" add: "At this point the fixture must be at standard conditions (4.5) and kept there for the duration of the test."

* 4.8.5.2 sentence 2 delete and substitute: "Immediately place the panel at standard conditions (4.5) in a vertical position and allow to stand for a period equivalent to the rated tack-free time (see 3.4.8)."

* 4.8.6.1 First and second sentence delete and substitute: "The base compound and accelerator shall stabilize at standard temperature for at least 8 hours before a sample of base compound is mixed with the proper amount of accelerator sufficient to fill a standard 1/2-pint can (1.3 liter) 2-7/8 inches in diameter by 2-7/8 inches high (73 mm by 73 mm) to within 1/2 inch (10 mm) of top. This can shall be tightly covered with the original can lid, except when testing the viscosity."

PAGE 23

* 4.8.6.2 First sentence delete and substitute: "The base compound, accelerator and application gun shall stabilize at standard temperature for at least 8 hours before a minimum of 250 grams of base compound are mixed with the proper amount of accelerator.".

* 4.8.7 Fifth sentence delete and substitute: "Apply approximately 0.015 inches (0.40 mm) of freshly mixed sealant to the drilled end of the specimens and allow to cure at standard conditions (4.5) for 1/2 hour."

PAGE 24

4.8.10, line 4, delete "1/8 inch (3 mm)" and substitute "1/4 inch (6 mm)".

4.8.20, line 5, delete "with 4.8.5, 4.8.6, 4.8.7 and 4.8.8" and substitute "with 4.8.5, 4.8.6, 4.8.7, 4.8.8 and 4.8.9".

4.8.20, line 5, delete "Two QQ-A-250/13 aluminum alloy peel panels" and substitute "Two QQ-A-250/12, T6 sulfuric acid anodized in accordance with MIL-A-8625, type II, class 1, coated with MIL-C-27725 peel panels.

PAGE 32

*4.8.22 (3) First sentence delete and substitute: "Fill base compound into cartridge being careful not to introduce air."

NOTE: The margins of this amendments marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidder and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationships to the last previous issue.

Custodians:
Army – MR
Navy – AS
Air Force – 11

Review activities:
Army – MI, AR, AT
Navy – SH, OS
Air Force – 84, 99
DNA – DS

Preparing activity:
Air Force – 11

Proj No. 8030-0673

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:56Z
Check the source to verify that this is the current version before use.