MIL-E-45188 (ORD)
22 October 1958
Superseding
OAC-PD-73
11 March 1957

(PROPOSED)

MILITARY SPECIFICATION

END, METALLIC BELT, CALIBER .30

1. SCOPE

1.1 This specification covers ends for caliber .30 metallic belts for use in the caliber .30 Browning Machine Gun.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATIONS

MILITARY

MIL-G-2550 - General Specification for Ammunition Except Small Arms Ammunition

MIL-P-10025 - Packing and Marking for Domestic Shipment of Inert Ammunition Components; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

A-5155914 - End, Metallic Belt, Cal. .30

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedures and Tables for Continuous Sampling by Attributes

(Copies of specifications, standards, drawings, and publications, required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

PSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.-Material shall be in accordance with applicable specifications and drawings.

3.2 End.-The end shall comply with all requirements specified on Drawing (Dwg) A5155914 and with all requirements specified in applicable specifications.

3.3 Hardness.-The ends shall meet the requirements for hardness specified on Dwg. A5155914 when tested as specified in 4.4.

3.4 Workmanship.-All ends shall be free of chips, dirt, grease, rust and other foreign material. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 General Provisions.-The quality assurance provisions contained in this section are applicable to inspection performed by or for the Government and shall be performed as prescribed below.

4.1.1 Contractor Quality Assurance System.-The contractor shall provide and maintain an effective Quality Assurance System acceptable to the Government covering the supplies under this contract. Results of all examinations and test performed under the Quality Assurance System shall be provided. A current written description of the system shall be submitted to the contracting officer prior to initiation of production. The written description will be considered acceptable when as a minimum, it provides the Quality Assurance required by this specification and other documents referenced in this specification. The contractor shall not be restricted to the inspection station nor to the method of inspection listed provided that an equivalent control is included in the approved quality assurance procedure. In cases of dispute, as to whether certain procedures of the system provide equal assurance, the comparable procedure of this specification shall be used. The contractor shall notify the Government of and obtain approval for any change to the written procedure that affects the degree of assurance that is required by this specification or other documents referenced herein.

4.1.1.1 At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all Quality Assurance Provisions of written plan and all requirements as stated in the contract.

b. Number of units of product inspected.

c. Results obtained for all inspections performed.

d. Drawing and specification numbers and dates. Together with an identification and date of changes.

e. Certificates of analysis including results of tests on materials used in the lot.

f. Number of items in lot.

g. Date submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

4.1.1.2 The certificate shall be signed by a responsible agent of the certifying organization and shall be accompanied by evidence of the agent's authority to bind his principle.

4.1.2 Government Verification Inspection.

4.1.2.1 At the beginning of the contract, Government verification will consist of: (a) all inspections listed herein which are not reserved for sole performance by the contractor, (b) a monitoring of those inspections reserved for sole performance by the contractor, and (c) monitoring of the contractor's inspection and quality control operations. Monitoring is defined in 4.1.2.2.

4.1.2.2 A reduced plan of inspection may be initiated after the contracting officer has determined that the following conditions have been complied with:

a. Ten consecutive lots have been accepted under normal inspection.

b. The estimated process average is less than the applicable lower limit shown in Table II of MIL-STD-105A.

c. Production is at a steady rate.

In the event that product quality is found to be undesirable as evidenced by the results of a periodic audit inspection or verification, or, if deviations from the prescribed are noted the Government inspector will reinstate normal inspection verification. Tightened inspection verification shall be instituted when the estimated process average exceeds the applicable upper limit shown in Table II of MIL-STD-105A. Using the contractor's written Quality Assurance Procedure, this specification and other contractual conditions as a guide, the Government inspector shall monitor all quality assurance operations performed by the contractor, at periodic, but unscheduled intervals. Monitoring consists of surviellance of the operations to determine whether the practices, methods, and procedures of the written procedure are being properly applied. Deviations from the prescribed or agreed upon procedures, or instances of poor practices which might have an effect upon the quality of the production shall be immediately called to the attention of the contractor. To avoid interference with operations, the contractor shall designate a responsible official or officials to whom the inspector will report such instances. Failure of the contractor to promptly correct deficiencies discovered shall be cause for rejection of the lot until corrective action has been taken to the satisfaction of the Government inspector. As an adjunct to his monitoring activities, the inspector may conduct inspection, at unscheduled, random intervals, of product from lots which have been inspected and found to be acceptable by the contractor.

4.1.2.3 Lot.-Unless otherwise specified in the contract or purchase order, a lot shall consist of all ends produced by one manufacturer, under one contract, in accordance with the same drawing, same drawing revision, same specification, and same specification revision.

4.2 Sampling.

4.2.1 Classification of Defects.-Sampling for all inspections listed under 4.3.2 will be conducted by the inspector in accordance with Standard MIL-STD-105 or Ordnance Inspection Handbook ORD-M608-11, as determined by the procuring activity.

4.2.2 Hardness Test.-Thirty-five (35) ends will be selected by the inspector from each eight hours production for the test specified in 4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

4.3 Inspection.

4.3.1 General.-Inspection will be as specified in Specification MIL-G-2550 and as specified herein. This inspection procedure is included for the information of the contractor and is not considered to be within the scope of work of the contract. Both the amount of inspection and the number of characteristics inspected may be increased by the contracting officer if difficulty is experienced with the material accepted or if one or more unlisted characteristics are not being controlled in a manner commensurate with their importance. If a sample does not pass the inspection, the material from which the sample was taken will be rejected; however, the contractor may screen out the defect or defects causing failure and resubmit the material if he so desires.

4.3.2 Classification of defects.-Inspection of the ends shall be as follows:

Categories and Defects	Method of Inspection
Minor AQL 4.00 percent	
41. Location of angle and bend.	Gage
42. Width outside tolerance.	Gage
43. Thickness outside tolerance.	Gage
44. Inside diameter of small loop.	Gage
45. Inside diameter of large loop.	Gage
46. Width of loop gap, max.	Gage
47. Radii at origin of loop.	Gage
48. Protective coating improper or incomplete.	Visual

4.4 Rockwell Hardness Test.-Samples selected as specified in 4.2.2 shall be tested by the contractor on a Rockwell Hardness Tester for compliance with the drawing requirements for hardness. The test shall be witnessed by the inspector. If any ends are found which do not meet drawing requirements, the production represented by the sample shall be rejected, not subject to retest.

5. PREPARATION FOR DELIVERY

5.1 Packing.

5.1.1 Level C.-Metallic belt ends shall be packed in accordance with specification MIL-P-10025.

5.2 Marking.

5.2.1 Containers shall be marked in accordance with specification MIL-P-10025.

5.3 Data card information shall be in accordance with specification MIL-G-2550.

6. NOTES

6.1 Ordering Data.-Procurement documents should specify the title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

NOTICE

This purchase description, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Custodian:
Army Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.