MIL-H-45193D
17 January 1985
SUPERSEDING
MIL-H-45193C
15 December 1977

MILITARY SPECIFICATION

HEATERS, GUN TYPE, ELECTRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and three sizes of portable, manually operated, hand held, electric heater gun used to supply a steady flow of air and heated air.

1.2 Classification.

1.2.1 Sizes. The heater gun shall be one of the sizes-corresponding to the heat ranges below, as specified (see 6.2.1):

Size 1 - +300°Fahrenheit (F) or less to +500°F or more
Size 2 - +500°F or less to +750°F or more
Size 3 - +750°F or less to +1000°F or more

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, ATTN: SMCAR-ETS (R), Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

CC-M-1807	- Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller).
UU-P-268	- Paper, Kraft, Wrapping.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-C-843	- Cushioning Material, Cellulosic.
PPP-T-60	- Tape, Packaging, Waterproof.

MILITARY

MIL-P-116	- Preservation, Methods of.

STANDARDS

FEDERAL

FED-STD-H28	- Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; With Appropriate Test Methods.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, Battery March Park, Quincy, MA 02269.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of Precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2.1), the contractor shall furnish one or more complete heater guns for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

* 3.2 Design. The heater gun shall be designed to deliver air at the temperature and in the volume specified herein. The heater gun shall be designed for operation when held with one hand or when resting on a stand. All parts subject to wear, breakage, or distortion shall be accessible for adjustment and repair by the use of common hand tools.

* 3.3 Material. The heater gun and its components shall be free of asbestos material, including amosite, chrysotile crocidolite, tremolite, anthophyllite, and actinolite. Materials not specifically designated herein or in the contract shall be of a quality commensurate with the best commercial practice within the electric heater gun industry. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

* 3.3.1 Reclaimed materials. The contractor is encouraged to use reclaimed materials for fabricating new parts without jeopardizing the chemical and physical properties, design integrity, and intent of the materials originally selected or specified. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner that shall restore them to the same chemical composition and physical properties as the materials originally selected for use. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment.

3.4 Construction. All parts and materials used in fabricating the heater gun shall be free of defects. In no event shall patching processes be used to reclaim defective parts. External surfaces shall be smooth and free of sharp edges. The construction of the heater gun shall be rugged and sturdy, and commensurate with the best commercial practice within the electric heater gun industry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

3.4.1 Castings and forgings. All castings shall be free from blowholes, porosity, hard spots, shrinkage defects, cracks, or other defects. Forgings shall be free from scale, inclusions, cold shuts, mismatching, sharp edges, or other defects. Castings and forgings shall be free from any properties adversely affecting their strength, durability, or suitability.

* 3.4.2 Welding, brazing, and soldering. Welding, brazing, and soldering shall be of a quality which shall sustain the performance requirements of the welded, brazed, or soldered part. However, these operations shall not be employed as repair measures for defective parts.

3.4.3 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for adjustment, and for preventing loss of tightness. All parts subject to removal or adjustment shall not be swaged, peened, staked, or otherwise deformed.

* 3.4.4 Electrical connections. Connections to screw-type terminals shall be mechanically secured with means to prevent loss of tightness. All other electrical connections shall be mechanically secured and soldered or brazed. Only rosin base fluxes shall be used in all soldering operations.

* 3.4.5 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

* 3.4.6 Safety provisions. Safety devices shall be provided for all parts presenting safety hazards to personnel. The operator's manual shall clearly outline any safety precautions relevant to the assembly, operation, disassembly, and repair of the heater gun. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.4).

* 3.4.6.1 Underwriter's Laboratories approval. Proof shall be submitted that the heater gun conforms to the standards of the Underwriter's Laboratories, Inc. The label of the Underwriter's Laboratories shall be accepted as conforming to this requirement. In lieu of the label, a written certification may be submitted from any nationally recognized testing agency, adequately equipped and competent to perform such services, that the heater gun has been tested and conforms to the standards, including method of test, of the Underwriter's Laboratories.

3.4.7 Interchangeability. All replaceable parts shall be designed and manufactured to such standards as shall permit replacement and adjustment without the need for modification of the parts or the electric heater gun.

3.4.8 Surfaces. Surfaces of all castings, forgings, molded parts, stampings, and welded parts shall be clean and free of sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous materials.

* 3.5 Performance and product characteristics. The operating temperatures of the Size 1 heater gun shall be from +300°F to +500°F. The operating temperatures of the Size 2 heater gun shall be from +500°F to +750°F. The operating temperatures of the Size 3 heater gun shall be from +750°F to +1000°F. The operating temperature for each size heater gun shall be the air temperature at the face of the air discharge tube. The heater gun shall provide a steady

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

flow of air in accordance with the requirements specified herein at a volume of at least 20 cubic feet per minute when operated in an ambient temperature of +75°F +5°F.

* 3.5.1 Operational cycle. The heater gun shall be capable of withstanding, without damage or malfunction, eight successive operation cycles with the small heat reflector attached. Each cycle shall consist of 45 minutes on and 15 minutes off, and shall be set for the temperatures listed below.

Size 1 - +500°F ± 25°F
Size 2 - +750°F ± 25°F
Size 3 - +1000°F ± 25°F

* 3.5.2 Temperature stability. Size 1 heater guns shall provide air at +500°F + 25°F within two minutes of the heater being activated. Size 2 heater guns shall provide air at +750°F + 25°F within two minutes of the heater being activated. Size 3 heater guns shall provide air at +1000°F ± 25°F within two minutes of the heater being activated. Upon attaining any desired operational temperature, that temperature shall vary no more than + 25°F without adjusting the heater gun for another operational temperature.

3.5.3 Dielectric strength. The heater gun shall withstand, without damage, a root mean square (rms) voltage of 1,000 volts plus twice its rated voltage applied for a period of one minute between each insulated circuit and the heater gun body. The voltage shall be a frequency of 60 Hertz (Hz).

* 3.5.4 Physical dimensions. The heater gun shall have physical dimensions that allow it to fit into a space no larger than 16 inches long by 12 inches high by 6 inches deep with the electrical cord attached to and stowed with the heater gun, and with the rest stand not attached to the body. The heater gun shall weigh no more than four pounds with the rest stand attached.

3.6 Detail of components. The heater gun shall consist primarily of the following major components:

(a) Body, with attachable stand, and handle
(b) Blower and motor
(c) Heating element
(d) Electric control switch
(e) power supply cord
(f) Air regulator
(g) Heat reflectors

* 3.6.1 Body and handle. The body and handle shall be fabricated of materials capable of withstanding the temperature and performance requirements specified herein. The handle shall be designed for easy handling and to perform the operation specified herein. The heater gun body shall incorporate a positively attached stand upon which the heater gun may rest stably during use or cool-down. The heater gun shall provide useable air, in accordance with the requirements specified herein, in either the hand held position or the rest stand position. The stand shall permit the heater gun to be positioned at any point within the 90 degree range between the angle parallel to the rest surface and the angle perpendicular to the rest surface. When attached to the heater gun, the stand shall not interfere with the normal operation of the heater gun.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

* 3.6.1.1 Protective screen. A protective mesh screen shall be provided to cover the open end of the heat discharge tube. The mesh size shall be such that an object 1/8 inch by 1/8 inch by 1/8 inch or larger shall not pass through the screen. The screen shall be separated from the heater element by at least 0.50 inch, and shall be designed to withstand without degradation the temperatures to which it will be subjected.

* 3.6.2 Electrical equipment. All electrical equipment and wiring, except when otherwise specified herein, shall be in accordance with NFPA 70.

3.6.2.1 Blower and motor. The blower shall be located so that it cools the motor as well as deliver air in accordance with the requirements specified herein. The motor shall conform to the requirements of CC-M-1807 and operate from 120 or 115 volts, 60 Hz, single phase alternating current.

* 3.6.2.2 Temperature rise. The heating element shall be insulated from other components of the heater gun so that the following temperature rises are not exceeded when the heater gun is operated in an ambient temperature of +75°F +5°F.

(a) Body temeprature adjacent to the nozzle shall be no more than 60°F above ambient.
(b) Body temperature adjacent to the motor shall be no more than 50°F above ambient.
(c) Nozzle temperature shall be no more than 300°F above ambient.

* 3.6.2.3 Electric control switch. The electric control switch may be either a toggle or rocker switch. The switch shall have three positions: one to operate the blower and heating element, one to operate the blower only, and one off position. When an automatic release switch is furnished, provision shall be made for locking the switch in each operating position. The switch shall be furnished with a permanent guard that shall minimize the likelihood of inadvertent actuation of the switch. The guard shall not interfere with normal operation of the gun. When the heater control switch is turned off, the switch will return to the fan or blower position before going to “total off” for the heater gun.

* 3.6.2.4 Power supply cord. Unless otherwise specified (see 6.2.1), the heater gun shall be wired with not less than six feet -of three-conductor, flexible electrical cord. The cord shall conform to NFPA 70 with a voltage and current-carrying capacity not less than the voltage and current rating of the motor and heater element. The power supply cord shall be oil and abrasive resistant, neoprene jacketed, and provided with a three-prong plug.

3.6.3 Air regulator. The heater gun shall incorporate an air regulating system which shall control the discharge air within the temperature range, volume, and velocity specified herein. Suitable markings shall be provided and shall be associated with the adjustment means to permit varying the temperature within the specified heat range. The markings shall indicate the direction of adjustment for increasing and decreasing the discharge air temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

* 3.6.4 Heat reflectors. Two heat reflectors, each with means for positive attachment to the discharge tube, shall be provided for use in shrinking heat-shrinkable tubing. The reflectors shall provide for the even distribution of heat to the tubing over at least 1.50 inch length. One reflector shall provide for use with tubing up to 0.75 inch diameter, and one reflector shall be provided for use with tubing from 0.75 inch to at least two inch diameter.

3.7 Product identification. The heater gun shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2.1), shall include the National Stock Number.

3.8 Workmanship. The heater guns, including all parts and accessories, shall be fabricated and finished in a workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp edges, marking of parts and assemblies, thoroughness of soldering, welding, brazing, painting, wiring and riveting, and alignment of parts and tightness of fastening devices.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection.

* 4.4.1 Inspection and test. Unless otherwise specified (see 6.2.1), quality conformance inspection shall be applied to production items offered for acceptance under the contract and shall consist of (a) through (c) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) product examination (see 4.5).
(b) Tests of 4.6.1 and 4.6.3.
(c) packaging inspection (see 4.7).

Source: https://assist.dla.mil – Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

* 4.4.2 Sampling. Sampling for quality conformance inspection shall in conformance with MIL-STD-105 using the following inspection Levels and Acceptable Quality Levels (AQL):

Inspection or test	Level	AQL
Product examination (see 4.5)	II	1.0
Tests (see 4.6.1 and 4.6.3)	II	1.0
Packaging inspection (see 4.7)	S-4	4.0

* 4.5 Product examination. The heater guns shall be examined to determine compliance with the requirements of Section 3 and the contract. As a minimum, the following characteristics shall be examined:

CHARACTERISTICS	REQUIREMENT PARAGRAPH
Design	3.2
Material	3.3
Reclaimed materials when applicable	3.3.1
Construction	3.4
Castings and forgings	3.4.1
Welding, brazing and soldering	3.4.2
Fastening devices	3.4.3
Electrical connections	3.4.4
Threads	3.4.5
Safety provisions	3.4.6
Underwriter's Laboratories approval	3.4.6.1
Interchangeability	3.4.7
Surfaces	3.4.8
Performance and product characteristics	3.5
Operational cycle	3.5.1
Temperature stability	3.5.2
Dielectric strength	3.5.3
Physical dimensions	3.5.4
Components	3.6
Body and handle	3,6.1
Protective screen	3.6.1.1
Electrical equipment	3.6.2
Blower and motor	3.6.2.1
Temperature rise	3.6.2.2
Electric control switch	3.6.2.3
Power supply cord	3.6.2.4
Air regulator	3.6.3
Heat reflectors	3.6.4
Product identification	3.7
Workmanship	3.8

A certificate of conformance may be provided to satisfy the examination requirement where more than a visual or dimensional verification is necessary.

4.6 Tests.

* 4.6.1 Performance test. The performance test shall be conducted in an ambient temperature of +75°F ±5°F. After operating the heater for at least 30 minutes with the heater gun on and blowing heated air at the maximum setting, the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

temperature of the body and nozzle shall be measured to determine compliance with 3.6.2.2. The temperature range, temperature stability, and volume shall be measured to determine compliance with 3.5.

* 4.6.2 Operational cycle. The heater gun shall be subjected to eight successive cycles of operation, with the temperature at the maximum setting, with each cycle consisting of 45 minutes on and 15 minutes off. At the conclusion of the test period, the heater shall be tested in accordance with 4.6.1.

4.6.3 Dielectric strength test. The heater gun shall be subjected to 1,000 volts rms plus twice the rated voltage between each insulated circuit and the heater body in accordance with 3.5.3. The voltage shall be attained within one second and maintained for a period of one minute. The heater gun shall then be inspected for evidence of damage. Failure to pass the dielectric test, or any resulting physical damage due to the dielectric test, shall be cause for rejection.

* 4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5. PACKAGING

* 5.1 Preservation. Preservation shall be Level A or Industrial. Unless otherwise specified (see 6.2.1), Industrial preservation shall be provided. When military (Level A) preservation is required, it shall be so specified in the contract.

5.1.1 Level A.

5.1.1.1 Cleaning and drying. Each heater gun shall be cleaned and dried in accordance with MIL-P-116. Cleaning shall be accomplished in accordance with process C-1 and drying shall be in accordance with any applicable procedure.

5.1.1.2 Disassembly. The heater guns may be disassembled to effect saving in cubage provided no special skill or tools are required for reassembly.

5.1.1.3 Unit packaging. Each gun shall be unit packaged in accordance with method IIe of MIL-P-116. The item shall be protected with cushioning material conforming to PPP-C-843, class B, type II, prior to placing in a snug fitting container. Isolate component parts to prevent marring or scratching the surfaces.

The unit container shall be overwrapped with paper conforming to UU-P-268 and secured with tape conforming to PPP-T-60. Closure shall be. accomplished in accordance with the container specification.

* 5.1.2 Industrial. Industrial preservation shall be as specified in ASTM D3951-82.

* 5.2 Packing. Packing shall be Level A, Level B, or Industrial. Unless otherwise specified (see 6.2.1), Industrial packing shall be provided. When military (Levels A and B) packing is required, it shall be so specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

* 5.2.1 Level A. Unit packages shall be packed in containers conforming to PPP-B-601, overseas type, or PPP-B-621, class 2. Blocking, bracing, and cushioning as applicable, shall be in accordance with MIL-STD-1186.

5.2.2 Level B. Unit packages shall be packed as specified in 5.2.1 except the shipping container shall conform to PPP-B-640, class 2.

* 5.2.3 Industrial. Industrial packing shall be as specified in ASTM D3951-82.

* 5.3 Marking. Marking shall be Level A, Level B, or Industrial. Unless , otherwise specified (see 6.2.1), Industrial marking shall be provided. When military (Levels A and B) marking is required, it shall be so specified in the contract.

* 5.3.1 Level A and B marking. Level A and B marking shall be as specified in MIL-STD-129.

* 5.3.2 Industrial marking. Industrial marking shall be as specified in ASTM D3951-82.

6. NOTES

* 6.1 Intended use. The heater gun is intended to be used for any thawing or drying operation requiring a stream of air and heated air. The heater is also intended to be used on heat shrinkable products used in electrical or electronic wiring requiring a stream of air and heated air.

6.2 Ordering data.

* 6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2.1).
(c) First article when required (see 3.1).
(d) Additional safety/health provisions required (see 3.4.6).
(e) Power supply cord if different (see 3.6.2.4).
(f) Product identification if different (see 3.7).
(g) Technical data required (see 3.8).
(h) First article inspection if different (see 4.3).
(i) Quality conformance inspection if different (see 4.4).
(j) Level of preservation, packing, and marking if different (see 5.1, 5.2, and 5.3).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract (see 6.3.1).

* 6.3.1 Repair part manuals. Repair part identification, in repair part manuals, shall include the prime contractor's name, nomenclature, part number, and price. Repair part identification shall also include the name of the original equipment/part manufacturer (OEM - actual part manufacturer), Federal Supply Code for Manufacturers (FSCM), nomenclature, part number and price of the part

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

immediately after the prime contractor's part identification. High mortality rate items shall be so identified as shown in MIL-M-7298.

* 6.4 Safety and health requirements. In order that equipment integrated into the user’s operational environment will comply with OSHA limitations and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc, as applicable, specific requirements concerning such points of operation, and other health and safety requirements, should be specified by the user (see 3.4.6).

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - AL
Air Force - 99

Review activity:
Air Force - 82

Preparing activity:
Army - AL

Project No. 4940-0470

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US ARMY Armament Research and Development Center
Attn: SMCAR-ETS (R)
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(FOLD ON THIS LINE)

(FOLD ON THIS LINE, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:32Z
Check the source to verify that this is the current version before use.