MIL-E-1/104B
28 December 1967
SUPERSEDING
MIL-E-1/104A
7 January 1954

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 1A5GT

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, power amplifier (B)

Outline	---	9-11 or 9-41 (EIA)
Base	---	B6-81, B6-84, B7-7, or B7-59
Envelope	---	T9
Cathode	---	Coated filament

Base connections:

Pin No.	---	1	2	3	4	5	7	8
Element	---	nc	+f	p	g2	g1	-f, g3	nc

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ik	Alt
Unit:	Vdc	Vdc	Vdc	Vdc	mAdc	ft
Maximum:	1.6	110	---	110	6.5	10,000
Minimum:	1.0	---	---	---	---	---
TEST CONDITIONS:	1.4	90	-4.5	90	---	---

REQUIREMENT OR TEST:

GENERAL

3.2 Qualification - Required

E-50.2 Holding period

E-50.3 Preheating

5. Preparation for delivery

(B) denotes technical changes only.

Source: https://assist.dla.mil -- Downloaded: 202610-15T12:55Z
Check the source to verify that this is the current version before use.

METHOD OR PARAGRAPH	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	See note 1	0.65	II	Ic1	0	-1.0	µAdc
Ⓑ 1246	Audio frequency noise	Esig = 700 mVac; Rp = 2,000 ohms (see note 2)	0.65	II	---	---	---	---
1341	Power output (2)	Power output (1); Ef = 1.1 Vdc (see note 1)	0.65	II	Po	60	---	mW
1256	Electrode current (anode)		0.65	II	Ib	2.8	5.2	mAdc
1201	Short and discontinuity detection		0.4	II	---	---	---	---
Appendix D, 20(a), 30	Visual and mechanical inspection criteria		---	---	---	---	---	---
Appendix D, 20(b)	Dimensions	Outline 9-11 or 9-41; dimensions A thru D	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
1211	Insulation of electrodes		4.0	L6	R	10	---	Meg
1031	Low-frequency vibration	Rp = 2,000 ohms	6.5	L6	Ep	---	500	mVac
1111	Base pin solder depth		6.5	L6	---	---	---	---
1301	Filament current		6.5	L6	If	44	56	mAdc
1101	Secureness of base and base insert		6.5	L6	---	---	---	---
1256	Electrode current (screen)		6.5	L6	Ic2	0.5	1.5	mAdc
1341	Power output (1)	Esig = 3.2 Vac; Rp = 25,000 ohms	6.5	L6	Po	90	---	mW
1306	Transconductance		6.5	L6	Sm	775	1,100	µmhos
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
4.7 and 1501	Life-test provisions (intermittent)	Group A; Ef = 1.4 Vac or Vdc	---	---	---	---	---	---
4.7.3	Life-test end point (intermittent) (500 hours)	Power output (1)	---	---	Po	50	---	mW

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:55Z
Check the source to verify that this is the current version before use.

NOTES:

1. This test is to be performed at the conclusion of the holding period.
2. The rejection level shall be set at the VU meter reading obtained during calibration. (R)
3. The tube described by this TSS is interchangeable with the tube procured to the previous issue.

Custodians:
Army - EL
Navy - ES
Air Force - 11

Review activities:
Army - EL
Navy - EC
Air Force - 11, 85
DSA - ES

User activities:
Army - MU, ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Air Force - 11

(Project 5960-2237-5)

Source: https://assist.dla.mil -- Downloaded: 202610-15T12:55Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:55Z
Check the source to verify that this is the current version before use.