MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5763

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, miniature, 175 MHz, beam-power amplifier

Outline --- 6-3 (EIA)

Base --- E9-1

Envelope --- T6-1/2

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7	8	9
Element	---	a	nc	g3	h	h	g2	k	g1	g1

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ec3	Ib	Ic1	Ik	Pp	Ehk	Pg2	Pi	TE	Alt
Unit:	V	Vdc	Vdc	Vdc	Vdc	mAdc	mAdc	mAdc	W	v	W	W	°C	ft
Maximum:	6.6	300	-125	250	0	50	5.0	65	12	100	2.0	15	250	Note 1
Minimum:	5.4	---	---	---	---	---	---	---	---	---	---	---	---	---
TEST CONDITIONS:	6.0	250	-7.5	250	0	---	---	---	---	---	---	---	---	---

GENERAL:

Qualification - Required

© denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1256	Electrode current (anode)		0.65	II	Ib	33	57	mAdc
1236	Power oscillation	Eb = 300 Vdc; Rg1 = variable; Ib = 58 mAdc; F = 135 MHz	0.65	II	Po	1.5	---	W
1231	Emission	Eb = Ec1 = Ec2 = 30 Vdc; Ec3 = 0 (see note 2)	0.65	II	Is	170	---	mAdc
1266	Total grid current	Rg1 = 0.1 Meg (see note 2)	0.65	II	Ic	0	-2.0	µAdc
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1031	Low-frequency vibration	Ec1 = -15 Vdc; Rp = 2,000 ohms	---	---	Ep	---	500	mVac
1301	Heater current		---	---	If	690	810	mAdc
1336	Heater-cathode leakage		---	---	Ihk	---	50	µAdc
1256	Electrode current (screen)		---	---	Ic2	---	10	mAdc
1331	Direct-interelectrode capacitance	No shield	6.5	Code E	Cgp Cin Cout	--- 6.0 3.8	0.3 11.0 5.2	pF pF pF
1211	Insulation of electrodes		4.0	S3	---	---	---	---
Ⓒ 1121	Base strain		---	---	---	---	---	---
Ⓒ 2126	Glass strain		4.0	I	---	---	---	---
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent life test	Group A; Eb = 300 Vdc; Ec2 = 300 Vdc; Rg1 = 17,000 ohms; Rg2 = 32,000 ohms; Ib = 45 mAdc; F = 120 MHz	---	---	---	---	---	---
---	Intermittent life-test end points (500 hours)	Power oscillation	---	---	Po	1.0	---	W

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

NOTES:

1. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.
2. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - MU
Air Force - 17
DSA - ES

User activities:
Army - WC
Navy - AS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2481)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.