MILITARY SPECIFICATION SHEET

ELECTRON TUBE, POWER

TYPE 8166

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Tetrode

See figure 1

Operating position: Vertical, base down or up

Weight: 1.5-pound nominal (680 grams)

ABSOLUTE RATINGS: C Telegraphy

Parameter:	F	Ef	Eb	Ec1	Ec2	Ib	Pg1	Pg2	Pp	T(seal)	TE	Cooling
Unit:	MHz	Vac	Vdc	Vdc	Vdc	mAdc	W	W	W	°C	°C	Note 1
Maximum:	110	7.9	6,000	-500	1,000	700	25	75	1,000	200	225	---
Minimum:	---	7.1	---	---	---	---	---	---	---	---	---	---
TEST CONDITIONS:	---	7.5	2,500	Adjust	500	400	---	---	---	---	---	Note 2

GENERAL:

Qualification - Required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:49Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1	4							
1301	Filament current	-		0.65	II	If	20.0	22.7	Aac
1231	Peak emission	-	eb = ec1 = ec2 = 2,500 v	0.65	II	is	15.0	---	a
1256	Electrode current (screen)	-		0.65	II	Ic2	-10	+15	mAdc
1261	Electrode voltage (grid)	-		0.65	II	Ec1	-15	-35	Vdc
1266	Total grid current	3		0.65	II	Ic1	---	-25	µAdc
1266	Primary grid emission (control)	-	Ef = 8.25 Vac; Pg1 = 30 W or Ic1 = 150 mAdc; t = 15 seconds; anode and screen-grid floating	0.65	II	Isg1	---	-250	µAdc
1266	Primary grid emission (screen)	-	Ef = 8.25 Vac; Pg2 = 90 W or Ic2 = 160 mAdc; t = 15 seconds; Ec1 = 0; anode floating	0.65	II	Isg2	---	-250	µAdc
	Quality conformance inspection, part 2	4							
1031	Low-frequency vibration	-	No voltages	---	---	---	---	---	---
1036	Bump	-	Angle = 10°	---	---	---	---	---	---
1316	Amplification factor (g1 to g2)	-	Ec2 = 1,000 Vdc; Ic2 = 75 mAdc; Eb = 0	---	---	Mu	6.1	7.7	---
1331	Direct-interelectrode capacitance	-		---	---	Cgp	---	0.35	pF
						Cin	23.8	32.4	pF
						Cout	6.8	9.4	pF
(C) 1236	Power oscillation	-	F = 110 MHz (min); Eb = 5,000 Vdc; Ec2 = 450 Vdc; Ib = 600 mAdc	---	---	Po	1,500	---	W
	Quality conformance inspection, part 3	5							
---	Life test	-	Group C; power oscillation; t = 500 hours	---	---	---	---	---	---
---	Life-test end points:								
1231	Peak emission	-		---	---	is	12.0	---	a
1266	Primary grid emission (control)	-		---	---	Isg1	---	-250	µAdc
1266	Primary grid emission (screen)	-		---	---	Isg2	---	-250	µAdc

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:49Z
Check the source to verify that this is the current version before use.

NOTES:

1. Adequate forced-air cooling must be provided to maintain base and anode seal temperatures below their maximum ratings. In all cases of operation, it is recommended that a heat-radiating connector, EIMAC HR-8, or equivalent, be installed on the anode terminal, and that a socket and chimney be used which provide for cooling of the seals. The following table applies to the sockets referenced on Drawings 259-JAN and 293-JAN, with the chimney as referenced on Drawing 293-JAN, at sea level, and with air at 25°C, and should be considered as minimum cooling requirements. The approximate pressure drop values given for the socket referenced on Drawing 259-JAN are as measured in the socket; those for the socket as referenced on Drawing 293-JAN are as measured in the equivalent of a pressurized chassis or plenum chamber. The data applies with maximum rated anode dissipation.

Frequency	Socket and chimney (see Drawing 259-JAN)		Socket and chimney (see Drawing 293-JAN)	
	Airflow (cfm)	Approximate pressure drop (In. H_2O)	Airflow (cfm)	Approximate pressure drop (In. H_2O)
30 to 110 MHz	35	1.9	35	1.0
Below 30 MHz	20	0.6	20	0.42

Cooling air should be supplied before or simultaneously with the application of filament voltage, and may be removed simultaneously with filament voltage. Operation at higher altitudes or higher ambient temperatures will require an increase in cooling airflow.

Ⓒ 2. During all electrical tests involving application of filament power, forced-air cooling of the tube is allowable and a heat-dissipating connector (EIMAC HR-8, or equivalent) may be used on the anode terminal.

3. This test is to be the first test performed at the conclusion of the holding period.

Ⓒ 4. When type 8166 and type 8189 of MIL-E-1/1473 are physically identical, and have been made in the same production run, differing only in high voltage processing and testing of type 8189, then one sample may represent both types as the tests are identical.

Ⓒ 5. When type 8166 and type 8189 of MIL-E-1/1473 are physically identical and have been made in the same production run, differing only in high voltage processing and testing of type 8189, then one life-test sample may represent both types.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 17, 80
DSA - ES


User activities:
Army - MU
Navy - AS, OS, MC, CG, SH

Preparing activity:
Navy - EC


Agent:
DSA - ES

(Project 5960-2870)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:49Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions in inches with metric equivalents (mm) in parentheses (see note)	
	Minimum	Maximum
Quality conformance inspection, part 2		
A	8.875 (225.43)	9.625 (244.48)
B		5.250 (133.35)
C	8.000 (203.20)	8.750 (222.25)
E		.313 (7.95)
Quality conformance inspection, part 3 (see note) ©		
D		3.625 (92.08)
F	.825 (20.96)	.925 (23.50)
G	Cap: C1-26 (EIA)	
N	1.495 (37.97)	1.505 (38.23)
P	.371 (9.42)	.377 (9.58)
Reference dimensions		
K	60°	
L	30°	
M	30°	



Pin connections	
Pin No.	Element
1 & 5	f
2 & 4	g2
3	g1
Cap	a

NOTE:
Dimensions listed under quality conformance inspection (QCI), part 3, shall be checked annually, with sampling as follows:

n1 = 4 c1 = 0 where c2 represents the total allowable failures for
n2 = 4 c2 = 1; the first and second samples combined.

In case of failure after double sampling, the failing dimension(s) shall become a part of QCI, part 2, for three consecutive successful submissions, at which time the test may revert to the QCI, part 3, basis.

FIGURE 1. Outline drawing of electron tube type 8166.

1974-603-113/3279

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:49Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:49Z
Check the source to verify that this is the current version before use.