MILITARY SPECIFICATION SHEET

SWITCHES, PUSHBUTTON, MOMENTARY, 5 AMPERES AND LOW LEVEL, MINIATURE, DUSTTIGHT OR WATERTIGHT

This amendment forms a part of MIL-S-8805/110B(EC), dated 17 April 1991, and is approved for use by the Space and Naval Warfare Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Material: Delete "Body: Polyphenylene sulfide in accordance with MIL-P-46174."

Material, add the following subparagraph:

"Terminals: Terminal finish may be .000030 inch minimum to .000100 inch maximum thick gold plate. When construction of the terminals is integral with the contacts and the gold plate exceeds .000050 inch thickness, no diffusion barrier is required."

PAGE 5

TABLE III, second column: Delete "5 amp" (4 places) and substitute "power circuit" (4 places).

CONCLUDING MATERIAL

Custodian:
Navy - EC

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5930-N732-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:23Z
Check the source to verify that this is the current version before use.