
INCH-POUND
MIL-PRF-8805/111C
4 July 2024
SUPERSEDING
MIL-PRF-8805/111B
19 November 2018

PERFORMANCE SPECIFICATION SHEET

SWITCH, ASSEMBLIES, SENSITIVE, TRIGGER, 7 AMPERES, UNSEALED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-PRF-8805.




Type	Dimension A	Side cover material
Type I Type II	.641 ±.016 .762 +.000 -.025	Aluminum or equivalent (black anodized Polyester or equivalent (color: black)

FIGURE 1. Configurations and dimensions.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:23Z
Check the source to verify that this is the current version before use.



SCHEMATIC DIAGRAM
(DPDT MOMENTARY)

1st POLE MAKES WITH PARTIAL DEPRESSING OF TRIGGER.
2nd POLE MAKES DEPRESSING TRIGGER THROUGH DETENT TO FULL "IN" POSITION.

NOTES:
1. Dimensions are in inches.
2. The terminal designation shall be permanently marked.
3. Unless otherwise specified, tolerance is ±.010.

FIGURE 1. Configurations and dimensions - continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1. Basic switch shall be MS24547-4 (MIL-PRF-8805/4).

Enclosure design: 1 (Unsealed).

Temperature characteristic: 1 (-55°C to +85°C).

Shock type: M(100 g).

Vibration grade: 2 (10 to 2,000 Hz).

Weight: 0.8 ounce maximum.

Dielectric withstanding voltage:

Sea level: 1,050 V rms.

Altitude (80,000 ft): 400 V rms. After electrical endurance, the dielectric withstanding voltage points of application between all unconnected terminals of the same pole is not applicable.

Operating characteristics:

Operating force: The actuating force measured at the bottom of the trigger shall be 2.250 ±.500 pounds to make the first pole; 6.500 ±.750 pounds shall be required to pass through the detent, and 6, +0, -3 pounds to continue travel after the detent.

Releasing force: 0.75 pound minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:23Z
Check the source to verify that this is the current version before use.

Actuating travel:

Switch 1:

Pretravel: .130 inch minimum from full out.

Overtravel: .015 inch minimum before first detent.

Switch 2:

Pretravel .020 inch minimum beyond first detent

Overtravel: .030 inch minimum before total travel.

Mechanical endurance: 100,000 cycles.

Electrical endurance: 50,000 cycles. After electrical endurance, the contact resistance shall not exceed 1 percent of the load resistance, using the electrical parameters of the minimum current test load.

Electrical ratings: See table I.

TABLE I. Electrical ratings.

Electrical ratings, 28 V dc				
Load	Silver contacts		Gold contacts	
	Sea level	80,000 feet	Sea level	80,000 feet
	amperes	amperes	amperes	amperes
Resistive	7	4	1	1
Inductive	5	2.5	.5	.5

Intermediate current: 50,000 cycles. After minimum current cycling, the contact resistance shall not exceed 1 percent of the load resistance, using the electrical parameters of the minimum current test load.

Part or Identifying Number (PIN): See table II

TABLE II. Part or Identifying Number (PIN's).

PIN	Contact material		
M8805/111-	Switch 1	Switch 2	Type
-01	Silver	Silver	I
-02	Gold	Silver	
-03	Gold	Gold	
-04	Silver	Silver	II
-05	Gold	Silver	
-06	Gold	Gold	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:23Z
Check the source to verify that this is the current version before use.

Qualification inspection:

Group submission: See table III. Table III applies provided that qualified MIL-PRF-8805/4 basic switches are utilized.

TABLE III. Qualification inspection.

Examination or test	Test sample	Extent of approval
Group I. Visual and mechanical examination Operating characteristics	M8805/111-01 (all sample units) M8805/111-06 (all sample units)	All PIN's
Group II (4 sample units). Strength of actuating means Thermal shock Vibration Shock (specified pulse) Operating characteristics Dielectric withstanding voltage Visual and mechanical examination	M8805/111-01 (4 sample units) M8805/111-06 (4 sample units)	
Group III. Salt spray (corrosion) Visual and mechanical examination	M8805/111-01 (2 sample units)	
Group IV (4 sample units). Contact resistance Low temperature operation Mechanical endurance at low temperature Mechanical endurance at high temperature Contact resistance Operating characteristics Dielectric withstanding voltage Visual and mechanical examination	M8805/111-01 (4 sample units)	
Group V (4 sample units). Electrical endurance altitude only Dielectric withstanding voltage Operating characteristics	M8805/111-01 (4 sample units) M8805/111-06 (4 sample units)	
Group VI. Intermediate current	M8805/111-01 (2 sample units)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:23Z
Check the source to verify that this is the current version before use.

Reference documents:
MIL-PRF-8805 MIL-PRF-8805/4

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2024-044)

Review activities:
Army - MI
Navy - AS, OS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:23Z
Check the source to verify that this is the current version before use.