
FED. SUP CLASS
5935



MS Part No. MS18174-1

DESIGN STANDARD FOR USE WITH MIL-C-28748/3.

Ⓒ denotes changes

P A Navy-EC Other Cust AF-85 Army-CR	International interest	TITLE Insert (insulator) rectangular connector, electrical, 14 (size 16 and 20 crimp removable) pin contacts	MILITARY STANDARD MS18174
Procurement Specification MIL-C-28748		SUPERSEDES	PAGE 1 OF 2

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-3223-4

APPROVED 20 Dec. 1965 REVISED Ⓒ 20 May 1970 Ⓑ 23 June 1972 Ⓒ 2 August 1982

User activities: Army - ME, AM, AR; Navy - MC, SH, OS, YD; Air Force -

Review activities: Army - MI, AT; Navy - AS; Air Force - 11, 99; DLA-ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.

INCHES	MM
.002	.05
.004	.10
.005	.13
.010	.25
.016	.41
.02	.51
.075	1.91
.09	2.29
.120	3.06
.130	3.30
.143	3.63
.150	3.81
.169	4.29
.195	4.95
.219	5.56
.260	6.60
.370	9.40
.438	11.13
.450	11.43
.51	12.95
.511	12.98
.600	15.24
.778	19.76
.938	23.83
1.250	31.75
2.290	58.17

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.015(.38 mm).
3. Metric equivalents are given for general information only and are based upon 1 inch = 25.4 mm.
4. Tolerance between any two adjacent contact centers shall be ±.004(.10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ±.006(.15 mm).
5. Contact identification may be located on either side of the contact hole but shall appear on the front and rear of each insert.
6. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
7. Referenced documents shall be of the issue in effect on date of invitation for bid.
8. Designed for use with MIL-C-39029/34 contacts.
9. Contact hole details shall be in accordance with MIL-C-28748.
10. The maximum insertion and withdrawal force (connector assembly) shall be 17.5 pounds.
11. Insert material shall be in accordance with MIL-C-28748.

APPROVED 20 Dec. 1965
REVISED (A) 20 May 1970 (B) 23 June 1972 (C) 2 August 1982

User activities: Army - ME, AM, AR; Navy - MC, SH, OS, YD; Air Force -
Review activities: Army - MI, AT; Navy - AS; Air Force - 11, 99; DLA-ES
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

P.A Navy - EC Other Cust AF - 85 Army - CR	International Interest	TITLE Insert (insulator) rectangular connector, electrical, 14 (size 16 and 20 crimp removable) pin contacts	MILITARY STANDARD MS 18174
Procurement Specification MIL-C-28748		SUPERSEDES	PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.