MILITARY SPECIFICATION

CARTRIDGE, 106MM: PRACTICE, M344A1, W/INERT PROJECTILE, W/O FUZE LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of practice cartridge designated as Cartridge, 106MM: Practice, M344A1, w/Inert Projectile, w/o Fuze.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-D-1000 - Drawings, Engineering and Associated Lists
MIL-A-2550 - Ammunition and Special Weapons; General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Inspection Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1167- Ammunition Data Card
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8847480	-	Cartridge, 106MM: Practice, M344A1, w/Inert Projectile, w/o Fuze
7548962	-	Container, Ammunition, Fiber, M316, for Cartridge, 106MM: HEAT, M344A1, w/Fuze PIBD, M509A1 and Practice, M344A1 w/Inert loaded Projectile, w/o Fuze for Rifle M40A1
7548963	-	Box, Packing, Ammunition for Cartridge, 106MM: HEAT, M344A1, w/Fuze, PIBD, M509A1 and Practice, M344A1 w/Inert loaded Projectile, w/o Fuze for Rifle M40A1 in Fiber Container M316

PUBLICATIONS

ARMY

ET-8847480-		Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material

3.1.1 General.-Materials shall be in accordance with applicable specifications and drawings.

3.2 Cartridges.-The cartridges shall comply with all requirements specified on Drawing (dwg.) 8847480, and with all requirements specified in applicable specifications.

3.3 Propellant Weight.-The weight of the propellant shall not differ by more than plus or minus (±) 0.25 ounce avoid dupois from that designated by the loading authorization for the particular lot of propellant used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

3.4 Bullet Pull.-The cartridge shall separate from the projectile at a load between 3000 lbs. minimum (min.) and 7000 lbs. maximum (max.).

3.5 Proving Ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.3.

3.5.1 Muzzle Velocity.-The corrected muzzle velocity at ambient temperature shall be not more than 1700 feet per second (fps) nor less than 1600 fps, and the standard deviation for the lot shall be not more than 11.0 fps.

3.5.2 Fin Opening.-The fins shall open.

3.5.3 Premature Bursts and Security of Parts.-There shall be no premature burst or indication of metal parts separation or breakup in the rifle bore or in flight before impact.

3.6 Assembly Torque.-Threaded joints shall withstand subsequent reapplication of the minimum assembly torque specified on the applicable drawings, without moving.

3.7 Workmanship

3.7.1 All parts shall be free of cracks, chips, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.7.2 The painting and marking shall be restored by the assembly contractor on any components furnished to him painted and marked, when such paintings and markings have been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Quality Conformance Inspection

4.2.1 Lot Formation.-The term "inspection lot", as used in this specification, is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions, and complies with the provisions for submission of product, as specified in Standard MIL-STD-105. Changes to the process, specifications or drawings, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

a. Cartridge cases of one type of metal and of one lot interfix number from one manufacturer, in accordance with the same drawing and drawing revision, same specification and specification revision.

b. Projectile metal parts from one manufacturer in accordance with the same drawing and drawing revision, same specification and specification revision.

c. Propellant from not more than one lot.

d. Loaded primers of one lot interfix number from one manufacturer.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for Critical Defects (and Major Defects, when so specified) shall be 100 percent (%). Sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of Major and Minor Defects listed, the contractor may elect to apply AQL's to individual defects, using an AQL of 0.40% for each Major Defect, and an AQL of 0.65% for each Minor Defect. When this method is elected, it shall be applied to all of the Major and Minor Defects listed in the applicable subparagraph of this section, except where 100% inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.2.1 Projectile, Prior to Loading (See dwg. 8847481, covering a detail of dwg. 8847480).

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical: None defined.			
Major: None defined.			
Minor:	AQL 1.00 Percent		
201.	Foreign matter in charge cavity	Visual	01001
202.	Evidence of poor workmanship (See 3.7)	Visual	01002

4.2.2.2 Projectile, Prior to Assembling Chamber (See dwg. 8847481, covering a detail of dwg. 8847480).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 Percent		
101.	Depth to face of inert filler	Gage	02001
102.	Packing O-Ring missing	Visual	02002
103.	Inert filler on body threads	Visual	02003
Minor: None defined.			

4.2.2.3 Projectile, Prior to Assembling of Fin Assembly (See dwg. 8847481, covering a detail of dwg. 8847480).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Chamber fails to withstand min. assembly torque (See 3.6)	Test	03001
Major: None defined.			
Minor:	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.7)	Visual	03002

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.2.4 Projectile, Prior to Assembly into Cartridge Case (See dwg. 8847481, covering a detail of dwg. 8847480).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 Percent		
101.	Fin assembly fails to withstand min. assembly torque (See 3.6)	Test	04001
102.	Any component missing or damaged	Visual	04002
Minor:	AQL 1.50 Percent		
201.	Threads and slot of fin and chamber assembly not coated with sealing compound	Visual	04003
202.	Ogive cap fails to withstand min. assembly torque (See 3.6)	Test	04004
203.	Evidence of poor workmanship (See 3.7)	Visual	04005

4.2.2.5 Primer, Prior to Assembly into Case (See dwg. 8838009, coveirng a detail of dwg. 8847480).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Flash hole missing	Visual	05001
Major:	None defined.		
Minor:	None defined.		

4.2.2.6 Liner, Prior to Assembling into Case (See dwg. 7549065, covering a detail of dwg. 8847480).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	None defined.		
Minor:	AQL 1.00 Percent		
201.	Liner damaged	Visual	06001
202.	Evidence of poor workmanship (See 3.7)	Visual	06002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.2.7 Cartridge Case and Liner, Prior to Assembling Projectile (See dwg. 8847480).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer obviously loose	Manual	07001
Major:	AQL 0.40 Percent		
101.	Foreign material in case	Visual	07002
Minor:	AQL 1.00 Percent		
201.	Length to case dimple	Gage	07003
202.	Evidence of poor workmanship (See 3.7)	Visual	07004

4.2.2.8 Cartridge Assembly (See dwg. 8847480)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer above flush	Visual-Manual	08001
2.	Liner damaged to extent that propellant can escape	Visual	08002
Major:	AQL 0.65 Percent		
101.	Liner not cemented in conformance with adhesive zone areas	Visual	08003
102.	Liner loose or insecure	Visual	08004
103.	Liner damaged to extent that moisture barrier is broken but not to extent that propellant can escape	Visual	08005
Minor:	AQL 1.50 Percent		
201.	Exterior coating damaged with an aggregate of bare spots totalling in excess of 1/4 square inch	Visual	08006
202.	Marking misleading or unidentifiable, including incorrect color coding	Visual	08007

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

203.	Adhesive on bourrelet	Visual	08008
204.	Evidence of poor workmanship (See 3.7)	Visual	08009

4.2.2.9 Unsealed Fiber Container (See dwg. 7548962).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 Percent		
101.	Packing component missing or out of place	Visual	09001
Minor:	AQL 1.50 Percent		
201.	Container cap cannot be removed by hand	Manual	09002
202.	Cartridge cannot be removed by hand	Manual	09003
203.	Glue or asphalt on cartridge	Visual	09004

4.2.2.10 Sealed Fiber Container (See dwg. 7548962).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 Percent		
101.	Container cut or damaged through all layers	Visual	10001
102.	Metal end loose or distorted	Visual-Manual	10002
103.	Tape incomplete or badly wrinkled	Visual	10003
Minor:	AQL 2.50 Percent		
201.	Tear tab length, min.	Gage	10004
202.	Contents loose	Manual	10005
203.	Gap between cover and body of container exceeding 1/8 inch	Gage	10006
204.	Cuts, scuffs or gauges in outer layers	Visual	10007
205.	Marking misleading or unidentifiable	Visual	10008

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.2.11 Sealed Wood Packing Box (See dwg. 7548963).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 Percent		
101.	Box damaged, exposing contents	Visual	11001
102.	Board loose or broken	Visual-Manual	11002
103.	Hardware or strapping missing, broken or loose	Visual-Manual	11003
104.	DOD symbol missing or incorrect	Visual	11004
Minor:	AQL 1.50 Percent		
201.	Handle missing or insecure	Visual-Manual	11005
202.	Car seal missing, unsealed or improperly positioned	Visual	11006
203.	Marking misleading or unidentifiable	Visual	11007

4.2.3 Testing

4.2.3.1 Check Test for Possible Deterioration of Primers.-If the total elapsed time between original acceptance of the primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to, and must satisfactorily pass, the check test for deterioration specified in the applicable primer specification immediately before the primer lot is assembled into the cartridges. The test shall be performed by the contractor on assemblies selected by the Government Inspector at the facility assembling the complete cartridges (See 6.4).

4.2.3.2 Propellant Weight (See 3.3) - Major Defect - Code No. 08010.-The propellant shall be weighed and check-weighed 100%. The check-weighing shall be accomplished independently of the original weighing using a different balance from that used to make the original weighing and, if performed manually, shall be performed by another operator. Any propelling charge which fails to comply with the applicable requirement shall be classed defective and removed from the lot subject to correction prior to resubmission. Equipment shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.3.3 Profile and Alignment (See dwg. 8847480) - Major Defect - Code No. 08011.-The cartridges shall be gaged 100% for profile and alignment. Any cartridge which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.4 Bullet Pull (See 3.4 and dwg. 8847480) - Major Defect - Code No. 08012.-The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Part II, Table B-3, Code Letter F and an AQL of 1.50% shall be used. The test shall be performed as specified in 4.3.2, with equipment in accordance with 4.2.4.

4.2.3.5 Proving Ground.-The following tests shall be performed as specified in 4.3.3.

4.2.3.5.1 Muzzle Velocity (See 3.5.1) - Major Defect - Code No. 08013.

4.2.3.5.1.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the applicable requirements, the sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Part II, Table B, Code Letter I and an AQL of 1.00% shall by used. In addition, if the velocity standard deviation of the sample multiplied by the factor 0.75 exceeds the requirement specified in 3.5.1, the lot shall be rejected.

4.2.3.5.1.2 After three (3) consecutive lots have met the criteria of 4.2.3.5.1.1, the sampling plan and procedure for this test shall be in accordance with MIL-STD-414, Section B, Part II, Table B-3, Code Letter F and an AQL of 1.00% shall be used. In addition, if the velocity standard deviation of the sample multiplied by the factor 0.65 exceeds the requirement specified in 3.5.1, the lot shall be rejected.

4.2.3.5.2 Fin Opening (See 3.5.2) - Major Defect - Code No. 08014.-This test shall be performed in accordance with 4.3.3.2. Acceptance and rejection shall be as follows:

Number of Rounds in Ballistic Sample	Accept	Reject
25	1	2
10	0	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.3.5.3 Premature Bursts and Security of Parts (See 3.5.3) - Critical Defect - Code No. 08015.-If any of the sample cartridges used in the proving ground tests fails to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.4 Refiring.-If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional sample rounds as required.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-8847480 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government Rights to Documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and Maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government Use of Contractor's Inspection and Test Equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test Methods and Procedures

4.3.1 Torque Tests.-The torque shall be applied while holding the parts immediately adjacent to the joints being tested so as to avoid possible loosening of other joints. The joint under test shall be marked to provide a means for detection of any movement between the adjacent parts. Any discernible movement between adjacent parts shall be regarded as a torque test failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.3.2 Bullet Pull.-The sample cartridges shall be tested for security of crimp of the cartridge case by applying the load in an axial direction. The rate of travel of the testing machine head shall be .100 to .125 inch per minute, inclusive.

4.3.3 Proving Ground.-These tests shall be conducted at a Government proving ground in accordance with the latest revision of the applicable Materiel Test Procedure and Acceptance Test Procedure. The cartridges shall be fired alternately with an equal number of calibrated reference rounds in a rifle for which it is standard, and observation shall be made for compliance with all applicable requirements.

4.3.3.1 Accuracy (For Information Only).-The cartridges fired in the muzzle velocity phase shall be fired at a screen placed 1,000 meters from the muzzle of the rifle. The hit pattern results shall be recorded on the firing record for informational purposes.

4.3.3.2 Fin Opening.-The rounds fired in the velocity accuracy tests shall be fired through 1/16 inch chipboard or with photographic coverage to determine proper fin opening.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level A.-The cartridges shall be preserved and packaged in accordance with dwg. 7548962.

5.2 Packing

5.2.1 Level A.-The cartridges in containers shall be packed in accordance with the information specified in Drawing C7548963.

5.3 Marking.-Marking shall be in accordance with drawings C7548962 and C7548963.

6. NOTES

6.1 Ordering Data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data Cards - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

6.2 Inspection Code Numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on the Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (See 6.3.5).

6.3 Inspection Equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection Equipment Lists (EL).-Inspection Equipment Lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes, as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection Equipment List Codes.-The inspection equipment, as defined in 6.3.3 and 6.3.4, will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.

MU - Army design, Mandatory for Use

6.3.3 Army Designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number).

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the currentversion before use.

When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor-prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor Designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which completely depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of Contractor Designs.-All submitted designs shall contain a reference to the applicable five-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as Critical and Major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-A. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged; however, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the currentversion before use.

6.4 Cost of Check Test.-The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers, or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Visual Examination.-When compliance with the applicable requirements is in doubt as a result of visual examination, the characteristic may be measured or gaged to determine acceptability.

6.6 Submission of Test Data and Ammunition Data Cards.-In addition to the normal distribution of records, when the cartridge is procured by the U. S. Army Munitions Command, one copy of all ballistic test data and ammunition data cards shall be forwarded to each of the following:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-QA-A-A
and SMUPA-AD-E-A2
Dover, New Jersey 07801

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1315-A-003

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters, Picatinny Arsenal
Dover, New Jersey 07801

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

Form Approved