MIL-C-48237 (MU)
27 July 1973

MILITARY SPECIFICATION

CARTRIDGE, 105MM, APDS-T, M728
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing of one type of Armor-Piercing, discarding sabot, tracer loaded cartridge, APDS-T, M728 , for use in 105MM Guns, U.K., TK., L7A1 and U.S., M68.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or requests for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-D-1000 - Drawings, Engineering and Associated Lists
MIL-A-2550 - Ammunition and Special Weapons; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1167- Ammunition Data Card
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

HANDBOOKS

MILITARY

MIL-HDBK-204- Inspection Equipment Design

DRAWINGS

ARMY

9276810 - Cartridge, 105MM, APDS-T, M728, Assembly and Marking Diagram

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

9278419	- Packing and Marking for Box, Packing, for Container, Ammunition, Fiber, PA72, for Cartridge, 105MM, APDS-T, M728
9278417	- Packing and Marking for Container, Ammunition, Fiber, PA72, for Cartridge, 105MM, APDS-T, M728
8828098	- Gage, Profile and Alignment
8828099	- Gage, Alignment Check
8828100	- Gage, Wear Limit Check

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable specifications and drawings.

3.2 Complete Round.-The cartridge shall comply with all requirements specified on Drawing (dwg.) 9276810 and with all requirements specified in applicable specifications.

3.3 Propellant Weight.-The weight of the propellant shall not differ by more than plus or minus (±) 0.12 ounce avoirdupois from that designated by the loading authorization for the particular lot of propellant used.

3.4 Cartridge Case Crimp (Bullet Pull).-The cartridge case shall separate from the shot at a load between 1300 pounds, minimum (min.), and 4,000 pounds, maximum (max.) when tested as specified in 4.3.1.

3.5 Security of Sub-Projectile.-The sub-projectile shall not rotate in the projectile sabot when subjected to 50 ± 5 inch-pounds torque in a counter-clockwise direction when facing nose of projectile.

3.6 Proving Ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

3.6.1 Muzzle Velocity. The corrected muzzle velocity of the cartridge, when fired at 70°F, shall be not more than 4700 feet per second (fps) nor less than 4650 fps, and the standard deviation of the lot shall be not greater than 12 fps max.

3.6.2 Tracer Functioning. The tracer shall ignite and there shall be visible evidence of the burning of the tracer composition to the target.

3.6.3 Safety. There shall be no hangfires, premature bursts or indications of metal parts failure in the gun bore or in flight, prior to impact, except as will normally occur with respect to the discarding of the sabot, during any of the proving ground tests conducted.

3.7 Workmanship

3.7.1 General. The cartridge and all components shall be free of cracks or burrs; and chips, dirt, grease, rust or other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents. The cartridge shall not be damaged in any manner during the loading operation.

3.7.2 The painting and marking shall be restored by the assembling contractor on any components furnished to him painted and marked, when such paintings and markings have been marred or obliterated. (Bare spots in painting, other than marking, are allowable provided that they total not more than 1/4 square inch in aggregate, and that the max. dimension of any individual bare spot does not exceed 3/16 inch.)

3.8 Weights. For informational purposes, individual propellant weight, projectile weight, and complete round assembly weight shall be recorded for each round.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection Provisions

4.2.1 Lot formation.-The term "inspection lot", as used in this specification, is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in Standard MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

Changes to the process, specification or drawing, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded complete round cartridges shall contain:

a. Cartridge cases from one manufacturer in accordance with the same drawing and drawing revision, same specification and specification revision; or, if resized cases are used, from not more than one lot.

b. Projectiles of one lot interfix number from one manufacturer in accordance with the same drawing and drawing revision, same specification and specification revision.

c. Propellant of one lot from one manufacturer.

d. Loaded primers of one lot interfix number from one manufacturer.

e. Loaded tracers of one lot interfix number from one manufacturer.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for Critical Defects (and Major Defects, when so specified) shall be 100 percent. Sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of Major and Minor Defects listed, the Contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each Major Defect and an AQL of 0.65 percent for each Minor Defect. When this method is elected, it shall be applied to all of the Major and Minor Defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.2.1 Primer, Prior to Assembly to Cartridge Case (See dwg. 8839499, covering a detail of dwg. 9276810).

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:			
	1. Any flash hole missing	Gage(CD)	01001
Major:	AQL 0.40 Percent		
	101. O-ring missing	Visual	01002
Minor: None defined.			

4.2.2.2 Cartridge Case Primer Assembly, Prior to Loading of Propellant (See dwg. 9276810).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 Percent		
	101. Primer fails to withstand disassembly torque	Torque Test(CD)	02001
	102. Liner Loose, Missing or obviously mislocated	Visual	02002
Minor:	AQL 1.50 Percent		
	201. Primer stake missing	Visual	02003
	202. Foreign matter in interior of case (See 3.7)	Visual	02004
	203. Primer bent or damaged	Visual	02005

4.2.2.3 Shot Loading Assembly, Prior to Assembly to Cartridge Case (See dwg. 9276809, covering a detail of dwg. 9276810).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 Percent		
	101. Plug and disc assembly fails to withstand disassembly torque	Torque Test(CD)	03001
	102. Component missing	Visual	03002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Minor:	AQL 1.50 Percent		
201.	Tracer closing disc missing, damaged or loose	Visual-Manual	03003
202.	Marking misleading or unidentifiable, including incorrect color code	Visual	03004
203.	Evidence of poor workmanship (See 3.7)	Visual	03005

4.2.2.4 Complete Round Assembly (See dwg. 9276810).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 Percent		
101.	Distance from rear face of cartridge case to top of electrode, max.	Gage(CD)	04001
102.	Assembly damaged	Visual	04002
Minor:	AQL 1.50 Percent		
201.	Exterior protective coating with bare spot	Visual	04003
202.	Marking misleading or unidentifiable, including incorrect color code	Visual	04004
203.	Evidence of poor workmanship	Visual	04005

4.2.2.5 Unsealed Fiber Container (See dwg. 9278416).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 Percent		
101.	Packing component missing	Visual	05001
Minor:	AQL 1.50 Percent		
201.	Glue or asphalt on cartridge	Visual	05002
202.	Container assembled improperly	Visual	05003
203.	Cartridge cannot be removed by hand	Manual	05004

4.2.2.6 Sealed Fiber Container (See dwg. 9278417).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 20260-26T03:55Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Major:	AQL 0.65 Percent		
101.	Tape incomplete or badly wrinkled	Visual	06001
102.	Container cut or damaged through all impregnated layers	Visual-Manual	06002
103.	Metal end loose or distorted	Visual-Manual	06003
Minor:	AQL 2.50 Percent		
201.	Tear tab length, min.	Gage(CD)	06004
202.	Gap exceeding 1/8 inch between cap and body of container	Visual	06005
203.	Marking misleading or unidentifiable	Visual	06006
204.	Cuts, scuffs or gouges in outer layers	Visual	06007
205.	Contents loose	Manual	06008

4.2.2.7 Sealed Wood Packing Box (See dwg. 9278419).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 Percent		
101.	Box damaged, exposing contents	Visual	07001
102.	Strapping missing or loose	Visual	07002
103.	Hardware missing, broken or loose	Visual	07003
104.	D.O.D. symbol missing or incorrect	Visual	07004
105.	Board loose or broken	Visual-Manual	07005
Minor:	AQL 2.5 Percent		
201.	Car seal missing, unsealed or improperly positioned	Visual	07006
202.	Marking misleading or unidentifiable	Visual	07007
203.	Hardware improperly engaged	Visual-Manual	07008
204.	Strapping improperly assembled	Visual-Manual	07009
205.	Handle missing or insecure	Visual-Manual	07010

4.2.3 Testing

4.2.3.1 Check Test for Possible Deterioration of Primers - Major Defect - Code No. 01003.-If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to, and must satisfactorily pass, the check test for deterioration specified in the applicable primer specification immediately before the primer lot is assembled into the cartridges. (See 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.3.2 Primer Above Flush (See dwg. 9276810) - Major Defect - Code No. 04006.-The cartridges shall be gaged (straight edge) 100 percent for primer above flush with base of case. Any cartridge which fails to meet the applicable requirements shall be classed defective and be removed from the lot.

4.2.3.3 Propellant Weight (See 3.3) - Major Defect - Code No. 02006.-The propellant shall be weighed and check-weighed 100 percent. The check-weighing shall be accomplished independently of the original weighing and, if performed manually, shall be performed by another operator. Any propellant charge which fails to comply with the applicable requirement shall be classed defective and removed from the lot, subject to correction prior to resubmission. Equipment shall be contractor designed.

4.2.3.4 Electrical Resistance (See dwg. 9276810) - Major Defect - Code No. 02007.-The cartridge cases, with primers assembled, shall be tested 100 percent for resistance. Any case-primer assembly which fails to meet the resistance requirement shall be classed defective and be removed from the lot. Testing shall be as specified in 4.3.2, using contractor designed equipment.

4.2.3.5 Profile and Alignment (See dwg. 9276810) - Major Defect - Code No. 04007.-The cartridges shall be gaged 100 percent for profile and alignment. Any cartridge which fails to meet the applicable requirement shall be classed defective and be removed from the lot. Equipment shall be in accordance with dwg. 8828098.

4.2.3.6 Cartridge Case Crimp (Bullet Pull) - (See 3.4 and dwg. 9276810) - Major Defect - Code No. 04008.

4.2.3.6.1 The sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter F, and an AQL of 1.5 percent. The test shall be performed as specified in 4.3.1, with contractor designed equipment.

4.2.3.7 Security of Sub-Projectile (See 3.5).-The cartridges shall be tested 100 percent for loose sub-projectiles. Any cartridge failing to meet the applicable requirements shall be classed defective and removed from the lot. Testing shall be as specified in 4.3.3, with contractor designed equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.3.8 Proving Ground.-The following tests shall be performed as specified in 4.3.4. These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedure. The sample cartridges shall be fired alternately with an equal number of calibrated reference rounds in a gun for which the cartridge is standard and observation made for conformance to all applicable requirements.

4.2.3.8.1 Muzzle Velocity (See 3.6.1) - Major Defect - Code No. 04009.

4.2.3.8.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter I and an AQL of 1.0 percent. In addition, if the standard deviation of the sample cartridge multiplied by the factor 0.75 exceeds the lot requirement, the lot shall be rejected.

4.2.3.8.1.2 After three consecutive lots have met the criteria of 4.2.3.8.1.1, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter F, and an AQL of 1.0 percent. In addition, if the standard deviation of the sample multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.8.2 Tracer Functioning (See 3.6.2) - Major Defect - Code No. 04010.

4.2.3.8.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sample cartridges fired in the test for muzzle velocity (See 4.2.3.8.1.1) shall be observed for tracer functioning. If three or more sample cartridges fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.8.2.2 After three consecutive lots have met the criteria of 4.2.3.8.2.1, the sample cartridges fired in the test for muzzle velocity (See 4.2.3.8.1.2) shall be observed for tracer functioning. If two or more sample cartridges fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.8.3 Extreme Temperature Firing (For Information Only) - Code No. 04011.-Twenty (20) cartridges shall be selected from each of the first three production lots and fired for muzzle velocity, target impact dispersion and maximum chamber pressure information at -35 degrees (^{O}F) (10 rounds) and 125 ^{O}F (10 rounds). Tests shall be conducted as specified in 4.3.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.2.3.8.4 Safety (See 3.6.3) - Critical Defect - Code No. 04012.-All cartridges fired in the proving ground tests shall be observed for premature burst, hangfires or breakup of metal parts. If any cartridge fails to comply with the applicable requirements, the lot shall be rejected.

4.2.3.8.5 Target-Impact-Dispersion (For Information Only).-The sample cartridges used in the test for muzzle velocity (See 4.2.3.8.1.1 and 4.2.4.8.1.2) shall be observed as specified in 4.3.4.1 for target-impact-dispersion information.

4.2.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.2.2 and in 4.2.3 (See 6.3).

4.2.4.1 Government Rights to Documentation.-Inspection equipment drawings may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3 Test Methods and Procedures

4.3.1 Cartridge Case Crimp (Bullet Pull).-The cartridge shall be tested in an appropriate tensile testing machine to determine the security of the crimp of the cartridge case to the projectile. The load shall be applied in an axial direction with the rate of travel of the testing machine head from 0.100 to 0.125 inch per minute.

4.3.2 Electrical Resistance.-The electrical resistance shall be measured between the primer electrode and the cartridge case with a maximum current of 20 milliamperes flowing through the primer.

4.3.3 Security of Sub-Projectile.-The appropriate fixture shall be assembled to the sub-projectile in a manner such that no rearward pressure is applied to the sub-projectile, and the specified torque applied. Observation shall be made to determine compliance with the applicable requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.3.4 Proving Ground

4.3.4.1 Velocity and Target Impact Dispersion. The ammunition fired in this test shall be conditioned at a temperature of 70°F± 2 F in a tech chamber until all propellant is stabilized at a uniform temperature prior to firing. This normally requires a period of 24 hours. The cartridge shall be fired at a cloth target placed at a distance of 1000 meters from the muzzle of the gun. Vertical and horizontal hit pattern results shall be expressed as probable errors in mils and shall be recorded on the firing record for informational purposes only (See 6.5). Muzzle velocity shall be determined and recorded for each round. In addition, maximum chamber pressure shall be recorded for the rounds fired in accordance with paragraph 4.2.3.8.1.1.

4.3.4.2 Tracer Functioning. Cartridges fired during the velocity test shall be observed for tracer functioning to the 1000 meter target. The distance over which the tracer burns shall be recorded to the nearest estimated 500 meters (i.e., failure, 500 meters, 1000 meters).

4.3.4.3 Extreme Temperature Firing (Information Only). For this test, ten (10) rounds shall be temperature-conditioned at -35°F ± 2°F and ten (10) rounds shall be temperature-conditioned at +125°F ± 2°F until all propellant is stabilized at a uniform temperature prior to firing. This normally requires a period of 24 hours. The cartridge shall be fired at a cloth target placed at a distance of 1000 meters from the muzzle of the gun. Muzzle velocity, maximum chamber pressure and target impact dispersion data shall be recorded.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging.

5.1.1 Level A.-The cartridge shall be preserved and packaged in accordance with dwg. 9278417.

5.2 Packing

5.2.1 Level A.-The containers shall be packed in accordance with dwg. 9278419.

5.3 Marking.-The containers and boxes shall be marked in accordance with dwgs. 9278417 and 9278419.

6. NOTES

6.1 Ordering Data.-Procurement documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

a. Title, number and date of this specification.

b. Data Cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection Code Numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on the Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (See 6.3.3).

6.3 Inspection Equipment Designs. Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers (under the "Method of Inspection" headings in Section 4). Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3, should he elect to do so.

6.3.1 SIE designs. SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing, as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor Designs. Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public.) Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government, and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (See 6.3.1c). Design shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval. - Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Cost of Check Test. - The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the assemblies or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Submission of Test Data and Ammunition Data Cards. In addition to the normal distribution of records, when the cartridge is procured by the Army Munitions Command, one copy of all ballistic test data and ammunition data cards shall be forwarded to each of the following:

Commander, Picatinny Arsenal
ATTN: SMUPA-QA-A-A and
SMUPA-AD-E-A2
Dover, New Jersey 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

6.6 Certain provisions of this specification are the subject of international standardization agreement ABCA-ARMY-STD-147. When amendment, revision or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned.

6.7 Proving Ground Test

6.7.1 Test Validity. If for any reason the proving ground considers that the test conditions have detrimentally affected the test results, the test shall be declared invalid and a new test shall be performed with additional samples.

6.7.2 Test Summary: See Next Page.

Custodian:

Army - MU

Preparing Activity:

Army-MU

Project Number: 1315-A-027

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973 -713-161 787

PROVING GROUND TEST SUMMARY

TEST	SAMPLE SIZE INITIAL (NOTE 1)	SAMPLE SIZE SUBSEQUENT	REQUIREMENTS	SAMPLING PARAGRAPH	TEST PROCEDURES PARAGRAPH
Muzzle Velocity	25	10	a. Muzzle Velocity (3.6.1)	4.2.3.8.1.1	4.3.4.1
			b. Tracer Functioning (3.6.2)	4.2.3.8.2.1	4.3.4.1
			c. Target Impact Dispersion (Info)	4.2.3.8.5	4.3.4.1
			d. Safety (3.6.3)	4.2.3.8.4	4.2.3.8.4
			e. Pressure (Info - NOTE 1)	4.2.3.8.1.1	4.3.4.1
Extreme Temperature Firing	20	0	a. Pressure (Info)	4.2.3.8.3	4.3.4.2
			b. Muzzle Velocity (Info)	4.2.3.8.3	4.3.4.2
			c. Target Impact Dispersion (Info)	4.2.3.8.3	4.3.4.2
			d. Safety (3.6.3)	4.2.3.8.4	4.2.3.8.4

NOTES: 1. Until three (3) consecutive lots are accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.