MILITARY SPECIFICATION

CHARGE, SPOTTING, MODEL APG-2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts manufacture, and loading, assembling and packing for one type of spotting charge designated as Model APG-2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-286 - Propellants, Solid, Sampling, Examination & Testing

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

9297939 - Spotting Charge, Model APG-2
9298103 - Packing and Marking for Box, Fiberboard for Spotting Charge (Model APG-2)

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

9298101 - Packing and Marking for Box, Wood Ammunition for Box, Fiberboard for Spotting Charge (Model APG-2)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM Designation E300 - Industrial Chemicals, Recommended Practice for Sampling

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadephia, Penn. 19103).

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly. - The spotting charge shall comply with all requirements specified on Drawing (dwg.) 9297939 and with all requirements specified in applicable specifications.

3.3 Moisture content of spotting charge powder. - The moisture content of the spotting charge powder used in loading the charges shall not exceed 0.30 percent.

3.4 Functioning. - The spotting charges shall function and shall comply with the following:

3.4.1 Rise time. - The spotting charges shall have an output rise time, in the 1.75 to 2.75 micron (μ) infrared region, of 12±3 milliseconds.

3.4.2 Output. - The spotting charges shall have a minimum peak energy output, in the 1.75 to 2.75μ infrared

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the current version before use.

region, of 4.5×10^4 watts/steradian. The mean of the peak energy output, in the 1.75 to 2.75 μ infrared region, minus 2.326 standard deviations shall be greater than or equal to 4.5×10^4 watts/steradian.

3.4.3 Duds. - The spotting charges shall not fail to function on the first attempt.

3.5 Workmanship. - All parts shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. The parts shall be clean, and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base metal. All required markings shall be neat and sharply defined.

3.6 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First Article Inspection

4.3.1 Submission. - The contractor shall submit a first article sample (see 6.2b) as designated by the Contracting Officer. The first article sample shall consist of twenty-

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the current version before use.

five (25) complete sets of parts and subassemblies (i.e. 25 each of every component and subassembly) and fifty (50) loaded spotting charge assemblies. The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

4.3.2 Inspections to be performed. - See MIL-A-48078, 4.4.2.1 through 4.4.2.4 and Table I specified herein.

4.3.3 Rejection. - (See MIL-A-48078)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-48352 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Charge, Spotting, Parts and Assemblies				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Parts Dwgs. 9297941, 9297943 & 9297944 Examination for defects	25(a)		3.1	4.4.2.1, 4.4.2.2 & 4.4.2.4
	Disc Assembly Dwg. 9297940 Examination for defects	25(a)		3.1	4.4.2.3
	Loaded Assemblies Dwg. 9297939 Examination for defects	50(b)		3.2	4.4.2.6
	Testing Functioning	50		3.4	4.4.3.4
Notes:	(a) 50 each and every component and subassembly (b) From 50 prior to functioning				

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of spotting charges shall contain:

a. Parts of one kind from one manufacturer.

b. Propellant M9 of the same type from not more than two lots produced by the same manufacture.

c. Aluminum powder of the same type, grade and class from one lot from one manufacturer.

4.4.2 Examination. - (See MIL-A-48078) - Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Pad				9297944
					NEXT HIGHER ASSEMBLY 9297939
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A&B	None defined				
Minor					
201	Diameter		0.65%	3.1	Gage
202	Thickness		0.65%	3.1	Gage
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Disc, Sealing				9297941
					NEXT HIGHER ASSEMBLY 9297940
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter		0.40%	3.1	Gage
132	Diameter of hole		0.40%	3.1	Gage
Minor					
201	Thickness of disc		0.65%	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the currenversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Disc Assembly		9297940
			NEXT HIGHER ASSEMBLY 9297939

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Adhesive not applied 360 degrees		0.40%	3.2	Visual
Minor					
201	Retaining disc not approximately centered		0.65%	3.2	Visual
202	Excessive adhesive within hole area		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DARPA-OA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Charge Case				9297943
					NEXT HIGHER ASSEMBLY
					9297939
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Charge case cracked or split		100.0%	3.1	Visual
Major B					
131	Length, closed end to indent		0.40%	3.1	Gage
132	Outside diameter of indents		0.40%	3.1	Gage
133	Overall length		0.40%	3.1	Gage
Minor					
201	Outside diameter, closed end		0.65%	3.1	Gage
202	Thickness of bottom		0.65%	3.1	Gage
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Spotting charge, prior to loading		9297939
			NEXT HIGHER ASSEMBLY
			9297939

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Felt pad missing or insecure		0.40%	3.2	Visual/Manual.
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9297939
4.4.2.6	Spotting Charge				NEXT HIGHER ASSEMBLY 9297939
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Charge case cracked or split		100.0%	3.2	Visual
102	Disc assembly inverted		100.0%	3.2	Visual
103	Disc assembly not securely taped		100.0%	3.2	Visual
104	Retaining disc broken		100.0%	3.2	Visual
Major B					
131	Powder charge missing		0.40%	3.2	Manual
Minor					
201	Marking misleading or unidentifiable		0.65%	3.2	Visual
202	Overall length		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Packing and Marking for Box, Fiberboard for Spotting Charge (Model APG-2) Prior to Closing		9298103
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Bottom of box not securely taped		0.40%	3.2	Visual
132	Any packing component (fillers-separators) missing		0.40%	3.2	Visual
133	Number of spotting charges incorrect		0.40%	3.2	Visual
134	Spotting charge reversed in separator		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Box, Fiberboard				9298103
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Plastic bag cut or torn		0.40%	3.2	Visual
132	Excess air not exhausted from bag		0.40%	3.2	Visual
133	Plastic bag not properly sealed		0.40%	3.2	Visual
134	Contents loose within box		0.40%	3.2	Manual
135	Top not securely sealed		0.40%	3.2	Visual
Minor					
201	Marking missing, incomplete or illegible		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T00:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48352 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Packing and Marking for Box, Wood Ammunition for Box, Fiberboard for Spotting Charge (Model APG-2) Prior to Closing				9298101
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Bottom filler missing		0.40%	3.2	Visual
132	Number of bagged fiberboard boxes incorrect		0.40%	3.2	Visual
133	Fillers missing from sides, ends and top		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-48352 (PA)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	Box, Packing, Ammunition, Wood	1	1	9298101
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Strapping missing, broken, loose or improperly fastened		0.40%	3.2	Visual/Manual
102	Box damaged		0.40%	3.2	Visual
103	Marking missing, incomplete or illegible		0.40%	3.2	Visual
Minor					
201	Wooden box cover nailed to box		0.65%	3.2	Visual
202	Metallic seal missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4B10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Chemical Sampling. - A representative sample shall be randomly selected for the applicable tests specified in 4.4.3. The procedure described in ASTM E300 shall be used to withdraw the samples. The applicable tests specified in 4.5 shall be performed using prescribed analytical procedure for replicate determination given in standard analytical textbooks.

4.4.3.2 Moisture content of spotting charge powder (See 3.3) - Major A defect. - The moisture content of the spotting charge powder shall be determined for each batch or blend of batches at the time of loading. A sample in sufficient quantity to perform the test detailed in 4.5.1.1 shall be selected and tested as specified in 4.5.1.1. If the moisture content is in excess of the percentage specified and loading has not begun the lot of spotting charge powder shall be rejected. If loading has begun, action on the unloaded spotting charge powder shall be as specified above and all spotting charges loaded with the questionable spotting charge powder shall be rejected.

4.4.3.3 Composition of spotting charge powder - (see dwg. 9297945) - Major A defect. - The composition of the spotting charge powder shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.5.1.2 shall be selected and tested as specified in 4.5.1.2. If the composition of the spotting charge powder fails to conform to the requirements as specified on the applicable drawing and if loading has not begun, the batch or blend of batches of spotting charge powder shall be rejected. If loading has begun, action on the unloaded spotting charge powder shall be as specified above and all spotting charges loaded with the questionable powder shall be rejected.

4.4.3.4 Functioning. - (see 3.4 and Table II) - A sample of fifty (50) spotting charges shall be randomly selected from each lot. If 2 or more spotting charges fail to function (dud), fail to meet rise time requirement or fail to meet min peak energy requirements the lot shall be rejected. If the calculated lower limit fails to equal or exceed the sample requirement the lot shall be rejected. The test shall be performed as in 4.5.2 using test equipment as specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the currentversion before use.

TABLE II

Defect	Defect Classification	Requirement Paragraph
Spotting charge fails to function on first attempt (Dud)	Major A	3.4.3
Spotting charge fails to meet rise time requirement	Major A	3.4.1
Individual charge fails to meet minimum peak energy	Major A	3.4.2
Sample peak energy mean minus 2.326 standard deviations is less than 4.5×10^4 watts/steradian	Major A	3.4.2

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Spotting charge powder

4.5.1.1 Moisture. - The moisture content of the spotting charge powder shall be determined in accordance with MIL-STD-286 (Karl Fischer) Method 101.5.

4.5.1.2 Composition

4.5.1.2.1 Aluminum. - An accurately weighed 0.5 gm sample shall be added to a 400 ml beaker containing 200 ml of acetone. The beaker shall be placed on an automatic stirrer for two hours or until the propellant is completely dissolved. Then the acetone and aluminum shall be filtered through a tared fine porosity fritted glass crucible. The aluminum residue in the crucible shall be washed four times with 20 mls. of acetone and four times with 25 mls. of water

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the current version before use.

to remove the potassium nitrate. After the washings the crucible shall be dried in an oven at 100° ±5°C for four hours or until constant weight is obtained. The crucible and content shall be weighed and the percent aluminum shall be determined as follows:

$$\text{Percent aluminum} = \frac{A}{B}(100)$$

where:

A = weight of residue
B = weight of sample of a moisture free basis

4.5.1.2.2 M9 propellant powder. - The percentage of M9 propellant powder in the sample shall be calculated on a moisture-free basis by subtracting from 100 the percentage of aluminum found in 4.5.1.2.1.

4.5.2 Functioning. - The spotting charge shall be confined in a test vehicle consisting of a 2"x3" pipe nipple and two cast iron pipe caps. One cap shall be modified with a 7/8" hole in the center to permit entry of a tetryl booster and an electric initiator. The round shall be suspended from the closed end cap between two towers so that the detectors receive a side view of the round. The distance from round to detector shall be 590 feet. The detector signals shall be amplified and the time intensity curves in the infrared region shall be recorded on film. Evaluation of the curves shall be made to determine compliance with the requirements of 3.4.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C. - The spotting charges shall be packaged in accordance with dwg. 9298103.

5.2 Packing

5.2.1 Level C. - The spotting charges shall be packed in accordance with dwg. 9298101.

5.3 The spotting charge fiberboard box and wooden box shall be marked in accordance with instructions contained in dwg. 9298101 and 9298103.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended Use. - The spotting charge Model APG-2 is intended for use with MIL-STD-331 test 210.1 Time to Airburst.

6.2 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

6.3 Submission of Inspection Equipment Designs for Approval - (see MIL-A-48078). - Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T-T Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander: Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1390-A-049

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.