MILITARY SPECIFICATION

CARTRIDGE, 105MM, SMOKE WP, M60A2, (MOD) W/FUZE M557 FOR HOWITZER M137 LOADING ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of cartridge designated as Cartridge, 105MM, Smoke WP, M60A2 (MOD) For use with the 105MM Howitzer M137.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, from a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

MIL-B-60381 - Burster, Projectile, XM 53E2, Loading, Assembling and Packing

STANDARDS

MILITARY

MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multi-level Continuous Sampling Procedures and Table for Inspection by Attributes

DRAWINGS

PICATINNY ARSENAL

PRODUCT AND PACKAGE DRAWINGS

8861520 - Marking Diagram for Pallets for Projectile 75MM to 130MM
9276004 - Packing and Marking for Container, Ammo Fiber PA-71, for 105MM How, Ammunition with Fuze (USAF Use Only)
9276005 - Container, Ammo, Fiber PA-71 for 105MM How. Ammo W/Fuze (USAF Use Only)
9277353 - Packing and Marking for Box, Pallet Type, Wirebound for 105MM How. Ammo. W/Fuze (USAF Use Only)
9289104 - Cartridge, 105MM, Smoke W.P., M60A2, (Mod) W/Fuze, PD, M557, for How., M137 Assembly

INSPECTION EQUIPMENT DRAWINGS

7258482 - Profile and Alignment Gage

(Copies of specifications, standards, drawings and publications required by the contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Material and parts shall be in accordance with applicable drawings and specifications.

3.2 Cartridges.-The cartridges shall comply with all requirements specified on Drawing (Dwg) 9289104 and with all requirements specified in applicable specifications.

3.3 Burster.-The burster shall be X-rayed 100 percent and meet the requirements of MIL-B-60381.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

3.4 Primer.-The primers shall have the required number and locations of flash holes as specified on the appropriate primer drawing.

3.5 Proving ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.2.

3.5.1 Muzzle velocity.-The corrected muzzle velocity of the projectile at ambient temperature shall be not more than 1645 feet per second nor less than 1595 feet per second and the standard deviation of the lot shall be not greater than 8 feet per second.

3.5.2 Premature bursts and security of parts.- There shall be no premature bursts or indication of metal parts failure in the gun bore or in flight before impact.

3.5.3 Functioning.-There shall be visible evidence of functioning upon impact as indicated by the presence of a smoke cloud with a minimum loss of screening effect due to pillaring action.

3.5.4 Safety.- There shall be no premature burst or indication of metal parts separation in the gun bore or in flight when fired with propellant adjusted to give a pressure of 42,000 pounds per square inch (psi) plus or minus 1500 psi.

3.6 Workmanship

3.6.1 Cartridge.-All manufacturing, processing and assembly operations of the cartridge shall be correctly performed in a thoroughly workmanlike manner. Parts shall be free of cracks, burrs, chips, dirt, grease, rust or other foreign material. The cleaning method used shall not be injurious to any of the parts nor shall they be contaminated by the cleaning agents.

3.6.2 Painting and marking.- The painting and marking shall be restored by the assembling contractor on any component furnished to him painted and marked, when such paintings and markings have been marred or obliterated.

3.6.3 Rotating band.-Care shall be exercised at all times so that the rotating band of the projectile is not nicked, burred,

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:56Z
Check the source to verify that this is the current version before use.

or otherwise damaged.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Quality Conformance Inspection.

4.2.1 Inspection Lot Formation.- Inspection lots shall comply with the lot formation provision of MIL-A-48078. In addition, inspection lots of Cartridge, 105MM Smoke WP, M60A2 (Mod.) shall contain:

a. Cartridge cases of one lot interfix number from one manufacturer.

b. Filled projectiles of one lot interfix number from one manufacturer.

c. Propelling charges from not more than one lot from one manufacturer.

d. Loaded fuze of one lot interfix number from one manufacturer.

e. Loaded burster, projectile of one lot interfix number from one manufacturer.

4.2.2 Examination.-See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Tests tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-1235.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9216522
4.2.2.1	Projectile as Received from WP Loading Facility				NEXT HIGHER ASSEMBLY 92889104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	WP leakage or evidence of leakage		100%	3.2	Visual
Major A					
101	Foreign matter in fuze and burster cavity		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9210894
4.2.2.2	Fuze Well Cup				NEXT HIGHER ASSEMBLY 9289104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Pitch diameter of thread		0.40%	3.2	Gage
132	Major diameter of thread		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Inside diameter		0.65%	3.2	Gage
204	Concentricity of inside diameter with pitch diameter of thread		0.65%	3.2	Gage
205	Thickness		0.65%	3.2	Gage
206	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.2.2.3	Projectile Burster				9223129
					NEXT HIGHER ASSEMBLY
					9289104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	X-ray		100%	3.3	
Major	None Defined				
Minor	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.2.2.4	Projectile, Prior to Assembly of Fuze Well Cup	1 OF 1	9216522
			NEXT HIGHER ASSEMBLY 9289104

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Projectile burster inverted		100%	3.2	Visual
2	Closure on projectile burster below flush		100%	3.2	Visual
Major A					
101	Projectile burster missing		0.40%	3.2	Visual
Minor					
201	Compound missing from threads		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9216522
4.2.2.5	Projectile Prior to Assembly of Fuze				NEXT HIGHER ASSEMBLY 9289104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Projectile zone weight incorrect		100%	3.2	Balance
2	Zone stenciling incorrect		100%	3.2	Visual
Major A					
101	Depth of fuze well minimum		0.40%	3.2	Gage
Minor					
201	Protective coating with total damaged area in excess of 1/4 square inch		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

10

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9216522
4.2.2.5	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY 9289104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
202	Marking missing, misleading or unidentifiable (except for zones), including color code		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.2.2.6	Primer, Prior to Assembly to Cartridge				8838130
					NEXT HIGHER ASSEMBLY 9289104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	One or more flash holes missing		100%	3.2	Visual
Major	None defined				
Minor	None defined				

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.2.2.7	Cartridge Case Prior to Assembly of Propelling Charge				8595386
					NEXT HIGHER ASSEMBLY 9289104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Primer missing or damaged		0.40%	3.2	Visual
Minor					
201	Foreign matter in interior of case		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.2.2.8	Propelling Charge, Prior to Assembly to Cartridge Case				9276669
					NEXT HIGHER ASSEMBLY 9289104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Any opening in bag large enough to permit escape of propellant		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

14

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.2.2.9	Cartridge Case with Propellant Charge Prior to Assembling to Projectile				9289104
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Foil side of bag not facing primer		0.40%	3.2	Visual
Minor	None defined				

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.2.2.10	Cartridge Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Primer above flush		100%	3.2	Gage
Major A					
101	Torque test failure of fuze		0.40%	3.2	Test
102	Gap between fuze and body		0.40%	3.2	Test
103	Rotating band damaged		0.40%	3.2	Visual
104	Profile and Alignment		100%	3.2	7258482
Minor					
201	Exterior Coating of projectile with an aggregate of bare spots in excess of 1/4 square inch		0.65%	3.2	Visual
202	Marking missing, misleading or unidentifiable including incorrect color		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.2.2.10	CONTINUATION SHEET				9289104
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Premature bursts and security of parts	See 4.2.3.2		3.5.2	4.3.2
2	Safety	See 4.2.3.2		3.5.3	4.3.2
Major A					
102	Muzzle Velocity	See 4.2.3.2	1.0%	3.5.3	4.3.2
103	Bullet Pull	See 4.2.3.1	1.5%	3.2	4.3.1

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9276005
4.2.2.11	Unsealed Fiber Container				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Packing Component missing		0.40%	3.2	Visual
Minor					
201	Cartridge cannot be removed by hand		0.65%	3.2	Visual
202	Container Cap cannot be removed by hand		0.65%	3.2	Visual
203	Glue or asphalt on Cartridge		0.65%	3.2	Visual
204	Packing components improperly assembled		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48353 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.2.2.12	Sealed Fiber Container				9276005
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Container Cut or damaged through all asphalt impregnated layers		0.40%	3.2	Visual/Manual
132	Metal end loose or distorted		0.40%	3.2	Visual/Manual
133	Tape incomplete or badly wrinkled		0.40%	3.2	Visual
Minor					
201	Tear tab length minimum		0.65%	3.2	Visual
202	Contents loose		0.65%	3.2	Manual
203	Gap between cover and body of container exceeding 1/8 inch		0.65%	3.2	Visual
204	Cuts, scuffs or gouges in outer layers		0.65%	3.2	Visual
205	Marking, misleading missing or unidentifiable		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.2.2.13	Sealed Pallet Type Wirebound				9277353
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Box damaged exposing contents		0.40%	3.2	Visual
132	Wire or strapping missing broken or		0.40%	3.2	Visual/Manual
133	DOD symbol missing or incorrect		0.40%	3.2	Visual
134	Board broken		0.40%	3.2	Visual
Minor					
201	Wire or strapping improperly assembled		0.65%	3.2	Visual/Manual
202	Marking misleading, missing or unidentifiable		0.65%	3.2	Vusual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.2.3 Testing

4.2.3.1 Bullet pull.-The sampling plan for this test shall be in accordance with MIL-STD-414, Section B, Part I Table B1, Code letter F and AQL 1.5 percent.

4.2.3.2 Proving ground. (See 6.5).

4.2.3.2.1 Muzzle velocity

4.2.3.2.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan shall be in accordance with MIL-STD-414, Section B, Table B-3, Code letter I and AQL of 1.0 percent. In addition, if the standard deviation of the muzzle velocity multiplied by the factor 0.75 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.1.2 After the three consecutive lots have met the criteria of 4.2.3.2.1.1, the sampling plan shall be in accordance with MIL-STD-414, Section B, Table B-3, Code letter F and AQL of 1.0 percent. In addition, if the standard deviation of muzzle velocity multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.2.2 Premature bursts and security of parts. If any of the sample projectiles used in any of the tests fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.2.3 Functioning

4.2.3.2.3.1 The sample cartridges used in the test for muzzle velocity (see 4.2.3.2.1.1) shall be tested for functioning. If more than two projectiles fail the specified requirement, the lot shall be rejected.

4.2.3.2.3.2 The sample cartridges used in the test for muzzle velocity (see 4.2.3.1.2) shall be tested for functioning. If more than one projectile fails the specified requirement, the lot shall be rejected.

4.2.3.2.4 Safety (See 6.6)

4.2.3.2.4.1 Beginning with the first lot produced and con-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

tinuing until three consecutive lots have complied with the applicable requirements, fifteen sample cartridges shall be randomly selected from each lot for this test. If any projectile fails to comply with the requirements, the lot shall be rejected.

4.2.3.2.4.2 After three consecutive lots have met the criteria of 4.2.3.2.4.1, five sample cartridges shall be randomly selected from each lot for this test. If any projectile fails to comply with the requirements, the lot shall be rejected.

4.2.3.2.5 Retest.-If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional sample rounds as required.

4.2.4 Inspection Equipment-.The inspection equipment required to perform the examinations and tests prescribed herein is described in the "paragraph reference/inspection method" column in the tables starting with paragraph 4.2.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.3 Test Methods and Procedures.

4.3.1 Bullet pull.-The security of the crimp of the cartridge case to the projectile shall be determined by applying a load in the axial direction with a rate of travel of the testing machine head of 0.100 to 0.125 inch per minute. Observation shall be made for compliance with the applicable requirement.

4.3.2 Proving ground.-These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedure. The sample cartridges shall be fired with standard propelling charges in M137 Howitzer. Observation shall be made for conformance to all requirements. (See 6.5)

4.3.2.1 Muzzle velocity and function.-The sample cartridges shall be fired with the standard charge for this test and observed for velocity and functioning.

4.3.2.2 Safety.-The sample cartridges shall be fired with propelling charges adjusted to give a pressure of 42,000 psi plus or minus 1500 psi in a weapon with M103 tube. In addition, for the first three production lots from each manufacturer (loading facility), a smear camera shall be used to observe the projectile

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the currentversion before use.

in flight in order to record any possible malfunction.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging.

5.1.1 Level A.-The cartridge shall be preserved and packaged in accordance with dwg. 9276005.

5.2 Packing

5.2.1 Level A.-The fiber container shall be packed in accordance with dwg. 9277353.

5.3 Marking.-The pallet shall be marked in accordance with dwg. 8861520. The fiber container shall be marked in accordance with dwg. 9276004.

6. NOTES

6.1 Intended use.-The cartridges covered by this specification are intended for use in the M137 Howitzer by the Air Force.

6.2 Ordering Data.-See MIL-A-48078.

6.3 Submission of Inspection Equipment Design for Approval.-See 6.2.3 of MIL-A-48078. Submit equipment designs, as required to Commander, Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover, New Jersey 07801.

6.4 Proving Ground Test Summary.

	Sample Size	Vel FPS	Ac Re	Press PSI
Quality Conformance First 3 consecutive acceptable lots.				
Velocity	25	1595-1645		
Functioning			2-3	
Safety	15			42000 ± 1500
Subsequent Lots				
Velocity	10	1595-1645		
Functioning			1-2	
Safety	5			42000 ± 1500

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the current version before use.

6.5 Submission of test data.-In addition to the normal distribution of records, when the cartridge is procured by the Department of the Army one copy of all ballistic test data will be forwarded to the following:

Commander
Picatinny Arsenal
Dover, New Jersey
ATTN: SARPA-QA-A-A, SARPA-AD-E-A and SARPA-AD-EP

6.6 Safety.-The crusher pressure gages shall be placed in cartridge case prior to crimping.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1315-A042

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:56Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.