INCH-POUND
MIL-C-48615B(AR)
23 June 1995
(see 6.4)

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY - CONTINUITY TEST CARD

This specification is approved for use by the U.S. Army Armament, Research, Development and Enginerring Center (ARDEC) available for use by all Departments and Agencies of the Department of Defense (see 6.1).

1. SCOPE

1.1 Scope. This specification establishes the requirements and quality assurance provisions for the Circuit Card Assembly - Continuity Test Card, 11732666 (See 6.1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-F-13926 - Fire Control Materiel, General Specification Governing the Manufacture and Inspection of

MIL-I-45607 - Inspection Equipment; Acquisition, Maintenance, and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use to improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: AMSTA-AR-EDE-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1240

DISTRIBUTION STATEMENT A. **Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-100	- Engineering Drawing Practices
MIL-STD-454	- Standard General Requirements for Electronic Equipment
MIL-STD-810	- Environmental Test Methods
MIL-STD-2000	- Standard Requirements for Soldered Electrical and Electronics Assemblies
MIL-STD-2073-1	- Procedures for Development and Application of Packaging Requirements

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from: DODSSP - Customer service, Standardization Documents Order Desk, 700 Robbins Avenue, Bldg 4D, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issue shall be those in effect on date of the solicitation.

U.S. Army Armament Research Development and Engineering Center (ARDEC)

DRAWINGS

11732666	- Circuit Card Assembly - Continuity Test Card

(Copies of Government drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets or MS standards), the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained (see contract provisions for additional precedence criteria).

3. REQUIREMENTS

3.1 Fabrication. The continuity test circuit card assembly, herein referred to as the assembly, shall be manufactured in accordance with Drawing 11732666 and drawings pertaining thereto and, when assembled, shall meet the requirements of this specification (see 4.5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

3.1.1 Function. The assembly shall provide the following functions:

a. Check for the presence of various system power sources and returns.
b. Check for the proper ammunition select logic signals.

3.1.2 General specifications. (see 4.6.3)

3.1.2.1 Manufacture and inspection. The following provisions of MIL-F-13926 apply:

a. Dimensions and tolerance
b. Effect of protective coating on dimensions (Inorganic type coating)
c. Part identification and marking
d. Workmanship (Including applicable portions of MIL-STD-2000 and MIL-STD-454, Requirement 9)

3.1.2.2 Standards of manufacture.

3.1.2.2.1 Assembly and soldering. The requirements of MIL-STD-2000 shall apply, as a minimum.

3.1.2.2.2 Interchangeability. The assembly shall be manufactured in accordance with interchangeability requirements as specified in MIL-STD-100.

3.1.3 Ambient conditions. Standard ambient conditions shall be as follows:

a.	Temperature	$73^{o} \pm 18^{o}F$
b.	Relative humidity	50 percent $\pm$ 30 percent
c.	Atmospheric pressure	28.5 + 2.0/$-$ 3.0 in. Hg.

3.2 First article. When specified in the contract or purchase order (see 6.2), the contractor shall furnish sample units for first article inspection and approval (see 4.4).

3.3 Performance. Unless otherwise specified, the assembly shall meet the performance requirements specified herein under standard ambient conditions of 3.1.3.

3.3.1 Terminal resistance. With no power or signals applied to the assembly, the resistance between terminals shall be as specified in Table I. (see 4.6.1.1).

3.3.2 Power sources. With the power sources (items 1.1, 1.2, and 1.3 of Table II) and interconnection (item 4.1 of Table II) applied to the assembly (see 4.6.1.2):

a. The output at pin P1-B2 shall be +5.25 $\pm$ 0.15V dc,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

measured with respect to pin P1-A13.

b. With pin P1-B2 interconnected with pin P1-A13, the output at pin P1-A2 shall be +2.53 ± 0.25V dc, measured with respect to pin P1-A13.

TABLE I. Resistance.

Item	Measure Between Pin	Pin	Resistance in Ohms
1	P1-B22	P1-A23	97,600 ± 976
2	P1-B24	P1-A23	97,600 ± 976
3	P1-A24	P1-A23	97,600 ± 976
4	P1-A21	P1-A23	140,000 ± 1,400
5	P1-B20	P1-A23	158,000 ± 1,580
6	P1-B21	P1-A23	158,000 ± 1,580
7	P1-A22	P1-A23	46,400 ± 464
8	P1-B3	P1-B17	280,000 ± 2,800
9	P1-A11	P1-B17	97,600 ± 976
10	P1-A16	P1-B17	294,000 ± 2,940
11	P1-B16	P1-B17	32,400 ± 324
12	P1-A18	P1-B17	53,600 ± 536
13	P1-B9	P1-B17	97,600 ± 976
14	P1-B18	P1-B17	97,600 ± 976
15	P1-A19	P1-B17	97,600 ± 976
16	P1-A17	P1-B17	150,000 ± 1,500
17	P1-A20	P1-B17	294,000 ± 2,940
18	P1-B12	P1-B17	97,600 ± 976
19	P1-A10	P1-B17	32,400 ± 324
20	P1-B19	P1-B17	150,000 ± 1,500
21	P1-B11	P1-B17	294,000 ± 2,940
22	P1-B10	P1-B17	150,000 ± 1,500
23	P1-A30	P1-B2	99,800 ± 998
24	P1-B23	P1-A1	150,000 ± 1,500

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. Loads, power and signals.

Item	Conditions	Characteristics	Pin Connector
1.0	Power Sources		
1.1	5.25V dc	Tolerance: ± 0.15V dc Ripple: 20 mV p-p max Current: 500 ma min	P1-A30(+) and P1-A13(-)
1.2	15V dc	Tolerance: ±0.030V dc Ripple: 20 mV p-p max Current: 500 ma min	P1-A1(+) and P1-A3(-) and between pins as specified
1.3	-15V dc	Tolerance: ±0.030V dc Ripple: 20 mV p-p max Current: 500 ma min	P1-A4(-) and P1-A3(+) and between pins as specified
2.0	Signal Sources		
2.1	30V, 400 Hz (MR1)	Square wave: +15V to -15V Tolerances: ±0.150V ± 1 Hz, phase 1	Applied to pin P1-A5 with return to pin P1-A3
2.2	30V, 400 Hz (MR2)	Square wave: +15V to -15V Tolerances: ±0.150V, ± 1 Hz, phase 2 (180° out-of-phase with item 2.1)	Applied to pin P1-A5 with return to pin P1-A3
2.3	AC Ref 2, 400 Hz	Sinewave: 5.000V rms Tolerances: ±0.005V rms ±1 Hz, phase 2 (in phase with item 2.2)	Applied as required
3.0	Load		
3.1	Resistor	10K ohms ±1 percent 1/8 watt	Inserted in series with item 2.3 when required
4.0	Interconnection		Interconnection of the following pins:
4.1			P1-A3 and P1-A13

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

3.3.3 Return logic. With the power sources (items 1.1, 1.2, and 1.3 of Table II) and interconnect (item 4.1 of Table II) applied to the assembly; and with pin P1-A23 interconnected with pin P1-A13; and (see 4.6.1.3)

a. With pins P1-A27 and P1-B27 interconnected with pin P1-A13, the output at pin P1-B26 shall be +1.96 ± 0.17V dc, measured with respect to pin P1-A13.

b. With pins P1-B26 and P1-B27 interconnected with pin P1-A13, the output at pin P1-A27 shall be 1.96 ± 0.17V dc, measured with respect to pin P1-A13.

c. With pins P1-B26 and P1-B27 interconnected with pin P1-A13, the output at pin B1-B27 shall be 1.96 ± 0.17V dc, measured with respect to pin P1-A13.

3.3.4 Ammo logic comparator. With the power sources (items 1.1, 1.2, and 1.3 of Table II) and interconnection (item 4.1 of Table II) applied to the assembly; and with each item's input conditions of Table III established in any item number order, the corresponding output at pin P1-B1 shall be as specified in Table III (see 4.6.1.4).

3.3.5 AC reference current comparator. With the power sources (items 1.1, 1.2, and 1.3 of Table II), signal sources (items 2.1 and 2.2 of Table II) and interconnection (item 4.1 of Table II) applied to the assembly; and with pins P1-A12, A25, A26, A28, A29, B25, B28, B29 and B30 interconnected to pin P1-A4; and with each item's input conditions of Table IV established in any item number order, the corresponding output at pin P1-B17 shall be as specified in Table IV (see 4.6.1.5).

3.3.6 Return current comparator. With the power sources (items 1.1, 1.2, and 1.3 of Table II), signal sources (items 2.1 and 2.2 of Table II), and interconnection (item 4.1 of Table II) applied to the assembly; and with each item's input conditions of Table V established in any item number order, the corresponding output at P1-B17 shall be as specified in Table V (see 4.6.1.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE III. Ammo logic comparator.

Item	Input Conditions at P1 Pins 1/, 2/						Output Conditions 3/ at P1-B1
	P1-B6	P1-B13	P1-A14	P1-B14	P1-A15	P1-B15	
1	NC	NC	NC	NC	NC	NC	+0.075 ± 0.075V dc
2	GND	NC	NC	NC	NC	GND	+4.9 ± 0.5 V dc
3	GND	NC	NC	NC	GND	NC	+4.9 ± 0.5 V dc
4	NC	GND	NC	GND	NC	NC	4.9 ± 0.5 V dc
5	NC	GND	GND	NC	NC	NC	4.9 ± 0.5 V dc
6	NC	GND	NC	NC	NC	NC	+0.075 ± 0.075V dc
7	GND	NC	GND	NC	GND	NC	+0.075 ± 0.075V dc

1/ GND = Interconnection with pin P1-A3. 2/ NC = No connection.
3/ Measured with respect to pin P1-A13.

TABLE IV. AC reference current comparator.

Item	Input Conditons at P1 Pins 1/, 2/, 3/							Output Conditions 4/ at P1-B17
	A9	B8	A8	B7	A7	A6	B5	
1	RMS1	NC	NC	NC	NC	NC	NC	-8.952 ± 0.300V dc
2	NC	RMS2	NC	NC	NC	NC	NC	-8.952 ± 0.300V dc
3	NC	NC	RMS2	NC	NC	NC	NC	-8.952 ± 0.300V dc
4	NC	NC	NC	RMS1	NC	NC	NC	-8.952 ± 0.300V dc
5	NC	NC	NC	NC	RMS2	NC	NC	-8.952 ± 0.300V dc
6	NC	NC	NC	NC	NC	RMS1	NC	-8.952 ± 0.300V dc
7	NC	NC	NC	NC	NC	NC	RMS2	-8.952 ± 0.300V dc
8	NC	NC	NC	NC	NC	NC	NC	-10.089 ± 0.300V dc

1/ NC = no connection. 2/ RMS1 = signal source item 2.3 of Table I.
3/ RMS2 = signal source item 2.3 of Table I, applied through load item 3.1 of Table I.
4/ measured with respect to pin P1-A3.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE V. Return current comparator.

Item	Input Conditions at P1 pins 1/, 2/									Output Conditions 3/ at P1-B17
	A26	A12	B30	B29	A29	B28	A28	A25	B25	
1	A4	A4	A4	A4	A4	A4	A4	A4	A4	-10.089 ± 0.300V dc
2	A4	NC	A4	A4	A4	A4	A4	A4	A4	-6.975 ± 0.300V dc
3	A4	A4	NC	A4	A4	A4	A4	A4	A4	-6.975 ± 0.300V dc
4	A4	A4	A4	NC	A4	A4	A4	A4	A4	-6.975 ± 0.300V dc
5	A4	A4	A4	A4	NC	A4	A4	A4	A4	-6.975 ± 0.300V dc
6	A4	A4	A4	A4	A4	NC	A4	A4	A4	-6.975 ± 0.300V dc
7	A4	A4	A4	A4	A4	A4	NC	A4	A4	-6.975 ± 0.300V dc
8	A4	A4	A4	A4	A4	A4	A4	NC	A4	-6.975 ± 0.300V dc
9	A4	A4	A4	A4	A4	A4	A4	A4	NC	-6.975 ± 0.300V dc
10	NC	A4	A4	A4	A4	A4	A4	A4	A4	-6.975 ± 0.300V dc

1/ A4 = interconnection with pin P1-A4 (-15V dc).
2/ NC = no connection.
3/ Measured with respect to pin P1-A3.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:56Z
Check the source to verify that this is the current version before use.

3.4 Environmental.

3.4.1 Temperature. The assembly shall be capable of operating as specified herein over the operating temperature range of +40°F to 100°F and shall not be damaged when subjected to the storage conditions ranging from -65°F to 160°F (see 4.6.2.1 and 4.6.2.2).

3.4.2 Vibration. The assembly shall be capable of operating as specified herein after withstanding exposure under the conditions of 3.1.3 to a sinusoidal vibration displacement of .03 inch double amplitude, 10 - 55 Hz in accordance with the applicable portions of Figure 1. Duration of exposure shall be not less than 80 minutes in each of three mutually perpendicular axes (see 4.6.2.3).




FIGURE 1. Vibration Curve.

3.4.3 Shock. The assembly shall be capable of operating as specified herein after exposure under the conditions of 3.1.3 to half sine wave shock pulses of 40 ± 4 gravity units (g's) for a duration of 18 ± 3 milliseconds (msec) in accordance with Figure 2. The assembly shall withstand three shock pulses applied in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

both directions along three mutually perpendicular axes (18 shocks). In addition, the assembly shall be capable of withstanding three half sine wave shock pulses of 100.0 ± 10.0 g's for a duration of 1.5 ± 0.2 msec applied in each direction along three mutually perpendicular axes (see 4.6.2.4).




FIGURE 2. Shock Pulse.

3.4.4 Temperature cycling. The assembly shall be capable of operating as specified herein after withstanding exposure to temperature cycling and soaking between the temperatures of -25°F and 140°F in accordance with Figure 3 (see 4.6.2.5).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.




FIGURE 3. Temperature cycling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Inspection equipment. Unless otherwise specified in the contract, the contractor shall supply, maintain and calibrate inspection equipment in accordancw with the provisions of MIL-I-45607 and standard commercial practice. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract (see 6.5).

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5 and 6.8).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the quality assurance provisions of MIL-F-13926 and the conditions of 3.1.3.

4.4 First article inspection. The requirements for first article approval and the designation of responsibility for first article inspection to either the Government or the contractor shall be specified in the contract (see 6.3).

4.4.1 Sample. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.4.2. The first article sample shall consist of two assemblies.

4.4.2 Inspection. Two assemblies shall be subjected to all the inspections specified in Tables VI, VII, and VIII. Tests 301 and 302 of Table VIII shall be performed first.

TABLE VI. Performance tests.

Item	Characteristics	Requirement	Test Procedure
101	Terminal resistance	3.3.1	4.6.1.1
102	Power sources	3.3.2	4.6.1.2
103	Return logic	3.3.3	4.6.1.3
104	Ammo logic comparator	3.3.4	4.6.1.4
105	AC reference current comparator	3.3.5	4.6.1.5
106	Return current comparator	3.3.6	4.6.1.6

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE VII. Environmental tests.

Item	Characteristic	Requirement	Test Procedure
201	High Temperature	3.4.1	4.6.2.1
202	Low Temperature	3.4.1	4.6.2.2
203	Vibration	3.4.2	4.6.2.3
204	Shock	3.4.3	4.6.2.4
205	Temperature cycling	3.4.4	4.6.2.5

TABLE VIII. General tests.

Item	Characteristic	Requirement	Test Procedure
301	Fabrication	3.1	Applicable drawings - Visual
302	General specifications	3.1.2	4.6.3 - Visual
303	Packaging inspection	5.1	4.6.4 - Visual

4.4.3 Failure. Failure of any assembly to meet any requirement shall be cause for refusal to grant first article approval. The Government reserves the right to terminate first article inspection upon any failure of any assembly to comply with any stated requirement.

4.4.4 Responsibility. The contractor, whether or not responsible, shall inspect the sample for conformance to all contractual requirements and shall submit a record of this inspection and certificates of conformance for materials. The Government reserves the right to witness inspection performed by the contractor.

4.5 Quality conformance inspection.

4.5.1 Procurement conditions. The following inspection plans shall apply where the assembly is procured for use as a:

	Use	Plan
a.	Logistics spare assembly apart from the next higher assembly	A, B and C
b.	Component assembly of the next higher assembly	B and C

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.5.2 Inspection plan A.

4.5.2.1 Environmental sample and tests. One assembly, as a control sample, shall be selected at random by the Government representative from each 50 assemblies produced or from each month's production, whichever occurs first. All the tests in Table VII shall be applied separately to the assembly.

4.5.2.2 Acceptance. When the sample assembly of the produced quantity fails to meet any specified requirement, the lot shall be rejected. Rejected lots shall be resubmitted for reinspection only after all assemblies are re-examined or retested and all defective assemblies are removed or defects corrected.

4.5.3 Inspection plan B.

4.5.3.1 Sample and tests. The sample shall be selected by the Government representative. All the tests in Table VIII and only the test of item 205 of Table VII shall apply. The following sampling plan (except that the visual examination for completeness, improper assembly and evidence of poor workmanship per items 301 and 302 shall be performed 100%) be utilized:

100%, c=0 for lot sizes of 10 or less
n=10, c=0 for lot sizes of 11 to 150
n=32, c=0 for lot sizes greater than 150

where, n=sample size and c=0 requires zero defects during inspection for acceptance

4.5.3.2 Acceptance. Where any one assembly in the sample fails to meet any specified requirement, the lot shall be rejected. Rejected lots shall be resubmitted as above.

4.5.4 Inspection plan C.

4.5.4.1 Sample and tests. Each assembly in every lot shall be subjected to all the tests in Table VI and shall be examined visually for completeness, improper assembly and evidence of poor workmanship per items 301 and 302 of Table VIII. The conditions of 3.1.3 apply.

4.5.4.2 Acceptance. Where any one assembly fails to meet any specified requirement, the defective assembly shall be removed from the lot and resubmitted only after all defects have been corrected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.6 Methods of inspection.

4.6.1 Performance tests.

4.6.1.1 Terminal resistance. Verify resistance values as specified in 3.3.1.

4.6.1.2 Power sources. Apply power sources and interconnections per 3.3.2. The outputs shall be measured and verified to comply with the requirements of 3.3.2.

4.6.1.3 Return logic. Apply power sources and interconnections per 3.3.3. The outputs shall be measured and verified to comply with the requirements of 3.3.3.

4.6.1.4 Ammo logic comparator. Apply the power sources, interconnection, and input conditions per 3.3.4. The output shall be measured and verified to comply with the requirements of 3.3.4.

4.6.1.5 AC reference current comparator. Apply the power sources, signal sources, interconnections, and input conditions per 3.3.5. The output shall be measured and verified to comply with the requirements of 3.3.5.

4.6.1.6 Return current comparator. Apply power sources, signal sources, interconnection, and input conditions per 3.3.6. The output shall be measured and verified to comply with the requirements of 3.3.6.

4.6.2 Environmental tests.

4.6.2.1 High temperature. Subject the assembly to the high temperature test specified in MIL-STD-810, Method 501 except storage temperature shall be 160°F for 48 hours. At the conclusion of the storage temperature test, stabilize the assembly at 100°F and subject it to the performance tests of Table VI. After testing, return the assembly to room temperature and subject it to the performance tests of Table VI.

4.6.2.2 Low temperature. Subject the assembly to the low temperature test specified in MIL-STD-810, Method 502. Maintain the temperature at -65°F for a period of 12 hours minimum. At the conclusion of the storage temperature test, stabilize the assembly at 40°F and subject it to the performance tests of Table VI. After testing, return the assembly to room temperature and subject the assembly to the performance tests of Table VI.

4.6.2.3 Vibration. Vibration A as specified in 4.6.2.3.1 shall be conducted only for first article inspection. Vibration B as specified in 4.6.2.3.2 shall be conducted only for quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.6.2.3.1 Vibration A. Mount the assembly in a suitable vibration fixture and subject the assembly to the vibration test specified in MIL-STD-810, Method 514, General Procedures and 3.4.2. The vibration amplitude shall have a tolerance of ±10%. The tolerance of the vibration frequency shall be ±2%, or ±1/2 Hz for frequencies below 25 Hz. Vibration sweeps shall be conducted with the duration of exposure not less than 80 minutes in each of three mutually perpendicular axes. At the conclusion of this test, subject the assembly to the performance tests of Table VI.

4.6.2.3.2 Vibration B. This test shall be conducted as in 4.6.2.3.1 except that the period of vibration shall be not less than 15 minutes in each axis.

4.6.2.4 Shock. Mount the assembly in a suitable shock fixture and subject it to the functional shock test for ground equipment specified in MIL-STS-810, Method 516, for a total of three half sine wave shock pulses in both directions along three mutually perpendicular axes (18 shocks). Peak amplitude shall be 40 ± 4 g's with a time duration of 18 ± 3 msec in accordance with Figure 2. At the conclusion of this test, subject the assembly to the performance tests of Table VI. Repeat this test with peak amplitude of 100.0 ± 10 g's with a time duration of 1.5 ± 0.2 msec in accordance with Figure 2.

4.6.2.5 Temperature cycling. With power and loads of Table I applied, subject the assembly to the temperature cycling specified in Figure 3. At the conclusion of this test, subject the assembly to the performance tests of Table VI.

4.6.3 General specifications. Verification shall be provided by examination, visually or through the use of standard measuring equipment, in accordance with 3.1.2.

4.6.4 Packaging inspection. The sampling and inspection of the perservation, packaging, packing and container marking shall be in accordance with MIL-STD-2073-1.

5. PACKAGING

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with MIL-STD-2073-1. The level of protection shall be as specified in the procurement document (see 4.6.4 and 6.2d).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

Publications and Form Center for Publication

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The Continuity Test circuit card assembly is intended to be used in the Field Test Set, 11733200.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

c. Inspection provisions for first article (see 6.3).

d. Applicable levels of preservation, packaging, packing and container marking (see 5.1 and 6.7).

6.3 First article. The contracting officer should provide specific guidance to offerors for the submission of a first article sample to be tested as specified in 4.4.2. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Supersession. Previous revisions of MIL-C-48615(AR) were for the U.S. Army Armament, Research, and Development Command's internal use only, and were not forwarded to the Naval Publications and Form Center for publication.

6.5 Submission of contractor inspection equipment designs for approval. Submit copies of designs as required to: Commander, U.S. Army ARDEC, Attn: AMSTA-AR-QAC-F, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.6 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.7 Levels of packaging. The following definitions describe the three levels of packaging in accordance with MIL-STD-2073-1.

a. Level A - Adequate protection for indeterminate storage and worldwide distribution.

b. Level B - Adequate protection for known shipment conditions and storage conditions normally not exceeding one year.

c. Level C - Adequate protection for shipment to a known site for immediate use.

6.8 Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equivalent, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractoe when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation. When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity.

6.9 Subject term (key word) listing.

Computer, M21
Fire Control
Tank, M60A3

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-0015)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.