MILITARY SPECIFICATION

# CARTRIDGES, 90MM: TP-T, XM764, LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of Cartridge designated as Cartridge TP-T, XM764 for use with 90MM Guns M36, M41 and M54 (Made from M71 projectiles or new projectiles).

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

| | | |
|---|---|---|
| MIL-A-2550 | - | Ammunition and Special Weapons, General Specification for |
| MIL-A-48078 | - | Ammunition, Standard Quality Assurance Provisions, General Specification for |

STANDARD

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes |

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| MIL-STD-109 | - | Quality Assurance Terms and Definitions |
| MIL-STD-414 | - | Sampling Procedures and Tables for Inspection by Variables for Percent Defective |
| MIL-STD-1168 | - | Lot Numbering of Ammunition |
| MIL-STD-1235 | - | Single and Multilevel Continuous Sampling Procedures and Tables for by Attributes. |

DRAWINGS

ARMY

| | | |
|---|---|---|
| 6518063 | - | Profile and Alignment |
| 7548301 | - | Ammo. Container, Fiber, M53A3 |
| 7548306 | - | Box, Packing, Ammo by 90MM Gun Ammo in Fiber Container M53A3 Assembly, Detail and Packing |
| 9297850 | - | Cartridge, 90MM, TP-T, XM764 |

## 3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawing and specification.

3.2 Cartridge.-The cartridge shall comply with all requirements specified on Drawing (dwg.) 9297850 and with all requirements specified in applicable specification.

3.3 Propellant weight.-The weight of the propellant shall not differ by more than plus or minus 0.25 ounce from that designated by the loading authorization for the particular lot of propellant used.

3.4 Cartridge case.-When the primer is removed from the case, the primer hole and counterbore along with mouth of case shall be gaged to assure compliance with the dwg requirements.

3.5 Bullet pull.-The cartridge case shall separate from the projectile at a load between 5,000 and 11,000 pounds, when tested as specified in 4.3.2.

3.6 Proving ground test.-The cartridges shall comply with the following requirements when test as specified in 4.3.1.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.6.1 Muzzle velocity.-The corrected muzzle velocity at 70 degrees shall be not more than 2430 feet per second (fps) nor less than 2370 fps and the standard deviation shall not exceed 8.5 feet per second.

3.6.2 Tracer functioning.-The tracer shall ignite and there shall be visible evidence of the burning of the tracer composition to the target.

3.6.3 Extraction.-The cartridge case shall extract freely from the gun after firing.

3.6.4 Safety.-There shall be no premature separation of metal parts in the gun bore or in flight before impact.

3.7 Primers.-The primers shall have the required number of flash holes.

3.8 Workmanship

3.8.1 General.-All parts shall be free from chips, dirt, grease, rust, burrs, and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The cartridge or components shall not be damaged in any manner during the renovation or loading operation.

3.8.2 Painting and Marking. The painting and marking shall be restored by the loading and assembling contractor on any component furnished him when such painting or marking has been marred or obliterated.

3.8.3 Cartridge case.- The cartridge case shall be free of any roughness, scratches, rust, cracks, splits or dents which will adversely affect their serviceability.

3.8.4 Rotating Band.-Care shall be exercised at all times so that the rotating band of the projectile is not nicked, burred, or otherwise damaged.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.2 Quality Conformance Inspection

4.2.1 Inspection Lot Formation. Inspection lots shall ›mply with the lot formation provision of MIL-A-48078. In .dition, inspection lots of Cartridge, 90MM, TP-T, XM764 shall ›ntain:

a. Projectile of one zone weight.

b. Propellant from not more than one lot.

c. Loaded tracers from one lot interfix number from one nufacturer.

d. Loaded primers from one lot interfix number from one nufacturer.

e. Cartridge cases of one lot interfix number from one nufacturer or one lot of previously complete cartridges (prior renovation).

f. Windshields of one lot interfix number from one nufacturer.

4.2.2 Examination.-See MIL-A-48078

a. Sampling Plans. Unless otherwise specified in the assification of Defects and Tests Tables, sampling plans for jor and minor defects shall be in accordance with MIL-STD-1235.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48758 (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 7548080 |
|---|---|---|---|---|---|
| 4.2.2.1 | Case, Prior to assembly of primer | | | | NEXT HIGHER ASSEMBLY 9297850 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Diameter of primer hole | | 0.40% | 3.2 | Gage |
| 132 | Diameter of counterbore | | 0.40% | 3.2 | Gage |
| 133 | Diameter of mouth | | 0.40% | 3.2 | Gage |
| 134 | Depth of counterbore | | 0.40% | 3.2 | Gage |
| Minor | | | | | |
| 201 | Overall length, Minimum (min.) | | 0.65% | 3.2 | Gage |
| 202 | Protective coating incomplete or damaged (see 3.8.2) | | 0.65% | 3.8 | Visual |
| 203 | Dents on case (see 3.8.3) | | 0.65% | 3.8 | Visual |
| 204 | Evidence of poor workmanship (see 3.8) | | 0.65% | 3.8 | Visual |

NOTES:
For reworked cartridge cases only.

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48758 (PA)

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.2.2.2 | Primer, prior to assembly to cartridge case | 1 OF 1 | 8838130 |
| | | | NEXT HIGHER ASSEMBLY 9297850 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | | | | | |
| 1 | One or more flash holes missing | | 100% | 3.7 | Visual |
| Major | None defined | | | | |
| Minor | None defined | | | | |

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48758 (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 9297852 |
|---|---|---|---|---|---|
| 4.2.2.3 | Projectile, prior to loading | | | | NEXT HIGHER ASSEMBLY 9297850 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | Depth of tracer cavity maximum (max.) | | 100% | 3.2 | Gage |
| Major | | | | | |
| 131 | Pitch diameter of tracer thread max. | | 0.40% | 3.2 | Gage |
| 132 | Minor diameter of tracer thread max. | | 0.40% | 3.2 | Gage |
| 133 | Length of perfect tracer thread min. | | 0.40% | 3.2 | Gage |
| 134 | Depth of tracer cavity, min. | | 0.40% | 3.2 | Gage |
| Minor | | | | | |
| 201 | Evidence of poor workmanship (see 3.8) | | 0.65% | 3.8 | Visual |

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 9297851 |
|---|---|---|---|---|---|
| 4.2.2.4 | Projectile | | | | NEXT HIGHER ASSEMBLY 9297850 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Weight of projectile in correct zone | | 100% | 3.2 | Balance |
| 132 | Gasket missing | | 0.40% | 3.2 | Visual |
| 133 | Weight zone marking incorrect | | 100% | 3.2 | Visual |
| 134 | Pad missing | | 0.5 | 3.2 | Visual |
| Minor | | | | | |
| 201 | Tracer fails to withstand minimum disassembly torque. | | 0.40% | 3.2 | Test |
| 202 | Windshield fails to withstand minimum disassembly torque. | | 0.40% | 3.2 | Test |
| 203 | Evidence of poor workmanship (see 3.8). | | 0.65% | 3.8 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48758 (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.2.2.5 | Cartridge case prior to loading | | | | 9297850 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Case damaged | | 0.65% | 3.8 | Visual |
| 202 | Foreign matter in interior of case | | 0.65% | 3.8 | Visual |
| 203 | Primer bent or otherwise damaged | | 0.65% | 3.8 | Visual |
| 204 | Evidence of poor workmanship (see 3.8) | | 0.65% | 3.8 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 9297850 |
|---|---|---|---|---|---|
| 4.2.2. 6 | Cartridge case prior to adding propellant | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major A 101 | Weight of propellant | | see 4.2.3.4 | 3.3 | |
| Minor | None defined | | | | |

NOTES:

SARPA-QA FORM 2567 FEB 74



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET 1 OF 2 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.2.2.7 | Cartridge | | | | 9297850 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | Primer above flush | | 100% | 3.2 | Gage |
| Major B | | | | | |
| 131 | Total length max. | | 0.40% | 3.2 | Gage |
| 132 | Assembly damaged | | 0.40% | 3.2 | Visual |
| 133 | Crimp missing or inadequate (to the extent that projectile is liable to separate) | | 0.40% | 3.2 | Visual-Manual |
| 134 | Rotating band damaged | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Marking misleading or unidentifiable, including incorrect color code | | 0.65% | 3.2 | Visual |
| 202 | Compound missing from crimp | | 0.65% | 3.2 | Visual |
| 203 | Evidence of poor workmanship (see 3.8) | | 0.65% | 3.8 | Viaual |
| Critical | | | | | |
| 1 | Premature bursts and security of parts | see 4.2.3.2 | | 3.6.4 | 4.3.1 |
| Major A | | | | | |
| 101 | Muzzle Velocity | see 4.2.3.2 | 1.0% | 3.6.1 | 4.3.1 |
| 102 | Tracer Function | see 4.2.3.2 | | 3.6.2 | 4.3.1 |
| 103 | Extraction | 4.2.3.2 | | 3.6.3 | |
| 104 | Bullet pull | see 4.2.3.3 | 1.5% | 3.5 | 4.3.2 |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET 2 OF 2 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.2.2.8 | CONTINUATION SHEET | | | | 9297850 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| 105 | Profile and alignment | | 100% | 3.2 | 6518063 |

NOTES:

SARPA-QA FORM 2567 FEB 74



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48758 (PA)

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| 4.2.2.8 | Unsealed Fiber Container | | 7548301 |
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Packing Component missing | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Cartridge cannot be removed by hand | | 0.65% | 3.2 | Visual |
| 202 | Container Cap cannot be removed by hand | | 0.65% | 3.2 | Visual |
| 203 | Glue or asphalt on cartridge | | 0.65% | 3.2 | Visual |
| 204 | Packing components improperly assembled | | 0.65% | 3.2 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.2.2.9 | Sealed Fiber Container | | | | 7548301 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Container cut or damaged through all asphalt impregnated layers | | 0.40% | 3.2 | Visual/Manual |
| 132 | Metal end loose or distorted | | 0.40% | 3.2 | Visual/Manual |
| 133 | Tape incomplete or badly wrinkled | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Tear tab length minimum | | 0.65% | 3.2 | Visual |
| 202 | Contents loose | | 0.65% | 3.2 | Manual |
| 203 | Gap between cover and body of container exceeding 1/8 inch | | 0.65% | 3.2 | Visual |
| 204 | Cuts, scuffs or gouges in outer layers | | 0.65% | 3.2 | Visual |
| 205 | Marking, misleading missing or unidentifiable | | 0.65% | 3.2 | Visual |

NOTES:



SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48758 (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.2.2.10 | Sealed wood packing box | | | | 7548306 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Box damaged | | 0.40% | 3.2 | Visual |
| 132 | Strapping missing, broken or loose | | 0.40% | 3.2 | Visual |
| 133 | Boards loose or nails protruding | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Marking misleading or unidentifiable | | 0.65% | 3.2 | Visual |

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.2.3 Testing

4.2.3.1 Check test for deterioration of primer.-If the total time between original acceptance of any primer lot and the assembly of that lot into complete round cartridges extends two years, or if the primers have been subject to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to, and must satisfactorily pass the check test, specified in the applicable primer loading specification immediately before the primer lot is assembled into the cartridges. The test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the primers into the cartridges.

4.2.3.2 Proving ground. (See 6.5).

4.2.3.2.1.1 Muzzle velocity

4.2.3.2.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified the sampling plan shall be in accordance with MIL-STD-414, Section B, Table B-3, Code letter I and AQL of 1.0 percent. In addition, if the standard deviation of the muzzle velocity multiplied by the factor 0.75 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.1.2 After the three consecutive lots have met the criteria of 4.2.3.2.1.1, the sampling plan shall be in accordance with MIL-STD-414, Section B, Table B-3, Code letter F and AQL of 1.0 percent, in addition, if the standard deviation of muzzle velocity multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.2.2 Premature bursts and security of parts. If any of the sample projectiles used in any of the tests fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.2.3 Tracer function.

4.2.3.2.3.1 The sample cartridges used in the test for muzzle velocity (see 4.2.3.2.1.1) shall be tested for functioning. If more than two projectiles fail the specified requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.2.3.2.3.2 The sample cartridges used in the test for muzzle velocity (see 4.2.3.1.2) shall be tested for functioning. If more than one projectile fails the specified requirement, the lot shall be rejected.

4.2.3.2.4 Safety

4.2.3.2.4.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements, ten sample cartridges shall be randomly selected from each lot for this test. If any projectile fails to comply with the requirements, the lot shall be rejected.

4.2.3.2.5 Extraction.-The cartridges fired in the tests shall be observed for compliance with extraction requirements. Failure of any cartridge shall be cause for rejection of the lot.

4.2.3.2.6 Retest.-If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional sample rounds are required.

4.2.3.3 Bullet pull.-The sampling plan for this test shall be in accordance with MIL-STD-414, Section B, Part I Table B3, Code letter F and AQL 1.5 percent.

4.2.3.4 Propellant weight.-The propellant shall be weighed and check-weighed 100 percent. The check-weighing shall be accomplished independently of the original weighing, using a different balance from that used to conduct the original weighing and, if performed manually, shall be performed by another operator. Any charge which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.5 Profile and alignment.-The cartridges shall be gaged 100 percent for profile and alignment. Any cartridge which fails to meet the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the "paragraph reference/inspection method" column in the tables starting with paragraph 4.2.2.1. The contractor shall submit for approval inspection equipment de-



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

gns in accordance with the terms of contract. See Section 6 MIL-A-48078 and 6.3 herein.

4.3 Test Methods and Procedures

4.3.1 Proving ground.-These tests shall be conducted at Government proving round in accordance with the applicable ceptance Test Procedure. The sample cartridges shall be red in a gun for which the cartridge is standard.

4.3.1.1 Muzzle velocity, tracer function and accuracy.- e cartridge shall be fired at a target 1000 meter down range i observation shall be made for velocity, tracer function and traction. In addition accuracy shall be taken for information ly.

4.3.1.2 Safety.-Assemble the rounds with a charge adsted to give a pressure 112 percent of the average pressure the particular lot of propellant. A smear camera shall be ed to observe the projectile in flight in order to record possible malfunction.

4.3.2 Bullet pull.-The security of the crimp of the cartige case to the projectile shall be determined by applying a id in the axial direction with a rate of travel of the sting machine head of 0.100 to 0.125 inch per minute. Obsertion shall be made for compliance with the applicable requirent.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level A.-The cartridge shall be preserved and kaged in accordance with dwg. 7548301.

5.2 Packing

5.2.1 Level A.-The fiber container shall be packed in ordance with dwg 7548306.

5.3 Marking.-The box shall be marked in accordance with g. 7548306. The fiber container shall be marked in accordce with dwg. 7548 301.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Intended use.-The cartridges covered by this specification are intended for use in the M36 and M41 Gun.

6.2 Ordering Data.-See MIL-A-48078.

6.3 Submission of Inspection Equipment Design for Approval.-See 6.2.3 of MIL-A-48078. Submit equipment designs, as required to Commander, Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover, New Jersey 07801.

6.4 Proving Ground Test Summary

| | Sample Size | Vel FPS | Ac Re | Press PSI |
|---|---|---|---|---|
| Quality Conformance | | | | |
| First 3 consecutive acceptable lots. | | | | |
| Velocity | 25 | 2370-2430 | | |
| Tracer Functioning | | | 2-3 | |
| Safety | 10 | | | 50,400±1500 |
| Extraction | | | 0-1 | |
| Subsequent Lots | | | | |
| Velocity | 10 | 2370-2430 | | |
| Tracer Functioning | | | 1-2 | |
| Extraction | | | 0-1 | |

6.5 Submission of test data.-In addition to the normal distribution of records, when the cartridge is procured by the Department of the Army one copy of all ballistic test data will be forwarded to the following:

Commander
Picatinny Arsenal
ATTN: SARPA-QA-A-A, SARPA-AD-E-A and SARPA-AD-EP
Dover, New Jersey 07801

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1315-A066



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

**DD FORM 1 JAN 72 1426** REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.