MILITARY SPECIFICATION

CARTRIDGE, 81MM, PRACTICE M879
LOADING, ASSEMBLING AND PACKING

This specification is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading, assembling and packing for one type of practice mortar cartridge designated as Cartridge, 81MM Practice M879.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extend specified herein. Unless otherwise specified the issues of these documents shall be those listed in the issue of the Department of Defense Index and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-C-70545 - Charge, Propelling, XM218/219/M220 Loading Assembling and Packing

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A FSC 1315
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedure and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of the specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

DRAWINGS

7257965	- Wear Limit Check
6518071	- Profile and Alignment
6518072	- Alignment Check
9310340	- Cartridge, Practice, 81MM, M879, W/Fuze, Practice, M751
9362798	- Packing and Marking for Box, Ammunition, Packing for Cartridge, 81MM, XM819, XM853 and M879
9381730	- Packing and Marking for Container Ammunition Fiber for Cartridge, 81MM, Practice M879

(Copies of specifications, standards, drawings and publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall superceded applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Cartridge. The cartridge shall comply with all requirements specified on (dwg) 9310340.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.3 Proving ground test. The cartridges shall comply with the following requirements when tested in accordance with 4.4.3.1 and 4.5.1.

3.3.1 Misfires. The cartridges shall not fail to fire from the weapon.

3.3.2 Short rounds. No cartridges shall have a horizontal range less than 80 percent of the average horizontal range (calculated without the short rounds).

3.3.3 Metal parts separation. There shall be no metal parts separation in the gun bore or in flight.

3.3.4 Range standard deviation. The horizontal range standard deviation shall be no greater than twenty-two (22) meters at charge zero and no greater than eighty-three (83) meters at charge four.

3.3.5 Duds. The fuze shall function upon ground impact of the cartridge.

3.4 Workmanship. The item of shipment, its components, and materials shall be free from dirt, chips, grease and other foreign matters. There shall be no cracks, scratches, dents, gouges, holes, porous areas, distortion, or undesirable characteristics which would in any way detract from the useability of the product for its intended purpose. Parts and assemblies shall be free from all contaminants and damage after cleaning.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set for in this specification shall become a part of the contractor's overall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The following types of inspections shall be conducted on this item.

a. First article inspection (see 4.3).

b. Quality conformance inspection. (see 4.4)

4.3. First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the components in the quantities indicated in Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

nt data which may be of use in improving this document(s) or to amend contractual requirements. Attach any pertine

TABLE I First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE: Cartridge, Practice, 81MM, M879, W/Fuze, Practice, M751	SHEET 1 OF 1	DRAWING NUMBER: See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge, Practice, 81mm, M879 w/Fuze, Practice, M751 (dwg. 9310340)				
	Examination for defects	9		3.1	4.4.2.4
	Proving Ground Test	96		3.3	4.4.2.4

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of practice cartridges shall contain:

a. Projectile body metal parts assemblies of one lot interfix number, from one manufacturer.

b. Fin assemblies of one lot interfix number, from one manufacturer.

c. Ignition cartridges of one lot interfix number, from one manufacturer.

d. Propelling charges made from not more than one lot of propellant, from one manufacturer.

e. Obturating rings of one lot interfix number, from one manufacturer.

f. Fuzes of one lot interfix, from one manufacturer.

4.4.2 Examination. See MIL-A-48078

a. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

b. Continuous Sampling in accordance with MIL-STD-1235 may be used if approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9381510
4.4.2.1	Charge, Propelling M220 (Prior to Assembly to Round)				NEXT HIGHER ASSEMBLY 9310340
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Container or container seal damaged to the extent that propellant shall escape		100%	3.1	4.5.2/Visual
Major 101	Container or container seal damaged but not to the extent that propellant shall escape		100%	3.1	4.5.2/Visual
Minor 201	Marking missing, illegible or incomplete		0.65%	3.4	4.5.2/Visual
202	Poor workmanship		0.65%	3.4	4.5.2/Visual

NOTES: If LAP of the propelling charge M220 and Cartridge M879 are performed at the same installation this paragraph is not required, see MIL-C-70545.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Ignition Cartridge, M299				9293422
					NEXT HIGHER ASSEMBLY 9310340
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Missing Loose or damaged components		100%	3.1	Visual
Minor 201	Marking missing, illegible or incomplete		0.65%	3.1	Visual
202	Poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.3	Support (Die Check)		1 OF 1	9381748
				NEXT HIGHER ASSEMBLY 9381747
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH / PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined			
Major				
101	Inside length	(a)		3.1 Gage
102	Inside radius to support wall	(a)		3.1 Gage
103	Width or rib (2 places)	(a)		3.1 Gage
104	Radius to outside surface of rib (3 places)	(a)		3.1 Gage
Minor				
201	Poor workmanship		0.65%	3.4 Visual

NOTES:
(a) Sample (3) parts from each Mold Cavity at the start of each molding run.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9381747
4.4.2.3.1	Support Assembly				NEXT HIGHER ASSEMBLY 9310340
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Foreign matter in lining material		0.40%	3.1	Visual
Minor					
201	Lining material damaged, wrinkled or torn		0.65%	3.1	Visual
202	Lining adhesive not properly adhering to support		0.65%	3.1	Visual/Manual
203	Poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cartridge, Practice, 81MM, M879 W/Fuze Practice, M751 (Prior to installation of Prop. Chg. Sup. Ass'y).	1 OF 2	9310340
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Depth of ignition cartridge from fin end below min.		100%	3.2	Gage
2	Obturating band missing		100%	3.2	Visual
3	Cracked fin housing		100%	3.2	Visual (4 power magnifier)
4	Propelling charges missing or damaged to the extent that propellant leaks		100%	3.1	Visual (See 4.5.2)
Special					
A	Warning marking missing		100%	3.2	Visual
B	Fin blade distorted		100%	3.2	Gage
C	Fuze Striker in Armed Position		100%	3.2	Visual
D	Fuze packing clip missing		100%	3.2	Visual
Major					
101	Obturating band not welded		100%	3.2	Visual
102	Obturating band not flush or below bourrelet diameter		100%	3.2	Visual
103	Cartridge assembly fails to freely enter profile and alignment gage		100%	3.2	Gage G81 001(A)
104	Obturating band damaged		0.40%	3.2	Visual
105	Fin assembly fails to meet minimum assembly torque (while cement still wet)		0.40%	3.2	Test

NOTES: (A) See dwg. 6518071 profile and alignment
6518072 alignment check
7257965 wear limit check

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.4	Cartridge, Practice, 81MM, M879 W/Fuze Practice, M751 (Prior to installation of Prop. Chg. Sup. Ass'y)		2 OF 2	9310340
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
106	Fuze fails to meet minimum assembly torque (while cement still wet)		0.40%	3.2	Test
107	Ignition Cartridge fails to meet minimum assembly torque (while cement still wet)		0.40%	3.2	Test
108	Fin assembly not fully seated		0.40%	3.2	Visual
109	Fuze assembly not fully seated		0.40%	3.2	Visual
110	Obturating band pull test	(A)		3.2	4.5.3
111	Obturating band assembled upside down		100%	3.2	Visual
112	Propellig charges not properly assembled		0.40%	3.1	Visual/4.5.2.1
113	Support missing or damaged		0.40%	3.1	Visual
114	Support tape missing		0.40%	3.1	Visual/4.5.2.1
115	Tape pull tab inadequate		0.40%	3.1	Visual
Minor					
201	Paint damaged in excess of 1/4 sq. inch		0.65%	3.2	Visual
202	Marking missing or incomplete		0.65%	3.2	Visual
203	Poor workmanship		0.65%	3.4	Visual

NOTES:
(A) See paragraph 4.5.3

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.5	Packing and Marking For Container Ammunition Fiber For Cartridge 81MM Practice M879 (While Packing)		1 OF 1		9381730
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special A	Packing stop missing from fuze		100%	3.1	Visual
Major 101	Propelling charge support missing or not secured		100%	3.1	Visual/Manual
Minor 201	Spacer, cushion or filler disc assembly missing		0.65%	3.1	Visual
202	Handle not properly assembled to container		0.65%	3.4	Visual/Manual
203	Poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Sealed Fiber Container (After Packing) Packing and Marking for Container, Ammo Fiber for Cart, 81MM, Prac M879	1 OF 1	9381730
			NEXT HIGHER ASSEMBLY 9362798

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Container damaged		0.40%	3.1	Visual
102	Fiberglass sealing strip incomplete or badly wrinkled (Before applying cloth sealing strip)		0.40%	3.1	Visual
103	Cloth sealing strip incomplete or badly wrinkled		0.40%	3.1	Visual
104	Metal ends loose or distorted		0.40%	3.1	Visual/Manual
105	Contents loose		0.40%	3.1	Visual/Audible/Manual
106	Pull tab missing or improper		0.40%	3.1	Visual
Minor					
201	Marking missing, illegible or incomplete		0.65%	3.1	Visual
202	Poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48635(AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.7	Box, Loaded and Sealed - Packing and Marking for Box, Ammo, Packing for Cartg, 81MM, M819, M853 & M879		1 OF 1		9362798 NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Boards split or loose exposing containers		0.65%	3.1	Visual
202	Contents loose		0.65%	3.1	Visual
203	Marking misleading or unidentifiable		0.65%	3.1	Visual
204	Strapping insecure		0.65%	3.1	Visual/Manual
205	Seal missing, unsealed or improperly positioned		0.65%	3.1	Visual/Manual
206	Poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Proving ground test. Testing shall be in accordance with 4.5.1.

4.4.3.1.1 Sampling plan. Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, ninety six (96) random sample cartridges shall be selected from each lot for this test. The lot shall be rejected if:

a. Two or more misfires occur.

b. One or more short rounds occur.

c. One or more metal parts separations occur.

d. Horizontal range standard deviation at charge 0 exceeds 22 meters or horizntal range standard deviation at charge 4 exceeds 83 meters.

e. Three or more duds occur.

4.4.3.1.2 Modified sampling plan. After three consecutive lots have complied with the criteria of 4.4.3.1.1, forty eight random sample cartridges shall be selected from each lot for this test. The lot shall be rejected if:

a. Two or more misfires occur

b. One or more metal parts separations occur

c. Horizontal range standard deviation at charge 0 exceeds 22 meters or horizontal range standard deviation at charge 4 exceeds 83 meters.

d. Three or more duds occur

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.4.2

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

4.5 Methods of inspection.

4.5.1 Proving ground test. The test shall be performed at a Government Proving ground in accordance with the applicable USATECOM Acceptance Test Procedure.

The cartridges shall be fired from a standard 81MM M252 mortar at an elevation of forty-five (45) degrees. One half of the sample cartridges shall be fired at charge zero and the other half at charge four. The individual velocities, pressures, deflections and ranges shall be recorded on the firing record (charge 4 only). Observation shall be made for misfires and duds, and shall be recorded. In the event of a misfire, the ignition cartridge shall be removed and forwarded to ARDC, Attn: SMCAR-LCE-E.for disassembly. Misfired ignition cartridges shall not be disassembled by the proving ground. Should metal parts separation occur, a photograph shall be taken of the evidence and attached to the firing record. The velocity and range standard deviations and arithmetic averages shall be calculated and recorded. Temperature of the day, weather and the time of firing shall be recorded. Range probable error shall be calculated and recorded.

Hawk or equivalent radar shall be used to observe for metal parts separation, unobserved short rounds and unobserved duds. In these events, an analysis should be made of the radar data and should be noted on the firing record. This shall include a comparison of times of flight of the unobserved rounds with that of the normal rounds. Prints of the radar traces of those rounds and prints of the preceeding and succeeding rounds, shall be attached to the firing record. Data from ballistically acceptable lots may be discarded. Smear camera shall be used to photograph all samples. The camera shall be positioned to pick up each round just outside the second velocity coil. Should an unobserved dud, short round or any other abnormal performance occur, a photo print of these rounds, and prints of all other rounds in that particular charge zone, in that lot, shall be attached to the firing record. Film from acceptable lots may be discarded.

[illegible] the ARDEC considers that the test conditions have detrimentally affected the test results, the test results shall be declared invalid and a new test shall be performed on additional sample cartridges.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

4.5.2 Damaged propelling charge. To ascertain that a damaged propelling charge is to be classed as critical or major, the following procedure shall be used:

a. Place the damaged charge on a M24 fin, oriented such that the propellant would be resting against the damaged surface.

b. The fin-charge assembly shall be hand shaken vigorously three times.

c. Examination shall be made for propellant spillage. If any propellant is observed, the damaged propelling charge shall be classed as a critical defect, if no propellant is observed, the damaged propelling charge shall be classed as a major defect.

4.5.2.1 Alternate assembly/inspection procedure. The contractor may elect to utilize the following assembly operations:

a. Place the support for the propelling charge in a holding fixture.

b. Properly place the four propelling charges in the support with gaps aligned upward.

c. Press the fin housing into the propelling charges and support assembly.

d. 100% visual inspection for damage to the ends of four propelling charges will be performed.

e. Continue the assembly/inspection operations.

4.5.3 Obturating band pull test. Properly install and weld an obturating band in a simulated 81MM body groove of the correct size and shape with a relief for a pull test hook. Weld seal must withstand a minimum pull of 10 lbs. and must fail under a pull of 40 lbs. Test one at the start of each production run and each 4 hours of assembly or after 350 assemblies. If the weld fails under 10 lbs. rework the production since the last test. If the strength is over 40 lbs. replace the bands on all rounds since the last test.

5. PACKAGING

5.1 Unit packaging.

5.1.1 Level A. Unit packaging for cartridge shall be in accordance with requirements of drawing 9381730.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

5.1.2 Level B. Same as Level A.

5.1.3 Level C. Same as Level A.

5.2 Packing.

5.2.1 Level A. Packing for cartridge shall be in accordance with requirements of drawing 9382798.

5.2.2 Level B. Same as Level A.

5.2.3 Level C. Same as Level A.

5.3 Marking.

5.3.1 Level A. Unit packaging for cartridge shall be marked in accordance with the requirements of drawing 9381730. Packing for cartridge shall be marked in accordance with the requirements of drawing 9382798.

5.3.2 Level B. Same as Level A.

5.3.3 Level C. Same as Level A.

6. NOTES

6.1 Intended use. The item covered by this specification is intended for use in Cartridge, 81mm, Practice M879.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of designs for approval. See 6.2.3 of MIL-A-48078. Submit equipment designs, as required, to Commander, AMCCOM, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.4 Submission of test data. One copy of proving ground ballistic acceptance test data (i.e, firing record) will be forwarded to the following: Commander, AMCCOM, ATTN: AMSMC-QAT-B(D) and SMCAR-LCU-S-I(D).

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

6.5 Proving ground test summary.

TEST	SAMPLE SIZE	REQUIREMENTS
Proving Ground	(See 4.4.3.1) Ninety six samples until three consecutive lots have complied with the acceptance criteria. Forty-eight samples thereafter.	a. Misfires (see 3.3.1) b. Short rounds (see 3.3.2.) c. Metal parts separation (see 3.3.3) d. Range Standard Deviation (see 3.3.4) e. Duds (see 3.3.5)

6.6 Submission of calibration and process control plans. Prior to implementation of calibration or process control plans in accordance with 4.2.2, plans shall be approved by ARDEC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.8 Data cards. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

6.9 Subject term (key word) listing.

AMSC number
Compliance
Conformance
Inspection
Military specification
Requirements
Shipment

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A910)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07801 5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-48635	CARTRIDGE, 81MM, PRACTICE M879 LOADING, ASSEMBLING & PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.