MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M751 WITH PYROTECHNIC SIGNATURE CARTRIDGE

This Specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the manufacture of metal parts and pyrotechnic signature cartridge for one type of point detonating practice fuze designated as Fuze, Point Detonating, Practice, M751.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

MIL-P-60412 - Packaging, Packing and Marking for Shipment of Artillery Type and Rocket Fuzes, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of the specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

DRAWINGS

9344009 - Fuze, PD, Practice, M751, Less Cartridge, Spotting
9344092 - Fuze, PD, Practice, Loading, M751
12598354 - Packing and Marking of Box, Fiberboard, Fuze Practice M751.
12598356 - Packing and Marking of Wood Box for Fuze, Practice M751.

(Copies of specifications, standards, drawings and publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of conflict between the text of this specification and the reference cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Fuze assemblies and parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.2.1 Fuze assemblies. The fuze assemblies shall comply with all requirements specified on drawing (dwg) 9344009 and associated drawings and with all requirements specified in applicable specifications and standards.

3.2.2 Fuze loading assembly. The fuze loading assembly shall comply with all requirements on dwg 9344092 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Functioning. Optional fuze settings shall be available for manual adjustment to simulate the M734 Multi-option fuze. However, the practice fuze shall detonate only on impact regardless of the setting.

3.4 Jolt and jumble. The fuze assembly shall be subjected to and must withstand the Jolt Test specified in MIL-STD-331, with the exception that the fuze shall not be disassembled and inspected after the Jolt Test. After completion of the Jolt Test, the same fuze shall be subjected to and must withstand the Jumble Test specified in MIL-STD-331.

3.5 Transportation vibration. The fuze assembly shall comply with the requirements of MIL-STD-331 Test 123, but at ambient temperature and four hours per axis.

3.6 Proving ground test. Loaded fuzes from the Transportation Vibration Test, when ballistically fired, shall provide a visible flash and smoke signature at a "naked eye" viewing range of 1500 meters. An audible signature must also be heard at this distance.

3.7 1.5 Meter drop test. The fuze assembly shall comply with the requirements of MIL-STD-331, Test 111.1, Procedure 1, paragraph 5.1.1. and paragraph 3.1.1.

3.8 Spring embrittlement. None of the springs used in the fabrication of the fuze shall break when extended or distorted to the point of minimum permanent distortion.

3.9 Twelve meter drop test. The loaded fuze assembly shall withstand the twelve-meter drop test specified in MIL-STD-331. To satisfy the requirements of MIL-STD-331, Test 103.2, the disassembled fuze must display the following conditions:

a. No loose powder shall be present in the fuze assembly.

b. The fuze has remained in the fully safe position.

c. The striker has not penetrated the spotting signature cartridge primer area.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.10 Ogive Pull Test. The ogive shall withstand a longitudinal pulling force of 50 + 5 pounds in the ogive at both the forward and rear section joint.

3.11 First article inspection. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be specified in the contract and 4.3 herein.

3.12 Workmanship. All parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, porosity, warpage, burn marks, checks, blisters, excess flash, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detailed specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set for in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Alternate inspection provisions. Alternative inspection procedures, methods or equipment (including tool inspection, statistical process control, substitute sampling plans, etc.) may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

specified here in. Prior to applying such alternative inspection procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Procuring Contracting Officer for evaluation and approval by the Government. When required, the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the quality assurance provisions herein. In cases of dispute as to whether certain procedures of the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply.

4.2 Classification of inspection. The following types of inspections shall be conducted on this item.

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following (see Table I for details):

Part Description	Drawing	Quantity
Body, Fuze	9343991	10
Ogive, Simulated M734 Rear Section	9387053	10
Ogive, Simulated M734 Forward Section	9387054	10
Ogive, Simulated, M734 Assembly	9331848	10
Shell, Shotgun, Primed, 20 Gauge	9344010	10
Cartridge, spotting	9341590	10
Wad	9341592	10
Spring, Setback Pin	9343992	10
Spring, Striker	9343993	10
Spring, Slider	9343994	10
Spring, Ball	9344006	10
Pin, Packing Clip	9344001	10
Clip, Packing	9344004	10
Packing Clip Assembly	9344005	10
Chamber, Fuze	9343997	10
Pin, Setback	9390437	10
Slider	9343999	10
Striker, Marking	9344007	10
Striker	9343995	10
Fuze Body Sub-Assembly	9344000	20
Fuze Body Assembly	9387100	10
Fuze, PD, Practice, Loading, M751	9344092	181

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Fuze, Point Detonating, Practice M751		SHEET 1 OF 6		DRAWING NUMBER: SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body, Fuze (Dwg 9343991) Examination for Defects	10		3.2	4.4.2.1
	Ogive, Simulated M734 Rear Section (Dwg 9387053) Examination for Defects	10		3.2	4.4.2.2
	Ogive, Simulated M734 Forward Section (Dwg 9387054) Examination for Defects	10		3.2	4.4.2.3
	Ogive, Simulated M734 Assembly (Dwg 9331848) Examination for Defects	10		3.2	4.4.2.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE: Fuze, Point Detonating, Practice M751		SHEET 2 OF 6		DRAWING NUMBER: SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shell, Shotgun, Primed 20 Gauge (Dwg 9344010) Examination for Defects	10		3.2	4.4.2.5
	Wad (Dwg 9341592) Examination for Defects	10		3.2	4.4.2.6
	Cartridge, Spotting (Dwg 9341590) Examination for Defects	10		3.2	4.4.2.7

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 6		DRAWING NUMBER
	Fuze, Point Detonating, Practice M751				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Setback Pin				
	(Dwg 9343992)				
	Examination for Defects	10		3.2	4.4.2.8
	Spring Embrittlement Test	10(a)		3.8	4.5.3
	Spring, Striker				
	(Dwg 9343993)				
	Examination for Defects	10		3.2	4.4.2.9
	Spring Embrittlement Test	10(a)		3.8	4.5.3
	Spring, Slider				
	(Dwg 9343994)				
	Examination for Defects	10		3.2	4.4.2.10
	Spring Embrittlement Test	10(a)		3.8	4.5.3

NOTES: (a) Only 10 units are required if non-destructive examination is followed by destructive tests.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
	Fuze, Point Detonating, Practice M751		4 OF 6	SEE BELOW
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Ball (Dwg 9344006)				
	Examination for Defects	10		3.2	4.4.2.11
	Spring Embrittlement Test	10(a)		3.8	4.5.3
	Pin, Packing Clip (Dwg 9344001)				
	Examination for Defects	10		3.2	4.4.2.12
	Clip, Packing (Dwg 9344004)				
	Examination for Defects	10		3.2	4.4.2.13
	Packing Clip Assembly (Dwg 9344005)				
	Examination for Defects	10		3.2	4.4.2.14
	Packing Clip Pull Test	10		3.2	4.5.9

NOTES: (a) Only 10 units are required if non-destructive examination is followed by destructive tests.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-F-48637(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, Point Detonating, Practice M751	5 OF 6	SEE BELOW
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Chamber, Fuze (Dwg 9343997) Examination for Defects	10		3.2	4.4.2.15
	Pin, Setback (Dwg 9390437) Examination for Defects	10		3.2	4.4.2.16
	Slider (Dwg 9343999) Examination for Defects	10		3.2	4.4.2.17
	Striker (Dwg 9343995) Examination for Defects	10		3.2	4.4.2.18
	Striker Marking (Dwg 9344007) Examination for Defects	10		3.2	4.4.2.19

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Fuze, Point Detonating, Practice M751		SHEET 6 OF 6		DRAWING NUMBER: SEE BELOW NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fuze, Body Sub-Assembly (Dwg 9344000)				
	Examination for Defects	20(a)		3.2	4.4.2.20
	Striker Push Out Test	20(a)		3.2	Test/4.5.10
	Setback Stake Pushout Test	20(a)		3.2	Test/4.5.11
	Packing Clip & Packing Clip Pin Assembly Retention Test	20(a)		3.2	Test/4.5.12
	Fuze Body Assembly (Dwg. 9387100)				
	Examination for Defects	10		3.2	4.4.2.21
	Ogive Pull Test	10		3.2	Test/4.5.13
	Fuze, PD, Practice, Loading, M751 (Dwg 9344092)				
	Examination for Defects	10		3.2	4.4.2.22
	Jolt and Jumble Test	15		3.4	Test/4.5.4
	Transportation Vibration Test	96		3.5	Test/4.5.5
	1.5 Meter Drop Test	45		3.7	Test/4.5.5
	Forty-Foot Drop Test	15		3.9	Test/4.5.8
	Proving Ground Test	80(b)		3.6	Test/4.5.7

NOTES: (a) Only 20 units are required if non-destructive examination is followed by the destructive test.
(b) These units are to be from the Transportation Vibration Test.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of M751 fuzes shall contain:

a. Primed 20 gauge shells of one lot interfix number, from one manufacturer.

b. Springs (for each type independently) of one lot interfix number, from one manufacturer.

c. Metal or plastic parts from one interfix lot number from one manufacturer.

d. No more than twenty thousand fuzes per inspection lot.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currenversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Body, Fuze	1 OF 2	9343991
			NEXT HIGHER ASSEMBLY: 9344000

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pitch diameter of internal thread		0.40%	3.2	Gage
102	Effective length of internal thread		0.40%	3.2	Gage
103	Location of setback pin hole		0.40%	3.2	Gage
104	Diameter of setback pin hole		0.40%	3.2	Gage
105	Location of ball hole		0.40%	3.2	Gage
106	Diameter of ball hole		0.40%	3.2	Gage
107	Location of slider hole		0.40%	3.2	Gage
108	Diameter of slider hole		0.40%	3.2	Gage
109	Diameter of slider spring cavity		0.40%	3.2	Gage
110	Depth of slider spring cavity		0.40%	3.2	Gage
111	True position of minor striker hole to rear cavity		0.40%	3.2	Gage
112	Diameter of smallest striker hole		0.40%	3.2	Gage
113	Diameter of aft stop counterbore		0.40%	3.2	Gage
114	Diameter of striker spring counterbore		0.40%	3.2	Gage
115	Diameter of striker head counterbore		0.40%	3.2	Gage
116	Length from datum of flange to striker head counterbore		0.40%	3.2	Gage
117	Length from datum of flange to striker spring counterbore		0.40%	3.2	Gage
118	Length from datum of flange to aft stop counterbore		0.40%	3.2	Gage
119	Depth of setback pin hole		0.40%	3.2	Gage
120	Depth of groove forward of flange		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil-3 Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9343991
4.4.2.1	Body, Fuze (cont)				NEXT HIGHER ASSEMBLY 9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MAJOR					
121	Width of groove forward of flange		0.40%	3.2	Gage
122	Body diameter at leading edge of groove		0.40%	3.2	Gage
123	Major diameter - external thread		0.40%	3.2	Gage
124	Pitch diameter - external thread		0.40%	3.2	Gage
125	Diameter of vent holes		0.40%	3.2	Gage
126	Outside diameter of flange		0.40%	3.2	Gage
127	Depth of rear cavity from flange		0.40%	3.2	Gage
128	Inside diameter at forward end of rear cavity		0.40%	3.2	Gage
129	Length of mounting boss		0.40%	3.2	Gage
130	Width between packing clip slots		0.40%	3.2	Gage
MINOR					
201	Location of packing clip pin hole		0.65%	3.2	Gage
202	Diameter of packing clip pin hole		0.65%	3.2	Gage
203	Diameter of packing clip pin counter bore		0.65%	3.2	Gage
205	Flange width		0.65%	3.2	Gage
206	Flange to nose length		0.65%	3.2	Gage
207	External thread improper		0.65%	3.2	Gage
208	Exhaust ports clear of flash		0.65%	3.2	Visual
209	Poor Workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9387053
4.4.2.2	Ogive, Simulated, M734 Rear Section				NEXT HIGHER ASSEMBLY 9331848
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Length of forward O.D.	(a)		3.2	Gage
102	Forward outside diameter	(a)		3.2	Gage
MINOR					
201	Letters improperly molded and filled	(a)		3.2	Visual
202	Aft outside diameter	(a)		3.2	Gage
203	Wall thickness at base	(a)		3.2	Gage
204	Wall thickness above base			3.2	Gage
205	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) 20 samples from each mold shall be examined for these features or dimensions.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Ogive, Simulated, M734 Forward Section	1 OF 1	9387054
			NEXT HIGHER ASSEMBLY: 9331848

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	I.D. Forward hole	(a)		3.2	Gage
102	I.D. Aft counterbore	(a)		3.2	Gage
103	Depth aft counterbore	(a)		3.2	Gage
104	Overall length	(a)		3.2	Gage
MINOR					
201	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) 20 samples from each mold shall be examined for these features or dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Ogive, Simulated, M734 Assembly				9331848
					NEXT HIGHER ASSEMBLY
					9387100
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	True position of forward and aft sections		0.40%	3.2	Gage
MINOR					
201	Overall length		0.65%	3.2	Gage
202	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Shell, Shotgun, Primed 20 Gauge	1 OF 1	9344010
			NEXT HIGHER ASSEMBLY: 9341590

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Primer not inserted properly into shell	(a)		3.2	Visual
102	Check test for deterioration of primer (when applicable)	(b)	0.10%	3.2	Test/4.5.2
103	Shell improperly assembled	(a)		3.2	Visual
104	Improper Material	(a)		3.2	(a)
MINOR					
201	Poor workmanship	(a)		3.12	Visual

NOTES:

(a) Certification by the contractor is required for compliance of all materials to applicable specifications and for compliance with the above listed inspections.

(b) Quantities shall be as defined in MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9341592
4.4.2.6	Wad				NEXT HIGHER ASSEMBLY 9341590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Diameter of wad	(a)		3.2	Gage
102	Improper material	(a)		3.2	(a)
103	Thickness of wad	(a)		3.2	(a)
MINOR					
201	Poor workmanship	(a)		3.12	Visual

NOTES: Certification by the contractor is required for compliance of all materials to applicable specifications and for compliance with the above listed inspections.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.7	Cartridge, Spotting		1 OF 1	9341590
				NEXT HIGHER ASSEMBLY: 9344092

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
Special A	Smoke Composition leaking or outside shell		100%	3.2	Visual
MAJOR					
101	Total length of cartridge, max		0.40%	3.2	Gage
102	Primer improperly sealed		0.40%	3.2	Visual
103	Cartridge crimp improperly sealed		100%	3.2	Visual
104	Improper weight of loaded assembly		0.40%	3.2	Gage
105	Outside diameter of cartridge forward of flange		0.40%	3.2	Gage
MINOR					
201	Poor workmanship		0.65%	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9343992
4.4.2.8	Spring, Setback Pin				NEXT HIGHER ASSEMBLY 9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Compressed length over max at max load	(a)	0.40%	3.2	Gage
103	Compressed length under min at min load	(a)	0.40%	3.2	Gage
104	Free length		0.40%	3.2	Gage
105	Spring embrittlement test	10		3.2	Test/4.5.3
MINOR					
201	Protective finish missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) Compress to height of .40 max. for 24 hours min. prior to checking load requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Spring, Striker	1 OF 1	9343993
			NEXT HIGHER ASSEMBLY: 9344000

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Compressed length over max at max load	(a)	0.40%	3.2	Gage
103	Compressed length under min at min load	(a)	0.40%	3.2	Gage
104	Free length		0.40%	3.2	Gage
105	Spring embrittlement test	10		3.2	Test/4.5.3
MONOR					
201	Protective finish missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) Compress to height of .40 max. for 24 hours min. prior to checking load requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Spring, Slider				9343994
					NEXT HIGHER ASSEMBLY 9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Compressed length over max at max load	(a)	0.40%	3.2	Gage
103	Compressed length under min at min load	(a)	0.40%	3.2	Gage
104	Free length		0.40%	3.2	Gage
105	Spring embrittlement test	10		3.2	Test/4.5.3
MONOR					
201	Protective finish missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) Compress to height of .27 max. for 24 hours min. prior to checking load requirements.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9344006
4.4.2.11	Spring, Ball				NEXT HIGHER ASSEMBLY 9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Compressed length over max at max load	(a)	0.40%	3.2	Gage
103	Compressed length under min at min load	(a)	0.40%	3.2	Gage
104	Free length		0.40%	3.2	Gage
105	Spring embrittlement test	10		3.2	Test/4.5.3
MONOR					
201	Protective finish missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) Compress to height of .25 max. for 24 hours min. prior to checking load requirements.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Pin, Packing Clip	1 OF 1	9344001
			NEXT HIGHER ASSEMBLY: 9344005

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Wire diameter		0.40%	3.2	Gage
102	Overall length		0.40%	3.2	Gage
103	Point diameter over max		0.40%	3.2	Gage
MONOR					
201	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Clip, Packing	1 OF 1	9344004
			NEXT HIGHER ASSEMBLY: 9344005

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Width between inside flats		0.40%	3.2	Gage
102	Thickness of material		0.40%	3.2	Gage
103	Depth of Emboss for Pin		0.40%	3.2	Gage
104	Width of clip at flats		0.40%	3.2	Gage
MONOR					
201	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Packing Clip Assembly				9344005
					NEXT HIGHER ASSEMBLY 9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Length of pin to inside radius		0.40%	3.2	Gage
102	Packing clip pull test		0.40%	3.2	Test/4.5.9
MINOR					
201	Protective coating missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - 27 - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9343997
4.4.2.15	Chamber, Fuze				NEXT HIGHER ASSEMBLY 9344009
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Overall Length		0.40%	3.2	Gage
102	Inside diameter of cavity		0.40%	3.2	Gage
103	Major diameter of thread		0.40%	3.2	Gage
104	Pitch diameter of thread		0.40%	3.2	Gage
105	Effective thread under min. length		0.40%	3.2	Gage
MONOR					
201	Wall thickness at bottom		0.65%	3.2	Gage
202	Cavity radius not present		0.65%	3.2	Visual
203	Outside diameter		0.65%	3.2	Gage
204	Outside radius of cup over max		0.65%	3.2	Gage
205	Chamfer missing from inside diameter at cup opening		0.65%	3.2	Visual
206	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Pin, Setback				9390437
					NEXT HIGHER ASSEMBLY
					9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Length of pin		0.40%	3.2	Gage
102	Outside diameter of pin		0.40%	3.2	Gage
103	Weight		0.40%	3.2	Gage
104	Straightness of pin		0.40%	3.2	Gage
MONOR					
201	Chamfer or radius both ends missing		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.12	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Slider				9343999
					NEXT HIGHER ASSEMBLY
					9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Length of slider		0.40%	3.2	Gage
102	Shank diameter		0.40%	3.2	Gage
103	Head diameter		0.40%	3.2	Gage
MONOR					
201	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9343995
4.4.2.18	Striker				NEXT HIGHER ASSEMBLY 9344007
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
SPECIAL					
A	Length from aft end to forward surface of aft flange		100%	3.2	Gage
MAJOR					
101	Aft shank diameter		0.40%	3.2	Gage
102	Length to aft flange rear shoulder		0.40%	3.2	Gage
103	Spring guide and aft flange outside diameter		0.40%	3.2	Gage
104	Length between aft end of stop shoulders		0.40%	3.2	Gage
105	Forward flange outside diameter		0.40%	3.2	Gage
106	True position of head outside diameter to forward flange outside diameter		0.40%	3.2	Gage
107	Head outside diameter		0.40%	3.2	Gage
108	True position of spring guide and aft flange outside diameter to forward flange outside diameter		0.40%	3.2	Gage
109	True position of aft shank diameter to forward flange outside diameter		0.40%	3.2	Gage
110	True position of center column to forward flange outside diameter		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.18	Striker				9343995
					NEXT HIGHER ASSEMBLY 9344007
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MINOR					
201	Length from rear face to forward face of forward flange		0.65%	3.2	Gage
202	Length of column		0.65%	3.2	Gage
203	Overall length		0.65%	3.2	Gage
204	Protective finish missing or incomplete		0.65%	3.2	Visual
205	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9344007
4.4.2.19	Striker, Marking				NEXT HIGHER ASSEMBLY 9344000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
SPECIAL A	Location or red stripe		100%	3.2	Gage
MAJOR	None defined				
MINOR 202	Poor workmanship		0.65%	3.12	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.20	Fuze, Body Sub-Assembly	1	1	9344000
				NEXT HIGHER ASSEMBLY 9387100

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1	Aft end of striker under min from rear cavity face		100%	3.2	Gage
2	Test rod passes under the end of striker when inserted into ball hole		100%	3.2	Manual/Gage
3	Striker not free to move		100%	3.2	Manual
SPECIAL					
A	Test rod passes through setback pin hole stake		100%	3.2	Manual/Gage
B	Test rod passes through ball hole stake		100%	3.2	Manual/Gage
C	Test rod passes over the forward edge of setback pin		100%	3.2	Manual/Gage
D	Packing clip assembly missing		100	3.2	Visual
E	Setback stake pushout test	(a)		3.2	Test/4.5.11
MAJOR					
101	Improper assembly of components		0.40%	3.2	Visual/Manual
102	Seals missing or not adhering		0.40%	3.2	Visual
103	Packing clip assembly retention		0.40%	3.2	Test/4.5.12
MINOR					
201	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) Of every one thousand fuzes produced, two fuzes shall be subject to this test. If a fuze fails this test, the previous one thousand fuzes since the last test shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48637(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Fuze Body Assembly				9387100
					NEXT HIGHER ASSEMBLY
					9344009
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1	Red striker band is showing on fuze		100%	3.2	Visual/Gage
MAJOR					
101	Ogive pull test		0.40%	3.2	Test/4.5.13
MINOR					
201	Marking misleading, unidentifiable or missing		0.65%	3.2	Visual
202	Ogive does not rotate at max. torque		0.65%	3.2	Gage
203	Embossed letters do not align with notch on fuze body		0.65	3.2	Visual
204	Poor workmanship		0.65%	3.12	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.22	Fuze, PD, Practice, Loading, M751	1 OF 1	9344092
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1	Red marking is showing on fuze striker		100%	3.2	Visual
MAJOR					
101	Length from aft end of chamber to fuze to fuze mounting flange		0.40%	3.2	Gage
102	Chamber improperly torqued to fuze		0.40%	3.2	Gage
103	Jolt and Jumble Test	15		3.4	Test/4.5.4
104	Transportation Vibration Test	96		3.5	Test/4.5.6
105	1.5 Meter drop test	45		3.7	Test/4.5.5
106	Proving ground test	80(a)		3.6	Test/4.5.7
MINOR					
201	Marking misleading, unidentifiable or missing		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.12	Visual

NOTES: (a) These units are to be from the Transportation Vibration Test.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing - SEE 4.5

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Methods of Inspection" headings in 4.4.2.

4.5 Methods of inspection

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examinations of inspections and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspection. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.1.2 Determination of safe fuze condition.

4.5.1.2.1 External fuze examination. Before removal of the ogive, the striker must not exhibit the red band indicating an armed fuze.

4.5.1.2.2 Internal fuze examination. After the completion of a test to determine if the fuze is in the safe condition, remove the chamber, the ogive and the four (4) foil seals. Examine for the following:

(a) The set back pin must extend over the head of the slider.

(b) No ball shall have been released into the firing position under the striker nor shall the striker extend into the spotting cartridge cavity or strike the cartridge itself.

4.5.1.2.2 Damaged fuze. A fuze that has broken in two with the spotting cartridge still intact shall be considered safe to dispose of.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.2 Check test for deterioration of primers. If the total time between original acceptance of any primed cartridge (20 gauge shotgun shell) lot and the assembly of that lot into the fuzes exceeds two years, at any time since previous tests, the primed cartridge lot shall be subjected to and must satisfactorily pass the functioning and output tests as performed by the original primed cartridge manufacturer immediately before the primed cartridges are up loaded with the signature mix and subsequently assembled into fuzes. This test shall be performed by the contractor (or qualified laboratory) on primed cartridges selected by the Government Inspector. The test shall be conducted without cost to the original primed cartridge manufacturer. The test shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primed cartridges were under the jurisdiction of either the primed cartridge manufacturer or the prime or sub fuze contractor.

4.5.3 Spring embrittlement. The spring shall be stretched along its longitudinal axis until the spring no longer returns to its original position. When the spring no longer returns to its original length or profile, it shall be considered distorted permanently. Any spring that breaks prior to this point shall be classed defective. One defective spring shall constitute cause for rejection of that particular spring lot.

4.5.4 Jolt and jumble. The loaded fuze assembly, with the packing clip assembly removed, shall be subjected to the Jolt Test specified in MIL-STD-331 with the exception that the fuze shall not be disassembled and inspected after the Jolt Test. After completion of the Jolt Test, the same fuze shall be subjected to and withstand the Jumble Test specified in MIL-STD-331. Any fuze assembly that fails the requirement shall be classed defective. One defective fuze shall constitute cause for rejection of that particular fuze lot.

4.5.5 1.5 Meter drop test. A random sample of forty five (45) loaded fuzes (primed shotgun shells may be substituted for Cartridge Spotting dwg. 9341590 for this test) shall be selected and subjected to the test as specified in MIL-STD-331 with the following conditions:

a. The fuze assembly shall be assembled to an M879 81MM practice round (the Government shall supply the M879 practice rounds for the contractor's use) and dropped with the impact orientation of the round as follows:

(1) Fuze nose down
(2) Major axis 45° from vertical nose down
(3) Base down

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

Fifteen (15) fuzes each, with the packing clip assembly removed, must be dropped in the above (1, 2, 3) orientations. No fuze shall be subjected to more than one drop. The selection of the fuze shall be random. All fuzes, attached to the M879 round shall be pre-temperature conditioned to +110°F+10°F prior to dropping and dropped within two minutes of being removed from the temperature conditioning chamber.

b. All fuzes shall be safe to fire after being subjected to this test. Any fuze that is not safe to fire for any reason shall be classed defective. One defective fuze shall constitute cause for rejection of that particular fuze lot.

4.5.6 Transportation vibration test. Ninety-six (96) loaded fuzes shall be subjected to the Transportation Vibration Test, with the packing clip assemblies in place, as specified in MIL-STD-331, Test 123, at ambient temperature and four hours per axis (total test time 12 hours). After this test has been performed, sixteen (16) fuzes shall be disassembled and inspected for damage and pyro cartridge leakage. Any fuze, when disassembled, that is found to be armed or not safe shall be classed defective. One or more defects shall constitute cause for rejection of that particular fuze lot. The remaining eighty (80) fuzes, remaining from transportation vibration test, shall be subjected to the Proving Ground Test in paragraph 4.5.7 herein.

4.5.7 Proving ground test. This test shall be performed at a Government Proving Ground in accordance with the applicable USA TECOM Acceptance Test Procedure.

The eighty (80) fuzes remaining from the Transportation Vibration Test shall be subjected to this test. All fuzes shall be fired from a M252 or M29 81MM mortar at ambient temperature on M879, 81mm mortar practice rounds on a flat non-grassy earthen surface with video camera coverage set 1500 meters from the point of impact or at the gun position for charge "O." Video camera speed shall be 120 frames per second minimum. The following firing schedule shall be used:

a. Twenty (20) rounds at charge "0" at a gun elevation of forty-five (45) degrees.

b. Twenty (20) rounds at charge "2" at a gun elevation of forty-five (45) degrees.

c. Forty (40) rounds at charge "4" with the gun elevation set so that the viewing distance of the observer is at least 1500 meters.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

The following acceptance/rejection criteria applies:

a. At charge "0" firing:

(1) One or more duds constitutes cause for lot rejection.

(2) One or more flash and audible only (no smoke) signature constitutes cause for lot rejection.

(3) One or more smoke and audible only (no flash) signature constitutes cause for lot rejection.

(4) One or more flash and smoke only (non audible) signature constitutes cause for lot rejection.

b. At charge "2" firing:

(1) One or more duds constitutes cause for lot rejection.

(2) One or more flash and audible only (no smoke) signature constitutes cause for lot rejection.

(3) Two or more smoke and audible only (no flash) signature constitutes cause for lot rejection.

(4) Two or more flash and smoke only (non audible signature constitutes cause for lot rejection.

c. At charge "4" firing:

(1) Two or more duds constitutes cause for lot rejection.

(2) Two or more flash and audible only (no smoke) signature constitutes cause for lot rejection.

(3) Five or more smoke and audible only (no flash) signature constitutes cause for lot rejection.

(4) Three or more flash and smoke only (non audible) signature constitutes cause for lot rejection.

A dud is defined as an unobservable signature upon ground impact of the round.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.8 Twelve meter drop test. The fifteen (15) loaded fuzes when assembled to an M879 81MM mortar round shall be subjected to the twelve meter drop test as specified in MIL-STD-331 with the exception that the complete round shall be dropped on its longitudinal side so that a round base down/nose down configuration of the fuze is attained in the complete pack. The pack is as specified on dwgs 9362798 and 9381730. This test constitutes five drops. Three drops shall have two of the three rounds in the nose-down position. The two remaining drops shall have two of the three rounds in the base-down position. The required packing material shall be supplied by the Government. If any fuze does not meet the requirement, that fuze(s) shall constitute cause for rejection of this particular first article test.

4.5.9 Packing clip pin pull test. Each packing clip to be tested shall be restrained in an appropriate fixture. Apply a pulling force of 10±2 pounds 90 degrees to the pin on the weld side of the assembly. If the pin begins to separate from the packing clip or separates completely, the assembly shall be classed defective.

4.5.10 Striker pushout test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial load of 40±5 pounds through the signature cartridge cavity on the base end of the striker. The fuze must be partially disassembled for this test as the slider must be removed. Any striker that is pushed out or moves if the stake deforms constitutes cause for rejection of this particular first article test.

4.5.11 Setback pin hole stake pushout test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial load of 40±5 pounds on the forward edge of the setback pin. The fuze must be partially disassembled for this test as the forward end of the setback pin must be exposed and the packing clip assembly must be removed. Any stake that breaks or deforms shall constitute cause for first article sample rejection or rejection of the previous one thousand fuzes prior to this test on a continuous production line operation.

4.5.12 Packing clip assembly retention test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply an axial pull of 2±.5 pounds on the packing clip perpendicular to the fuze assembly in such a manner as to test the packing clip assembly's ability to remain in place. Any packing clip assembly that pulls out of the fuze fails this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.13 Ogive pull test. Each fuze to be tested shall be restrained in an appropriate fixture. Apply a longitudinal pulling force of 50+5 pounds in the ogive at both the forward and rear section joint. Any ogive that separates or becomes disassembled from the fuze shall be classed defective.

5. PACKAGING

5.1 Packaging.

5.1.1 Level A. Not applicable.

5.1.2 Level B. Not applicable.

5.1.3 Level C. The fuze shall be packaged in accordance with drawing 12598354.

5.2 Packing.

5.2.1 Level A. Not applicable.

5.2.2 Level B. Not applicable.

5.2.3 Level C. The fuze, packaged as specified in 5.1, shall be packed for shipment in accordance with drawing 12598356.

5.3 Marking. Marking of the fiberboard and wood boxes shall comply with drawing 12598354 and drawing 12598356 respectively.

6. NOTES

6.1 Intended use. The fuze covered by this specification is intended for use in Cartridge, 81MM, Practice M879.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of designs for approval. See para. 6.2.3 of MIL-A-48078. Submit equipment designs, as required to Commander, ARDEC, ATTN: AMSMC-QAT-I(D), Picatinny Arsenal, NJ 07806-5000.

6.4 Data Cards. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

6.5 Subject term (key word) listing.

Compliance
Conformance
Fuze
Inspection
Practice
Requirements
Shipment
Training

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A573)

☆ U.S. GOVERNMENT PRINTING OFFICE: 1987—704-036/74272

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-48637	FUZE, POINT DETONATING, PRACTICE, M751 WITH PYROTECHNIC SIGNATURE CARTRIDGE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

7a. NAME OF SUBMITTER *(Last, First, MI)* — Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* — Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* — Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.