MILITARY SPECIFICATION

CARTRIDGE, 40mm, M918 TP, ESCAPEMENT ASSEMBLY FOR METAL PARTS AND LOADING, ASSEMBLING AND PACKAGING

This specification is approved for use within the U.S. Army Armaments Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the metal parts, loading assembling and packaging of escapement assembly for use in Cartridge, 40mm, M918TP.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement there to, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-D-14978 - Detonator, Stab, M55
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specifications for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1310
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWINGS (See 6.8)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

8886357 - Escapement Assembly
9399374 - Projectile Assembly

(Copies of specifications, standards, handbooks and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of nongovernment documents which is current on the date of solicitation.

CODE OF FEDERAL REGULATIONS

TITLE 49 - Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20315. Orders should specify "49 CFR 100-199 (Latest revision)").

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-1474 - Indentation Hardness of Organic Coatings, Test for

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

(Application for copies of ASTM Publications should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philidelphia, PA 19103.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the reference cited herein, (except for associated detail specifications, specifications sheets or MS Standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg.) 8886357 and with all requirements specified in applicable specifications.

3.3 Contamination and distortion of Lexan parts. Extreme care should be taken throughout all phases of manufacture to avoid contaminating "Lexan" parts with certain solvent materials which may attach the "Lexan" material. Specific information on "Lexan" destructive solvents may be obtained from the General Electric Co,, Chemical and Metallurigical Division, Pittsfield, MA.

3.4 First article testing. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein.(See 4.3 and 6.7).

3.5 Transportation vibration. Prior to transportation vibration test, the escapement assembly shall be x-rayed and shall not be armed or partially armed (as evidenced by the detonator moving any degree from the safe position) or have any safety feature missing or not in its proper position (i.e. detent, detent spring, setback pin, setback pin retainer). After performance of the transportation vibration test the escapement assembly shall be x-rayed again and shall not be armed or partially armed (as evidenced by the detonator moving any degree from the safe position) or have any safety feature not in its proper position. After this inspection the escapement assembly shall pass the arming time test specified in 4.5.10.

3.6 Jolt. The escapement assembly, assembled to a projectile, shall be x-rayed and shall not be armed or partially armed (as evidenced by the detonator moving any degree from the safe position) or have any safety feature missing or not in its proper

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

position (i.e. detent, detent spring, setback pin, setback pin retainer). After being subjected to the jolt test, it shall be x-rayed again and shall not be armed or partially armed (as evidenced by the detonator moving any degree from the safe position) or have any safety feature not in its proper position.

3.7 Jumble. The escapement assembly, assembled to a projectile shall be x-rayed and shall not be armed or partially armed (as evidenced by the detonator moving any degree from the safe position) or have any safety feature missing or not in its proper position (i.e. detent, detent spring, setback pin, setback pin retainer). After being subjected to the jumble test, it shall be x-rayed again and shall not be armed or partially armed (as evidenced by the detonator moving any degree from the safe position) or have any safety feature not in its proper position.

3.8 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough and workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified herein or in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requiements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsiblity of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of any defective material.

4.1.2 Test equipment and inspection facilities. The manufacturer shall insure that the test and inspection facilities of sufficient accuracy, quality and quanity are established and maintained to permit performance of required inspections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (4.3)

b. Quality Conformance Inspection (4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Parts description	Drawings	Quantity
Pin, Setback	9276568	25
Spring, Setback	9276673	25
Rotor Asembly	8886363	50
Verge Assembly	8886365	50
Pinion Assembly	8886368	50
Rotor and Gear Sector Assembly	9219871	25
Escapement Assembly	8886357	266

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48669(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER SEE BELOW
	Escapement Assembly and Components				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin, Setback (Dwg. 9276568)				
	Examination for defects	25		3.2	4.4.2.1
	Spring, Setback (Dwg. 9276673)				
	Examination for defects	25		3.2	4.4.2.2
	Push Test of simulated setback pin	25		3.2	4.5.1
	Verification of heat treat	1/		3.2	4.5.2
	Rotor Assembly (Dwg. 8886363)				
	Examination for defects	50		3.2	4.4.2.3
	Push off test	50		3.2	4.5.7
	Verge Assembly (Dwg. 8886365)				
	Examination for defects	50		3.2	4.4.2.4
	Torque Test	50		3.2	4.5.3
	Disassembly test	50		3.2	4.5.4
	Pinion Assembly (Dwg. 8886368)				
	Examination for defects	50		3.2	4.4.2.5
	Push off test	50		3.2	4.5.5
	Torque Test (when applicable)	50		3.2	4.5.6

NOTES: 1/ Three (3) setback springs having the lowest push force from the simulated setback pin push test.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48669(AR)

PARAGRAPH	TITLE: Escapement Assembly and Components		SHEET 2 OF 2		DRAWING NUMBER: SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rotor and Gear Sector Assembly (Dwg. 9219871)				
	Examination for defects	25		3.2	4.4.2.6
	Static push test	25		3.2	4.5.8
	Escapement Assembly (Dwg. 8886357)				
	Examination for defects	50 1/		3.2	4.4.2.7
	Arming test	50 1/		3.2	4.5.9
	Arming time, min	50 1/		3.2	4.5.10
	Safety test (non arming)	50 1/		3.2	4.5.11
	Static pull test of spring setback	50 1/		3.2	4.5.12
	Transportation vibration	108		3.2, 3.5	4.5.10, 4.5.13, 4.5.16
	Jolt	12		3.6	4.5.14. 4.5.16
	Jumble	96		3.7	4.5.15, 4.5.16

NOTES: 1/ Same assemblies.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection Lot formation. Inspection lots shall comply with the lot information provisions of MIL-A-48078. Each inspection lot shall contain:

a. Detonators from one interfix lot number and from one manufacturer.

b. Metal parts or components from one interfix lot number and from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9276568
4.4.2.1	Pin, Setback				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL 1.	Length large end to flange, min.		100%	3.2	Gage
MAJOR 101.	Diameter of body at small end, max.		.40	3.2	Gage
MINOR 201	Poor workmanship		.65	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9276673
4.4.2.2	Spring, Setback				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Diameter between tangs		.40	3.2	Gage
102.	Tang broken, bent or missing		.40	3.2	Visual
103.	Push test of simulated setback pin	125 1/	1-2	3.2	4.5.1
MINOR:					
201.	Length, max		.65	3.2	Gage
202.	Poor workmanship		.65	3.8	Visual

NOTES: 1/ Per heat treat batch.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886363
4.4.2.3	Rotor Assembly				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Detonator stake missing (2)		.40	3.2	Visual
102.	Detonator inverted		.40	3.2	Visual
103.	Detonator above flush		.40	3.2	Gage/Probe
104.	Discernible bulge on detonator		.40	3.2	Visual
105.	Push off test	125	1-2	3.2	4.5.7
MINOR					
201.	Poor workmanship		.65	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886365
4.4.2.4	Verge Assembly				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Bearing diameters (see Dwg. 8886367)		.40	3.2	Gage
102.	Thickness of verge (see Dwg. 8886366)		.40	3.2	Gage
103.	Outside diameter of verge (see Dwg. 8886366)		.40	3.2	Gage
104.	Depth of cutout on verge (see Dwg. 8886366)		.40	3.2	Gage
105.	Distance from shoulder of arbor to end of bushing		.40	3.2	Gage
106.	Torque test	125	1-2	3.2	4.5.3
107.	Disassembly test	125	1-2	3.2	4.5.4
MINOR					
201.	Lubricant missing		.65	3.2	Visual
202.	Poor workmanship		.65	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48669(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886368
4.4.2.5	Pinion Assembly				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Bearing diameter (2) (See Dwg. 8886369)		.40	3.2	Gage
102.	Starwheel thickness (See Dwg. 8886370)		.40	3.2	Gage
103.	True position of outside diameter of starwheel with bearing diameters		.40	3.2	Gage
104.	Distance from top of pinion to top of bushing		.40	3.2	Gage
105.	Perpendicularity of starwheel with bearing diameters		.40	3.2	Gage
106.	Push off test	125	1-2	3.2	4.5.5
107.	Torque test (when applicable)	125	1-2	3.2	4.5.6
MINOR					
201.	Lubricant missing		.65	3.2	Visual
202.	Poor workmanship		.65	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48669(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9219871
4.4.2.6	Rotor and Gear Sector Assembly		NEXT HIGHER ASSEMBLY 8886363

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR 101.	Static push off test	50	1-2	3.2	4.5.8
MINOR	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48669(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886357
4.4.2.7	Escapement Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1.	Arming time, min		100%	3.2	4.5.10
2.	Rotor in armed or partially armed position		100%	3.2	Visual/Probe
3.	Safety test (non-arming)		100%	3.2	4.5.11
4.	Detent spring missing		100%	3.2	Visual/Probe
5.	Detent missing or not engaged in teeth of sector gear		100%	3.2	Visual/Probe
6.	Setback spring missing		100%	3.2	Visual/Probe
7.	Setback pin missing or retracted		100%	3.2	Visual/Probe
8.	Static Pull test of setback spring		100%	3.2	4.5.12
9.	Transportation vibration (Safe)	50	0-1	3.5 1/	4.5.13, 4.5.16
10.	Jolt	12	0-1	3.6	4.5.14
11.	Jumble	50	0-1	3.7	4.5.15
MAJOR					
101.	Arming test	125	1-2	3.2	4.5.9
102	Transportation vibration (operable)	50 2/	0-1	3.2,3.5 3/	4.5.10, 4.5.13
MINOR					
201.	Face of posts above flush after stake		.65	3.2	Gage
202.	Poor Workmanship		.65	3.8	Visual

NOTES: 1/ Applies to all requirements except arming time.
2/ Same assemblies as specified in Critical 9.
3/ Applies to arming time requirement only.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Verification of heat treatment of setback spring. After completion of the push test of simulated setback pin, the three (3) setback springs exhibiting the lowest push test force shall be subjected to this test. If any setback spring fails to comply with the requirement specified on the applicable drawing, the heat treatment batch represented by the sample shall be rejected.

4.4.3.2 Check test for deterioration of detonators. If the total time betwee original acceptance of any lot and the assembly of that lot into the escapement assembly exceeds two years, or if the detonators have been subjected to adverse conditions, however brief, at any time since the previous tests, the detonator lot shall be subjected to and must satisfactorily pass, the check test for deterioration specified in MIL-D-14978 immediately before the detonator lot is assembled into the escapement assembly. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling the detonators into the escapement assembly (See 6.6). The test shall be conducted at Government expense without cost to the contractor who loaded the detonator or the contractor assembling the detonator into the escapement assembly and shall not constitute a basis for rejection against either contractor except where deterioration has occured as a direct result of carelessness in handling, storage, etc., permitted while the detonator lot was under the responsibility of either contractor. The Contracting Officer shall arrange to have the contractor reimbursed for the expense incurred in the performance of check tests.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method Column in the Tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Push test of simulated setback pin into spring setback. The setback spring shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied to a simulated setback pin. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.2 Verification of heat treat of spring setback. The setback spring shall be subjected to the Knoop hardness reading in accordance with ASTM-D-1474. This test is a destructive test. Parts so tested shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 20260-26T03:57Z
Check the source to verify that this is the currentversion before use.

4.5.3 Torque test of verge assembly. The verge assembly shall be placed in an approved fixture and the torque specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.4 Disassembly test of verge assembly. The verge assembly shall be placed in an approved fixture and the disassembly force specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.5 Push off test of pinion assembly. The pinion assembly shall be placed in an approved fixture and the load specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.6 Torque test of pinion assembly (when applicable). The pinion assembly shall be placed in an approved fixture and the load specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.7 Push off test of rotor assembly. The rotor assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.8 Static push test of rotor and gear sector assembly. The rotor and gear sector assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.9 Arming test. The escapement assembly shall be placed in an approved fixture and rotated at the arming speed specified on the applicable drawing. This test is a non-destructive test. Parts successfully tested may be returned to the lot after the rotor has been returned to the safe position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.10 Arming time. The escapement assembly shall be placed in an approved fixture and rotated at the speed specified on the applicable drawing. The arming time shall be measured. This test is a non-destructive test. Parts successfully tested shall be returned to the lot after the rotor has been returned to the safe position. However, escapement assemblies subjected to the transportation vibration test shall not be returned to the lot.

4.5.11 Safety test (non-arming). This test shall be performed after completion of the tests specified in 4.5.9 and 4.5.10. The escapement assembly shall be placed in an approved fixture and rotated at the non-arming speed specified on the applicable drawing. This test is a non-destructive test. Parts successfully tested may be returned to the lot.

4.5.12 Static pull test. The escapement assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. This is a non-destructive test. Parts so tested may be returned to the lot.

4.5.13 Transportation vibration. Prior to the transportation vibration test, the escapement assemblies shall be x-rayed to determine compliance with 3.5 (except arming time). They shall then be packed in their regular shipping container and tested in accordance with Test 119 of MIL-STD-331. Simulated assemblies shall be used to ensure a full container. After completion of the test, the escapement assemblies shall be x-rayed again to determine compliance with 3.5 (except arming time). After this examination they shall be subjected to the arming time test specified in 4.5.10. This is a destructive test. Assemblies so tested shall not be returned to the lot.

4.5.14 Jolt. Prior to the jolt test, the escapement assemblies, assembled in accordance with projectile assembly Dwg. 9399374 (except with inert body insert assembly), shall be x-rayed to determine compliance with 3.6. They shall then be tested in accordance with Test 101.1 of MIL-STD-331. After completion of the test, the projectile assemblies shall be x-rayed again to determine compliance with 3.6. This is a destructive test. Assemblies so tested shall not be returned to the lot.

4.5.15 Jumble. Prior to the jumble test, the escapement assemblies assembled in accordance with projectile assembly Dwg. 9399374, (except with inert body insert assembly), shall be x-rayed to determine compliance with 3.7. They shall then be tested in accordance with Test 102.1 of MIL-STD-331. After completion of the test, the projectile assemblies shall be x-rayed again to determine compliance with 3.7. This is a destructive test. Assemblies so tested shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T03:57Z
Check the source to verify that this is the currentversion before use.

4.5.16 X-ray of escapement assembly or projectile assembly. The escapement assembly or projectile assembly, as applicable, shall be examined for compliance with 3.5, 3.6 or 3.7 as applicable. Examination shall be performed with X-ray equipment or any other method acceptable to the contracting officer. The test shall be conducted in two (2) planes:

a. From the top of the escapement assembly down.

b. From the side of the escapement assembly.

5. PACKAGING

5.1 Packing and marking.

5.1.1 Level B. Escapement assemblies shall be packaged, packed and marked in accordance with Code of Federal Regulations, Title 49, Parts 100-199.

5.2 Shipping. When components from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The assemblies covered by this specification are intended for use with the Cartridge, 40mm, M918 TP.

6.2. Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Quantity required and delivery schedule.

c. Lists of drawings, publications and specifications, showing applicable revision dates.

d. Responsibility for furnishing inert projectile assemblies (Dwg. 9399374) less escapement assemblies.

e. Criteria for inspection of parts and assemblies.

f. Packaging instructions, if different.

g. Quality Conformance Inspection, if other than specified in Section 4 of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

h. First Article Sample requirements, if other than specified in Section 4 of this specification.

6.3. Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARDC, AMSMC-QAF-I(D), Dover, NJ, 07801-5001. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph.

6.4 Submission of results of contractor conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examination or tests to Commander, ARDC, ATTN: AMSMC-QAF-S(D), Dover, NJ 07801-5001.

6.5 Submission of test data. In addition to the normal distribution of record, when the escapment assemblies are procured by ARDC, one copy of all ballistic data and ammunition data cards shall be forwarded to Commander, ARDC, ATTN: AMSMC-QAF-S(D), Dover, NJ 07801-5001.

6.6 Cost of check test. The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the detonator assembly. The tests shall be conducted at Government expense without cost to the contractor who loaded the detonator assembly of to the contractor assembling the detonator assembly into the escapement assembly; and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the detonator assembly lot was under jurisdiction of either contractor.

6.7 First article. When first article inspection is required, the contracting officer should include specific instructions in aquisition documents regarding arrangements for examinations, test and approval of the document for first article.

6.8 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, ARRADCOM drawings. Technical data originally prepared by these activities are now under the cognizance of ARDC.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A502)

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.