MILITARY SPECIFICATION

CARTRIDGE, 40mm, M918 TP; PROJECTILE ASSEMBLY FOR METAL PARTS AND LOADING, ASSEMBLING AND PACKAGING

This Specification is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the metal parts, loading, assembling and packaging for one type of projectile assembly for use in Cartridge, 40mm, M918 TP.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified (see 6.2), the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement there to, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-E-516	- Enamel, Lustreless, Quick-Drying Styrenated Alkyd Type
TT-C-490	- Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coating

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-A-8625	- Anodic Coating, for Aluminum and Aluminum Alloys
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specifications for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWINGS (see 6.10)

US ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9399372 - Cartridge, 40MM, M918 TP
9399374 - Projectile Assembly
12624588 - Packing and Marking for Box, Fiberboard, Outer, for projectile, 40mm, M918 TP

(Copies of specifications, standards, handbooks and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of initiation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR-100-199 - Interstate Commerce Commision Rules and Regulations for the Transportation of Explosive and Other Dangerous Article

(The Interstate Commerce Commision regulations are now a part of the Code of Federal Regulations (1967 editions and revisions) available from the Superintendent of Documents, US Government Printing Office, Washington, DC 20315. Orders for the above publications, should cite "49 CFR 100-199 (Latest revision)).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-B117 - Standard Method of Salt Spray (fog) Testing

(Application for copies should be addressed to The American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of Precedence. In the event of a conflict between the text of this specification and the reference cited herein, (except for associated detail specifications, specifications sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless specified exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg.) 9399374 and with all requirements specified in applicable specifications.

3.3 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3 and 6.6).

3.4 Functioning. The projectile assembly, on impact, shall produce sufficient sound, smoke and flash under standard atmospheric conditions. There shall be no evidence of an air burst (see 6.8).

3.4.1 Safety. The projectile shall not lodge in the bore of the weapon and there shall be no evidence of a premature burst (see 6.7).

3.5 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough and workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with -11 requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Test equipment and inspection facilities. The manufacturer shall insure that test and Inspection facilities of sufficient accuracy, quality and quantity are established and maintained to permit performance of required inspections.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (4.3)

b. Quality Conformance Inspection (4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Parts description	Drawings	Quantity
Projectile Assembly	9399374	788
Body Insert	9399382	25
Ogive Assembly, 40MM, M918	9399390	50
Firing Pin Assembly	9399391	50
Firing Pin	9399392	25
Firing Pin Plate	9399393	25

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

Ogive M918TP	9399394	25
Spring, Anti-creep	9399395	50
Body	9399396	25
Body Assembly	9399402	50
Cap, Inner	9399405	25
Cap, Outer	9399406	25
Capsule, Assembly	9399407	50

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-C-48683A(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Projectile and Components	1 OF 3	SEE BELOW
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin, Firing (Dwg. 9399392)				
	Examination for defects	25		3.2	4.4.2.1
	Plate, Firing Pin Dwg. (9399393)				
	Examination for defects	25		3.2	4.4.2.2
	Firing Pin Assembly (Dwg. 9399391)				
	Examination for defects	50		3.2	4.4.2.3
	Push test, firing pin assembly	50		3.2	4.5.1
	Ogive, M918 TP (Dwg. 9399394)				
	Examination for defects	25		3.2	4.4.2.4
	Salt Spray	4		3.2	4.5.2.1
	Insert, Body (Dwg. 9399382)				
	Examination for defects	25		3.2	4.4.2.5

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH CATEGORY	TITLE: Projectile and Components		SHEET 2 OF 3		DRAWING NUMBER: SEE BELOW NEXT HIGHER ASSEMBLY
	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Anti-Creep (Dwg. 9399395) Examination for defects	50		3.2	4.4.2.6
	Load Test	50		3.2	4.5.3
	Ogive Assembly, 40mm, M918 (Dwg.9399390) Examination for defects	50		3.2	4.4.2.7
	Cap, Inner (Dwg. 9399405) Examination for defects	25		3.2	4.4.2.8
	Cap, Outer (Dwg. 9399406) Examination for defects	25		3.2	4.4.2.9
	Capsule Assembly (Dwg. 9399407) Examination for defects	50 1/		3.2	4.4.2.10

NOTES: 1/ A sufficient number of assemblies shall be disassembled to obtain the sample specified in 4.5.7.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
	Projectile and Components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Dwg. 9399396)				
	Examination for defects	25		3.2	4.4.2.11
	Body Assembly (Dwg. 9399402)				
	Examination for defects	50		3.2	4.4.2.12, 4.4.2.13
	Salt Spray	4		3.2	4.5.2.2
	Push test of rotating band	50		3.2	4.5.9
	Projectile Assembly (Dwg. 9399374)				
	Examination for defects	25		3.2	4.4.2.14
	Functioning				4.5.6
	1000 Meter (M), min. Test	288	10-11 1/	3.4	4.5.6, 4.5.6.1
	135 to 200 feet Test	100	1-2 1/	3.4	4.5.6, 4.5.6.2
	Rapid fire test, 150 to 656.2 feet (200M)	100	3-4 1/	3.4	4.5.6, 4.5.6.3
	Hot and cold temp test	300 3/	4/	3.4	4.5.6, 4.5.6.1, 4.5.6.2, 4.5.6.3
	Safety	788 2/	0-1	3.4.1	4.5.6, 4.5.6.1, 4.5.6.2, 4.5.6.3
	Air Burst	788 2/	1-2	3.4	4.5.6, 4.5.6.1, 4.5.6.2, 4.5.6.3

1/ Accept/Reject numbers apply to cartridges that do not provide flash, smoke or sound.

2/ Same projectiles that are subjected to 1000 meter, min, 200 foot, and rapid fire tests.

NOTES: 3/ 100 rounds shall be subjected to each of the functioning tests listed above, see 4.5.6. 4/ Functioning test results except for air bursts and safety (3.4.1) are for informational purposes only.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Each inspection lots shall contain:

a. Metal parts from one lot interfix number and from one manufacturer.

b. Escapement assemblies from one lot interfix number and from one manufacturer.

c. Flash charge composition from one interfix lot number and from one manufacturer.

4.4.2 Examination for defects.

a. Sampling plan. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Pin, Firing		9399392
			NEXT HIGHER ASSEMBLY 9399391

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Profile of firing pin point		.40	3.2	Gage
102.	Length, firing pin point to backside of shoulder		.40	3.2	Gage
MINOR					
201.	Outside diameter at backside of shoulder		.65	3.2	Gage
202.	Total length		.65	3.2	Gage
203.	Poor workmanship		.65	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Plate, Firing Pin		9399393
			NEXT HIGHER ASSEMBLY 9399391

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Diameter, outside		.40	3.2	Gage
102.	True position of center hole to outside diameter		.40	3.2	Gage
MINOR					
201.	Diameter, center hole		.65	3.2	Gage
202.	Thickness		.65	3.2	Gage
203.	Flatness		.65	3.2	Gage
204.	Poor workmanship		.65	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1			DRAWING NUMBER 9399391
4.4.2.3	Firing Pin Assembly				NEXT HIGHER ASSEMBLY 9399390
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR 101.	Push test, firing pin assembly	80	Acc-1 Rej-2		4.5.1
MINOR 201.	Poor workmanship		.65	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9399394
4.4.2.4	Ogive, M918 TP		NEXT HIGHER ASSEMBLY 9399390

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Major diameter, thread		.40	3.2	Gage
102.	Pitch diameter, thread		.40	3.2	Gage
103.	Largest outside diameter		.40	3.2	Gage
104.	Total length		.40	3.2	Gage
105.	True position, largest outside diameter to thread pitch diameter		.40	3.2	Gage
106.	True position, inside diameter to thread pitch diameter		.40	3.2	Gage
107.	Larger, inside diameter		.40	3.2	Gage
108.	Depth to step on inside diameter		.40	3.2	Gage
109.	Salt Spray/Protective finish	4	1/	3.2	4.5.2.1
MINOR					
201.	Length, full thread		.65	3.2	Gage
202.	Length to shoulder at thread relief		.65	3.2	Gage
203.	Diameter of thread relief		.65	3.2	Gage
204.	Incorrect color		.65	3.2	Visual
205.	Wall thickness		.65	3.2	Gage
206.	Poor workmanship		.65	3.5	Visual

NOTES: 1/ Rejection shall be in accordance with MIL-A-8625.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399382
4.4.2.5	Insert, Body				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Length, body		.40	3.2	Gage
102.	Diameter, outside		.40	3.2	Gage
103.	Parallelism of rear surface with front face		.40	3.2	Gage
104.	True position, setback spring cavity		.40	3.2	Gage
105.	True position, through hole to outside diameter		.40	3.2	Gage
106.	True position, setback spring cavity to setback pin cavity		.40	3.2	Gage
107.	True position, powder cavity to outside diameter		.40	3.2	Gage
108.	Depth of setback pin cavity		.40	3.2	Gage
109.	Depth of setback spring cavity		.40	3.2	Gage
MINOR					
201.	Diameter, powder cavity		.65	3.2	Gage
202.	Depth, powder cavity		.65	3.2	Gage
203.	Angle, outside diameter		.65	3.2	Gage
204.	Location, angle		.65	3.2	Gage
205.	Diameter, through hole		.65	3.2	Gage
206.	Diameter, setback pin cavity		.65	3.2	Gage
207.	Diameter, setback spring cavity		.65	3.2	Gage
208.	Poor workmanship		.65	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Spring, Anti-Creep		9399395
			NEXT HIGHER ASSEMBLY 9399390

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Load Test	125	Acc-1 Rej-2		4.5.3
102.	Thickness		.40	3.2	Gage
103.	Outside diameter, min		.40	3.2	Gage
MINOR					
201.	Poor Workmanship		.65	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399390
4.4.2.7	Ogive Assembly,40mm, M918				NEXT HIGHER ASSEMBLY 9399374
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL 1.	Anti-creep spring missing		100%	3.2	Probe/4.5.10
MAJOR 101.	Depth to firing pin point		.40	3.2	Gage
102.	Firing pin assembly improperly seated		.40	3.2	Visual
MINOR 201.	Poor workmanship		.65	3.5	Visual

NOTES:

1/ Assembly shall be inspected in inverted (open end of ogive facing down) position.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Cap, Inner		9399405
			NEXT HIGHER ASSEMBLY 9399407

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR 101.	Wall thickness, Min.		.40 1/	3.2	Gage
MINOR 201.	Length		.65 1/	3.2	Gage
202.	Outside diameter, max (closed end)		.65 1/	3.2	Gage
202.	Inside diameter, min		.65 1/	3.2	Gage
201.	Poor workmanship		.65 1/	3.5	Visual

NOTES:

1/ See paragraph 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399406
4.4.2.9	Cap, Outer				NEXT HIGHER ASSEMBLY 9399407
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Wall thickness, Min		.40 1/	3.2	Gage
MINOR					
201.	Length		.65 1/	3.2	Gage
202.	Outside diameter, max (closed end)		.65 1/	3.2	Gage
203.	Inside diameter, min		.65 1/	3.2	Gage
204.	Poor workmanship		.65 1/	3.5	Visual

NOTES:
1/ See paragraph 4.4.3.1.

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Capsule Assembly		9399407
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR 101.	Absence of powder		100%	3.2	Visual
MINOR 201.	Poor workmanship		.65	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399396
4.4.2.11	Body				NEXT HIGHER ASSEMBLY 9399402
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Presence of cracks		100%	3.2	Visual
102.	Pitch diameter of thread		.40	3.2	Gage
103.	Minor diameter of thread		.40	3.2	Gage
104.	Runout of indicated point on taper with outside large diameter		.40	3.2	Gage
105.	Large outside diameter		.40	3.2	Gage
106.	Location large diameter on taper		.40	3.2	Gage
107.	Diameter at end of taper		.40	3.2	Gage
108.	Total runout at indicated lengths on body with pitch diameter (2)		.40	3.2	Gage
109.	Thickness through base center		.40	3.2	Gage
110.	Thickness of groove (6) in base		.40	3.2	Gage
MINOR					
201.	Diameter of rotating band surface (after knurling)		.65	3.2	Gage
202.	Width of rotating band surface		.65	3.2	Gage
203.	Total length		.65	3.2	Gage
204.	Length of effective thread, min		.65	3.2	Gage
205.	Distance from open end to back of rotating band seating surface		.65	3.2	Gage
206.	Poor workmanship		.65	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Body Assembly, prior to paint		9399402
			NEXT HIGHER ASSEMBLY 9399374

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Parallelism, back of rotating band with open end		.40	3.2	Gage
102.	Distance from open end to back of rotating band, max		.40	3.2	Gage
103.	Push test of rotating band	50	Acc-0 Rej-1	3.2	4.5.9
104.	Profile of rotating band		.40	3.2	Gage
MINOR					
201.	Poor workmanship		.65	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399402
4.4.2.13	Body Assembly, After Painting				NEXT HIGHER ASSEMBLY 9399374
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Body Diameter max		.40	3.2	Gage
102.	Diameter of rotating band		.40	3.2	Gage
103.	Salt spray/protective finish	1/	1/	3.2	4.5.2.2
MINOR					
201.	Incorrect color of body		.65	3.2	Visual
202.	Brown stripe missing or not 360°		.65	3.2	Visual
203.	Poor Workmanship		.65	3.5	Visual

NOTES: 1/ Sampling and rejection shall be in accordance with TT-C-490.

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.14	Projectile Assembly		9399374
			NEXT HIGHER ASSEMBLY 9399372

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1.	Rotor in armed or partially armed position 1/		100%	3.2	Probe/4.5.10
2.	Detent spring missing 1/		100%	3.2	Visual
3.	Detent missing or not engaged in teeth of sector gear 1/		100%	3.2	Probe/4.5.10
4.	Setback spring missing 1/		100%	3.2	Probe/4.5.10
5.	Setback pin missing or retracted 1/		100%	3.2	Probe/4.5.10
6.	Safety	244 2/	0-1	3.4.1	4.5.6, 4.5.6.1, 4.5.6.2, 4.5.6.3
MAJOR					
101.	Total length, max		100%	3.2	Gage
102.	Gap between body and ogive, min		.40	3.2	Gage
103.	True position, rotating band to ogive diameter		.40	3.2	Gage
104.	Assembly torque, prior to sealant cure	3/	3/	3.2	4.5.4
105.	Pressure test	125	3-4	3.2	4.5.5
106.	Functioning				
	1000 meter, min, test	144	6-7 4/	3.4	4.5.6, 4.5.6.1
	135 to 200 feet, test	50	0-1 4/	3.4	4.5.6, 4.5.6.2
	Rapid fire test, 150 to 656.2 feet (200 meter)	50	2-3 4/	3.4	4.5.6, 4.5.6.3
107.	Airburst	244 2/	0-1	3.4	4.5.6, 4.5.6.1, 4.5.6.2, 4.5.6.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.14	Projectile Assembly				9399374
					NEXT HIGHER ASSEMBLY 9399372
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MINOR 201.	Poor workmanship		.65	3.5	Visual

NOTES: 1/ Performed on escapement assembly prior to assembly to projectile.
2/ Same projectiles that are subjected to 1000 meter, min, 135 to 200 ft and rapid fire tests.
3/ CSP-2, Code Letter K, AQL 0.40% of MIL-STD-1235.
4/ Accept/Reject numbers apply to cartridges that do not provide flash, smoke or sound.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9399389
4.4.2.15	Flash Charge Composition, bulk, prior to loading into capsule		NEXT HIGHER ASSEMBLY 9399407

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR 101.	Moisture content	per batch	1/	3.2	4.5.7
MINOR	None defined				

NOTES: 1/ If the batch of flash charge composition fails the requirement of the drawing, it shall be classed defective and not used in production.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12624588
4.4.2.16	Unsealed inner fiberboard box				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Improper number of projectiles		.40	3.2	Visual
102.	Projectile inverted		.40	3.2	Visual
103.	Filler missing		.40	3.2	Visual
104.	Supports missing		.40	3.2	Visual
MINOR	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Sealed Inner Fiberboard Box, Prior to Sealing Bag				12624588
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Container damaged		.40	3.2	Visual
102.	Corners not blunted		.40	3.2	Visual
MINOR	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12624588
4.4.2.18	Unsealed Outer Box				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Heat seal test of packing seals (after sealing bag)	1/	1/	3.2	4.5.8
102.	Bag torn or perforated		.40	3.2	Visual
103.	Bag improperly sealed		.40	3.2	Visual
104.	Fillers missing		.40	3.2	Visual
MINOR:	None defined				

NOTES: 1/ Sampling and rejection shall be in accordance with MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12624588
4.4.2.19	Sealed Outer Box				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Box damaged		.40	3.2	Visual
MINOR					
201.	Marking missing or unidentifiable		.65	3.2	Visual
202.	DOT marking missing		.65	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the first article and quality conformance inspection tables.

4.4.3.1 Dimensional control of plastic parts. In place of normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (see Note 1), a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in applicable paragraphs after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective parts shall be removed from production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL or 0.40 percent for each major defect and an AQL or 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request. Contractor design of gages and test equipment required to perform inspections listed herein shall be forwarded to Commander, US Army ARDEC, ATTN: AMSMC-QAF-I (D), Picatinny Arsenal, NJ 07806-5000 for approval prior to manufacture of equipment. The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1. In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60 minutes, etc.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to Commander, US Army ARDEC, ATTN: AMSMC-QAF-S (D), Picatinny Arsenal, NJ 07806-5000. If there is a change in material, or in the cycle time, or if the cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3.2 Dimensional control of stamped parts. In place of normal sampling associated with the classification of defects, and with the approval of the contracting officer, the tool used to form affected characteristic shall be inspected prior to use in production. In addition, 5 sample parts shall be inspected by use of an impression molded into the cavity and checked for dimensional requirements prior to starting production. An additional sample of 2 shall be selected and inspected from the last portion of each shift's production to verify continued acceptance.

If any defective parts are found during sampling, the tool producing the defective parts shall be removed from production. Further, parts produced since the last tool control check shall be returned to the contractor for corrective action. Only acceptable tools shall be placed in production. All tools forming referenced characteristics removed from production because of any fault, may, after reworking, be returned to production, provided they pass the qualification tests above.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Push test of firing pin assembly. The firing pin assembly shall be placed in an approved fixture and the push test specified on Dwg. 9399391 shall be applied. This test is a non-destructive test. Parts successfully tested may be returned to the lot.

4.5.2 Salt spray.

4.5.2.1 Ogive, M918 TP. This test shall be conducted in accordance with ASTM-B-117 for 48 hours. Salt solution shall be 5 percent. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.2.2 Body Assembly. This test shall be conducted in accordance with ASTM-B-117. This test shall be conducted for 48 hours along 1.25 inches of the outside length measured from the open end. The surface area rear of this point may be tested for 24 hours minimum. Salt spray test not required for inside surface of body assembly. The rotating band may be masked off for this test. Salt solution shall be 5 percent. This test is a destructive test. Parts so tested may not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.3 Load test of anti-creep spring. The anti-creep spring shall be placed in a fixture and the load specified on Dwg. 9399390 shall be applied. This test is a non-destructive-test. Parts successfully tested may be returned to the lot.

4.5.4 Assembly torque of ogive assembly prior to sealant cure. The projectile assembly shall be placed in an approved fixture and the torque specified on the applicable drawing shall be applied. Observation shall be made for the applicable requirement. This test is a non-destructive test. Parts successfully tested may be returned to the lot.

WARNING: This test is conducted on assemblies containing an explosive element. Test barricades (where used), procedures and equipment shall have prior approval.

4.5.5 Air Pressure test. The projectile shall be placed in an approved fixture and air applied to produce a specified pressure. Observations shall be made for a drop in pressure indicating a leak. This is a non-destructive test. Parts so tested may be returned to the lot.

4.5.6 Functioning. This test shall be conducted as follows:

The projectile assemblies, being tested shall be assembled as complete cartridges, (Dwg. 9399372), linked, temperature conditioned at 70° ± 5°F for at least eight (8) hours, and then fired within fifteen (15) minutes after being removed from temperature soak. During first article inspection only, hot and cold temperature testing shall be performed for the tests specified in 4.5.6.1, 4.5.6.2 and 4.5.6.3. For the high temperature test, the linked cartridges shall be conditioned at 125°F ± 5°F for at least four (4) hours but no more than twelve (12) hours. For the low temperature test, the linked cartridges shall be conditioned at -25°F ± 5°F for at least four (4) hours. Fifty (50) cartridges shall be fired for each hot and each cold portion of each of the three (3) tests. During hot and cold temperature testing only failure to comply with the safety (3.4.1) and air burst requirements shall be cause for rejection of the first article quantity. Functioning during hot and cold temperature testing shall be recorded for informational purposes only. Test cartridges shall be fired from an approved 40mm MK19 MOD III Grenade Machine Gun.

4.5.6.1 1,000 meters, minimum. The linked cartridges shall be fired and impact at 1000 meter minimum from the machine gun on level terrain. Observation shall be made for gun stoppages (information only), projectile stuck in bore, premature bursts, air bursts, and functioning on the impact medium.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.6.2 135 to 200 feet. The linked cartridges shall be fired and impact at 135 to 200 feet from the machine gun on a 1/2 inch thick celotex target. Observation shall be made for gun stoppages (information only), projectile stuck in bore, premature bursts, air bursts, and functioning on the impact medium.

4.5.6.3 Rapid fire functioning. The linked cartridges shall be fired in bursts of five (5), and impact at 150 to 656.2 feet (200M) from the machine gun into 10 inches minimum of coarse sand graded at approximately 25° with the horizontal. The sand shall be raked so that idividual craters do not overlap. In addition, the sand shall be raked after each dud. If a projectile assembly falls outside the impact medium, it shall be declared a "no-test". When the proving ground reports ballistic test results, the number of "no-test" cartridges shall also be recorded. Observation shall be made for gun stoppages (information only), projectile stuck in bore, premature bursts, air bursts, and functioning on the impact medium.

4.5.7 Moisture content of flash charge. An accurately weighed position of three (3) grams (g.) of the charge composition shall be transferred to a tared dish. The moisture dish and contents shall be placed in a drying oven at 70 ± 2°C for 4 hours, cooled in a desiccator and weighed. The percentage of moisture in the sample shall be calculated as follows:

$$\text{Percentage of Moisture} = \frac{100A}{W}$$

Where:

A = loss in weight of moisture dish and contents.

W = weight of sample, g.

4.5.8 Heat seal test of packing seals. This test shall be performed in accordance with specification MIL-P-116.

4.5.9 Push test of rotating band. The body assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. Observation shall be made for compliance with the applicable requirement. This is a non-destructive test. Parts so tested may be returned to the lot.

4.5.10 Probe inspection. This inspection shall be performed using automatic inspection equipment designed by the contractor and approved by the Government. See MIL-A-48078.

5. PACKAGING

5.1 Preservation and packaging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

5.1.1 Level B. Preservation and packaging shall be in accordance with Dwg. 12624588,

5.2 Packing.

5.2.1 Level B. The projectile assembly shall be packed in accordance with Dwg. 12624588.

5.3 Marking. Marking shall be in accordance with Dwg. 12624588 and Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Unitization. Unitization shall be prescribed by the procuring agency as specified in the contract or order.

5.5 Shipping. When shipments of more than one lot are made at one time, such as in a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. This specification covers the metal parts, loading, assembling and packaging for Projectile assembly for Cartridge, 40mm, M918 TP.

6.2. Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Quantity required and delivery schedule.

c. Lists of drawings, publications and specifications, showing applicable revision dates.

d. Responsibility for furnishing test machine gun, cartridge case assemblies, escapement assemblies and links.

e. Criteria for inspection of parts and assemblies.

f. Packaging instructions, if different.

g. Quality Conformance Inspection, if other than specified in Section 4 of this specification.

h. First Article Sample requirements, it other than specified in Section 4 of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

6.3. Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, US Army ARDEC, AMSMC-QAF-I (D), Picatinny Arsenal, NJ, 07806-5000. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph.

6.4 Submission of results of contractor conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of-examination or tests to Commander, US Army ARDEC, ATTN: AMSMC-QAF-S (D), Picatinny Arsenal, NJ 07806-5000.

6.5 Submission of test data. In addition to the normal distribution of records, when the cartridges are procured by ARDC, one copy of all ballistic data and ammunition data cards shall be forwarded to Commander, US Army ARDEC, ATTN: AMSMC-QAF-S (D), Picatinny Arsenal, NJ 07806-5000.

6.6 First article. When a first article inspection is required, the contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, test and approval of the documents for first article.

6.7 Premature burst. A premature burst is considered to have occured if the projectile functions in the weapon bore or in flight up to 20 feet from the weapon muzzle.

6.8 Air burst. A projectile that functions inflight further than 20 feet from the weapon muzzle.

6.9 Conditions for use of Level B preservation. When Level B preservation is specified (see 5.1), this level of protection should be reserved for the acquisition of Cartridge, 40mm, M918 TP for resupply worldwide under known favorable handling, transportation and storage conditions.

6.10 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, US Army Armament Research and Development Command (ARRADCOM) or US Army Armament Research and Development Center (ARDC) drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

6.11 Subject term (key word) listing.

M918 TP Cartridge
40mm
MK19 Grenade Launcher
M129 Grenade Launcher
M550 Escapement Assembly

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A430)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-48683A	Cartridge, 40MM, M918 TP, Projectile assembly for metal parts

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
and loading, assembling and packing	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.