MIL-F-48277B (AR)
24 August 1978
SUPERSEDING
MIL-F-48277A (AR)
12 NOVEMBER 1976

MILITARY SPECIFICATION

FUZE, POINT DETONATING, M739 LESS BOOSTER PELLET

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the fabrication of parts and loading, assembling and packing for the M739 Point Detonating Artillery Ammunition Fuze, Less Booster Pellet.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-D-14978 - Detonator, Stab, M55, Loading, Assembling and Packing for
MIL-D-48025 - Detonator, Stab, M99, Loading, Assembling and Packing for
MIL-A-48078 - Ammunition, Standard, Quality Specification for
MIL-P-60412 - Packaging, Packing and Marking for Shipment of Artillery Type and Rocket Fuzes, General Specification for

FSC: 1390

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS (See 6.7)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9294769 - Fuze, Point Detonating, M739, Less Booster Pellet
9294992 - Plug, Test
9294993 - Disk, Test

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material and parts.-Materials and parts shall be in accordance with applicable drawings, standards and specifications.

3.2 Fuze assemblies.-The M739 Point Detonating fuze assemblies, less booster pellets, shall comply with all requirements specified on drawing (dwg.) 9294769 and with all requirements specified in applicable specifications and standards.

3.3 Jolt and jumble.-The fuze assemblies with inert boosters and booster cups shall comply with the requirements of MIL-STD-331, Tests 101 and 102.

3.4 Transportation vibration.-The fuze assemblies less booster pellet and booster cup shall comply with the requirements of MIL-STD-331, Test 401, Procedure II.

3.5 Fuze leak test.-The fuze assemblies, less booster pellet and booster cup shall produce no more than one bubble per second when subjected to this test.

3.6 Proving ground

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

3.6.1 Premature bursts.-There shall be no premature bursts in the gun bore or in the flight before impact.

3.6.2 Non-functioning.-The fuze shall not function upon impact with target, when subjected to this test.

3.6.3 Functioning

3.6.3.1 Superquick.-The fuze shall cause the projectile to function high order, and the fuze shall show no evidence of reverse functioning (see 6.5).

3.6.3.2 Delay.-The fuze shall cause the projectile to function high order.

3.7 First article inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, dirt, grease and oil (except where specifically required), rust and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and legible.

3.9 Propagation test.-The fuze assemblies with test disk, test plug and booster cups shall arm and function high order as evidenced by a minimum .170 inch diameter hole in the test disk.

3.10 Die castings.-The die castings shall be of uniform quality, free of cold shuts, blowholes and shrinkage defects. The casting must be dry, clean, and free from chips. All unfilled castings shall be rejected.

3.10.1 Flash removal.-All flash must be completely removed from parting lines, internal and external profiles, cored holes and ejector pin marks, except as noted on drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

3.10.2 Gates.-All waste material remaining from the gate must be removed except when so noted on the drawings.

3.10.3 Remelted scrap.-No scrap shall be used other than sprues, gates, and rejected die castings of the particular alloy required by the item print and produced in the manufacturer's own plant. The rejected die castings used shall be free from finishes, lubricants or any substance which may contaminate the alloy.

3.10.4 Surface porosity

3.10.4.1 Bottom plate.-No voids greater than .005" x .005" shall be permitted in the ramp surface of the setback pin hole.

3.10.4.2 Gear plate spacer.-No voids greater than .005" x .005" shall be permitted in either spinlock bearing surface.

3.10.4.3 Intentionally omitted.

3.10.4.4 Rotor body.-No voids greater than .005" x .005" shall be permitted in the upper plate bearing surface.

3.10.4.5 Intentionally omitted.

3.10.4.6 Gears.-No voids greater than .005" x .005" shall be permitted in any of the tooth profiles. No voids greater than .005" x .005" shall be permitted in the pinion flange upper bearing surface or in the gear flange lower bearing surface of the gear and pinion assembly. No voids greater than .005" x .005" shall be permitted in the escape wheel flange upper bearing surface or in the pinion flange lower bearing surface of the escape wheel and pinion assembly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.-The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the current version before use.

4.3 First article inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following:

a. Eighteen (18) each completed fuze body assemblies (dwg. 9258606) with inert boosters and booster cups for the Jolt and Jumble Test.

b. Twenty-five (25) each of every component part.

c. Twenty-five (25) each of every sub-assembly.

d. One-hundred fifty (150) each (dwg. 9294769) fuzes less booster pellet assemblies. These samples shall be used for the First Article Ballistic Acceptance Test (see 4.5.27.1). Fifteen fuze samples shall be TV tested prior to ballistic test.

e. Fifty (50) each (dwg. 9294769) fuzes less booster pellet assemblies for the Propagation Test (see 4.5.17).

The first article sample shall consist of parts and assemblies which have been produced by the contractor or furnished by a supplier, and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract, and submit a record of this inspection with the sample including statements of findings for materials, processes and tests. When a multiple cavity mold is used in the fabrication of die cast components, a minimum of ten components from each mold cavity shall be included in the first article sample; 25 are required if only one cavity is used. Each component shall bear a mark which identifies it with its particular cavity. The mark shall be located where subsequent machining shall not obliterate the

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the current version before use.

mark. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity, as determined by the Government.

4.3.2 Inspections to be performed.-The first article parts submitted in accordance with Paragraph 4.3 will be subjected by the Government to any or all of the applicable examinations and tests specified in 4.4.2 and 4.4.3 of this specification and to any or all of the requirements of the applicable drawings and specifications.

4.3.3 Rejection.-See MIL-A-48078 (PA)

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078 (PA). In addition, inspection lots of M739 PD Fuzes less booster pellets shall contain:

a. Delay plunger assemblies of one lot interfix number from one manufacturer.

b. M55 detonators of one lot interfix number from one manufacturer.

c. M99 detonators of one lot interfix number from one manufacturer.

d. Lead assemblies of one lot interfix number from one manufacturer.

4.4.2 Examination.-See MIL-A-48078 (PA).

a. Sampling plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Pin, Firing				9258619
					NEXT HIGHER ASSEMBLY 9258618
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of shaft and profile of point		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Firing Pin Assembly		9258618
			NEXT HIGHER ASSEMBLY 9294606

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test	80		3.2	4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Support, Firing Pin		9258614
			NEXT HIGHER ASSEMBLY 9294606

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Load test	80		3.1	4.5.4
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Housing, Detonator				9258617
					NEXT HIGHER ASSEMBLY
					9294606
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth of detonator cavity		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	True position of detonator cavity with outside diameter		0.65%	3.1	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Firing Pin and Housing Assembly		9294606
			NEXT HIGHER ASSEMBLY 9258613

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Distance from bottom of detonator cavity to firing pin point		100%	3.2	Gage
Major					
101	Load test	80		3.2	4.5.21
102	Inward buckling of firing pin tube		0.40%	3.2	Visual
Major					
131	Outside diameter, max.		0.40%	3.2	Gage
Minor					
201	Crimp incomplete		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Firing Pin Housing and Detonator Assembly		9258613
			NEXT HIGHER ASSEMBLY 9258606

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Detonator inverted or missing, prior to application of seal tape		100%	3.2	Gage
Major 131	Overall length, max.		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Holder, Crossbar	1 OF 1	9258624
			NEXT HIGHER ASSEMBLY: 9258622

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of four rain holes	(a)		3.1	Visual 4.5.7
Major					
131	Presence of four dimples	(a)		3.1	Visual 4.5.7
132	Presence of longitudinal separation	(a)		3.1	Visual 4.5.7
Minor					
201	Evidence of poor workmanship	(a)		3.8	Visual 4.5.7

NOTES:
(a) Five (5) pieces per punch per day

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Cup, Booster		9258607
			NEXT HIGHER ASSEMBLY 9294769

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness of bottom of cup.		0.40%	3.1	Gage
102	Depth of wrench holes		0.40%	3.1	Gage
Major					
131	Inside diameter of cup		0.40%	3.1	Gage
132	Depth of cup		0.40%	3.1	Gage
133	Thread length, min.		0.40%	3.1	Gage
134	Pitch diameter of thread		0.40%	3.1	Gage
135	Major diameter of thread		0.40%	3.1	Gage
Minor					
201	Protective finish missing or inadequate		0.65%	3.1	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual
203	Location of wrench holes		0.65%	3.1	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Interrupter		9258629
			NEXT HIGHER ASSEMBLY
			9258625

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Large diameter, min.		100%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.12	Sleeve, Setting (Die Check)		9258628
			NEXT HIGHER ASSEMBLY 9258625

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Body diameter, min.	(a)		3.1	Gage/4.5.24
b.	Interrupter diameter, max.	(a)		3.1	Gage/4.5.24
Major					
101	O-Ring diameter	(a)		3.1	Gage/4.5.24
102	True position of small slot with retainer seating diameter	(a)		3.1	Gage/4.5.24
103	True position of large slot with retainer seating diameter	(a)		3.1	Gage/4.5.24
104	True position of screwdriver slot with retainer seating diameter	(a)		3.1	Gage/4.5.24
Major					
131	Interrupter diameter, min.	(a)		3.1	Gage/4.5.24
132	Width of screwdriver slot	(a)		3.1	Gage/4.5.24
133	Radial length of stop	(a)		3.1	Gage/4.5.24
134	Location of stop	(a)		3.1	Gage/4.5.24
135	Large outside diameter	(a)		3.1	Gage/4.5.24
136	Length of O-Ring diameter	(a)		3.1	Gage/4.5.24
137	True position of large outside diameter with body diameter	(a)		3.1	Gage/4.5.24

NOTES:
(a) Three (3) samples per cavity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 2 OF 2		DRAWING NUMBER
4.4.2.12	CONTINUATION SHEET			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
138	Distance from retainer to top of large outside diameter	(a)		3.1	Gage/4.5.24
139	True position of O-Ring diameter with body diameter	(a)		3.1	Gage/4.5.24
140	Depth of retainer seating diameter	(a)		3.1	Gage/4.5.24
141	Length of large outside diameter	(a)		3.1	Gage/4.5.24
142	Retainer seating diameter	(a)		3.1	Gage/4.5.24
Minor					
201	Depth of small slot	(a)		3.1	Gage/4.5.24
202	Depth of large slot	(a)		3.1	Gage/4.5.24
203	Depth of interrupter cavity	(a)		3.1	Gage/4.5.24
204	Width of large slot	(a)		3.1	Gage/4.5.24
205	Width of small slot	(a)		3.1	Gage/4.5.24
206	Thickness of stop	(a)		3.1	Gage/4.5.24
207	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.24

NOTES:
(a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9258628
4.4.2.13	Sleeve, Setting				NEXT HIGHER ASSEMBLY 9258625
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Body diameter, min.	(a)		3.1	Gage/4.5.29
b.	Interrupter diameter, max.	(a)		3.1	Gage/4.5.29
Major					
101	O-Ring diameter	(a)		3.1	Gage/4.5.29
Major					
131	Retainer seating diameter	(a)		3.1	Gage/4.5.29
132	Length of large outside diameter	(a)		3.1	Gage/4.5.29
Minor					
201	Width of large slot	(a)		3.1	Gage/4.5.29
202	Width of small slot	(a)		3.1	Gage/4.5.29
203	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.29

NOTES: (a) Three (3) samples per 50,000 pieces per cavity. Sample size increases for larger production run (see 4.4.3.4)

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Retainer Interrupter (Die Check)		9258626
			NEXT HIGHER ASSEMBLY 9258625

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
131	Width of large tab	(a)		3.1	Gage/4.5.24
132	Width of small tab	(a)		3.1	Gage/4.5.24
133	True position of small tab with body diameter	(a)		3.1	Gage/4.5.24
134	True position of large tab with body diameter	(a)		3.1	Gage/4.5.24
135	Interrupter diameter	(a)		3.1	Gage/4.5.24
136	Depth of smallest inside diameter, min.	(a)		3.1	Gage/4.5.24
137	Body diameter	(a)		3.1	Gage/4.5.24
138	Distance from bottom to top of body diameter	(a)		3.1	Gage/4.5.24
Minor					
201	Smallest inside diameter	(a)		3.1	Gage/4.5.24
202	Depth of interrupter diameter	(a)		3.1	Gage/4.5.24
203	True position of interrupter diameter with body diameter	(a)		3.1	Gage/4.5.24
204	Diameter over tabs	(a)		3.1	Gage/4.5.24
205	Thickness of large tab	(a)		3.1	Gage/4.5.24
206	Thickness of base	(a)		3.8/3.10	Visual/4.5.24
207	Evidence of poor workmanship				

NOTES:
(a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Retainer Interrupter		9258626
			NEXT HIGHER ASSEMBLY
			9258625

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
131	Interrupter diameter	(a)		3.1	Gage/4.5.29
132	Depth of smallest inside diameter, min.	(a)		3.1	Gage/4.5.29
133	Distance from bottom to top of body diameter	(a)		3.1	Gage/4.5.29
Minor					
201	Thickness of base	(a)		3.1	Gage/4.5.29
202	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.29

NOTES:

(a) Three (3) samples per 50,000 pieces per cavity. Sample size increases for larger production run (see 4.4.3.4)

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Setting Sleeve Assembly		9258625
			NEXT HIGHER ASSEMBLY 9294595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Retainer inverted		100%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-46277A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.17	Plate, Gear, Lower (Die Check)		9258651
			NEXT HIGHER ASSEMBLY
			9258650

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of gear and pinion hole	(a)		3.1	Gage/4.5.25
103	True position of gear and pinion hole	(a)		3.1	Gage/4.5.25
104	Diameter of escape wheel and pinion hole	(a)		3.1	Gage/4.5.25
106	True position of escape wheel and pinion hole	(a)		3.1	Gage/4.5.25
107	Diameter of pallet shaft hole	(a)		3.1	Gage/4.5.25
109	True position of pallet shaft hole	(a)		3.1	Gage/4.5.25
110	Diameter of rotor hole	(a)		3.1	Gage/4.5.25
112	True position of rotor hole	(a)		3.1	Gage/4.5.25
113	Diameter of lock pin hole	(a)		3.1	Gage/4.5.25
115	True position of lock pin hole	(a)		3.1	Gage/4.5.25
Major					
131	Flatness	(a)		3.1	Gage/4.5.25
132	Diameter of module pin holes (four)	(a)		3.1	Gage/4.5.25
134	True position of module pin holes (three)	(a)		3.1	Gage/4.5.25
135	Radius of locating notch	(a)		3.1	Gage/4.5.25
137	True position of locating notch	(a)		3.1	Gage/4.5.25
138	Diameter of assembly lug	(a)		3.1	Gage/4.5.25
139	True position of assembly lug	(a)		3.1	Gage/4.5.25
140	Die breakage in gear and pinion hole, max.	(a)		3.1	Gage/4.5.25
141	Die breakage in escape wheel and pinion hole, max.	(a)		3.1	Gage/4.5.25

NOTES: (a) Five (5) samples per punch.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46277B (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.2.7			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Die breakage in rotor hole, max.	(a)		3.1	Gage/4.5.25
Minor					
201	Thickness	(a)		3.1	Gage/4.5.25
202	Outside diameter	(a)		3.1	Gage/4.5.25
203	Diameter of lead hole, min.	(a)		3.1	Gage/4.5.25
204	True position of lead hole	(a)		3.1	Gage/4.5.25
205	Diameter of setback pin boss hole, min.	(a)		3.1	Gage/4.5.25
206	Evidence of poor workmanship	(a)		3.6	Visual/4.5.25

NOTES: (a) Five (5) samples per punch.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

23

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Plate, Gear, Lower		9256651
			NEXT HIGHER ASSEMBLY: 9256650

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of gear end pinion hole	(a)		3.1	Gage/4.5.7
102	Diameter of escape wheel and pinion hole	(a)		3.1	Gage/4.5.7
103	Diameter of rotor hole	(a)		3.1	Gage/4.5.7
Major					
131	Flatness	(a)		3.1	Gage/4.5.7
132	Lubricant missing	(b)	0.40%	3.1	Visual
Minor					
201	Thickness	(a)		3.1	Gage/4.5.7
202	Bushing diameter	(a)		3.1	Gage/4.5.7
203	Evidence of poor workmanship	(a)		3.3	Visual/4.5.7

NOTES:
(a) Five (5) samples per day per punch.
(b) Inspection sample shall be taken from a production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.19	Shaft, Pallet		9258652
			NEXT HIGHER ASSEMBLY 9258650

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of smallest diameter		0.40%	3.1	Gage
102	Runout of smallest diameter		0.40%	3.1	Gage
Major					
131	Lubricant missing		0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9259650
4.4.4.20	Lower Plate and Shaft Assembly				NEXT HIGHER ASSEMBLY 9258643
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Push-out test	80		3.2	4.5.15
102	Distance from plate to bearing surface		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 8567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-462770 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Pin, Lock, Rotor				9258649
					NEXT HIGHER ASSEMBLY 9258643
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of locking diameter, min.		0.40%	3.1	Gage
102	Cutoff nibpresent on locking diameter end		0.40%	3.1	Visual
Major					
131	Lubricant missing		0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46277C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.22	Spring, Pin, Lock				9258647
					NEXT HIGHER ASSEMBLY
					9258643
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length under min. load		0.40%	3.1	Gage
102	Length under max. load		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.23	Plate, Bottom (Die Check)		9238644
			NEXT HIGHER ASSEMBLY 9238643

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of lead hole	(a)		3.1	Gage/4.5.24
102	Diameter of large setback pin hole	(a)		3.1	Gage/4.5.24
103	True position of large setback pin hole	(a)		3.1	Gage/4.5.24
104	Diameter of small setback pin hole	(a)		3.1	Gage/4.5.24
105	True position of small setback pin hole	(a)		3.1	Gage/4.5.24
106	Diameter of locking pin hole	(a)		3.1	Gage/4.5.24
107	True position of locking pin hole	(a)		3.1	Gage/4.5.24
110	Angle of top of setback pin hole	(a)		3.1	Gage/4.5.24
111	Depth of large setback pin hole	(a)		3.1	Gage/4.5.24
112	Surface porosity	(a)		3.10.4.1	4.5.24/4.5.26
Major					
131	Outside diameter	(a)		3.1	Gage/4.5.24
132	Diameter of module pin holes (four)	(a)		3.1	Gage/4.5.24
133	True position module pin holes (three)	(a)		3.1	Gage/4.5.24
135	Distance from bottom of plate to top of setback pin boss	(a)		3.1	Gage/4.5.24
136	Depth of locking pin disc hole	(a)		3.1	Gage/4.5.24
138	Radius of locating notch	(a)		3.1	Gage/4.5.24
139	True position of locating notch	(a)		3.1	Gage/4.5.24
140	Diameter of spacer tab hole	(a)		3.1	Gage/4.5.24

NOTES: (a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.4.2.23	TITLE		SHEET 2 OF 2		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
101	True position of spacer tab hole	(a)		3.1	Gage/4.5.24
102	Depth of spacer tab hole, min.	(a)		3.1	Gage/4.5.24
103	Diameter of lead hole	(a)		3.1	Gage/4.5.24
104	Diameter of rotor hole	(a)		3.1	Gage/4.5.24
105	True position of rotor hole	(a)		3.1	Gage/4.5.24
Minor					
201	Distance from bottom plate to bottom of setback pin and lead holes	(a)		3.1	Gage/4.5.24
202	Thickness from top of plate to bottom of plate	(a)		3.1	Gage/4.5.24
203	Thickness of thick portion of plate	(a)		3.1	Gage/4.5.24
204	Thickness of thin portion of plate	(a)		3.1	Gage/4.5.24
205	Depth of rotor hole	(a)		3.1	Gage/4.5.24
206	Diameter of top of setback pin boss	(a)		3.1	Gage/4.5.24
207	True position of top of setback pin boss	(a)		3.1	Gage/4.5.24
208	True position of outside diameter	(a)		3.1	Gage/4.5.24
209	Diameter of two assembly holes	(a)		3.1	Gage/4.5.24
210	True position of assembly holes	(a)		3.1	Gage/4.5.24
211	Evidence of poor workmanship	(a)		3.6/3.10	Visual/4.5.24

NOTES: (a) Three (3) samples per cavity.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.24	Plate, Bottom		9258644
			NEXT HIGHER ASSEMBLY
			9258643

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of large setback pin hole	(a)		3.1	Gage/4.5.29
102	Depth of setback pin hole	(a)		3.1	Gage/4.5.29
103	Surface porosity	(a)		3.10.4.1	Gage/4.5.26/4.5.29
Major					
131	Diameter of lead hole	(a)		3.1	Gage/4.5.29
132	Lubricant missing	(b)	0.40%	3.1	Visual
Minor					
201	Thickness from top of plate to bottom of plate	(a)		3.1	Gage/4.5.29
202	Thickness of thin portion of plate	(a)		3.1	Gage/4.5.29
203	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.29

NOTES:
(a) Three (3) samples per 50,000 pieces per cavity. Sample size increases for larger production (see 4.4.3.4).
(b) Inspection sample shall be taken from a production lot.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.25	Spacer, Plate, Gear (Die Check)		9256643
			NEXT HIGHER ASSEMBLY
			9256643

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth of lead hole	(a)		3.1	Gage/4.5.24
102	True position of lead hole	(a)		3.1	Gage/4.5.24
103	Diameter of locking pin hole	(a)		3.1	Gage/4.5.24
104	True position of locking pin hole	(a)		3.1	Gage/4.5.24
105	True position of spin shaft holes	(a)		3.1	Gage/4.5.24
107	Diameter of spin detent spring holes	(a)		3.1	Gage/4.5.24
108	True position of spin detent spring holes	(a)		3.1	Gage/4.5.24
109	Profile of rotor lug slot	(a)		3.1	Gage/4.5.24
110	Profile of spin detent area	(a)		3.1	Gage/4.5.24
111	Profile of rotor cavity	(a)		3.1	Gage/4.5.24
112	Profile of pallet shaft and gear area	(a)		3.1	Gage/4.5.24
113	Surface porosity	(a)		3.10.4.2	4.5.24/4.5.26
114					
Major					
131	Outside diameter	(a)		3.1	Gage/4.5.24
132	Radius of locating notch	(a)		3.1	Gage/4.5.24
133	True position of locating notch	(a)		3.1	Gage/4.5.24
134	Diameter of tab	(a)		3.1	Gage/4.5.24
135	True position of tab	(a)		3.1	Gage/4.5.24
136	Thickness of bottom	(a)		3.1	Gage/4.5.24
137	Diameter of nodule pin holes (four)	(a)		3.1	Gage/4.5.24
138	True position of nodule pin holes (three)	(a)		3.1	Gage/4.5.24

NOTES: (a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-45277A (AR)

PARAGRAPH 4.4.2.25	TITLE		SHEET 2 OF 2		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
140	Diameter of upper plate tab hole	(a)		3.1	Gage/4.5.24
141	True position upper plate tab hole	(a)		3.1	Gage/4.5.24
142	Depth of upper plate tab hole, min.	(a)		3.1	Gage/4.5.24
143	Profile of gear slot	(a)		3.1	Gage/4.5.24
144	Diameter of lead hole	(a)		3.1	Gage/4.5.24
145	Diameter of spin shaft holes	(a)		3.1	Gage/4.5.24
Minor					
201	Thickness	(a)		3.1	Gage/4.5.24
202	True position of outside diameter	(a)		3.1	Gage/4.5.24
203	Diameter of rotor hole	(a)		3.1	Gage/4.5.24
204	True position of rotor hole	(a)		3.1	Gage/4.5.24
205	Diameter of pallet shaft hole	(a)		3.1	Gage/4.5.24
206	True position of pallet shaft hole	(a)		3.1	Gage/4.5.24
207	Depth of spin shaft holes	(a)		3.1	Gage/4.5.24
208	Any chamfer missing	(a)		3.1	Visual/4.5.24
209	Evidence of poor workmanship	(a)		3.3/3.10	Visual/4.5.24

NOTES: (a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 20260-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.26	Spacer, Plate, Gear		9258646
			NEXT HIGHER ASSEMBLY
			9258643

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of locking pin hole	(a)		3.1	Gage/4.5.29
102	Surface porosity	(a)		3.10.4.2	4.5.26/4.5.29
Major					
131	Diameter of spin snaft holes	(a)		3.1	Gage/4.5.29
132	Thickness of bottom	(a)		3.1	Gage/4.5.29
Minor					
201	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.29

NOTES: (a) Three (3) samples per 50,000 pieces per cavity. Sample size increases for larger production run (see 4.4.3.4).

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.27	Plate and Spacer Assembly				9253643
					NEXT HIGHER ASSEMBLY
					9294833
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of lock pin disk stake		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.28	Shaft, Rotor				9258641
					NEXT HIGHER ASSEMBLY
					9258639
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of bearing diameters		0.40%	3.1	Gage
Major					
131	Lubricant missing		0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.29	Body, Rotor (Die Check)				9258640
					NEXT HIGHER ASSEMBLY
					9258639
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight, min.	(a)		3.1	Balance/4.5.24
102	Angularity of spin detent holding surfaces	(a)		3.1	Gage/4.5.24
103	Diameter of locking pin hole	(a)		3.1	Gage/4.5.24
105	True position of locking pin hole	(a)		3.1	Gage/4.5.24
106	Diameter of setback pin hole	(a)		3.1	Gage/4.5.24
108	True position of setback pin hole	(a)		3.1	Gage/4.5.24
109	Finish on bearing surface	(a)		3.1	Gage/4.5.24
110	Surface porosity	(a)		3.10.4.4	4.5.24/4.5.26
Major					
131	Diameter of rotor shaft hole	(a)		3.1	Gage/4.5.24
132	True position of rotor gear lugs	(a)		3.1	Gage/4.5.24
133	Diameter of large detonator hole, min.	(a)		3.1	Gage/4.5.24
134	True position of large detonator hole	(a)		3.1	Gage/4.5.24
135	Depth of detonator hole	(a)		3.1	Gage/4.5.24
136	Protrusion of rotor gear lugs, min.	(a)		3.1	Gage/4.5.24
137	Thickness of rotor at detonator hole	(a)		3.1	Gage/4.5.24
138	Thickness from bearing surface to bottom of flange	(a)		3.1	Gage/4.5.24
139	Thickness of rotor at flange	(a)		3.1	Gage/4.5.24
140	Outside diameter	(a)		3.1	Gage/4.5.24

NOTES: (a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.4.2.29	TITLE		SHEET 2 OF 2		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
141	True position of outside diameter	(a)		3.1	Gage/4.5.24
142	Profile of locking pin notch	(a)		3.1	Gage/4.5.24
Minor					
201	Diameter of rotor gear tab hole	(a)		3.1	Gage/4.5.24
202	Depth of rotor gear tab hole	(a)		3.1	Gage/4.5.24
203	Diameter of rotor gear lugs	(a)		3.1	Gage/4.5.24
205	Diameter of larger detonator hole, max.	(a)		3.1	Gage/4.5.24
206	Diameter of small detonator hole	(a)		3.1	Gage/4.5.24
207	Protrusion of rotor gear lugs, max.	(a)		3.1	Gage/4.5.24
208	Radius from center to detonator boss	(a)		3.1	Gage/4.5.24
209	Profile of large irregular slot	(a)		3.1	Gage/4.5.24
210	Diameter of bearing surface	(a)		3.1	Gage/4.5.24
211	Profile of flange	(a)		3.1	Gage/4.5.24
212	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.24

NOTES: (a) Three (3) samples per cavity.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.30	Body, Rotor		9258640
			NEXT HIGHER ASSEMBLY
			9258639

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight, min.	(a)		3.1	Balance/4.5.29
102	Surface porosity	(a)		3.10.4.4	4.4.26/4.5.29
Major					
131	Diameter of rotor shaft hole	(a)		3.1	Gage/4.5.29
132	Thickness of rotor at detonator hole	(a)		3.1	Gage/4.5.29
133	Thickness of rotor at flange	(a)		3.1	Gage/4.5.29
134	Lubricant missing	(b)	0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.29

NOTES: (a) Three (3) samples per 50,000 pieces per cavity. Sample size increases for larger production runs (see 4.4.3.4)
(b) Inspection sample shall be taken from a production lot.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.31	Gear, Rotor (Die Check)	1 OF 1	9258642
			NEXT HIGHER ASSEMBLY 9258639

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tooth to tooth composite error	(a)		3.1	Gage/4.5.25
102	Diameter of rotor shaft hole	(a)		3.1	Gage/4.5.25
Major					
131	Diameter of assembly tab	(a)		3.1	Gage/4.5.25
132	True position of assembly tab	(a)		3.1	Gage/4.5.25
133	Diameter of small rotor lug hole	(a)		3.1	Gage/4.5.25
134	True position of small rotor lug holes	(a)		3.1	Gage/4.5.25
136	Profile around rotor shaft hole	(a)		3.1	Gage/4.5.25
137	Thickness	(a)		3.1	Gage/4.5.25
Minor					
201	Diameter of large rotor lug holes	(a)		3.1	Gage/4.5.25
202	True position of large rotor lug holes	(a)		3.1	Gage/4.5.25
203	Diameter of setback pin hole	(a)		3.1	Gage/4.5.25
204	True position of setback pin hole	(a)		3.1	Gage/4.5.25
205	Profile of rotor flange notch	(a)		3.1	Gage/4.5.25
206	Large radius	(a)		3.1	Gage/4.5.25
207	Evidence of poor workmanship	(a)		3.8	Visual/4.5.25

NOTES: (a) Five (5) pieces per punch.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.32	Gear, Rotor		9258642
			NEXT HIGHER ASSEMBLY 9258639

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of rotor shaft hole	(a)		3.1	Gage/4.5.7
102	Tooth to tooth composite error	(a)		3.1	Gage/4.5.7
Major					
131	Thickness	(a)		3.1	Gage/4.5.7
132	Lubricant missing	(b)	0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship	(a)		3.8	Visual/4.5.7

NOTES:
(a) Five (5) pieces per day per punch.
(b) Inspection sample shall be taken from a production lot.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.33	Rotor Assembly		9256639
			NEXT HIGHER ASSEMBLY 9294833

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Detonator inverted or missing		100%	3.2	Gage/Visual
102	Distance between bearing surfaces, max.		0.40%	3.2	Gage
103	Detonator push out test		0.40%	3.2	4.5.11
Major					
131	Sensitive end not flush or below flush		0.40%	3.2	Visual
132	Rotor gear stake incomplete or missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.34	Spinlock				9256638
					NEXT HIGHER ASSEMBLY 9294833
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight	60		3.1	4.5.26
102	Load Test	80		3.1	4.5.23
103	Profile of holding surfaces		0.40%	3.1	Gage
Major					
131	Lubricant missing		0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46277A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2. 35	Rear Axle Pinion Assembly (Die Cast)		9256553
			NEXT HIGHER ASSEMBLY
			9294833

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of small diameters	(a)		3.2	Gage/4.5.24
102	Tooth to tooth composite error of large gear	(a)		3.2	Gage/4.5.24
104	Tooth to tooth composite error of pinion	(a)		3.2	Gage/4.5.24
106	Distance between bearing surfaces	(a)		3.2	Gage/4.5.24
107	Surface porosity	(a)		3.10.4.6	4.5.24/4.5.26
108	Gate above flush max.	(a)		3.2	Gage/4.5.24
109	Flash in chamfer areas (not finn.)	(a)		3.2	Manual/4.5.24
Major					
131	Thickness of gear	(a)		3.2	Gage/4.5.24
132	Distance from lower bearing surface to top of pinion	(a)		3.2	Gage/4.5.24
133	Distance from hub diameter to end	(a)		3.2	Gage/4.5.24
Minor					
201	Hub diameter	(a)		3.2	Gage/4.5.24
202	True position of hub diameter	(a)		3.2	Gage/4.5.24
203	Bearing diameter	(a)		3.2	Gage/4.5.24
204	True position of bearing diameter	(a)		3.2	Gage/4.5.24
205	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.24

NOTES: (a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 20260-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (NR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.36	Gear and Pinion Assembly		9258653
			NEXT HIGHER ASSEMBLY 9294833

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of small diameters	(a)		3.2	Gage/4.5.29
102	Tooth to tooth composite error of large gear	(a)		3.2	Gage/4.5.29
104	Tooth to tooth composite error of pinion	(a)		3.2	Gage/4.5.29
106	Surface porosity	(a)		3.10.4.6	4.5.26/4.5.29
107	Gate above flash max.	(a)		3.2	Gage/4.5.29
108	Flash in chamfer areas (not firm)	(a)		3.2	Manual/4.5.29
Major					
131	Thickness of gear	(a)		3.2	Gage/4.5.29
132	Lubricant missing	(b)	0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.29

NOTES: (a) Three (3) samples per 50,000 pieces per cavity. Sample size increases for larger production runs (see 4.4.3.4).
(b) Inspection sample shall be taken from a production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z -
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER 9258655
4.4.2.37	Escape Wheel and Pinion Assembly (Die Check)			NEXT HIGHER ASSEMBLY 9294833
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of small diameters	(a)		3.2	Gage/4.5.24
102	Tooth to tooth composite error on pinion	(a)		3.2	Gage/4.5.24
106	Distance between bearing surfaces	(a)		3.2	Gage/4.5.24
107	Surface porosity	(a)		3.10.4.6	4.5.24/4.5.26
108	Gate above flush max.	(a)		3.2	Gage/4.5.24
109	Flash in chamfer areas (not final)	(a)		3.2	Manual/4.5.24
Major					
131	Thickness of escape wheel	(a)		3.2	Gage/4.5.24
132	Distance from bearing surface to end of pinion	(a)		3.2	Gage/4.5.24
133	Distance from bearing surface to end	(a)		3.2	Gage/4.5.24
Minor					
201	Small bearing surface diameter	(a)		3.2	Gage/4.5.24
202	True position of small bearing surface diameter	(a)		3.2	Gage/4.5.24
203	Large bearing surface diameter	(a)		3.2	Gage/4.5.24
204	True position of large bearing surface diameter	(a)		3.2	Gage/4.5.24
205	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.24

NOTES: (a) Three (3) samples per cavity.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46277 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.38	Escape Wheel and Pinion Assembly		9258655
			NEXT HIGHER ASSEMBLY 9294833

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of small diameters	(a)		3.2	Gage/4.5.29
102	Tooth to tooth composite error on pinion	(a)		3.2	Gage/4.5.29
106	Surface porosity	(a)		3.2	4.5.26/4.5.29
107	Gate above flush max.	(a)		3.2	Gage/4.5.29
108	Flash in chamfer areas (not fins)	(a)		3.2	Manual/4.5.29
Major					
131	Thickness of escape wheel	(a)		3.2	Gage/4.5.29
132	Lubricant missing	(b)	0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship	(a)		3.8/3.10	Visual/4.5.29

NOTES: (a) Three (3) samples per 50,000 pieces per cavity. Sample size increases for larger production run(see 4.4.3.4)
(b) Inspection samples shall be taken from a production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
4.4.2.39	Pallet (Die Check)			9258631
				NEXT HIGHER ASSEMBLY 9294833

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total profile	(a)		3.1	Gage/4.5.25
102	Diameter of hole	(a)		3.1	Gage/4.5.25
Major					
131	Thickness	(a)		3.1	Gage/4.5.25
132	Excessive die breakage in hole	(a)		3.1	Gage/4.5.25
133	Excessive die breakage on engagement surfaces	(a)		3.1	Gage/4.5.25
Minor					
201	Evidence of poor workmanship	(a)		3.8	Visual/4.5.25

NOTES: (a) Five (5) pieces per punch.

48

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-40277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.40	Pallet		9258631
			NEXT HIGHER ASSEMBLY
			9294833

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile of engagement surfaces (2 places)	(a)		3.1	Gage/4.5.7
102	Diameter of hole	(a)		3.1	Gage/4.5.7
Major					
131	Thickness	(a)		3.1	Gage/4.5.7
132	Lubricant missing	(b)	0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship	(a)		3.8	Visual/4.5.7

NOTES:
(a) Five (5) pieces per day per punch.
(b) Inspection sample shall be taken from a production lot.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2		DRAWING NUMBER
4.4.2.41	Plate, Gear, Upper (Die Check)			9258032
				NEXT HIGHER ASSEMBLY 9294833
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH / PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined			
Major				
101	Diameter of gear and pinion hole	(a)		3.1 Gage/4.5.25
103	True position of gear and pinion hole	(a)		3.1 Gage/4.5.25
104	Diameter of escape wheel and pinion hole	(a)		3.1 Gage/4.5.25
106	True position of escape wheel and pinion hole	(a)		3.1 Gage/4.5.25
107	Diameter of pallet shaft hole	(a)		3.1 Gage/4.5.25
109	True position of pallet shaft hole	(a)		3.1 Gage/4.5.25
110	Diameter of rotor hole	(a)		3.1 Gage/4.5.25
112	True position of rotor hole	(a)		3.1 Gage/4.5.25
Major				
131	Flatness	(a)		3.1 Gage/4.5.25
132	Diameter of module pin holes (three)	(a)		3.1 Gage/4.5.25
134	True position of module pin holes (three)	(a)		3.1 Gage/4.5.25
135	Radius of locating notch	(a)		3.1 Gage/4.5.25
137	True position of locating notch	(a)		3.1 Gage/4.5.25
138	Diameter of assembly lug	(a)		3.1 Gage/4.5.25
139	True position of assembly lug	(a)		3.1 Gage/4.5.25
140	Die breakage in gear and pinion hole, max.	(a)		3.1 Gage/4.5.25
141	Die breakage in escape wheel and pinion hole max.	(a)		3.1 Gage/4.5.25
142	Die breakage in rotor hole, max.	(a)		3.1 Gage/4.5.25

NOTES: (a) Five (5) samples per punch.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-302773 (SH)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
4.4.2. 41					
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Liner					
201	Thickness	(a)		3.1	Gage/4.5.25
202	Outside diameter	(a)		3.1	Gage/4.5.25
203	Diameter of flashhole	(a)		3.1	Gage/4.5.25
204	True position of flashhole	(a)		3.1	Gage/4.5.25
205	Profile of setting slot	(a)		3.1	Gage/4.5.25
206	Evidence of poor workmanship	(a)		3.6	Visual/4.5.25

NOTES: (a) Five (5) samples per punch.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2. 42	Plate, Gear, Upper		9256832
			NEXT HIGHER ASSEMBLY 9294833

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of gear and pinion hole	(a)		3.1	Gage/4.5.7
102	Diameter of escape wheel and pinion hole	(a)		3.1	Gage/4.5.7
103	Diameter of rotor hole	(a)		3.1	Gage/4.5.7
Major					
131	Flatness	(a)		3.1	Gage/4.5.7
132	Lubricant missing	(b)	0.403	3.1	Visual
Minor					
201	Thickness	(a)		3.1	Gage/4.5.7
202	Outside diameter	(a)		3.1	Gage/4.5.7
203	Evidence of poor workmanship	(a)		3.6	Visual/4.5.7

NOTES:
(a) Five (5) samples per day per punch.
(b) Inspection sample shall be taken from a production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.43	Safing and Arming Module Subassembly		9294033
			NEXT HIGHER ASSEMBLY
			9258030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Non-arming test		100%	3.2	4.5.14
2	Arming time, min		100%	3.2	4.5.13.2
3	Rotor not locked by the spin detents after non-arming test		100%	3.2	Gage
Major					
101	Arming test		100%	3.2	4.5.13.1
102	Arming time, max.		100%	3.2	4.5.13.2
103	Locking of rotor		100%	3.2	4.5.13.3
104	Lead assembly push out test	80		3.2	4.5.12
105	Lead cup stake not flush or below flush		0.40%	3.2	Gage/Visual
106	Lead improperly assembled or missing		100%	3.2	Gage/Visual
107	Protrusion of pins		0.40%	3.2	Visual
Major					
151	Outside diameter, max		0.40%	3.2	Gage
152	Height, max		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46277A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.44	Spring, Pin Setback				9253536
					NEXT HIGHER ASSEMBLY
					9270630
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height under min load		0.40%	3.1	Gage
102	Height under max load		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.1	Visual
202	Ends not square		0.65%	3.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-43277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.45	Pin Setback		9258634
			NEXT HIGHER ASSEMBLY
			9258630

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
102	Load test	80		3.1	4.5.22
103	Weight	80		3.1	4.5.28
104	Diameter of small end		0.40%	3.1	Gage
105	Length of small diameter		0.40%	3.1	Gage
106	Radius of small diameter		0.40%	3.1	Gage
107	Radius of outside of large diameter (top end)		0.40%	3.1	Gage
108	Radius of outside of large diameter (bottom end)		0.40%	3.1	Gage
109	Large diameter		0.40%	3.1	Gage
110	Length of large diameter and ramp angle		0.40%	3.1	Gage
111	Angle of ramp		0.40%	3.1	Gage
Major					
131	Lubricant Missing		0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	Location of large diameter		0.65%	3.1	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.46	Safing and Arming Module Assembly				9258630
					NEXT HIGHER ASSEMBLY 9282958
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Non-arming test		100%	3.2	4.5.15
2	Rotor not locked in the unarmed position after non-arming test		100%	3.2	Gage
Major					
101	Push test on setback pin disk	80		3.2	4.5.19
102	Setback pin freedom of movement test		100%	3.2	4.5.20
103	Setback pin disk and stakes not flush or below flush		0.40%	3.2	Gage/Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2. 47	Retainer, S&A				9258620
					NEXT HIGHER ASSEMBLY
					9262958
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
131	Pitch diameter of thread		0.40%	3.1	Gage
132	Major diameter of thread		0.40%	3.1	Gage
Minor					
201	Base thickness		0.65%	3.1	Gage
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
4.4.2.48	S&A Module and Retainer Assembly			9282958
				NEXT HIGHER ASSEMBLY 9258606
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
131	Overall height, max.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-[illegible] (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.49	Body, Fuze				9258609
					NEXT HIGHER ASSEMBLY 9294595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of flash hole with delay plunger cavity		0.40%	3.1	Gage
102	Diameter of flash hole		0.40%	3.1	Gage
103	True position of firing pin housing and detonator cavity with delay plunger cavity		0.40%	3.1	Gage
107	Diameter of setting sleeve cavity, max.		0.40%	3.1	Gage
Major					
131	Pitch diameter of external thread		0.40%	3.1	Gage
132	Major diameter of external thread		0.40%	3.1	Gage
133	Pitch diameter of S&A retainer thread		0.40%	3.1	Gage
134	Minor diameter of S&A retainer thread		0.40%	3.1	Gage
135	Diameter of delay plunger cavity		0.40%	3.1	Gage
136	Diameter of setting sleeve retaining ring groove		0.40%	3.1	Gage
137	Profile of ogive		0.40%	3.1	Gage
138	Length from nose to base of wrench slot flange		0.40%	3.1	Gage
139	Length from base of fuze to base of wrench slot flange		0.40%	3.1	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46277B (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.49					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
140	Width of wrench slots		0.40%	3.1	Gage
142	Outside diameter at base, max.		0.40%	3.1	Gage
143	ID dia./or delay nomenclature missing or improperly located		0.40%	3.1	Visual
144	Length from flange to bottom of nose cap groove		0.40%	3.1	Gage
145	Diameter of nose cap groove		0.40%	3.1	Gage
146	Undercut for nose cap		0.40%	3.1	Gage
Minor					
201	Cross position of outside diameter at base with major diameter of external thread		0.65%	3.1	Gage
202	Evidence of poor workmanship		0.65%	3.5	Visual
203	Depth of automation wrench hole max. (as applicable)		0.65%	3.1	Gage

09

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.50	Fuze Body and Setting Sleeve Assembly		9294595
			NEXT HIGHER ASSEMBLY 9259606

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a	Interrupter non-arming test		100%	3.2	4.5.10
Major					
101	Interrupter arming test		0.15%	3.2	4.5.9
103	Setting sleeve assembly torque test	80		3.2	4.5.5
104	Setting sleeve retaining ring stake test	80		3.2	4.5.6
105	Retaining ring stake missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.51	Screw, Closing		9258611
			NEXT HIGHER ASSEMBLY 9258606

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
131	Pitch diameter of thread		0.40%	3.1	Gage
132	Height of undercut, max.		0.40%	3.1	Gage
Minor					
201	Base thickness		0.65%	3.1	Gage
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.52	Fuze Body Assembly, Prior to Assembling S&A Module and Retainer Assembly	1 OF 1	9258606
			NEXT HIGHER ASSEMBLY: 9294769

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	S&A module not in unarmed position		100%	3.2	Gage/Visual
Special					
a	Delay plunger centrifugal pin not in unarmed position		100%	3.2	Gage/Visual
Major					
101	Delay plunger missing or inverted		100%	3.2	Gage/Visual
104	Step height between body and nose cap and completeness of crimp		0.40%	3.2	Gage/Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-402770 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.53	Fuze Body Assembly				9258606
					NEXT HIGHER ASSEMBLY 9294769
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Dimension from external flange to bottom of S&A module retainer	80	0.40%	3.2	Gage
103	Leak test			3.2	4.5.8
Major					
131	Length from tip of nose cap to flange, max.		0.40%	3.2	Gage
133	Fuze not set super quick		0.40%	3.2	Visual
Minor					
201	Lot identification nomenclature missing or inadequate		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.54	Fuze, PD, M739, Less Booster Pellet Destructive Lot Acceptance Test				9294769
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Jolt and Jumble Test, MIL-STD-331, Tests No. 101 and 102	9		3.3	4.5.1
2	Transportation Vibration Test, MIL-STD-331, Test No. 401, Procedure II	10		3.4	4.5.2
3	Premature Burst	30 (a)		3.6.1	4.5.27.2
4	Non-functioning test	10		3.6.2	4.5.27.2
Special					
a	Initiation of M99 detonator during Jolt and Jumble test	9		3.3	4.5.1
b	.11 delay plunger armed or .12 delay element initiated during Jolt and Jumble test	9		3.3	4.5.1
c	Setting sleeve assembly interrupter not fully seated after Jolt and Jumble test	9		3.3	4.5.1
Major					
101	Transportation Vibration Test, MIL-STD-331, Test 401, Procedure II	10		3.4	4.5.2/4.5.27.2
102	Functioning 60	40 (b)		3.6.3.1	4.5.27.2
103	Reverse functioning	40 (b)		3.6.3.1	4.5.27.2
104	Functioning delay	30		3.6.3.2	4.5.27.2
105	Propagation Test functioning	12		3.9	4.5.17
106	Parts damaged, broken or disassembled during Jolt & Jumble test so that fuze is unsafe to transport, handle or store.	9		3.3	4.5.1

NOTES:

(a) Premature burst information is to be taken when firing tests 4, 102 and 104.

(b) Ten (10) of these fuzes are from test 101.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONTROL INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46277B (SR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3.3	Cap, hose				9296909
					NEXT HIGHER ASSEMBLY
					9294709
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of scoring (4 places)		0.40%	3.1	Visual
Major					
102	Thickness		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48277B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.56	Fuze Body Assembly, Prior to Assembling Nose Cap				9258606
					NEXT HIGHER ASSEMBLY 9294769
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Firing pin and detonator assembly missing or inverted		100%	3.2	Gage
102	One or more crossbar(s) missing		0.40%	3.2	Gage
Major					
131	Crossbar holder assembly stake missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Jolt and jumble test

4.4.3.1.1 Beginning with the first lot produced and continuing until three consecutive lots have been found acceptable, a sample of eighteen (18) fuzes shall be selected from each lot for this test. If any fuze fails to comply with the requirements of the test, the lot shall be rejected.

4.4.3.1.2 After three consecutive lots have met the criteria specified in 4.4.3.1.1, the sample size shall be as specified in 4.4.2.54. If any fuze fails to comply with the requirements of the test, the lot shall be rejected.

4.4.3.2 Transportation vibration test

4.4.3.2.1 Beginning with the first lot produced and continuing until three consecutive lots have been found acceptable, a sample of fifteen (15) fuzes shall be selected from each lot for the test. If any fuze fails to comply with the requirements of the test, the lot shall be rejected.

4.4.3.2.2 After three consecutive lots have complied with the criteria of 4.4.3.2.1, the sample size shall be as specified in 4.4.2.54. If any assembly fails to comply with the requirements of the test, the lot shall be rejected.

4.4.3.3 Proving ground tests

4.4.3.3.1 Beginning with the first lot produced and continuing until three consecutive lots have been found acceptable, a sample size of one hundred thirty-five (135) fuzes shall be randomly selected for this test. The lot shall be rejected if the requirements of 4.5.27.1 are not met.

4.4.3.3.2 After three consecutive lots have complied with the criteria specified in 4.4.3.3.1, the sample size shall be as specified in 4.4.2.54. The lot shall be rejected if the requirements of 4.5.27.2 are not met.

4.4.3.3.3 In the event that 4.2-inch cartridges are not available for use in the above tests, the 105MM cartridge fired at Zone 1 propellant charge is considered to be an acceptable alternate test vehicle.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

4.4.3.4 Dimensional control of die cast parts.-The sample quantities for this test shall be three (3) for production runs up to fifty-thousand (50,000) pieces. When a production run exceeds 50,000 pieces the sample quantity shall be increased by one (1) for each twenty-thousand (20,000) pieces or portion thereof in excess of 50,000. The number of samples selected and the total number of pieces refer to each cavity of the die. Criteria for selection of the first and last pieces shall be as specified in 4.5.29. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be rejected.

4.4.3.5 Propagation test

4.4.3.5.1 Beginning with the first lot produced and continuing until three consecutive lots have been found acceptable, a sample of fifty (50) fuzes shall be randomly selected for use in the propagation test in accordance with 4.5.17. If two or more fuzes fail to satisfy the definition of high order functioning, the lot shall be rejected.

4.4.3.5.2 After three consecutive lots have complied with the criteria of 4.4.3.5.1, the sample size shall be as specified in 4.4.2.54. If any assembly fails to satisfy the definition of high order functioning, a second sample of thirty-eight (38) assemblies shall be tested without failure to determine acceptability of the lot. Any additional failures will be cause for lot rejection. If a failure occurs in the initial sample of twelve (12) assemblies, the sampling plan for the next lot shall revert to that of 4.4.3.5.1, regardless of the second sample results.

4.4.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 (PA) and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Jolt and jumble test.-The loaded fuze assemblies with inert boosters and booster cups shall be subjected to the jolt test as specified in MIL-STD-331, Test 101. After completion of the jolt test, the fuze shall not be disassembled, but shall be radiographically inspected in two

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

planes to determine the proper safe condition of the setback pin, rotor, interrupter and firing pin assemblies and then shall be subjected to the jumble test in accordance with MIL-STD-331, Test 102. At the conclusion of the Jumble Test the fuzes shall be X-rayed to assure safe disassembly. The fuzes shall then be disassembled to determine compliance with the requirements of the test. As a minimum inspection requirement for Critical Defects, no S&A explosive element shall be initiated nor shall any S&A be in the armed or partially armed condition. The partially armed condition of the S&A is that condition where the rotor is not locked by both spin locks and setback pin.

4.5.2 Transportation vibration test.-The loaded fuze body assemblies shall be subjected to the transportation vibration test in accordance with MIL-STD-331, Test 401, Procedure II. The sample shall then be radiographically inspected in two planes as follows to determine compliance with the safety aspects of the test:

a. Horizontal Plane - Screwdriver slot facing viewer.
b. Horizontal Plane - Screwdriver slot at left.

As a minimum inspection requirement for Critical Defects, no S&A shall be in an armed or partially armed (setback pin not locking rotor) condition. As a minimum inspection requirement for Major Defects, the x-ray shall indicate that no metal parts components are broken and that the screwdriver slot is in proper alignment.

4.5.3 Firing pin assembly pull test.-The firing pin assembly shall be assembled to an applicable test fixture and an axial pull load of 80 pounds shall be applied to the firing pin. If two or more firing pins come loose or detach from the assembly the lot shall be rejected. Assemblies subjected to this test shall not be returned to the lot.

4.5.4 Support, firing pin, load test.-The firing pin support shall be assembled to an applicable test fixture and the required load shall be applied in an axial direction at a uniform rate. The results of the test shall be recorded to determine compliance with the requirements. If one or more parts fail to meet the requirements of the 100-pound load test the lot shall be rejected. If two or more parts fail to meet the requirements of the 140-pound test the lot shall be rejected. Parts subjected to this test shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

4.5.5 Setting sleeve assembly torque test.-The torque required to rotate the setting sleeve assembly shall be applied to the screw driver slot in the setting sleeve while holding the fuze body in such a manner as to avoid damage. If two or more assemblies fail to meet the requirements of the test the lot shall be rejected. Assemblies subjected to this test may be returned to the lot.

4.5.6 Setting sleeve retaining ring stake test.-The torque shall be applied to the screwdriver slot while holding the fuze body in such a manner as to avoid damage. Starting with the sleeve set in the SQ position apply a 10-in. lb. torque in the clockwise direction and inspect visually for ring movement when the sleeve rotates to the Delay retaining ring stop. Then apply the 10-in. lb. torque in a counter-clockwise direction and inspect visually for ring movement when the sleeve rotates to the SQ retaining ring stop. If any rotation of the retaining ring is observed, in either SQ or Delay position, check the flash hole opening of the slot in the setting sleeve (SQ position only). If the opening through the slot is less than 0.120 inches diameter, when the sleeve is against the SQ stop, the assembly shall be classed defective. If two or more defectives are found, the lot shall be rejected. Assemblies subjected to this test may be returned to the lot.

4.5.7 Dimensional control of stamped parts.-As a control of the punch during production, five (5) parts from each punch shall be selected for inspection. The five parts are to be selected from the end of the day's production. As a control of each punch for production, the parts shall be inspected to the requirements listed on the applicable Classifieication of Defects and Test charts. If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool check shall be rejected.

4.5.8 Leak test.-The complete fuze body assembly, less booster pellet and booster cup, shall be submerged in water to a depth of not less than three (3) inches of water. The chamber shall be subjected to a vacuum pressure differential of five (5) psi minimum for a period of not less than 15 seconds. The water shall contain the wetting agent Niaconal

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the currentversion before use.

NR (Sodium Alkyl Aryl Sulfonate) or equivalent in concentration of approximately 1 1/2 teaspoons per gallon of water. A fuze with a continuous stream of bubbles in excess of one bubble per second shall be classified as defective. If two or more assemblies fail to meet the requirement of the test the lot shall be rejected. Assemblies successfully subjected to this test may be returned to the lot.

4.5.9 Interrupter arming test.-The unarmed assembly shall be subjected to this test by rotation approved equipment. The setting sleeve shall be rotated until it comes to rest against the SQ stop. The assemblies shall be rotated at 1700 revolutions per minute (RPM's) maximum. Any assembly which has a flash hole opening of less than 0.078 inch shall be rejected and removed from the lot.

4.5.10 Interrupter non-arming test.-The unarmed assembly shall be subjected to this test by rotation approved equipment. The setting sleeve shall be rotated until it comes to rest against the SQ stop. The assemblies shall be rotated at 1100 RPM's minimum. Any assembly which has greater than .005 inch gap between the flash hole and the interrupter shall be rejected and removed from the lot.

4.5.11 Push test of detonator in rotor assembly.-The rotor assembly shall be assembled to an applicable test fixture and the required load shall be applied to the insensitive end of the detonator in an axial direction. Any assembly in which the detonator does not remain flush or below flush under the applied load shall be classed defective.

4.5.12 Lead assembly push out test.-The safing and arming module subassembly shall be disassembled and assembled to the applicable test fixture and the required load shall be applied to the lead cup assembly from a direction opposite the green end. If two or more lead cup assemblies or displaced material do not remain flush or below flush with the bottom plate the lot shall be rejected. A dummy lead may be used for test purposes. Assemblies subjected to this test shall not be returned to the lot.

4.5.13 Arming test

4.5.13.1 Arming.-The unarmed safing and arming module subassembly shall be subjected to this test by rotation approved equipment. The safing and arming module subassembly shall be assembled to the applicable test fixture and rotated about its central axis in a counterclockwise direction when viewed from the top, at 1700 + 100 revolutions per minute (RPM). Any assembly that fails to arm shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

4.5.13.2 Arming time.-The unarmed safing and arming module subassembly while being tested as specified in 4.5.13.1 shall be tested for the arming time. The time required for each module to reach the armed position shall be determined by applicable testing equipment. The rotor shall be restrained from movement until the required rpm is achieved and the arming time count shall begin with removal of the restraint. Any unit that arms in less than 700 milliseconds or more than 1200 milliseconds shall be rejected.

4.5.13.3 Locking.-The armed safing and arming module subassembly subjected to the arming test in 4.5.13.1 shall be examined for the rotor being locked by the rotor lock pin. Any assembly that is not in the locked position after the arming test shall be rejected.

4.5.14 Non-arming test.-The unarmed safing and arming module subassembly after successful completion of the arming test shall be assembled to the applicable test fixture and subjected to this test in rotation approved equipment. The assembly shall be rotated about its central axis in a counter-clockwise direction when viewed from the top at 1100 ± 50 RPM's. Any assembly that does not remain in the full safe position when spun at 1100 ± 50 RPM's for a minimum of 1.5 seconds shall be rejected.

4.5.15 Non-arming test.-The unarmed safing and arming module assembly shall be assembled to the applicable test fixture and subjected to this test by rotation approved equipment. The assembly shall be rotated about its central axis in a counterclockwise direction when viewed from the top at 4000 RPM's minimum. Any assembly that does not remain in the safe, out-of-line position when spun at 4000 RPM's minimum for a minimum of 0.5 seconds, shall be rejected. The spinlocks may retract during this test and the rotor may move to a partially armed position provided the setback pin prevents arming. The rotor assemblies of all units that successfully pass this test must be returned to the fully safe position.

4.5.16 Push test on pallet shaft.-The lower plate and shaft assembly after staking shall be held in an appropriate test fixture and the push out force shall be applied axially to the pallet shaft from the staking side of the plate. If two or more assemblies fail to withstand the 2-pound push out force the lot shall be rejected. Assemblies subjected to this test may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the current version before use.

4.5.17 Propagation test.-Fuze body assemblies (dwg. 9258606) shall be assembled with test disk (dwg. 9294993), test plug (dwg. 9294992) and booster cup (dwg. 9258607). The S&A module assemblies (dwg. 9258630) shall have setback pin removed so that the pin is not locking the rotor. The fuze assembly shall be spun about its central axis at a spin rate not exceeding 3400 RPM to arm the fuze. The assembly shall then be dropped, nose down, while spinning, a sufficient height onto a hard surface, to initiate the explosive train. The fuze assemblies shall then be disassembled and determination made of high-order functioning, which is defined as a minimum 0.170 inch hole in the test disk. The sample of fuze assemblies shall be tested with half set super quick (SQ) and half set delay. Identify reverse functionings (see 6.5) for information only. Note: Determination of reverse functioning may be accomplished by examination of the Seal Disc (dwg. 9258632). Lot samples used for the propagation test may be selected during production prior to the application of RTV to the S&A Module and Retainer Assembly (see dwg. 9258606) so as to facilitate disassembly following the test.

4.5.19 Push test on setback pin disk.-The safing and arming module assemblies shall be disassembled and assembled to the applicable test fixture and the required load shall be applied through the setback pin to the setback pin disk. If two or more setback pin disks do not remain flush or below flush with the bottom plate under the applied load the lot shall be rejected. Assemblies subjected to this test shall not be returned to the lot.

4.5.20 Setback pin freedom of movement test.-The safing and arming module assembly shall be assembled to an applicable test fixture and the setback pin shall be depressed such that a minimum distance of .350 inches shall be obtained from the top of the upper gear plate to the top of the setback pin. After release, the setback pin must return to the locking position. The test method shall cause the setback pin, after being depressed the minimum distance, to contact the ramp surface before returning to its original position. Any setback pin that does not depress to the required height shall be rejected and removed from the lot. In addition any setback pin that does not return to the locking position shall be rejected and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.5.21 Firing pin and housing assembly load test.-The firing pin and housing assembly shall be assembled to an applicable test fixture and the required load shall be applied in an axial direction at a uniform rate. When the applied load reaches one hundred (100) pounds the maximum deflection shall not exceed .035 inches. If two or more assemblies exceed the maximum deflection of .035 inches the lot shall be rejected. Assemblies subjected to this test shall not be returned to the lot.

4.5.22 Setback pin load test.-The setback pin shall be assembled to an appropriate test fixture that allows a minimum of .060 inch protrusion of the small diameter. The fixture shall provide support on the large diameter and the chamfer. The required load shall be applied perpendicular to the longitudinal axis at a uniform rate. If two or more setback pins are deformed or fractured the lot shall be rejected. Setback pins subjected to this test shall not be returned to the lot.

4.5.23 Spinlock load test.-The spinlock shall be assembled to an appropriate test fixture that holds the spinlock by the shaft hole. The load shall be applied perpendicular to the indicated surface at a uniform rate. If two or more spinlocks are fractured or deformed the lot shall be rejected. Spinlocks subjected to this test shall not be returned to the lot.

4.5.24 Die check for cast parts.-A sample of at least three (3) parts from each cavity shall be inspected in accordance with the applicable die check classification of defects and tests paragraph to qualify a new or reworked cavity for use in the production. Individual cavity identification must be provided. If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. All cavities formerly removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test. When production from a cavity reaches 100,000 pieces since the last qualification test, a sample of three (3) parts from that cavity shall be subjected to the qualification test.

4.5.25 Die check for stamped parts.-A sample of at least five (5) parts from each punch shall be inspected in accordance with the applicable die check classification of defects and tests paragraph to qualify a new or reworked cavity for use in the production. If any defective parts are found during qualification of the tool, the tool producing the defective

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

part shall not be used in production. All tools removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test above. When production reaches 100,000 pieces since the last qualification test, a sample of five (5) parts shall be subjected to the qualification test.

4.5.26 Surface porosity.-Preliminary inspection for surface porosity shall be performed using Government approved sample display boards. If no suspect defects are found when comparing lot samples with display board samples, the lot shall be accepted without further inspection for surface porosity. Suspect defects shall be examined using appropriate magnification, e.g., toolmaker's microscope, to determine compliance with the applicable requirements. Any void which exceeds either the length or width requirement dimension shall be classed as a defect. Any sample that exceeds the applicable maximum number of surface porosity defects shall be cause for rejection of the lot. If a suspect defect is found on an inside surface, such as the inside diameter of a hole, the part shall be sectioned prior to examination under magnification, taking care to avoid cutting into the suspect area.

4.5.27 Proving ground test

4.5.27.1 First article and first three consecutive acceptable lots.-The fuzes shall be assembled to the appropriate HE loaded projectiles, except for the nonfunctioning test and tests against plywood targets where inert loaded projectiles with T2 supplementary charges shall be used, and fired from the weapons specified below. Target distances for all ground impact phases (no plywood screen) shall be any convenient distance. For all ground impact functioning, appropriate geophonic sensing devices shall be employed to verify high order functioning of the projectiles upon impact. The acceptance criteria is as follows:

DEFECT	ACCEPT	REJECT
Premature Burst	0	1
Non-functioning	0	1
Duds*	3	4
Reverse Functioning	1	2

*Two duds allowed in either SQ or Delay provided total duds does not exceed three (3).

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the currentversion before use.

WEAPON	ZONE	QUANDRANT ELEVATION	TARGET	FUZE SETTING	SAMPLE SIZE
Non-Functioning					
105MM M102	7		1" Plywood @ 115 Feet	SQ	20
Functioning					
105MM M102	7	Low	Ground	SQ	20*
105MM M102	7		1" Plywood @ 500 Feet	SQ	10
105MM M102	7		8" Plywood @ 500 Feet	D	20**
155MM M109A1	2	Low	Ground	SQ	20
155MM M109A1	2		8" Plywood @ 500 Feet	D	20
175MM M107	3	Low	Ground	SQ	10
4.2-in. Mortar	12		2" Plywood @ 500 Feet	SQ	5****
4.2-in. Mortar	12		8" Plywood @ 500 Feet	D	5****
Low Temperature ($-45^{\circ}F$)***					
105MM M102	7	Low	Ground	SQ	10
High Temperature ($+145^{\circ}F$)***					
105MM M102	7	Low	Ground	SQ	10

*Ten (10) Transportation Vibration Conditioned Fuzes.
**Five (5) Transportation Vibration Conditioned Fuzes.
***The fuzed rounds shall be placed in a temperature conditioning chamber. The fuzed rounds shall be maintained in the chamber until a steady state condition at either the high or low temperature is achieved. The rounds shall be saturated for 24 hours minimum and fired at that temperature.
****Refer to 4.4.3.3.3.

Note: Wherever the 105MM M102 weapon is required, the 105MM M108 is an equivalent alternate weapon.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

4.5.27.2 Production lots.-The testing shall be conducted as specified in 4.5.27.1. The acceptance criteria and sample sizes are as specified below.

DEFECT	ACCEPT	REJECT
Premature Burst	0	1
Non-functioning	0	1
Duds	2	3
Reverse Functioning	1	2

WEAPON	ZONE	QUANDRANT ELEVATION	TARGET	FUZE SETTING	SAMPLE SIZE
Non-Functioning					
105MM M102	7		1" Plywood @ 115 Feet	SQ	10
Functioning					
105MM M102	7	Low	Ground	SQ	10*
105MM M102	7		8" Plywood @ 500 Feet	D	10
105MM M102	7		1" Plywood @ 500 Feet	SQ	10
155MM M109A1	2	Low	Ground	SQ	15
155MM M109A1	2		8" Plywood @ 500 Feet	D	15
4.2-in. Mortar	12		2" Plywood @ 500 Feet	SQ	5**
4.2-in. Mortar	12		8" Plywood @ 500 Feet	D	5**

*Ten (10) Transportation Vibration Conditioned Fuzes.
**Refer to 4.4.3.3.3.

Note: Wherever the 105MM M102 weapon is required, the 105MM M108 is an equivalent alternate weapon.

If any production lot fails to meet the above criteria, testing shall revert to 4.5.27.1 until three consecutive lots have been accepted.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

4.5.28 Weight test.-The parts shall be weighed on a balance capable of reading grams to three decimal places. If two or more samples fail to meet the weight requirements, the lot shall be rejected. Parts subjected to this test may be returned to the lot.

4.5.29 Dimensional control of cast parts.-As a control of the cavity during production three (3) or more parts from each cavity shall be inspected during the production run. The production run is defined as that period of operation of the die from the time the die has reached proper operating temperature until the die is cooled below that temperature. Of the three (3) or more samples to be inspected, one shall be selected at the start, one at the end and the others during the production run. As a control of each cavity during production, the parts shall be inspected to the requirements listed on the applicable Classification of Defects and Tests charts.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.-Packing, packaging and marking shall be in accordance with the requirements and inspection procedures specified in MIL-P-60412 for the Fuze Body Assembly and MIL-STD-1169 for the Booster Cup. Fuze Body Assemblies for ballistic acceptance test may be packed in accordance with the requirements of MIL-P-60412 for the Fuze, PD, M739 (Level A).

6. NOTES

6.1 Intended use.-The parts and assemblies covered by this specification are intended for use on Artillery Ammunition.

6.2 Ordering data.-See MIL-A-48078 (PA).

6.3 Submission of designs for approval - See MIL-A-48078 (PA).-Submit equipment designs, as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801

6.4 Submission of first article samples.-Instructions as to the location of the evaluation of the first article samples shall be obtained from the Contracting Officer. Upon receipt of such request, the Contracting Officer shall advise ARRADCOM and instructions will be issued accordingly. All inquiries shall be forwarded to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QA-QAM, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

6.5 Reverse functioning.-Reverse functioning is defined as Delay functioning of the fuze when set in the Superquick (SQ) position.

6.6 Check test for deterioration of detonator.-If the total elapsed time between the acceptance of any detonator lot and assembly of that lot into fuze lots exceeds two (2) years, or if the detonators have been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be check-tested as specified in MIL-D-14978 and MIL-D-48025 immediately prior to detonator assembly into fuzes. This test shall be conducted at Government expense without cost to the supplier who loaded the detonator or the supplier assembling the detonator into the fuze, and shall not constitute a basis for rejection against either supplier, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., while the detonator lot is under the jurisdiction of either contractor.

6.7 Drawings.-Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
ARMY - AR

Preparing Activity:
ARMY - AR

Project Number: 1390-A191

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-48277B - Fuze Point Detonating M739 Less Booster Pellet

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAR
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.