INCH-POUND

MIL-F-48625A(AR)
11 September 1992
SUPERSEDING
MIL-F-48625(AR)
25 August 1989

MILITARY SPECIFICATION

FUZE, 25MM, POINT DETONATING, SELF DESTRUCT M758

This Specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains the requirements and quality assurance provisions for fabrication of parts, assembly and packing for the M758, Point Detonation, Self Destruct, 25mm Fuze. (See 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise document, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation. (See 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550	-Ammunition and Special Weapons, General Specification for
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

STANDARDS

MILITARY

MIL-STD-109	-Quality Assurance Terms and Definitions
MIL-STD-331	-Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-651	-Visual Inspection Standards for 20mm Ammunition and Components

(Unless otherwise indicated, copies and federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Bldg. 4 D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.6)

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

11820607	-Fuze, Inner Packing
11820608	-Fuze, Outer Packing
11820609	-Fuze, Point Detonating, Self-Destruct, 25mm, M758
12013230	-Cartridge, High Explosive Incendiary Tracer, 25mm, M792

PUBLICATIONS

CFR-100-199	-Department of Transportation Regulation 49

(Copies of other Government documents, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currentversion before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issue of documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issue of documents not listed in the DoDISS are the issues of documents cited in the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI-B46.1 -Surface Texture, Surface Roughness

(Application for copies should be addressed to: The American National Standard, 1430 Broadway, New York City, New York 10080.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications. (See 4.5.1)

3.2 Components and assemblies. The components and assemblies to be used in first article samples and production lots shall comply with all requirements specified on Drawing 11820609 and associated drawings and with all requirements specified in applicable specifications and standards. All parts and assemblies shall be manufactured by the identical process used to produce the First Article sample and no deviations from that process shall be made without contracting officer approval. (See 4.5.1)

3.3 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3 and 6.2).

3.4 Environmental.

3.4.1 Jolt. The fuzes shall be capable of withstanding a 0.50 sine wave pulse of 230 ± 30 g's for 2.0 ± 0.2 milliseconds (ms) duration at a maximum pulse rate of 40 shocks/minute when tested in accordance with MIL-STD-331, Test 101.3. Fuzes subjected to this test are not required to be operable but must remain safe to store, transport and handle (see 4.5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.4.2 Jumble. The fuzes shall be capable of withstanding rough handling when tested in accordance with MIL-STD-331, Test 102.2. Fuzes subjected to this test are not required to be operable but must remain safe to store, transport and handle (see 4.5.3).

3.4.3 Salt spray (fog). The fuzes shall be capable of withstanding a 5% salt solution exposure for 48 hours when tested in accordance with MIL-STD-331, Test 107.1. After exposure, the fuze shall be safe to handle and able to resist the effects of a moist, salt-laden atmosphere in a test chamber (see 4.5.4).

3.4.4 Transportation vibration/temperature. The fuzes shall be capable of withstanding a 5 to 500 hertz (HZ) continuous logarithmic sweep vibration with 0.50 inch peak to peak displacement at temperatures from -46° to 62° when tested in accordance with MIL-STD-331, Test 404. After conditioning, the fuzes shall be safe to handle and meet the leak detection, non-arming, target sensitivity and self destruct requirements (see 4.5.5).

3.4.5 Leak detection. The fuzes with all explosive elements present shall withstand immersion for one minute at a vacuum differential of 304.8mm of mercury when tested in accordance with a modified MIL-STD-331, Test No. 118 (Bubble Method). Fuzes, subjected to this test, shall be safe to handle and be capable of meeting the performance requirements. There shall be no evidence that any water has entered the fuze (see 4.5.6).

3.4.6 Extreme temperature. The fuze shall be capable of functioning from -46° to 62°C when tested for target sensitivity and self-destruct (see 4.5.8 and 4.5.9).

3.5 Ballistic functioning.

3.5.1 Inbore premature burst. The fuze shall not function in the bore of the weapon.

3.5.2 Close in premature burst. The fuze shall not function from the muzzle to within ten (10) meters of flight from the weapon.

3.5.3 Downrange premature burst. The fuze shall not function after 10 meters and prior to 1000 meters of uninterrupted flight.

3.5.4 Non-arming. The fuze shall not function upon impact with a target of 0.063 inch nominal thickness aluminum plate, 2024T3, at 0° angle of obliquity at a distance of ten meters or less across the temperature range from -46°C to 62°C (see 4.5.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.5.5 Target sensitivity. The fuze shall function upon impact with a target of 0.063 inch nominal thickness aluminum plate, 2024T3, at a distance of 200 ± 1 meters at 0° obliquity across the extreme temperature range from -46° to 62°C for First Article Acceptance Testing (FAAT). For the operational temperature range, the fuze shall function over the temperature range of -32°C to 52°C (see 4.5.8).

3.5.6 Self-destruct. The fuze shall function after 6.2 sec (min) and prior to ground impact or uninterrupted flight (without impact) across the extreme temperature range from -46° to 62°C for First Article Acceptance Testing (FAAT). For the operational temperature range, the fuze shall function over the temperature range of -32°C to 52°C (see 4.5.9).

3.6 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. All parts and assemblies shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any part or assembly, nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and legibly defined. Required packing shall be dry.

3.6.1 Sealant migration. Sealant shall not migrate into rotor cavity.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or, actual nor does it commit the Government to accept any defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 and MIL-A-2550 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.2.1 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in the requirements and test method paragraphs in this specification.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample consisting of:

Part Description	Drawing	Quantity
Components and Subassemblies	See 4.4.2.1 through 4.4.2.12	125 each
Fuze assemblies	11820609	604 (min)

4.3.2 Inspections to be performed. The examinations and tests listed in Table I shall be performed on the first article sample in accordance with the test methods prescribed in 4.5. Unless otherwise specified, tests shall be conducted at 20° ± 10°C.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currentversion before use.

4.3.3 Rejection. If any of the fuze components or subassemblies or assemblies fail to comply with the requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon the failure of any component, subassembly or assembly to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, 25MM, PDSD M758	1 OF 2	11820609
			NEXT HIGHER ASSEMBLY 12013230

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Examination for defects	125 100% 604 100%	3.2 3.2	4.4.2.1 to 4.4.2.11 4.4.2.13 Critical 1-2 Major 101-109 Minor 201-203
	Fuze Assembly			
	Jolt	9 Acc-0 Rej-1	3.4.1	4.5.2
	Jumble	8 Acc-0 Rej-1	3.4.2	4.5.3
	Salt fog	36 Acc-0 Rej-1	3.4.3	4.5.4
	Transportation vibration/			
	Temperature 1/		3.4.4	4.5.5 (Procedure 2)
	Leak detection	39 Acc-0 Rej-1	3.4.5	4.5.5, 4.5.6
	Ballistic Tests 2/	512		
	Non-arming 3/			
	-46° ± 3°C	44 Acc-3	3.5.4	4.5.5, 4.5.7
	21° ± 3°C	44 Rej-4		
	62° ± 3°C	44		

NOTES: 1/ The fuzes subjected to this test shall be tested subsequently as listed below. Additional units will be conditioned to replace "no test" situations.
2/ Reject is a single premature of any kind which occurs during ballistic tests.
3/ Accept and reject numbers are cumulative over all temperatures for each test parameter.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2	DRAWING NUMBER
	Fuze, 25mm, PDSD M758			11820609
				NEXT HIGHER ASSEMBLY
				12013230
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Target Sensitivity 3/		3.5.5	4.5.5, 4.5.8
	-32° ± 3°C	44		
	21° ± 3°C	44 Acc-3		
	52° ± 3°C	44 Rej-4		
	Extreme Temperature 3/		3.4.6	4.5.4, 4.5.8
	Target Sensitivity 3/			
	-46° ± 3°C	44 Acc-8		
	62° ± 3°C	44 Rej-9		
	Self-destruct 3/		3.4.6	4.5.5, 4.5.9
	-32° ± 3°C	32		
	21° ± 3°C	32 Acc-3		
	52° ± 3°C	32 Rej-4		
	Extreme Temperature Self-destruct 3/		3.4.6	4.5.8, 4.5.9
	-46° ± 3°C	32 Acc-7		
	62° ± 3°C	32 Rej-8		

NOTES: 3/ Accept and reject numbers are cumulative over all temperatures for each test parameter.

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each fuze shall contain:

a. Detonators from one manufacturer and one lot interfix number.

b. Assy, lead (dwg. 93848411) from one manufacturer and one lot interfix number.

4.4.2 Examination and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sampling inspection

	Inspection Levels					
Lot Size	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150000 to 500000	1250	500	200	125	50	13
500001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

Source: https://assist.dla.mil Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions. Unless otherwise specified or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluating (see 6.9). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currenversion before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Rotor		9378211
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Cast part weigh or density	Acc-0/Rej-1 Level III	3.2	SMTE
102.	Cast part formed completely	Acc-0/Rej-1 Level III	3.2	SMTE/Visual 1/
103.	Overall part diameter	Acc-0/Rej-1 Level III	3.2	SMTE
104.	Overall part thickness	Acc-0/Rej-1 Level III	3.2	SMTE
105.	Detonator cavity (min)	Acc-0/Rej-1 Level III	3.2	SMTE
106.	Presence of "V" shaped depression	Acc-0/Rej-1 Level III	3.6	Visual 1/
Minor				
201.	Workmanship	Acc-0/Rej-1, Level IV	3.6	Visual/Manual 1/

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Base		11820611
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Diameter of cavity	Acc-0/Rej-1 Level III	3.2	SMTE
102.	Depth of cavity	Acc-0/Rej-1 Level III	3.2	SMTE
103.	Diameter of ball groove	Acc-0/Rej-1 Level III	3.2	SMTE
104.	Location of ball groove ramp	Acc-0/Rej-1 Level III	3.2	SMTE
105.	Pitch diameter of threads	Acc-0/Rej-1 Level III	3.2	SMTE
Minor				
201.	Surface finish (internal functional surface)	Acc-0/Rej-1, Level IV	3.2	SMTE
202.	Major diameter of threads	Acc-0/Rej-1, Level IV	3.2	SMTE
203.	Threads not full	Acc-0/Rej-1, Level IV	3.2	Visual 1/
204.	Workmanship	Acc-0/Rej-1, Level IV	3.6	Visual/Manual 1/

NOTES:
1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 11820605
4.4.2.3	Probe		NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Length from shoulder to rear face	Acc-0/Rej-1 Level III	3.2	SMTE
Minor				
201.	Diameter of Datum A	Acc-0/Rej-1, Level IV	3.2	SMTE
202.	Workmanship	Acc-0/Rej-1, Level IV	3.6	Visual/Manual 1/

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 11820627
4.4.2.4	Pin, Firing (Less Lubrication)		NEXT HIGHER ASSEMBLY 11820626

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Profile of point	Acc-0/Rej-1 Level III	3.2	SMTE
Minor				
201.	Overall length	Acc-0/Rej-1 Level IV	3.2	SMTE
202.	Surface finish on shaft	Acc-0/Rej-1 Level IV	3.2	Visual 1/
203.	Workmanship	Acc-0/Rej-1 Level IV	3.6	Visual/Manual 1/

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects, as applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.5	Ogive		11820615
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Diameter of body assembly cavity	Acc-0/Rej-1 Level III	3.2	SMTE
102.	True position of body assembly cavity 1/	Acc-0/Rej-1 Level III	3.2	SMTE
103.	Diameter of piston assembly cavity	Acc-0/Rej-1 Level III	3.2	SMTE
104.	Length from base stop to body assembly stop	Acc-0/Rej-1 Level III	3.2	SMTE
105.	Location of ball groove ramp 1/	Acc-0/Rej-1 Level III	3.2	SMTE
106.	Angle of ball groove ramp 1/	Acc-0/Rej-1 Level III	3.2	SMTE
107.	Length from base stop to piston assembly to stop (min)	Acc-0/Rej-1 Level III	3.2	SMTE
108.	Lubricant missing on piston assembly cavity	Acc-0/Rej-1 Level III	3.2	Visual
109.	Location and presence of crimp groove for probe cap	Acc-0/Rej-1 Level III	3.2	SMTE/Visual 2/

NOTES:
1/ Use sample of 10/lot, c=0, when feature is machine controlled.
2/ MIL-STD-651 shall apply in defining and evaluating visual defects.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.5	Ogive (cont'd)		11820615
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201.	Burrs (at transitions of probe, piston assembly and body assembly cavities)	Acc-0/Rej-1, Level IV	3.6	Visual 1/
202.	Foreign matter (excluding lubrication)	Acc-0/Rej-1, Level IV	3.6	Visual 1/
203.	Internal chamfers or radii improper, missing or incorrect	Acc-0/Rej-1, Level IV	3.6	Visual 1/
204.	Workmanship	Acc-0/Rej-1, Level IV	3.6	Visual/Manual 1/
205.	Length of base stop to front face	Acc-0/Rej-1, Level IV	3.2	SMTE
206.	Diameter of probed cavity	Acc-0/Rej-1, Level IV	3.2	SMTE
207.	Surface finish (internal functional surfaces)	Acc-0/Rej-1, Level IV	3.2	SMTE 2/

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.
2/ ANSI-B46.1 shall apply in defining and evaluating surface texture.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Washer, Setback	1 OF 1	11820629
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201.	Inside diameter (min)	Acc-0/Rej-1, Level III	3.2	SMTE
202.	Workmanship	Acc-0/Rej-1, Level IV	3.6	Visual/Manual 1/

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Spring, Piston		11820613
			NEXT HIGHER ASSEMBLY 11820612

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Spring force (destruction load test)	50 Acc-1 Rej-2	3.2	SMTE
Minor	None defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Spring, Setback	1 OF 1	11820610
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Spring force (destruction load test)	50 Acc-1 Rej-2	3.2	SMTE
Minor	None defined			

NOTES:

AMSMC Form 1570a, 1 Jul 89

Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.9	Piston Assembly		11820614
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101.	Length of firing pin in assembly	Acc-0/Rej-1 Level III	3.2	SMTE
102.	True position of firing pin greater than 50% over tolerance	Acc-0/Rej-1 Level III	3.2	SMTE
103.	Lurication missing on firing pin (Dwg 11820627 or piston seal dwg 11820623)	Acc-0/Rej-1 Level III	3.2	Visual/Manual 1/
104.	Flow rate check	100%	3.2	SMTE 2/
105.	Firing pin pushout test (destructive test)	40 Acc-0 Rej-1	3.2	SMTE
106.	Tears, nicks, cuts or voids in piston seal	Acc-0/Rej-1 Level III	3.2/ 3.6	Visual 1/

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

2/ This check is performed 100% on a qualified and verified assembly machine, with the defects being automatically removed. If the machine fails verification (or if the assemblies are hand assembled), the assemblies are 100% bench checked with defects manually removed then submitted for inspection verification verification of bench checks.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.9	Piston Assembly		11820614
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201.	Foreign matter except lubrication	Acc-0/Rej-1 Level VI	3.6	Visual 1/
202.	True position of firing pin less than or equal to 50% over tolerance	Acc-0/Rej-1 Level III	3.2	SMTE

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 11820621
4.4.2.10	Rotor Assembly		NEXT HIGHER ASSEMBLY 11820619

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None Defined			
Major				
101.	Detonator assembly missing	Acc-0/Rej-1 Level III	3.2	Visual 1/
102.	Detonator assembly inverted	Acc-0/Rej-1 Level III	3.2	Visual 1/
103.	Rotor sear missing	Acc-0/Rej-1 Level III	3.2	Visual 1/
104.	Width of firing pin slot (min)	Acc-0/Rej-1 Level III	3.2	SMTE
105.	Detonator pushout test (destructive test)	40/lot Acc-0/Rej-1	3.2	SMTE
106.	Detonator assembly damaged	Acc-0/Rej-1 Level III	3.2	Visual
107.	Rotor sear damaged or incomplete	Acc-0/Rej-1 Level III	3.2	SMTE
Minor				
201.	Lubricant missing	Acc-0/Rej-1 Level IV	3.2	Visual 1/
202.	Workmanship	Acc-0/Rej-1 Level IV	3.6	Visual 1/

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Body Assembly	1 OF 1	11820619
			NEXT HIGHER ASSEMBLY 11820612

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1.	Rotor in armed position	100%	3.2	SMTE/X-ray
Major				
101.	Arm/non arm spin check	100%	3.2	Spin Fixture/SMTE
102.	Outside diameter of body assembly (max)	Acc-0/Rej-1 Level III	3.2	SMTE
103.	Length from rear face of lower body to piston assembly bearing surface of upper body	Acc-0/Rej-1 Level III	3.2	SMTE
104.	Lockweights assemblies missing or improperly assembled, in body assembly	100%	3.2	SMTE/X-ray
Minor				
201.	Splits or cracks (upper body)	Acc-0/Rej-1 Level IV	3.2	Visual 1/
202.	Workmanship	Acc-0/Rej-1 Level IV	3.6	Visual 1/
203.	Improper assembly or missing ball test	Acc-0/Rej-1 Level III	3.2	SMTE

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Body and Spring Assembly		11820612
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None Defined			
Major				
101.	Improper assembly or missing piston spring, support washer or retainer	Acc-0/Rej-1 Level III	3.2	Visual
Minor	None Defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Fuze, 25mm, PDSD, M758 less Lead		12912998
			NEXT HIGHER ASSEMBLY 12013230

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1.	Rotor in armed position (fuze assembly less lead	100%	3.2	SMTE/X-ray
Major				
101.	Outside diameter of fuze, max	Acc-0/Rej-1 Level III	3.2	SMTE
102.	Runout of outside diameter of fuze with Datum "A"	10 Acc-0 Rej-1	3.2	SMTE
103.	Length from rear face of ogive to rear face of base (max)	Acc-0/Rej-1 Level III	3.2	SMTE
104.	Length from probe cap to rear face of ogive (max)	Acc-0/Rej-1 Level III	3.2	SMTE
105.	Incomplete or improper assembly/fuze nose cap missing, cracked, split or dented	Acc-0/Rej-1 Level III	3.2	Visual
Minor				
201.	Workmanship	Acc-0/Rej-2 Level IV	3.6	Visual 1/
202.	Pitch diameter of threads (See dwg. 11820611)	Acc-0/Rej-2 Level IV	3.2	SMTE

NOTES:

1/ MIL-STD-651 shall apply in defining and evaluating visual defects, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 3	DRAWING NUMBER
4.4.2.14	Fuze, 25mm, PDSD, M758		11820609
			NEXT HIGHER ASSEMBLY 12013230

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None Defined			
Major				
101.	Length from probe to rear face of ogive (max)	Acc-0/Rej-1 Level III	3.2	SMTE
102.	Lead inverted or missing	Acc-0/Rej-1 Level III	3.2	Visual 1/
103.	Seal tape missing	Acc-0/Rej-1 Level III	3.2	Visual 1/
104.	Sealing compound missing from base/ogive joint	Acc-0/Rej-1 Level III	3.2	Visual 1/
105.	Torque test (destructive test)	10 Acc-0 Rej-2	3.2	SMTE 2/
106.	Pull test (destructive test)	10 Acc-0 Rej-2	3.2	SMTE 2/
107.	Missing setback spring	100% Acc-0/Rej-1	3.2	SMTE/X-ray

NOTES: 1/ MIL-STD-651 shall apply in defining and evaluating visual defects as applicable. 2/ If only 1 defect occurs, randomly select a second sample at n= 30, c= 1 (reject on 2 or more defects) and then use the same sample for pull test (106) at n= 10, C= 0 (reject on 2 or more defects). If only 1 defect occurs, randomly select a second sample at n= 30, C=1 (reject on 2 or more defects).

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-F-48625A(AR)

PARAGRAPH	TITLE	SHEET 2 OF 3	DRAWING NUMBER 11820609
4.4.2.14	Fuze, 25mm, PDSD, M758		NEXT HIGHER ASSEMBLY 12013230

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201.	Overall length	Acc-0/Rej-1 Level IV	3.2	SMTE
202.	Marking missing, incorrect or illegible	Acc-0/Rej-1 Level IV	3.2	Visual
203.	Workmanship	Acc-0/Rej-1 Level IV	3.6	Visual
	Ballistic Test			
	Transportation vibration/ temperature 1/		3.4.4	4.5.5 (Procedure II)
	Leak detection 2/	32 0-2 64 1-2	3.4.5	4.5.5, 4.5.6
	Sealent in cavity	32 0-1	3.6.1	4.5.5, 4.5.6 3/
	Ballistic Tests 4/ 5/ Non-arming -46° ± 3°C 21° ± 10°C 62° ± 3°C	39 1-4 129 3-4	3.5.4	4.5.5, 4.5.7

NOTES: 1/ The fuzes subjected to this test shall be tested subsequently as listed below. Additional units will be conditioned to replace "no test" situations.
2/ Leak detection samples shall be torn down and inspected as listed below.
3/ Waterproofness sample can be used.
4/ Accept and reject numbers are cumulative over all temperatures for each test parameter.
5/ Fuzes need not be torqued and locktited to projectiles for fuze ballistic test acceptance test.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Fuze, 25mm, PDSD M758	3 OF 3	11820609
			NEXT HIGHER ASSEMBLY 12013230

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA		REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Target Sensitivity 4/ -32° ± 3°C 21° ± 10°C 52° ± 3°C	57 114	2-5 4-5	3.5.5	4.5.5, 4.5.8
	Self-destruct 4/ -32° ± 3°C 21° ± 10°C 52° ± 3°C	39 120	2-6 5-6	3.5.6	4.5.5, 4.5.9
	Jolt	9	0-1	3.4.1	4.5.2
	Jumble	8	0-1	3.4.2	4.5.3
	Salt Fog	18	100%	3.4.3	4.5.4.2

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The tests (first article and quality conformance) shall be performed on inspection lots as defined in 4.4.1. The sampling plans for test shall conform to the provisions of 4.4.2.c.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6.3 herein.

4.5 Methods of inspection.

PRECAUTION - This specification covers sampling and testing of chemical, toxic explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, sub-assemblies and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Quality Conformance Inspection.

4.5.2 Jolt. The test and inspection shall be performed in accordance with the procedures specified in MIL-STD-331, Test 101.3, to demonstrate compliance with the requirement of 3.4.1.

4.5.3 Jumble. The test and inspection shall be performed in accordance with the procedures specified in MIL-STD-331, Test 102.2, to demonstrate compliance with the requirement of 3.4.2.

4.5.4 Salt spray (fog).

4.5.4.1 First Article:

a. Fuzes with metal stamped or ink stamped lot numbering identification: the test shall be performed in accordance with procedures specified in MIL-STD-331, Test No. 107.1. Thirty-six (36) fuzes shall be subjected to the 48 hour test. All test

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

shall be disassembled and inspected as specified in test No. 107.1 to determine compliance with the requirements of 3.4.3.

b. Fuzes with laser etched lot number identification: the test shall be performed in accordance with procedures specified in MIL-STD-331, Test No. 107.1. Eighteen (18) fuzes shall be subjected to the 48 hour test and eighteen (18) fuzes shall be subjected to a 336 hour test. All 18 fuzes subjected to the 48 hour test shall be disassembled and inspected as specified in test no 107.1 to determine compliance with the requirements of 3.4.3. All 18 fuzes subjected to the 336 hour test shall be visually inspected for the presence of red rust. The presence of red rust shall be cause for test failure.

4.5.4.2 Quality Conformance Inspection (Lazer Etched Fuzes Only).

a. A sample of eighteen fuzes from the first production lot shall be subjected to a 336 hour Salt Fog test. The Testing shall be in accordance with Test C-3 of MIL-STD-331. The presence of red rust shall constitute a test failure.

b. Every eighth consecutive production lot shall be tested in accordance with 4.5.4.2 A. The 336 hour Salt fog will be required on the initial lot following any break in production exceeding ninety calendar days.

4.5.5 Transportation vibration-temperature. The test shall be performed in accordance with Test 404, procedure 2, specified in MIL-STD-331. Fuzes subjected to the subsequent leak detection test of 4.5.6 shall be pre-conditioned by this test. Fuzes subjected to subsequent ballistic testing shall be pre-conditioned by this test prior to being tested in accordance with 4.5.7 through 4.5.9.

4.5.6 Leak detection and sealent migration. The test shall be performed in accordance with the procedures specified in MIL-STD-331, Test 118, the Bubble Method, with the following exceptions. The test items will be threaded into a suitable fixture simulating assembly to a cartridge body and then immersed to a depth of 20mm above the tip of the nose cap. A vacuum of 304.8mm Hg will be maintained in the air space over the liquid for one minute minimum and then released. The water should contain a dye penetrant so leakage will be easily detected when fuzes are disassembled. All fuzes will be disassembled to determine compliance with 3.4.5 and 3.6.1 (see 4.5.5).

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

4.5.7 Non-arming. The fuzes assembled to cartridges per section 2 to form M792 cartridges, per 12013230 (See 4.5.10), shall be stabilized for six (6) hours minimum at the required temperatures. Within two (2.0) minutes after removal from the temperature conditioning chambers the cartridges will be tested at a range of 10 meters with an angle of impact of 0° ± 5° on 0.063" 2024T3 aluminum (see 3.5.4).

4.5.8 Target sensitivity. The fuzes assembled to cartridges per section 2 to form M792 cartridges, per 12013230 (See 4.5.10), shall be stabilized for six (6) hours minimum at the required temperatures. Within two (2.0) minutes after removal form the temperature conditioning chamber the cartridges will be tested at a range of 200 ± 1 meters with an angle of impact of 0° + 10° on 0.063" 2024T3 aluminum (see 3.5.5).

4.5.9 Self-destruct. The fuzes assembled to cartridges per section 2 to form M792 cartridges, per 12013230 (See 4.5.10), shall be conditioned for six (6) hours minimum at the required temperatures. The cartridges will be tested during darkness within two (2.0) minutes after removal from the temperature conditioning chambers with the firing angle of 18° to 30°. Functioning time shall be determined for compliance with requirements (see 3.5.6).

5. PACKAGING

5.1 Packaging requirements. Packaging shall be as specified on Drawing 11820607 and Department of Transportation Regulation 49 CFR 100-199.

5.2 Packing and marking. Packing and marking shall be as specified on Drawing 11820608.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The fuzes are intended for assembly to the M792 25mm High Explosive Incendiary-Tracer Cartridge.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currentversion before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.2).

c. Requirements for submission of first article sample. (see 3.3).

d. Requirements for quality conformance inspection sampling plan. (see 4.4.)

6.3 Submission of inspection equipment designs for approval. Submit equipment designs as required to Commander, ARDEC ATTN: SMCAR-QAF-I(D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements Lists, DD Form 1423 in the contract.

6.4 Submission of results of contractor conducted examinations and tests. Unless otherwise specified by the contracting officer, the contractor should forward requested records of examinations or tests to Commander, ARDEC ATTN: SMCAR-QAF-I(D), Picatinny Arsenal, NJ 07806-5000.

6.5 Process deviation. A process deviation is defined as a change in the approved basic method of manufacture, or an operational change which alters the metallurgical or physical properties of the item.

6.6 Drawings. Drawings listed in section 2 of this specification under the heading U.S. Army Armament Research Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, U.S. Army Armament Research and Development Center (ARDC), U.S. Army Armament Research and Development Command (ARRADCOM). Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.7 Deterioration of explosive components.

6.7.1 Check test for deterioration of detonators. If the total time between original manufacture of any lot and the scheduled fuze lot acceptance test exceeds two years, or if the

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currentversion before use.

detonators have been subjected to adverse conditions at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass the functional tests specified on the drawing prior to assembly into the fuze. The sampling plan for these tests shall be in accordance with Table II, Inspection Level III. This test shall be performed by the contractor on detonators selected by the inspection department at the facility assembling the detonator into the fuze.

6.7.2 Check test for deterioration of leads. If the total time between original manufacture of any lot and the scheduled fuze lot fuze acceptance test exceeds two years, or if the leads have been subjected to adverse conditions at any time since previous tests, the lead lot shall be subjected to and must satisfactorily pass the functional test specified on the applicable drawing prior to assembly into the fuze. The sampling plan for these tests shall be in accordance with Table II, Inspection Level III. This test shall be performed by the contractor on leads selected by the inspection department at the facility assembling the lead into the fuze.

6.8 Subject term (key word) listing.

Rotor
Base
Probe
Ogive
Washer, Setback
Spring, Piston
Piston Assembly

6.9 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality evaluation by the technical activity responsible for the preparation of this specification.

6.10 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A776)

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-F-48625	11 SEPTEMBER 1992

3. DOCUMENT TITLE

FUZE, 25MM, POINT DETONATING, SELF DESTRUCT, M758

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U. S. Army ARDEC Specifications And Standardization Office/Bldg. 6	(1) Commercial (201) 724-6675	(2) AUTOVON 880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S Picatinny Arsenal, N. J. 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the current version before use.