INCH-POUND

MIL-M-48183B (AR)
24 September 1992
SUPERSEDING
MIL-M-48183A (AR)
4 November 1977

MILITARY SPECIFICATION

MUNITION FOR PROJECTILE, 155MM, M692/M731, DELAY DETONATOR FOR

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the fabrication of parts, loading, assembling and packing for one type of Delay Detonator for the munition used in Projectiles, 155MM, M692/M731. (See 6.1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification, standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation. (See 6.2)

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-286- Propellants, Solid: Sampling, Examination and Testing
MIL-STD-650- Explosive: Sampling, Inspection and Testing

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094).

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those in cited in the solicitation.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9298409- Cord, Detonating
9298429- Delay Detonator
9298433- Propellant Nut Assembly
9298699- Functioning Test Configuration for Delay Detonator
9321509- Packing and Marking for Box, Inner
9321511- Packing and Marking for Box, Outer
9321513- Packing and Marking for Box, Packing

PUBLICATIONS

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 100-199

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with the applicable drawings and specifications.

3.2 Delay detonator. The delay detonator shall comply with all requirements specified on dwg. 9298429, all associated drawings, and with all requirements specified in applicable specification.

3.3 Temperature conditioning and function. The Delay Detonator when temperature conditioned at -25 ± 5°F, 70° ± 5°F or 125 ± 5°F shall function within the delay time specified on 9298429.

3.4 First article inspection. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.5 Workmanship.

3.5.1 Workmanship - stem. The stem shall be free of dirt, grease, chips, gouges, cracks and any other defects which would make the item unsuitable for the intended use. Any cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated.

3.5.2 Workmanship - delay detonator. The delay detonator shall be loaded in a thorough, workmanlike manner and shall be free of chips, dirt, grease, and other foreign matter that may impair proper functioning.

4 QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the currentversion before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspections, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item:

a. First Article Inspection. (See 4.3)

b. Quality Conformance Inspection. (See 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Stem (See note)	9298430	25
Delay Detonator	9298429	125

NOTE: If stem (9298430) is Government Furnished Material (GFM) it shall not be submitted for First Article Inspection.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in this detail specification and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.3 Rejection. See MIL-A-48078. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of any assembly, component or test specimen to comply with any of the requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Delay Detonator and Stem		SHEET 1 OF 1		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Stem (Dwg. 9298430) Examination for Defects	25		3.2	4.4.2.1, See Note 1
	Delay Composition (Dwg. 9298432) Heat of Reaction	-		3.2	4.5.2 and Dwg.9298432 See Note 2
	Delay Detonator (Dwg. 9298429) Examination for Defects	125		3.2	4.4.2.3
	Functioning and Delay Time	125		3.2	4.5.3 and Dwg. 9298699
	a. 70 ± 5°F	25			
	b. -25 ± 5°F	50			
	c. +125 ± 5°F	50			

NOTES: 1. This examination not applicable if stems are Government Furnished Material (GFM).
2. Certification and test data shall be furnished for the heat of reaction determination for Delay Composition used in the delay Detonator.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Delay Detonators Assemblies shall contain:

a. Stems of one lot interfix number from one manufacturer.

b. Lead azide from one batch or blending of batches which results in homogeneity of all lead azide used in loading the entire detonator lot.

c. RDX from one batch or blending of batches which results in homogeneity of all RDX in loading the entire detonator lot.

d. Delay composition from one batch or blending of batches which results in homogeneity of all delay compositions used in loading the entire detonator lot.

4.4.2 Examination and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

TABLE II Atttributes sampling inspection

Lot Size	Inspection Level					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13

Numbers under inspection levels indicate sample size; asterisks indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.3). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Stem	1 OF 2	9298430
			NEXT HIGHER ASSEMBLY 9298429

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Overall length	Level II	3.2	Gage Note 1
102	Largest diameter (Flange)	Level II	3.2	Gage
103	Diameter of cavity	Level II	3.2	Gage
104	Length of flange	Level II	3.2	Gage
105	Length from face at open end to bottom of cavity	Level II	3.2	Gage
106	Angle at base of cavity	Level II	3.2	Gage
107	Finish in cavity for specified depth	Level II	3.2	Gage
108	Chamfer at intersection of flange and face at open end	Level II	3.2	Gage Note 1
109	Chamfer at intersection of cavity and face at open end	Level II	3.2	Gage Note 1
Minor				
201	Small diameter, solid end	Level IV	3.2	Gage
202	Diameter of relief area (2 places)	Level IV	3.2	Gage
203	True position of relief diameter with shank diameter	Level IV	3.2	Gage

NOTES:
1. If stems are modified from stems per 9207799, which were accepted per MIL-D-50575, only these characteristics need be inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Stem	2 OF 2	9298430
			NEXT HIGHER ASSEMBLY 9298429

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
204	True position of small diameter at solid end with shank diameter	Level IV	3.2	Gage
205	Length of flat between second shoulder and beginning of taper between first and second shoulders at solid end	Level IV	3.2	Gage
206	Length from face at open end to middle shoulder	Level IV	3.2	Gage
207	Length from face at open end to beginning of taper on shank	Level IV	3.2	Gage
208	Length from face at solid end to nearest shoulder	Level IV	3.2	Visual
209	Any angle missing	Level IV	3.2	Gage
210	Diameter of shank	Level IV	3.2	Gage
211	Largest diameter at solid end (2 places)	Level IV	3.2	Gage
212	True position of flange diameter with shank diameter	Level IV	3.2	Gage
213	True position of cavity diameter with shank diameter	Level IV	3.2	Gage
214	True position of largest diameter at solid end with shank diameter	Level IV	3.2	Gage Note 1
215	Protective finish missing	Level IV	3.2	Visual Note 1
216	Poor workmanship	Level IV	3.2	Visual Note 1

NOTES: 1. If stems are modified from stems per 9207799, which were accepted per MIL-D-50575, only these characteristics need be inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Delay detonator (prior to loading base charge)	1 of 1	9298429
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Weight of base charge	Level II	3.2	Balance
102	Heat of reaction of delay composition		3.2	4.5.2
103	Volatiles content of explosive and pyrotechnic components		3.2	4.5.1
Minor				
201	Poor workmanship	Level IV	3.5.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Delay Detonator	1 OF 1	9298429
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of shank, max.	Level II	3.2	Gage
102	Diameter of flange, max.	Level II	3.2	Gage
103	Depth to top of charge	Level II	3.2	Gage
104	Charge cracked or chipped	Level II	3.2	Visual
105	Chamfer on flange missing	Level II	3.2	Visual
106	Chamfer on cavity missing	Level II	3.2	Visual
107	Functioning and Delay Time		3.3	4.5.3, 9298699
	a. 70 ± 5°F	25		
	b. -25 ± 5°F	50		
	c. +125 ± 5°F	50		
Minor				
201	Poor workmanship	Level IV	3.5.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Packing and Marking for Box, Inner	1 OF 1	9321509
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Incorrect number of delay detonators	Level II	3.2	Visual
102	Delay detonator inverted	Level II	3.2	Visual
103	Spacer missing	Level II	3.2	Visual
104	Red and black marks on cover missing	Level II	3.2	Visual
Minor				
201	Filler or cushion missing	Level IV	3.2	Visual
202	Marking incorrect or unidentifiable	Level IV	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Packing and Marking for box outer, prior to sealing bag	1 OF 1	9321511
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Incorrect number of inner boxes	Level II	3.2	Visual
102	Inner boxes facing wrong way	Level II	3.2	Visual
103	Fillers missing	Level II	3.2	Visual
104	Corners not blunted	Level II	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Packing and Marking for box, outer	1 OF 1	9321511
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Heat seal of barrier bag missing or incomplete	Level II	3.2	Visual
102	Barrier bag torn or punctured	Level II	3.2	Visual
Minor				
201	Marking incorrect or unidentifiable	Level IV	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Packing and Marking for box, packing prior to sealing	1 OF 1	9321513
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Incorrect number of bagged outer boxes	Level II	3.2	Visual
Minor 201	Fillers missing	Level IV	3.2	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:55Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Box, Packing, (Sealed)	1 OF 1	9321513
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Box damaged exposing contents	Level II	3.2	Visual
102	Strapping missing, broken or loose	Level II	3.2	Visual
103	Hardware missing, broken or loose	Level II	3.2	Visual
Minor				
201	Contents loose	Level IV	3.2	Visual/Manual
202	Marking incorrect or unidentifiable	Level IV	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Volatiles content of pyrotechnic and explosive components. The contractor shall provide adequate controls to insure compliance with the applicable requirement. The volatiles content of the pyrotechnic and explosive components shall be determined at the loading station at the time of loading the detonator. This determination shall be made at least once for each eight (8) hours of production. A sample of approximately 10 grams shall be selected for this test. The samples shall be stored in air-tight containers until this test is performed. If the volatiles content fails to comply with the requirement specified on the applicable drawing and loading has not begun, the lot shall be rejected until corrective action has been verified by repeating the volatiles content determination. If loading has begun, detonators loaded with the non-conforming components shall be rejected. This test shall be performed as specified in MIL-STD-650, Method 101.5 or 101.6.

4.5.2 Heat of reaction of delay composition. Prior to loading, a sample of delay composition shall be selected from the lot to be used in loading the delay detonators and shall be subjected to this test. If the heat or reaction (calories/grams) fails to comply with the requirements specified on the applicable drawing, the delay composition lot shall be rejected for use in loading delay detonators. If loading has begun, delay detonators loaded with the nonconforming delay composition shall be rejected. The test shall be performed as specified in MIL-STD-286 Method 802.1 (Heat of Explosion).

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T03:55Z
Check the source to verify that this is the currentversion before use.

4.5.3 Functioning and delay time of delay detonator. This test shall be conducted using the configuration specified on 9298699. The propellant nut assemblies (Dwg. 9298433) and detonating cord (Dwg. 9298409) used for this test shall be from accepted lots. Place the delay detonator into the detonator tube and assemble the propellant nut assembly. Care shall be taken to assure the spring grip fastener in the detonator tube holds the delay detonator against the orifice plate of the nut. Affix the detonating cord firmly in the slot of the nut. Align the detonator tube in the fixture so that one of the output holes is directed at the photocell opening.

Prior to testing, those units to be tested at cold temperature shall be conditioned for 2 hours minimum at $-25^{o} \pm 5^{o}F$ while those tested at hot temperature shall be conditioned for 2 hours minimum at $+125^{o} \pm 5^{o}F$ and those units to be tested at $70^{o} \pm 5^{o}F$ shall be conditioned for 2 hours minimum. The detonator tube, propellant nut and delay detonator shall be conditioned as a unit.

The lot of delay detonators shall be rejected if any one of the following occur:

1. If the combined total of three (3) or more detonators (a) fail to fire and/or (b) fire in the out-of-line position.

2. If eight (8) or more detonators fire prior to or later than the specified delay time.

Records shall be maintained of the actual delay time for each delay detonator tested. The test shall be conducted using approved barricades.

4.5.4 Dimensional control of stem characteristics. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool for use in production. In addition, a random sample of ten (10) parts shall be selected from the last portion of each four (4) hours of production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:55Z
Check the source to verify that this is the current version before use.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

5. PACKAGING

5.1 Preservation and packaging (Level C). The delay detonator assemblies shall be preserved and packaged in accordance with dwg. 9321509 and 9321511.

5.2 Packing (Level C). The delay detonator assemblies, preserved and packaged as specified in 5.1, shall be packed in accordance with dwg. 9321513.

5.3 Marking. Marking shall be in accordance with the drawings and the Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Shipping. When components from more than one lot are shipped at one time, such as in a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory)

6.1 Intended use. The delay detonator covered by this specification is intended for use in the munition for the Projectiles, 155MM, M692/M731.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced in section 2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

6.3 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation to the procuring contracting officer.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as, US Army Armament Research and Development Command, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: SMCAR-QAT-I (D), Picatinny Arsenal, New Jersey 07806-5000. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.6 Subject term (keyword) listing.

Propellants
Stem
RDX
Shank

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian
Army-AR

Preparing activity:
Army-AR

(Project 1375-A206)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revisio letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization t waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGES	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-M-48183B	920724

3. DOCUMENT TITLE: MUNITION FOR PROJECTILE, 155MM, M692/M731, DELAY DETONATOR FOR

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

[redacted]

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)
U.S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial: 201-724-6675 (2) AUTOVON: DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.*

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:55Z
Check the source to verify that this is the current version before use.