MIL-P-48250 (PA)
15 March 1974
(see 6.6)

MILITARY SPECIFICATION

PRIMER, STAB, M55
PARTS AND LOADING, ASSEMBLING, AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts and the loading, assembling and packing for one type of initiating device designated as Primer, Stab, M55. (This primer is used solely for testing flash detonators).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Packaging, Method of
MIL-A-2550 - Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-650 - Explosives: Sampling, Inspection, and Testing
MIL-STD-1168 - Lot Numbering of Ammunition

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGING DRAWINGS

9218452 - Primer, Stab, M55
9258182 - Box, Set-up, Packing, Ammunition, Inner for Small Explosive components.
9258183 - Box, Set-up, Packing, Ammunition, Outer, for Small Explosive Components
9258184 - Box, Packing, Ammunition, for Small Explosive Components

INSPECTION EQUIPMENT DRAWINGS
8816367 - Holder, firing pin
8827828 - Sleeve
8827829 - Bushing
8827934 - Adapter, ball, steel
8855295 - Disc, lead, coined
9200012 - Pin, firing
9201952 - Assembling, firing

(Copies of specifications, standards and drawings, required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Parts.-The parts shall be in accordance with the applicable drawings and specifications.

3.2 Assembly.-The primer assembly shall comply with all requirements specified on Drawing (dwg.) 9218452 and with all requirements specified in applicable specifications.

3.3 Moisture content

3.3.1 Primer Mixture.-At the time of loading, the moisture content of the primer mixture used in loading the primers shall not exceed 0.30 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

3.3.2 Lead Azide.-At the time of loading, the moisture content of the lead azide used in loading the primers shall not exceed 0.50 percent.

3.4 Functioning

3.4.1 Output.-The primer shall function, on the first attempt, under an applied energy of 11.85 inch ounces, and shall cause perforation of the coined lead disc to a diameter of 1/4 inch minimum.

3.4.2 Waterproofness.-The primer shall be waterproof as evidenced by normal functioning, after being immersed in water maintained at 75 degrees Fahrenheit (°F) plus or minus 5°F, at a depth of 2 inches minimum for not less than 48 hours.

3.5 Workmanship.-All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing components shall be dry.

3.6 First Article Inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-Prior to the start of regular production the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2, and 4.2.3. The first article sample shall consist of three hundred forty (340) loaded primers and 50 complete sets of parts (i.e., 50 each of every component) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the same to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Components will be subjected by the Government to any or all of the examinations and tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any component fails to comply with the applicable requirements, the first article sample shall be rejected. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article sample or portion thereof. Until a first article sample is accepted, the contractor is, in no way, authorized by the Government to initiate regular production unless otherwise directed by the contracting officer.

4.2.4 Loaded Primers. - A sample of three hundred forty (340) loaded primers shall be submitted in accordance with 4.2.1 and tested as specified in 4.3.3.3.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units for product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantitiy of units from which the sample was drawn and shall not be construed to represent any prior to subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded primer assemblies shall contain:

a. Parts of one lot interfix number from one supplier.

b. Primer mixture from one batch or blending of batches, which results in homogeneity of all primer mixture used in the loading of a lot.

c. Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraphs of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Disc (see dwg. 9218454 covering a detail of dwg. 9218452).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Diameter	Gage	01001
102.	Thickness	Gage	01002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	01003

4.3.2.2 Cup, prior to coating (see dwg. 9218453 covering a detail of dwg. 9218452).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Outside diameter	Gage	02001
102.	Wall thickness	Gage	02002
103.	Length	Gage	02003
104.	Thickness through bottom	Gage	02004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	02005

4.3.2.3 Cup, after coating (see dwg. 9218452).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Coating missing or contains bare spot	Visual	03001
Major:	None defined		
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	03002

4.3.2.4 Assembly (see dwg. 9218452).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Cup cracked or split	Visual	04001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

Major:	AQL 1.00 percent		
101.	Length	Gage	04002
102.	Diameter, maximum (max.)	Gage	04003
103.	Crimp not full 360 degrees	Visual	04004
104.	Disc punctured or torn	Visual	04005
105.	Cup damaged	Visual	04006
106.	End color identification missing or incorrect	Visual	04007
107.	Disc seal missing or incomplete	Visual	04008
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	04009

4.3.2.5 Box, Set-Up, Inner, after loading and prior to closing slide cover (see dwg.9258182).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Filler and cushion assembly missing	Visual	05001
2.	Filler and cushion assembly improperly assembled	Visual	05002
3.	Stiffener missing	Visual	05003
4.	Slide cover assembled reversed	Visual	05004
Major:	AQL 0.40 percent		
101.	Release paper missing	Visual	05005
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	05006
202.	Evidence of poor workmanship (see 3.5)	Visual	05007

4.3.2.6 Box, Set-Up, Outer, with Inner set-up boxes assembled and prior to assembling top and sealing strip (see dwg. 9258183).

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

Critical:			
1.	Red surfaces on inner set-up boxes do not alternate on same side of outer set-up box.....	Visual	06001
2.	Stiffner not facing one direction.....	Visual	06002
Major: None defined			
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible.....	Visual	06003
202.	Evidence of poor workmanship (see 3.5).....	Visual	06004

4.3.2.7 Box, Packing, Ammunition, prior to assembling cover and strapping (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.65 percent		
101.	Bags containing set-up boxes damaged.....	Visual	07001
102.	Cushioning material incomplete or missing from around outer set-up boxes.....	Visual	07002
103.	Marking missing, misleading or unidentifiable.....	Visual	07003
104.	Barrier bag seal incomplete or improperly positioned.....	Visual	07004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5).....	Visual	07005

4.3.2.8 Box, Packing, Ammunition (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Major:	AQL 0.65 percent		
101.	Strapping missing, broken, or improperly fastened.....	Visual-Manual	08001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

102.	Box damaged	Visual	08002
103.	Marking missing, broken or illegible	Visual	08003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	08004

*4.3.3 Testing

4.3.3.1 Moisture content of lead azide (see 3.3) - Major defect - Code No. 04010. - The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample in sufficient quantity to perform the test detailed in 4.4.1 shall be selected and tested as specified in 4.4.1. If the moisture content is in excess of the percentage specified and loading has not begun the lot of lead azide shall be rejected. If loading has begun, action on the unloaded lead azide shall be as specified above and all primers loaded with the questionable lead azide shall be rejected.

4.3.3.2 Primer Mixture

4.3.3.2.1 Moisture content of primer mixture (see 3.4) - Major defect - Code No. 04012. - The moisture content of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.4.1, shall be selected and tested as specified in 4.4.1. If the moisture content is in excess of the percentage specified and loading has not begun, the batch or blend of batches of primer mixture shall be rejected. If loading has begun, action on the unloaded primer mixture shall be as specified above and all detonators loaded with the questionable primer mixture shall be rejected.

4.3.3.2.2 Composition (see dwg. 8865554). - Major Defect - Code No. 05012. - The composition of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.4.3, shall be selected and tested as specified in 4.4.3. If the composition of the primer mixture fails to conform to the requirements specified on the applicable drawing and if loading has not begun, the batch or blend of batches of primer mixture shall be rejected. If loading has begun, action on the unloaded primer mixture shall be as specified above and all detonators loaded with the questionable primer mixture shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.3.3.3 Functioning

4.3.3.3.1 Output (see 3.4.1) - Major defect - Code No. 04013. - The sample size, acceptance or rejection of the lot shall be in accordance with Table I. The test shall be performed as specified in 4.4.2.1 using test equipment in accordance with 4.3.4 and 4.4.2.1. If more than one loading machine is used in the production of the inspection lot, the sample shall be selected so as to represent proportional quantities of production from each machine.

TABLE I

Lot Size	Sample	Accept	Reject
to 150,000	First 315	0	3
	Second 315	3	4
150,001 to 300,000	First 500	1	4
	Second 500	4	5
300,001 to 500,000	First 800	2	5
	Second 800	6	7
500,001 and over	First 1250	3	7
	Second 1250	8	9

4.3.3.3.3.2 Waterproofness (see 3.5.2) Major defect - Code No. 04014. - A sample of 25 primers shall be selected at random from each lot. If one or more primers fail to comply with the requirement specified the lot shall be rejected. The test shall be performed as specified in 4.4.2.2 using test equipment as specified in 4.3.4 and 4.4.2.1.

4.3.3.4 Determination of composition of primer mixture (see dwg. 9218452) - Major Defect - Code No. 09001. - A sample of approximately one gram shall be selected from each batch or blend of batches for test as specified in 4.4.3. All the composition represented by the sample shall be rejected if the sample fails to comply with the requirements.

4.3.3.5 Heat seal test of sealed bag (see dwg. 9258183) - Major defect - Code No. 06005.-Sampling, acceptance criteria and test procedures for this test shall be as specified in Specification MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

4.3.4 Inspection Equipment.-Inspection equipment required to perform the inspections prescribed in this specification is identiified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection design and approval.

4.4 Test methods and procedures

4.4.1 Moisture content of lead azide and primer mixture. - The moisture content of the lead azide and primer mixture shall be determined in accordance with Standard MIL-STD-650, Method 101.6 except that a two (2) gram sample shall be used.

4.4.2 Functioning

4.4.2.1 Output. - The primer shall be assembled in the applicable test fixture. A steel ball approximately 1 and 3/16 inches in daimeter weighing 3.95 ounces max., shall be dropped from a height of three (3) inches max., to the firing pin used to function the primer. the length of drop is measured as the distance between the bottom of the ball and the top of the firing pin. A primer that fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective. The method of inspection shall be in accordance with dwgs. 8816367, 8827828, 8827829, 8827934, 8855295, 9200012, and 9201952.

4.4.2.2 Waterproofness.-The primers shall be immersed under water to the required depth for the specified time. The primer shall be subjected to the functioning test specified in 4.4.2.1 within one (1) hour after removal. Any primer which fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective.

4.4.3 Determination of composition of primer mixture

4.4.3.1 Potassium chlorate

4.4.3.1.1 Preparation of solutions

4.4.3.1.1.1 Solution Number 1.-To approximately 800 ml. distilled water, in a one liter amber glass bottle, 400 grams (gm.) of potassium thiocyanate shall be added. The bottle shall be sealed with a rubber stopper and the reagent bottle

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

and contents shaken until the solid material is dissolved. To this solution 1.0 gm. of lead thiocyanate, 1.0 gm. of antimony sulfide and 1.0 gm. of lead azide shall be added. The bottle shall again be stoppered and the reagent bottle and contents vigorously shaken for several minutes, and then allowed to stand overnight. Portions of the saturated solution shall be filtered before using.

4.4.3.1.1.2 Solution Number 2.-To approximately 400 ml. of distilled water, in a one-half liter amber glass reagent and 1.0 gm. of lead thiocyanate, 1.0 gm. of antimony sulfide and 1.0 gm. of lead azide shall be added. The bottle shall be sealed with a rubber stopper and the reagent bottle and contents vigorously shaken for several minutes and then allowed to stand overnight. Portions of the saturated solution shall be filtered before using.

4.4.3.1.2 Procedure.-A portion of approximately 1.0 gm. of the sample shall be accurately weighed directly into a tared 30 ml. sintered glass crucible of medium porosity. From a burette 3.0 ml. of Solution Number 1 shall be added to the crucible. The solution shall be swirled for exactly one minute, taking care not to spill any liquid; aspirated with suction and the bottom of the crucible wiped dry using tissue paper. The washing shall be continued, using one more 3.0 ml. portion, two 2.0 ml. and two 1.0 ml. portions, making a total of 12.0 ml. The crucible shall be removed and the bottom of the crucible, the funnel, the adapter and the suction flask washed with water. The test tube shall be placed in the flask and the stem of the filtering funnel inserted into the test tube. The crucible and contents shall be washed with one 1.0 ml. portion of Solution Number 1 as above, and aspirated with suction, catching the filtrate in the test tube. The test tube shall be removed, 1.0 ml. of distilled water added and the chlorate ion, determined as follows:

The tube shall be inclined at an angle of about 45 degrees and from a dropper about 0.5 ml. of a solution containing 1.0 gm. of diphenylamine in 100 gm. of concentrated sulfuric acid two distinct layers. If an appreciable amount of chlorate ion is present, a distinct blue ring will be visible at the border of the two layers. On shaking the tube, the ring disappears, but the contents assume a blue coloration, which lasts several seconds, depending on the amount of chlorate ion present. If only a trace of chlorate ion is present the blue ring may not

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

form, but upon shaking the test tube, a slight bluish coloration will appear momentarily throughout the solution, lasting only a fraction of a second. If a definite blue ring forms, the washing shall be repeated as before using one 1.0 ml. portion of Solution Number 1, and finally a 0.5 ml. portion of the same solution, as needed, depending on the outcome of the tests for the chlorate ion. (Usually a total of 14.0 or 14.5 ml. of Solution Number 1 is sufficient). After complete removal of potassium chlorate the inside of the crucible shall be washed with 1.0 ml of Solution Number 2 and aspirated immediately. The bottom of the crucible shall be wiped dry with tissue paper and dried in an oven at 80 degrees C. plus or minus 1 degree C. for 30 minutes, cooled in a desiccator and weighed. The percentage of potassium chlorate shall be calculated as follows:

Potassium Chlorate, percent = 100B divided by W (1-M)

where:
B = loss in weight of contents of crucible, grams.
W = weight of sample, grams.
M = percent moisture divided by 100

4.4.3.2 Antimony sulfide.

4.4.3.2.1 Preparation of solution of Ferric ammonium sulfate.-To approximately 120 ml. of distilled water, in a one-half liter reagent bottle, 125 gm. of ferric ammonium sulfate shall be added. The bottle shall be stoppered and shaken vigorously for several minutes and then allowed to stand overnight. Portions of the saturated solution shall be filtered before using.

4.4.3.2.2 Procedure.-A portion of approximately 1 gm. of the sample shall be accurately weighed directly into a tared 30 ml. sintered glass crucible of medium porosity. Five ml. of one percent nitric acid shall be added and the crucible constantly swirled for one minute in order to dissolve all the ingredients of the powder except antimony sulfide. Care shall be taken not to spill any liquid. The mixture shall be filtered by applying suction employing a vacuum flask. The crucibel shall be removed from the adapter and the bottom wiped dry with tissue paper. The operations of washing, using 5.0 ml. of one percent nitric acid each time and swirling for exactly one minute shall be repeated. After a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

total of 40 ml. of one percent nitric acid has been used, the crucible shall be removed and the bottom of it washed with water. The funnel, the funnel adapter and the vacuum flask shall be washed with water; the filtrate and washings shall be discarded. About 1 ml. of saturated solution of ferric ammonium sulfate shall be placed in the flask. The contents of the crucible shall be treated as before with 5.0 ml. of one percent nitric acid and filtered by means og suction into the flask. If the liquid in the flask turns red, due to th presence of the thiocyanate ion in the filtrate, the washing of the contents in the crucible shall be repeated with additional 5.0 ml. portions of one percent nitric acid until a negative test for the sulfocyanate ion is affected. (Usually a total of 50 ml. is sufficient). The crucible and contents shall be dried in an oven at 80 degrees C. plus or minus 1 degree C. for 30 minutes, cooled in a desiccator and weighed. The percentage of antimony sulfide shall be calculated as follows:

Antimony sulfide, percent = 100A divided by B

where:
A = weight of residue in the crucible
B = weight of sample on a moisture-free basis

4.4.3.3 Lead azide.-The lead azide content shall be determined using the (Eudiometer) method and apparatus in Standard MIL-STD-650 Method No. 407.1.

4.4.3.4 Lead thiocyanate.-The percentage of lead thiocyanate in the sample shall be calculated on a moisture-free basis by subtracting from 100 the sum of the percentages of potassium chlorate, antimony sulfide and lead azide.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level C.-Packaging shall be as specified on dwgs. 9258182 and 9258183.

5.2 Packing

5.2.1 Level C.-Packing shall be as specified on dwg. 9258184.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

5.3 Marking.-Marking of all packaging and packing shall comply with dwgs. 9258182, 9258183 and 9258184.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Submission of test data and ammunition data cards.-In addition to the normal distribution of records, for loaded items procured by the Department of the Army, one copy of all functioning test data and ammunition data cards shall be forwarded to the following:

Commander
Picatinny Arsenal
Dover, New Jersey 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

Attn: SARPA-QA-A-M
SARPA-AD-E-P-2

6.5 Check test for possible deterioration.-The following test is designed to prevent primers that have deteriorated being assembled into major ammunition items. The test shall be performed on primers from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the primers are assembled does not require that the check test be performed, the contracting officer should insert in the contract a provision for the performance of the check test. The contracting officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration.

6.5.1 Functioning. - A sample of 315 detonators shall be selected at random from each lot. If 4 or more detonators fail to comply with the requirement specified, the lot shall be rejected. If more than one defective is found, a second sample of 315 shall be selected at random and tested. If in the combined first and second sample a totoal of 5 or more defectives are found the lot shall be rejected. The test shall be performed as specified in 4.4.2.1 using test equipment as specified in 4.3.4 and 4.4.2.1.

6.6 Supersession data.-This specification includes the requirements of PA-PD 2962 dated 8 May 1967, with Amend 1 dtd 5-1-73.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1375-A-055

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:55Z
Check the source to verify that this is the current version before use.