MILITARY SPECIFICATION

SLEEVE AND GRAIN ASSEMBLY

This specification is approved for use by NAVSEASYSCOM, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of Sleeve and Grain Assembly referred to herein as the grain assembly.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-48569	Catapult, Aircraft ejection seat, CKU-7/A, metal parts assembly

STANDARDS

FEDERAL

FED-STD-313	Material Safety Data Sheets, Preparation and the Submission of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Division (611), Indian Head, MD 20640, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

3.2 Operating temperature. The base detonator shall meet 3.0

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-453	Inspection, Radiographic
MIL-STD-810	Environmental Test Methods

DRAWINGS

NAVAL ORDNANCE STATION, INDIAN HEAD, MD (Code Ident 14083)

D11820365	Sleeve and Grain Assembly
D9297892	Box, Fiberboard (Inner) Packing Ammunition for Sleeve and Grain Assembly for Catapult, CKU-7/A
D9297893	Box, Packing Ammunition for Sleeve and Grain Assembly for Catapult, CKU-7/A
D9297894	Box, Fiberboard (Outer) Alternative Packing, Ammunition for Sleeve and Grain Assembly for Catapult, CKU-7/A

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Chemical Propulsion Information Agency

Publication No. 21	JANNAF Solid Propellant Mechanical Behavior Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Chemical Propulsion Information Agency, Applied Physics Laboratory, Johns Hopkins University, 8621 Georgia Avenue, Silver Spring, MD 20910.)

Code of Federal Regulations

49 CFR 100-199 Transportation

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402. Orders for the above publication should request the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 First article. When specified in the contract (see 6.2), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.4).

3.2 Conformance to documents. Materials, parts and assemblies shall conform to the applicable drawings and referenced specifications.

3.3 Formulation and materials. The grain assembly shall consist of formulations and materials in the proportion and quantity to produce an assembly which will meet the ballistic requirements of TABLE I (see 6.6).

TABLE I. Performance Limits in CKU-7/A Rocket Catapult.

Temperature, °F	-65 to -70	65 to 70	160 to 165
Action time *, ms (Maximum)	550	550	550
Ignition Delay, ms (Maximum)	25	25	25
Thrust, lb_f (Maximum)	7350	7350	7600
Resultant Impulse, $lb_f.s$ (Minimum)	1100	1100	1100

*See 6.5 for definition

3.4 Environmental. Each grain assembly when assembled with all other components of the CKU-7/A catapult shall withstand the following environmental exposure with no evidence of disintegration of propellant or derangement of components. In addition, each assembly shall meet the ballistic requirements of TABLE I.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the current version before use.

3.4.1 Vibration. Each grain assembly shall be capable of withstanding the vibration test of MIL-STD-810, Method 514.2, Procedure I, Part 1 and Curve C of figure 514.2-2 as evidenced by satisfactory ballistic performance in accordance with TABLE I.

3.4.2 Temperature shock. Each grain assembly shall be capable of withstanding a Temperature Shock Test in accordance with MIL-STD-810, Method 503.1, except 93°C (200°F) will be substituted for 71°C (160°F), as evidenced by satisfactory ballistic performance in accordance with TABLE I. The change in temperature from 93°C to -54°C (-65°F) and back to 93°C with the prescribed soaking time constitutes one cycle. Forty cycles shall be conducted per unit.

3.4.3 Temperature - altitude - humidity. Each grain assembly shall be capable of withstanding the temperature - altitude - humidity test of MIL-STD-810, Method 518.1, Procedure I, as evidenced by satisfactory ballistic performance in accordance with TABLE I.

3.4.4 High Temperature. Each grain assembly shall be capable of withstanding the high temperature test of MIL-STD-810, Method 501.1, Procedure I, except that the test item shall be maintained at 93°C (200°F) for 50 hours(h) minimum, as evidenced by satisfactory ballistic performance in accordance with TABLE I.

3.4.5 Low temperature. Each grain assembly shall be capable of withstanding the low temperature test of MIL-STD-810, Method 502, Procedure I, except that the test item shall be maintained at 54°C (-65°F) for 50 h minimum, as evidenced by satisfactory ballistic performance in accordance with TABLE I.

3.5 Propellant mechanical properties. The mechanical properties of the cured propellant shall meet the requirements of TABLE II. A representative sample from each propellant mix shall be cured with the charges from that mix for testing in accordance with 4.8.1.

3.6 Functional.

3.6.1 Ballistics. When assembled into acceptable rocket catapult hardware in accordance with MIL-C-48569, the grain assembly shall comply with the requirements of TABLE I.

3.6.2 Resultant thrust. The rocket resultant thrust shall not exceed 5,000 pounds force (lb_f) for a period longer than 0.03 second(s) at any temperature condition and shall not at any time exceed 7,600 lb_f.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the currentversion before use.

TABLE II. Propellant mechanical properties.

Characteristic	Requirement	
	Minimum	Maximum
Elongation, %		
-65° F	20	--
80° F	20	--
200° F	20	--
Tensile Strength, PSI		
-65° F	300	--
80° F	90	--
200° F	65	--
Modulus, PSI		
-65° F	--	5100
80° F	--	1050
200° F	--	800

3.7 Material safety data sheets. The contractor shall prepare and submit material safety data sheets in accordance with FED-STD-313 as specified in the contract.

3.8 Workmanship. The workmanship shall be of sufficiently high quality to ensure satisfactory operation, reliability, and durability consistent with the requirements and application of the charge assembly and in accordance with the following:

3.8.1 Voids. Total void volume shall not exceed 0.250 cubic inch per grain. Propellant void maximum dimensions shall not exceed 0.375 inch. Interconnected voids shall be considered as a single void.

3.8.2 Cracks/Unbonds. There shall be no cracks in the propellant and no unbonds between the propellant and the liner.

3.8.3 Foreign matter. The assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.3 Test conditions. Unless otherwise specified, all tests required by this specification shall be performed in an atmospheric pressure of 7.8 to 9.4 kiloPascals (kPa) (28 to 32 inches of mercury), a temperature of 15.5 to 33°C (60 to 90°F), and a relative humidity of not more than 90 percent.

4.4 First article inspection.

4.4.1 Initial production sample. Unless otherwise specified in the contract (see 6.2), an initial production sample of 21 grain assemblies is required and shall be submitted to an activity designated by the procuring activity (see 6.2) for initial production inspection. Initial production sample grain assemblies shall be manufactured using the methods and procedures proposed for production. Any production of the grain assemblies by the contractor, prior to approval of the initial production sample, shall be at the contractor's risk. Initial production samples shall not be included as a part of the quantity specified for delivery in the contract (see 6.2).

4.4.2 Initial production inspection. The initial production inspection is conducted for the purpose of determining prior to starting production, that the contractor's production methods are capable of producting grain assemblies that comply with the technical requirements of the contract. The initial production inspection shall consist of the tests of 4.8 in the sequence specified in TABLE III performed on units that have passed the quality conformance inspection of 4.5 with the exception of the static firing test of 4.8.2. The quality conformance inspection shall be performed by the contractor prior to submission of the initial production sample. Failure of any grain assembly to comply with any requirement of this specification shall be cause for rejection of the initial production sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE III. Initial production evaluation test program. 1/

Para. no.	Test	Motor number																				
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
4.9.1	Vibration 200° F	a									a		a									
	-65° F		a	a								b										
4.9.2	Temperature Shock				a	a	a				b	a	b									
4.9.3	Temperature-Altitude-Humidity							a			c	c	c									
4.9.4	High Temperature								a		e	d	e									
4.9.5	Low Temperature									a	d	e	d									
4.9.6	Static Fire 200° F	b				b	b		b		f		f				a	a	a			
	70° F													a	a	a						
	-65° F		b	b				b		b		f								a	a	a

1/ Letters denote sequence of testing.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:56Z
Check the source to verify that this is the current version before use.

4.4.2.1 Initial production sample failure. If a failure, a malfunction, an out-of-tolerance condition, or an inability to obtain results due to loss of data occurs during or after an initial production test, the supplier will determine analytically the most probable cause of non-compliance. If the non-compliance is unique to the unit tested, the test may be repeated (in full or in part) with a substitute unit and testing continued on the remainder of the program. If this analytical examination reveals the suppliers production techniques to be inadequate (see 4.4.2), the production inadequacy must be corrected and all or part of the initial production sample testing as defined in 4.4.2 repeated at the discretion of the Government.

4.4.2.2 Retest. At the discretion of the procuring activity, initial production sample tests, or any portion thereof, shall be repeated under the following conditions:

a. The manufacturer has modified his product through a change of raw materials, production procedures, or methods. The supplier shall notify the procuring activity prior to the incorporation of any such changes, and shall provide quantitative evidence of the effect of such changes on the performance or characteristics of the product. The requirement for retesting will be based on an evaluation, by the procuring activity, of the evidence supplied.

b. There is evidence that the quality of the product has not been maintained. This evidence may be in the form of accumulated failure reports of the product, of system failures attributable to the product, or failure of the product to pass any of the tests for quality verification that may be conducted by or for the procuring agency.

c. Any change in design or documentation by the procuring activity.

d. Any interruption of production by the contractor.

4.5 Quality conformance inspection. The quality conformance inspection shall consist of the examination of 4.8 and the tests of 4.9 performed on samples selected per 4.6.

4.6 Sampling for quality conformance inspection. Unless otherwise specified, sampling shall be in accordance with MIL-STD-105.

4.6.1 Lot size. For the purpose of identification and shipment, a lot shall consist of a maximum of 1200 grain assemblies, exclusive of static firing test samples, provided the homogeneity of the inspection lots has been retained as follows: ingredients from the same lot of raw materials. A production lot shall be that number of grain assemblies manufactured with no change in design, construction or manufacturing techniques from those used in fabricating the initial production sample, and which are to be presented for acceptance at one time. Each production lot shall contain assemblies cast from a single propellant mix.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.6.2 Sampling for examination. Sampling for examination for major and minor defects shall be in accordance with TABLE IV.

4.6.3 Sampling for tests.

4.6.3.1 Sampling for mechanical properties test. Samples for the mechanical properties tests of 4.8.1 shall be prepared for each lot from sample propellant cured in accordance with 3.5.

4.6.3.2 Sampling for functional tests. Twenty-one sample grain assemblies shall be selected from each lot for testing in accordance with 4.8.2. These samples shall be forwarded to the activity designated by the procuring activity for test (see 6.2).

4.6.3.3 Sampling for radiographic examination. Each grain assembly shall be radiographically inspected in accordance with 4.8.3.

4.7 Quality conformance examination. Examination for major and minor defects shall be performed on a defect basis using the sampling plan and associated criteria in TABLE IV in accordance with the classification of defects contained in TABLE V. If the total number of defects per classification for either the major or minor classification exceeds the acceptance number of TABLE IV, the lot shall be rejected. All nonconforming material or parts shall be removed from the lot. Four power (4X) magnification may be used in performing visual examination for such defects as burrs or foreign matter.

TABLE IV. Sampling plan.

Lot size	Sample size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	-	-	-	-
301 - 800	50	0	1	1	2
801 - 1200	90	1	2	2	3

TABLE V. Classification of defects.

Classification	Defect	Method of inspection
Sleeve Drawing 11820366		
CRITICAL None defined		
MAJOR 101 102	 Overall length Thickness, Wall	 Gage Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE V. Classification of defects. - Continued

Classification	Defects	Method of inspection
103	Diameter, outside	Gage
104	Material defective	Visual
MINOR		
201	Burr or sharp corners	Visual
202	Foreign matter	Visual
Sleeve and Grain Assembly, Drawing 11820365		
CRITICAL		
1	Grain defects (cracks, grooves, cuts, voids or scratches)	Visual/ X-ray
2	Disbond of grain to sleeve	Visual/ X-ray
MAJOR		
101	Length of finished grain	Gage
102	Sleeve defective	Visual
103	Propellant Grain defective	Visual
104	Foreign matter	Visual
MINOR		
201	Liner defective	Visual
202	Marking missing, incorrect or illegible	Visual
Box, Packing, Ammunition for Sleeve and Grain Assembly Drawing D9297893		
CRITICAL		
None defined		
MAJOR		
None defined		
MINOR		
201	Contents loose	Manual/ Visual
202	Quantity of contents incorrect	Visual
203	Separation or filler missing	Visual
204	Sealer incomplete, loose or distorted	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE V. Classification of defects. - Continued

Classification	Defects	Method of inspection
205	Cut or damaged	Visual
Box, Fiberboard (Inner) Packing Ammunition for Sleeve and Grain Assembly Drawing D9297892		
CRITICAL None defined		
MAJOR None defined		
MINOR		
201	Contents loose	Manual
202	Hardware missing, loose, broken, or improperly engaged	Manual/ Visual
203	Strapping missing, loose, broken, or improperly assembled	Manual/ Visual
204	Contents of box exposed	Visual
205	Box damaged	Visual
206	Marking missing, incorrect or illegible	Visual
207	Number of incorrect grain	Visual
Box, Fiberboard (Outer) Alternative Packing, Ammunition for Sleeve and Grain Assembly Drawing D9297894		
CRITICAL None defined		
MAJOR None defined		
MINOR		
201	Contents loose	Manual
202	Box broken or damaged	Visual
203	Number of units contained incorrect	Visual
204	Marking missing, incorrect or illegible	Visual
205	Tape incomplete	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.8 Quality conformance tests.

4.8.1 Mechanical properties. A representative sample from each propellant mix shall be cured with the cartridge main charge and the grain assemblies from that mix and tested in accordance with JANNAF Solid Propellant Mechanical Behavior Manual, CPIA Publication No. 21, Class C - Development Screening Testing. Compliance with all the requirements of TABLE II of this specification shall be demonstrated for the first article sample and each individual lot during production. Failure to meet these requirements shall be cause for rejection of the lot.

4.8.2 Functional. Seven units assembled in acceptable hardware shall be static fired at each temperature specified in TABLE I. These tests shall be completed by the procuring activity for each production lot. Failure of any unit to meet the ballistic requirements of TABLE I shall result in rejection of the lot.

4.8.3 Radiographic examination. Each grain assembly shall be radiographically inspected, while at ambient temperature, in two mutually perpendicular longitudinal planes in accordance with MIL-STD-453 to verify compliance with 3.8.1 and 3.8.2. Each grain assembly shall be inspected at ambient temperature after being maintained at that temperature for 4 hours.

4.9 Initial production tests.

4.9.1 Vibration. The vibration test shall be conducted in accordance with MIL-STD-810, Method 514.2, Procedure I, Part 1 of Table 514.2-II, and Curve C of figure 514.2-2.

4.9.2 Temperature shock. The temperature shock test shall be conducted in accordance with MIL-STD-810, Method 503.1, except that 93°C will be substituted for 71°C. The change in temperature from 93°C to -54°C back to 93°C with the prescribed soaking time constitutes one cycle. Forty cycles shall be conducted per rocket grain.

4.9.3 Temperature - altitude - humidity. Temperature - altitude - humidity testing shall be conducted in accordance with MIL-STD-810, Method 518.1, Procedure I.

4.9.4 High temperature. High temperature testing shall be conducted in accordance with MIL-STD-810, Method 501.1, Procedure I at 93°C for a period of 50 h minimum.

4.9.5 Low temperature. Low temperature testing shall be conducted in accordance with MIL-STD-810, Method 502, Procedure I, at 54°C (-65°F), for a period of 50 h minimum.

4.9.6 Static fire. Following the environmental test sequence specified in TABLE III, each initial production sample grain assembly, installed in acceptable hardware, shall be static fired at the temperature

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

specified in TABLE III.

4.10 Measuring and test equipment. The supplier shall provide for the selection, evaluation, approval, maintenance and control of all inspection standards, gages, measuring and test equipment necessary to determine conformance to this specification.

4.11 Instrumentation accuracy. Unless otherwise specified, the test instrumentation systems shall be such as to yield data of the following accuracies. The percentage figures represent the limits of error expressed in percent of expected maximum value.

a.	Temperature	±1°C (±2°F)
b.	Barometric Pressure	±5 percent
c.	Pressure	±5 percent
d.	Time	±5 percent for functional tests

5. PACKAGING

5.1 Preservation, packaging and packing. Packing shall be level A in accordance with Drawings D9297892 and D9297893.

5.2 Marking. In addition to any special markings required by the contract (see 6.2), marking shall be in accordance with MIL-STD-129, MIL-STD-130, and Code of Federal Regulations 49 CFR 171-179.

6. NOTES

6.1 Intended use. The sleeve and grain assembly described herein is intended for use in conjunction with CKU-7/A Aircraft Ejection Seat Catapult Assembly in accordance with MIL-C-48568.

6.2 Ordering Data. Procurement documents should specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification
b. Quantity required exclusive of first article and static fire sample units (see 3.1, 4.4 and 4.6.3.2)
c. When a first article sample is not required (see 3.1, 4.4 and 6.4)
d. Assigned activity for first article testing (see 4.4) and quality conformance inspection functional testing (see 4.6.3.2 and 4.8.2)
e. Any special markings required (see 5.2)
f. Safety precautions (see 6.3.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

6.2.2 Contract data requirements. Any data required for delivery in connection with this document shall be specified on a DD Form 1423 incorporated into the contract. Such data will be delivered as identified on completed (numbered) DIDs (Data Item Descriptions/DD 1664) which will be documented in the Applicable ADL (Authorized Data List).

6.3 Explosive hazard classification. The explosive hazard classification for this grain assembly shall be:

Explosive Hazard Classification: Class 2
Storage Compatibility Group: Group J
Department of Transportation (DOT) Hazard Class: Class B
DOD Marking: Propellant Explosive

6.3.1 Hazard notice. The rocket motor described herein is flammable and/or explosive and consequently presents a hazard in manufacture, handling, storage and shipment. The contractor should recognize this hazard and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents.

6.3.2 Safety precautions. The safety precaution requirements of the "Contractor's Safety Manual for Ammunition, Explosives, and Related Dangerous Material" (DOD 4145.26M) are applicable and should be specified in the contract or order as required by the Armed Services Procurement Regulations (ASPR) 1-323.

NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives Ashore" (OP 5) should be made applicable.

6.4 First article sample waiver. First article samples submitted and approved on a recent contract may be accepted by the procuring activity in lieu of an additional first article inspection. When the first article sample is waived (see 6.2.1(c)), the procurement document should contain a statement specifying that the standards of workmanship exhibited by the previously approved first article sample shall determine the minimum requirements of the current contract or order.

6.5 Action time. Action time is defined as the time between the points where the rocket axial thrust reaches 10 percent of its maximum value at the start of burning and falls below 10 percent of the maximum value at the end of burning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

6.6 Advisory propellant formulation.

	Ingredient	Function	%
1.	Carboxyl-Terminated Polybutadiene Polymer	Binder	
2.	Resin, Liquid Epoxy Trifunctional Grade B	Curing Agent	14.50
3.	Chromium 2- Ethyl Hexoate Class 2	Curing Catalyst	
4.	Lecithin	Wetting Agent	0.05
5.	Dibutyl Carbitol Formal	Plasticizer	1.65
6.	Aluminum	Fuel Additive	2.00 max
7.	Ammonium Perchlorate	Oxidizer	80.00
8.	Iron Oxide	Burning Rate Catalyst	1.80

6.7 Advisory liner formulation.

	Ingredient	Function	%
1.	Carboxyl-Terminated Polybutadiene Polymer	Binder	
2.	Resin, Liquid Epoxy Trifunctional Grade B	Curing Agent	90
3.	Chromium 2-Ethyl Hexoate Class 2	Curing Catalyst	
4.	Thermax	Filler	10

6.8 Possible source. The following products have met the requirements of this specification in past procurement actions:

Thiokol liner TPL-317A
Thiokol propellant TPH-9001

They were obtained from:

Longhorn Army Ammunition Plant
Thiokol Chemical Corp.
Longhorn Division
Marshall, Texas

This information is for the convenience of the procuring activity and is not to be construed as a waiver of any requirement of this specification nor as any limitation of additional potential sources of supply.

Custodian:
NAVY - OS

Preparing Activity:
NAVY - OS

Project Number:
1377-N637

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-S-48567(OS) "SLEEVE AND GRAIN ASSEMBLY"

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the currentversion before use.

FOLD

POSTAGE AND FEES PAID
DOD 316

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer
Naval Ordnance Station
Standardization Division (611)
Indian Head, MD 20640

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:56Z
Check the source to verify that this is the current version before use.