MILITARY SPECIFICATION

WARHEAD SECTION, GM, PRACTICE, LIGHTWEIGHT: M252E1

PARTS AND ASSEMBLING

This Specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts and assembling of the Warhead Section, GM, Practice, Lightweight: M252E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS ,

MILITARY

MIL-T-5021	- Tests Aircraft and Missile Welding Operator's Qualifications
MIL-I-6812	- Bolt, Aircraft
MIL-I-6866	- Inspection Process, Magnetic Particle
MIL-S-7742	- Screw threads, standard, optimum selected series; General Specification for
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-453	- Inspection, Radiographic
MIL-STD-1168	- Lot Numbering of Ammunition

DRAWINGS

PICATINNY ARSENAL

PRODUCT AND PACKAGE DRAWINGS

9216660	- Shipping and Storage Container for Lance Warhead Sections and Adaption Kits, Pkg and Mkg
9294619	- Warhead Section, GM, Practice: Lightweight, M252E1
9294724	- Marking Instructions for Warhead Section, GM, Practice LT WT-M252E1

INSPECTION EQUIPMENT DRAWINGS

11430242	- Runout Fixture Plate, M252 Warhead
11430243	- Instruction Tag Runout Fixture, M252

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

ASTM E 18-67	- Tests for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing 9294619, all associated drawings, and with all requirements specified in applicable specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

3.3 Mechanical properties.-Cold-working or heat-treating (including quenching-and-tempering, normalizing, normalizing-and-tempering, annealing, and stress-relieving) operations, shall be performed in such a manner as to produce the specified properties uniformly through-out the entire lot. The contractor shall determine the detailed procedures to produce parts meeting the required mechanical properties. These procedures shall be documented and submitted with the first article sample to the Contracting Officer. Changes in these procedures shall also be documented and submitted to the Contracting Officer.

3.4 Welding.-All skin welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of good fusion, penetration, and soundness of deposit representative of good welding practice. The process shall be such as to prevent warpage beyond dimensional requirements.

3.4.1 Qualification of Welders.-Only welders qualified in accordance with Specification MIL-T-5021 shall be permitted to weld steel components. A complete qualification test for each welder or welding operator in making warhead skins shall consist of making butt weld qualification test coupons in accordance with Specification MIL-T-5021. The test coupons must satisfactorily pass the test specified in Specification MIL-T-5021.

3.4.2 Material sag.-Sag of material in the area adjacent to the weld shall not be more than .010 below the surface of the joined part.

3.5 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.6 First article testing.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspections.-The responsibility for inspection shall comply with MIL-A-48078.

4.2 Classification of Inspection.-The following types of inspection shall be conducted on this item:

a. First article inspection
b. Quality conformance inspection

4.3 First Article Inspection.-

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contractor for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing No.	Quantity
Warhead Section, GM Practice: Lightweight	9294619	1
M252E1 Nose cone tip	10246034	1
Nose cone skin	10246038	1
Nose cone assembly	10246033	1
Skin, forward	10246031	1
Skin, center	10246028	1
Skin, aft	10246026	1
Bulkhead assembly, nose cone	9294699	1
Frame extension assembly, welded	9294697	1
Frame assembly, welded	9294698	1
Frame assembly	9294702	1
Bulkhead assembly, aft	10246071	1
Frame assembly, warhead	9294703	1
Cable Assembly	9294695	1
Bolt, Tee	9237322	8
Nut, external wrenching	9237309	8
Pin, alignment	8877425	4
Pin, shear	8877426	12
Seal, aft section	9267740	1

4.3.2 Inspections to be performed.-The First Article parts submitted in accordance with Paragraph 4.3.1 will be subjected by the Government to any or all the requirements of the applicable drawings and to the inspections of Table I. All inspections listed in Table I shall be classified Major unless otherwise specified.

4.3.3 Rejection.-See MIL-A-48078 (PA).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Warhead Section, GM, Practice: Lightweight, M252E1 (Dwg. 9294619) Examination for Defects	1		3.2	4.4.2.19
	Nose Cone Tip (Dwg. 10246034) Examination for Defects	1		3.2	4.4.2.1
	Nose Cone Skin (Dwg. 10246038) Examination for Defects	1		3.2	4.4.2.2
	Nose Cone Assembly (Dwg. 10246033) Examination for Defects	1		3.2	4.4.2.3
	Skin, Forward (Dwg. 10246031) Examination for Defects	1		3.2	4.4.2.4
	Skin, Center (Dwg. 10246028) Examination for Defects	1		3.2	4.4.2.5

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-20T05:30Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Skin, Aft (Dwg. 10246026) Examination for Defects	1		3.2	4.4.2.6
	Bulkhead Assembly, Nose Cone (Dwg. 9294699) Examination for Defects	1		3.2	4.4.2.7
	Frame extension assembly, welded (Dwg. 9294697) Examination for Defects	1		3.2	4.4.2.8
	Frame assembly, welded (Dwg. 9294698) Examination for Defects	1		3.2	4.4.2.9
	Frame Assembly (Dwg 9294702) Examination for Defects	1		3.2	4.4.2.10
	Bulkhead assembly, aft (Dwg. 10246071) Examination for Defects	1		3.2	4.4.2.11
	Frame assembly, warhead (Dwg. 9294703) Examination for Defects	1		3.2	4.4.2.12

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cable Assembly (Dwg. 9294695) Examination for Defects	1		3.2	4.4.2.13
	Bolt, Tee (Dwg. 9237322) Examination for Defects	8		3.2	4.4.2.14
	Nut, external wrenching (Dwg. 9237309) Examination for Defects	8		3.2	4.4.2.15
	Pin, alignment (Dwg. 8877425) Examination for Defects	4		3.2	4.4.2.16
	Pin, Shear (Dwg. 8877426) Examination for Defects	12		3.2	4.4.2.17
	Seal, aft section (Dwg. 9267740) Examination for Defects	1		3.2	4.4.2.18

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-20T05:30Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection.-

4.4.1 Inspection Lot Formation.-Inspection losts shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of warheads shall contain:

a. XM819 Fuzes with the same interfix number from one manufacturer.

4.4.2 Examination.-See MIL-A-48078 (PA)

a. Sampling Plans.-Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105 Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Nose Cone Tip				10246034
					NEXT HIGHER ASSEMBLY
					10246033
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Angle improper		0.40%	3.2	Gage
102	Length tip to shoulder		0.40%	3.2	Gage
103	Largest diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T05:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10246038
4.4.2.2	Nose Cone Skin				NEXT HIGHER ASSEMBLY 10246033
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Penetrant examination of weld		100%	3.2	4.5.1
102	Thickness		0.40%	3.2	Gage
103	Diameter large end		0.40%	3.2	Gage
104	Diameter small end		0.40%	3.2	Gage
105	Outside contour improper		0.40%	3.2	Gage
106	Length		0.40%	3.2	Gage
Major B					
131	Sag		0.40%	3.4.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10246033
4.4.2.3	Nose Cone Assembly, Welded				NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Penetrant examination of weld		100%	3.2	4.5.1
Major B 131	Sag		0.40%	3.4.2	Gage
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:36Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10246031
4.4.2.4	Skin, Forward				NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Penetrant examination of weld		100%	3.2	4.5.1
102	Thickness		0.40%	3.2	Gage
103	Outside contour improper		0.40%	3.2	Gage
104	Length		0.40%	3.2	Gage
Major B					
131	Sag		0.40%	3.4.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Skin, Center				10246028
					NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Penetrant examination of welds		100%	3.2	4.5.1
102	Thickness		0.40%	3.2	Gage
103	Outside contour improper		0.40%	3.2	Gage
Major B					
131	Sag		0.40%	3.4.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2020-10-20T05:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10246026
4.4.2.6	Skin, Aft				NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Penetrant examination of welds		100%	3.2	4.5.1
102	Thickness		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
104	Length		0.40%	3.2	Gage
Major B					
131	Sag		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9294699
4.4.2.7	Bulkhead Assembly, Nose Cone				NEXT HIGHER ASSEMBLY 9294703
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Penetrant examination		100%	3.2	4.5.1
102	Location of fuze mounting holes		0.40%	3.2	Gage
103	Depth of fuze mounting holes, min		0.40%	3.2	Gage
104	Pitch diameter of fuze mounting holes		0.40%	3.2	Gage
105	Minor diameter of fuze mounting holes		0.40%	3.2	Gage
106	Depth of recess for cable assembly connector receptacle		0.40%	3.2	Gage
107	Angle of outside tapered surface		0.40%	3.2	Gage
108	Pitch diameter of insert for mounting frame assembly		0.40%	3.2	Gage
109	Minor diameter of insert for mounting frame extension assembly		0.40%	3.2	Gage
110	Diameter of outside shoulder on tapered surface		0.40%	3.2	Gage
111	Diameter at start of tapered surface		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9294697
4.4.2.8	Frame extension assembly, welded				NEXT HIGHER ASSEMBLY 9294703
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Penetrant examination		100%	3.2	4.5.1
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9294698
4.4.2.9	Frame Assembly, Welded				NEXT HIGHER ASSEMBLY 9294702
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Penetrant examination of welds		100%	3.2	4.5.1
Minor 201	Evidence of poor workmanship		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-20 05:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Frame Assembly		9294702
			NEXT HIGHER ASSEMBLY 9294703

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Any component damaged, missing, or improperly assembled		100%	3.2	Visual
102	Torque of aft bulkhead assembly screws		100%	3.2	Gage
103	Concentricity intermediate bulkhead with aft bulkhead assembly		0.40%	3.2	Gage
104	Concentricity center bulkhead with aft bulkhead assembly		0.40%	3.2	Gage
105	Concentricity forward bulkhead with aft bulkhead assembly		0.40%	3.2	Gage
106	Length intermediate bulkhead diameter to aft surface		0.40%	3.2	Gage
107	Length center bulkhead diameter to aft surface		0.40%	3.2	Gage
108	Length forward bulkhead diameter to aft surface		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10246071
4.4.2.11	Bulkhead Assembly, Aft				NEXT HIGHER ASSEMBLY 9294702
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Penetrant examination		100%	3.2	4.5.1
102	Location slots for tee bolt shank		0.40%	3.2	Gage
103	Location alignment pin holes		0.40%	3.2	Gage
104	Location shear pin holes		0.40%	3.2	Gage
105	Width aft section seal groove		0.40%	3.2	Gage
106	Depth aft section seal groove		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2020-10-20T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.12	Frame Assembly, Warhead		9294703
			NEXT HIGHER ASSEMBLY 9294619

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Any component damaged, missing or improperly assembled		100%	3.2	Visual
102	Harness fed through a bulkhead touching bulkhead		100%	3.2	Gage
103	Torque of screws holding frame extension assembly to frame assembly		100%	3.2	Gage
104	Torque of frame assembly ballast screws (2 places)		100%	3.2	Gage
105	Torque of dummy weight assembly screws (Find No. 5)		100%	3.2	Gage
106	Torque of dummy weight assembly screws (Find No. 6)		100%	3.2	Gage
107	Torque of dummy weight assembly screws (Find No. 7)		100%	3.2	Gage
108	Torque of nose cone bulkhead assembly to frame extension assembly screws		100%	3.2	Gage
109	Torque of main ballast screws		100%	3.2	Gage
110	Torque of cable assembly screws		100%	3.2	Gage
111	Location of Pin 1 in cable assembly		100%	3.2	Visual
112	Insulation resistance of Cable Assembly		100%	3.2	4.5.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9294703
4.4.2.12	Frame Assembly, Warhead				NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2020-10-20T05:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Cable Assembly		9294695
			NEXT HIGHER ASSEMBLY 9294703

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Any component damaged, missing or improperly assembled		0.40%	3.2	Visual
102	Insulation resistance		100%	3.2	4.5.6
103	Continuity and resistance		100%	3.2	4.5.7
Major B					
131	Overall length		0.40%	3.2	Gage
132	Length to pigtail wire		0.40%	3.2	Gage
133	Length of Pigtail		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9237322
4.4.2.14	Bolt, Tee				NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Internal defects inspection		100%	3.2	4.5.2
102	Magnetic particle inspection		100%	3.2	4.5.3
103	Pitch diameter		0.40%	3.2	4.5.4
104	Major diameter		0.40%	3.2	4.5.4
105	Hardness	25*	Acc.0 Rej. 1	3.2	4.5.5
Minor					
201	Symmetry of bolt shank to "A" and "B"		0.65%	3.2	Gage
202	Overall dimension handle, max		0.65%	3.2	Gage
203	Dimension handle, bearing surface, min.		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

*or five (5) percent of lot, whichever is greater

Source: https://assist.dla.mil -- Downloaded: 2020-10-20T05:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9237309
4.4.2.15	Nut, External Wrenching				NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Magnetic particle inspection		100%	3.2	4.5.3
102	Pitch diameter		0.40%	3.2	4.5.4
103	Minor diameter		0.40%	3.2	4.5.4
Minor					
201	Distance across flats of double hex		0.65%	3.2	Gage
202	Largest distance across double hex, min.		0.65%	3.2	Gage
203	Length of double hex, min.		0.65%	3.2	Gage
204	Diameter of bearing surface, min.		0.65%	3.2	Gage
205	Largest outside diameter, max.		0.65%	3.2	Gage
206	Length of largest outside diameter min.		0.65%	3.2	Gage
207	Overall length, max.		0.65%	3.2	Gage
208	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8877425
4.4.2.16	Pin, Alignment				NEXT HIGHER ASSEMBLY 9294619
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Length		0.40%	3.2	Gage
102	Distance to shoulder		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	True position of threads		0.40%	3.2	Gage
105	Pitch diameter of threads		0.40%	3.2	Gage
106	Major diameter of threads, min.		0.40%	3.2	Gage
107	Length of chamfer		0.40%	3.2	Gage
108	Locking element missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	Pin, Shear		8877426
			NEXT HIGHER ASSEMBLY
			9294619

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Length		0.40%	3.2	Gage
102	Distance from end to shoulder		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	True position of threads		0.40%	3.2	Gage
105	Pitch diameter of threads, min.		0.40%	3.2	Gage
106	Major diameter of thread, min		100%	3.2	Visual
107	Locking element missing		0.40%	3.2	Visual
108	Chamfer missing				
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48381 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Seal, aft section		9267740
			NEXT HIGHER ASSEMBLY 9294619

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Direction of wires		0.40%	3.2	Visual
Major B					
131	Width		0.40%	3.2	Gage
132	Height		0.40%	3.2	Gage
133	Length		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-20T05:30Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.19	Warhead Section, GM, Practice: Lightweight, M252E1		9294619
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Any component damaged, missing or improperly assembled		100%	3.2	Visual
102	Electrical interface of cable assembly and fuze		100%	3.2	4.5.8
103	Torque of nose cone assembly screws		100%	3.2	Test
104	Runout		100%	3.2	11430242 and 11430243
105	Weight		100%	3.2	Test
106	Longitudinal C.G.		100%	3.2	Test
107	Radial C.G.		100%	3.2	Test
108	Pitch and yaw moment of inertia		100%	3.2	Test
109	Roll moment of inertia		100%	3.2	Test
110	Torque of plug		100%	3.2	Gage
111	Torque of small trim ballast bolt (when applicable)		100%	3.2	Gage
112	Torque of large trim ballast bolt (when applicable)		100%	3.2	Gage
113	Warhead missing from fuze mounting screws		100%	3.2	Visual
114	Torque of fuze mounting screws		100%	3.2	Gage
115	Tee bolts bind		100%	3.2	Manual
116	Gap between sections, max.		0.40%	3.2	Gage
117	Forward facing steps, max.		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.19	Warhead Section, GM, Practice: Lightweight M252E1				9294619
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
118	Aft facing steps, max.		0.40%	3.2	Gage
119	Height of alignment pins		0.40%	3.2	Gage
120	Height of shear pins		0.40%	3.2	Gage
121	Marking missing incomplete or illegible		0.40%	3.2	Visual
Minor					
201	Location of C.G. dots		0.65%	3.2	Gage
202	Location of forward strap band		0.65%	3.2	Gage
203	Location of aft strap band		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Shipping and Storage Cntr for Lance Warhead Sections and Adaption Kits, Pkg and Mkg (prior to assembly of top assembly)	1 OF 1	9216660
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Improper number of studs in mailing bag		100%	3.2	Visual
102	Desiccant missing		100%	3.2	Visual
103	"TOP" marking on warhead misoriented		100%	3.2	Visual
104	Torque of strap assembly bolts improper		100%	3.2	Gage
105	Torque of external wrenching nuts to support plate improper		100%	3.2	Gage
106	Any component missing or improperly assembled		100%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Shipping and Storage Cntr. for Lance Warhead Sections and Adaption Kits, Pkg and Mkg	1 OF 1	9216660
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Top assembly improperly assembled		0.40%	3.2	Visual
102	T-bolts missing or improperly assembled		0.40%	3.2	Visual
103	T-bolt torque improper		0.40%	3.2	Gage
104	Lead seals missing or improperly assembled		0.40%	3.2	Visual
105	Marking missing, incomplete or illegible		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-26T05:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment.-The inspection equipment required to perform the examinations and prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.5 Test Method and Procedures.-

4.5.1 Penetrant examination.-The part shall be subjected to penetrant inspection in accordance with MIL-I-6866. Parts so tested, is acceptable, shall be returned to the lot.

4.5.2 Internal defects inspection of tee bolt.-The tee bolt shall be inspected for internal defects in accordance with MIL-STD-453, Q.L. 2-2T. Parts so tested, if acceptable, shall be returned to the lot.

4.5.3 Magnetic particle inspection of tee bolt and external wrenching nut.-The tee bolt and external wrenching nut shall be inspected for defects in accordance with MIL-I-6868 and MIL-B-6812. Parts so tested, if acceptable, shall be returned to the lot.

4.5.4 Inspection of bolt and external wrenching nut threads.-The threads of the tee bolt and external wrenching nut shall be inspected in accordance with MIL-S-7742. Parts so tested, if acceptable, shall be returned to the lot.

4.5.5 Hardness of tee bolt.-The tee bolt shall be subjected to the hardness test in accordance with ASTM E 18-67 (Part 31) This is a non-destructive test. Parts so tested, if acceptable, shall be returned to the lot.

4.5.6 Insulation resistance of cable assembly.-The cable assembly shall be subjected to the insulation resistance test using approved test equipment. This is a non-destructive test. Assemblies subjected to this test, if acceptable, shall be returned to the lot.

4.5.7 Continuity and resistance of cable assembly.-After performance of the test specified in 4.5.6 the cable assembly shall be subjected to the continuity and resistance test using approved test equipment. This is a non-destructive test. Assemblies subjected to this test, if acceptable, shall be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

4.5.8 Electrical interface of cable assembly and fuze.-The warhead section shall be subjected to this test using approved test equipment. This is a non-destructive test. Assemblies subjected to this test, is acceptable, shall be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-

5.1.1 Level A.-The warhead shall be preserved and packaged in accordance with Dwg. 9216660, as applicable.

5.2 Packing .-

5.2.1 Level A.-The warhead, preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwg. 9216660 as applicable.

5.3 Marking.-Marking shall be in accordance with Dwg. 9216660, as applicable and Code of Federal Regulations, Title 49, Parts 171-179.

5.4 Shipping.-When warheads from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended Use.-Not applicable

6.2 Ordering data.-See MIL-A-48078 (PA)

6.3 Submission of Designs for Approval.-See 6.2 of MIL-A-48078. Submit equipment designs, as required, to Commander, Picatinny Arsenal, Attn: SARPA-QA-T-T, Dover, New Jersey 07801.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1340-A441

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 JAN 72

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:56Z
Check the source to verify that this is the current version before use.