INCH-POUND

MIL-E-22200/10B(SH)
AMENDMENT 2
14 November 1990
SUPERSEDING
AMENDMENT 1
16 July 1990
(See 6.7)

MILITARY SPECIFICATION

ELECTRODES, WELDING, MINERAL COVERED, IRON POWDER, LOW-HYDROGEN, MEDIUM, HIGH TENSILE AND HIGHER-STRENGTH LOW ALLOY STEELS

This amendment forms a part of MIL-E-22200/10B(SH), dated 24 March 1989, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 9

Table VI, under "procedures" and "requirements", delete: "MIL-E-222200" and substitute "MIL-E-22200".

PAGE 11

Table VIII, under first column "Types", delete: horizontal line separating "MIL-7018-M" and "MIL-10018-M1 and MIL-12018-M2".

AMSC N/A FSC 3439

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:25Z
Check the source to verify that this is the current version before use.

PAGE 12

* 4.4.2, after last sentence add: "Subject to NAVSEA approval, a modified inspection level A plan may be used for MIL-12018-M2 electrodes which will allow a lot to be defined as the quantity of any one size and type produced in one continuous 8-hour period from covering identified by wet mix or controlled chemical composition and core wire identified by heat number or controlled chemical composition. When electrode covering is identified by wet mix, wet mix equivalency testing shall be performed and reported for those wet mixes not selected for full lot conformance testing. An appropriate quality control plan and recent conformance test data must be approved by NAVSEA. This plan and data must demonstrate acceptable quality control and consistent chemical analysis and mechanical properties for at least 25 consecutive wet mixes. Should a lot fail quality conformance testing due to unacceptable toughness or yield strength using the modified inspection level A plan, then testing must revert back to the standard inspection level A until 5 consecutive wet mixes are successfully tested and the data approved by NAVSEA. Based on successful test results obtained using the modified inspection level A plan after a minimum trial period of one year, inspection level B may be used for MIL-12018-M2 electrodes, subject to NAVSEA approval."

PAGE 13

* 4.5.1(b), after last sentence add: "If it is nessesary to splice two plates together to form the base plates, they shall be welded with full penetration welds."

* 4.5.1(c), after last sentence add: "If it is nessesary to splice two plates together to form the base plates, they shall be welded with full penetration welds."

PAGE 14

* Table IX, for "flat position", for "1/8 diameter", under "MIL-10018", delete: "45 to 55" and substitute: "40 to 50"; for "vertical-up position", for "1/8 and 5/32 diameter", under "MIL-10018", delete: "40 to 50" and substitute: "45 to 55".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:25Z
Check the source to verify that this is the current version before use.

PAGE 15

* 4.5.1(j), delete and substitute: "For electrode sizes smaller than 3/16 inch size, the weld bead placement shall be as shown in Figure 2. Where necessary, the root opening may be increased to allow proper bead placement and avoid slag entrapment. The total number of weld passes, the actual root opening and the actual bead placement shall be recorded and reported with a schematic sketch."

PAGE 17

4.7.1, first sentence, delete: "very" and substitute: "every".

The margins of this amendment are marked up with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 3439-N781)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:25Z
Check the source to verify that this is the current version before use.