MILITARY SPECIFICATION

STAND, SUSTAINER TEST MK13 Mod 0

1. SCOPE

1.1 This specification covers one type of mobile test stand for use with the TERRIER missile sustainer BT-3.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification.

MILITARY SPECIFICATIONS

MIL-P-116	Preservation, Methods of
MIL-B-121	Barrier Material, Greaseproofed, Flexible (Waterproofed)
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Boxes, Fiber

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

DRAWINGS

Bureau of Ordnance LD 489037 and all drawings, specifications, and standards listed thereon.	Stand, Sustainer Test, MK13 Mod 0

(Copies of specification, standards, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency by the contracting officer).

3. REQUIREMENTS

3.1 Materials. Components of the sustainer test stands shall be made of materials as specified on the applicable drawings. Alloy composition, hardness, and other characteristics of all materials shall comply with the provisions of the pertinent specification and as indicated on the applicable drawing.

3. 2 Design changes. No design change shall be made in any componen which will alter the functional characteristics of the complete equipment. Design changes not in the foregoing category but intended only to simplify fabrication, may be made only on receipt of approval in writing, prior to manufacture or use, from the Bureau of Ordnance, Approval of such change shall not constitute a deviation from the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

3.3 Dimensions. Dimensions and tolerances shall be as specified on the drawings, Where tolerances are not given, the dimensions shall be adhered to within limitations customary in good commercial practice.

3.4 Finish. Metal components shall be finished in accordance with requirements on the pertinent drawings. The surf aces of all components shall be free from burrs, roughness, and excessive oxides or corrosion.

3.5 Markings. All identification nameplates and markings indicated on the drawings shall be present and shall be clearly legible.

3.6 Workmanship. The stands shall be uniform in appearance and of good quality, comparable to general commercial practice. They shall be free from cracks, burrs, splits, sharp edges and other defects which may hinder their functional operation or be injurious to handling personnel.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractors responsibility. Unless otherwise specified herein he supplier is responsible for the performance of all inspection requirements, prior to submission for Government inspection and acceptance, Except as otherwise specified, the supplier may utilize his own facilities r any commercial laboratory acceptable to the Government. Inspection ecords of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

4.2 Sampling. Sampling for examination shall be conducted in accordance with Standard MIL-STD-105.

4.3 Lot. Lot size for examination shall be the individual sustainer test stand.

4.4 Examination. The sample stands shall be carefully inspected and measured to determine conformance with the requirements of this specification and the applicable drawings.

4.5 Packaging. The inspector shall ascertain that the packaging method used will comply with the general requirements of this specification.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. The lift trucks shall be packed for domestic shipment in such manner as to insure acceptance by common carrier for safe transportation at the lowest rate to the point of delivery. Adequate protection from physical damage must be provided including protection against damage by weather. If the equipment is to be shipped overseas the requirements for overseas shipment shall be applicable.

5.1.1 Level A.

5.1.1.1 Cleaning. Unless otherwise specified, the sustainer test stand shall be cleaned in accordance with Method C-1 of Specification MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

5.1.1.2 Drying. Unless otherwise specified the sustainer test stand shall be dried in accordance with one or more of the procedures given in Specification MIL-P-116 - provided the procedure is not injurious to the item.

5.1.1.3 Preservative application. Unpainted ferrous metal surfaces subject to corrosion shall be brush coated with P-2 type preservative in accordance with specification MIL-P-116.

5.1.1.4 Unit packaging. Unit packaging of the sustainer test stand shall be in accordance with Method I of Specification MIL-P-116. Surfaces preserved as specified in 5.1.1.3 shall be wrapped in barrier material conforming to MIL-B-121, Grade A, so as to protect the preservative coated surfaces, Barrier material shall be held in place by a suitable tape or twine. The wheels and casters shall be removed from the main frame and packaged in a fiber board box conforming to Specification PPP-B-636 Type I or II, Class 2. The parts shall be cushioned, blocked and braced to prevent movement within the container.

5.1.1.5 Intermediate package. Not applicable.

5.1.2 Level B. Not applicable.

5. 1.3 Level C.

5.1.3.1 Cleaning and drying. Cleaning and drying shall be in accordance with 5.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

5.1.3.2 Preservative application. None.

5.1.3.3 Unit packaging. Unit packaging shall be in accordance with Method III of Specification MIL-P-116.

5.1. 3.4 Intermediate package. Not applicable.

5.2 Packing.

5.2. 1 Level A.

5.2. 1.1 Exterior containers. The sustainer test stand packaged as described in 5.1 shall be packed in a wood box conforming to specification PPP-B-621, Class 2, Style 2 or Style 4. The wheels and casters, packaged as specified in 5.1 shall be packed in the same container with the rest of the sustainer test stand. Sufficient blocking and bracing shall be provided to prevent damage to the equipment during shipment and multiple handling.

5.2.2 Level B. Not applicable.

5.2.3 Level C. The sustainer test stand packaged in accordance with 5.1 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Containers shall comply with the carrier rules and regulations applicable to the mode of transportation.

5.3 Marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

5.3.1 Special markings. None

5.3.2 Normal markings. In addition to the markings required by contract or order, unit packages. intermediate packages (when used), and shipping containers shall be marked in accordance with the requirements of MIL-STD-129, including serial numbers.

6. NOTES

6.1 Intended use. The sustainer test stands procured under this specification are intended for use in testing the TERRIER missile sustainer BT-3. The stands can be rolled about to move the component to the desired position.

6.2 Security. Preparation, production, and handling of classified material shall be in conformity with provisions of the Industrial Security Manual for Safe -guarding Classified Information (Attachment to DD Form 441), and current security regulations of the cognizant Inspector of Naval Material.

6.3 Ordering Data. Procurement documents should specify the title, number, and date of this specification.

6.4 Options. Desired options shall be forwarded to the contracting officer prior to use by the contractor.

6.4.1 The attention of the contracting officer is invited to the Quality .ssurance Provisions and options in Specification MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

6.5 Criteria for use of proper level of preservation, packaging and packing shall be as follows:

For Level A. This level shall be used for those items which are to be shipped to indeterminate destinations or stored under indeterminate conditions for redistribution anywhere.

For Level C. This level shall be used only when it is definitely known that the packaged item is to be shipped to domestic installations for immediate use at the first receiving activity.

6.6 Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation the United States Government thereby incur no responsibility nor any obligation whatsoever; and the fact that the Governme have formulated, furnished, or in anyway supplied the said drawings, specifica tions, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians

Navy-Bureau of Ordnance

Preparing activity

Navy-Bureau of Ordnance

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:28Z
Check the source to verify that this is the current version before use.