8 October 1959
SUPERSEDING
NAVORD OS 3973A
12 August 1946

MILITARY SPECIFICATION

TELESCOPE MARK 104 MOD 0

1. SCOPE

1.1 This specification covers the requirements for procurement of the Telescope Mark 104 Mod 0.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification.

SPECIFICATIONS

FEDERAL

UU-T-101 - Tape, Gummed; Mending, Reinforcing, and Securing (Paper, Cellulose, and Cloth).
PPP-B-585 - Boxes; Wood, Wirebound.
PPP-B-601 - Boxes; Wood, Cleated Plywood.
PPP-B-621 - Boxes; Wood, Nailed and Lock-Corner.

MILITARY

MIL-G-15793 - Grease, Instrument.
MIL-L-10547 - Liners, Case, Waterproof.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-167 - Mechanical Vibrations of Shipboard Equipment.

DRAWINGS

BUREAU OF ORDNANCE

DR. 181117 - Shock Test Stand for Circuit Breakers and Control Equipment
LD 167943 - Telescope Mark 104 Mod 0 (Assembly) List of Drawings, Assemblies, Parts, Specifications, etc.

FSC 6650

Source: https://assist.dla.mil -- Downloaded: 202610-19T11:27Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

BUREAU OF ORDNANCE

OP 400 - General Instruction for the Design, Manufacture, and Inspection of Naval Ordnance Equipment.

NAVORD OS 8983 - Complex Weapons; Handling and preparation for Delivery; General Requirements for.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General requirements. - Requirements for manufacture shall be in accordance with Publications OP 400. The telescope shall conform to LD167943 and all documents listed thereon, this specification and the contract order.

3.2 Preproduction sample. - Unless otherwise specified in the contract or order (see 6.2), a preproduction sample is required (ss 4.3.1) for each such contract or order. Samples shall be manufactured using the methods, procedures, and plant location proposed for the production lot. Samples shall be inspected as specified under 4.4 such inspection being for the purpose of determining that the manufacturer's production process will produce telescopes that will meet the requirements of this specification.

3.3 Optical and mechanical requirements. -

3.3.1 Internal cleanness. - The optical components shall be carefully cleaned before being assembled into the telescope to ensure freedom from dust, dirt, moisture, fingerprints, and other foreign matter. Telescope compartments shall be clean and dust free before optical components are assembled therein. The assembled telescope shall be internally clean.

3.3.2 Range focus. - The movement of the range focusing lens mount shall be smooth and even in both directions throughout its length of travel. By movement of the lens mount, the telescope shall be capable of being focused, free from parallax with respect to the reticle, on targets at all ranges from fifteen (15) feet to infinity.

3.3.3 Optical cementing. - The cement film binding optical elements together shall be free from foreign particles, bubbles, cement starts, milkiness, and other defects that might reduce the effectiveness of the telescope. Excess cement shall be removed from the exterior of cemented

Source: https://assist.dla.mil -- Downloaded: 20260-19T11:27Z
Check the source to verify that this is the current version before use.

parts; however, no reagent shall be used that could be absorbed into the cement film and cause subsequent deterioration of the cement film or cement starts. All cemented optical elements shall be marked with the symbol "CC" indicating cellulose caprate cement. Marking shall be on the edge of lenses.

3.3.4 Reticle. - The lines and numerals of the reticle shall be distinct, sharp, and clean cut and shall not appear broken because of improper filling or other causes. There shall be no fillets at the intersections of lines and no closed in numerals.

3.3.5 Stray light. - No stray light shall be visible in or surrounding the field of view, nor shall there be any false pupils or other concentrations of stray light in or adjacent to the exit pupil. No paint, enamel, lacquer, or other material which may become detached from the surface to which applied may be used on the interior of the telescope.

3.3.6 Image quality. - The image of a round bright star shall appear round with sharply defined edge under the conditions of 4.4.3.4.6. The image shall be free from points, flares, rays, fog, haze, or halos other than the normal diffraction rings. No difference in coloration between one side of the star and the other shall be seen. A slightly defocused image shall remain round. The images of adjacent red and blue star targets shall be simultaneously in focus.

3.3.7 Resolution. - The limit of resolution shall not exceed 5 seconds of arc simultaneously in both horizontal and vertical directions.

3.3.8 Eyepieces focus. - The eyepiece shall be fixed focus with respect to the reticle and the focal setting shall be minus 0.70 $\pm$ 0.15 diopters.

3.3.9 Alignment. - The telescope shall meet the alignment requirements specified on Drawing 511713 listed on LD 167943.

3.4 Environmental requirements. -

3.4.1 Shock. - The telescope shall be capable of withstanding six 150 foot-pound blows, two in each of three mutually perpendicular directions.

3.4.2 Shock-transportation, storage, and handling. - Telescope packs conforming to 5.3.1, 5.3.2, and 5.3.3 shall be capable of withstanding the tests of 4.4.3.3.2. After these tests, the telescope shall show no damage and shall meet the optical and mechanical requirements specified herein.

3.4.3 Vibration. - The telescope shall be capable of withstanding Type I environmental vibration as defined in Standard MIL-STD-167 at frequencies between 200 and 1500 cycles per minute at an amplitude of plus and minus 0.030-inch.

Source: https://assist.dla.mil -- Downloaded: 202640-19T11:27Z
Check the source to verify that this is the currentversion before use.

3.4.4 Vibration-transportation. - Telescope packs conforming to 5.3.1, 5.3.2, and 5.3.3 shall be capable of withstanding the tests of 4.4.3.3.4. After these tests, the telescope shall show no damage and shall meet the optical and mechanical requirements specified herein.

3.4.5 Pressure-temperature. - The corrected internal pressure drop in the telescope shall not exceed 1-pound per square inch (psi) from an initial internal pressure of 4 psi during a period of 72 hours. There shall be no condensation or moisture on the internal surfaces of the telescope and on the surfaces of optical components when the telescope is cooled from an ambient temperature of approximately 72°F to minus 20°F.

3.6 Lubrication. - The eyepiece draw tube and the range focusing draw tube shall be lubricated with instrument grease conforming to Specification MIL-G-15793. The grease shall be applied sparingly so as to avoid contamination of the optical elements.

3.7 Workmanship. - Workmanship shall be of such quality as to produce material of uniform high quality and has to meet all requirements of the applicable drawings and of this specification.

4. QUALITY ASSURANCE PROVISIONS AND TEST REQUIREMENTS

4.1 Unless otherwise specified herein, the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 Lot. - For purpose of sampling a lot shall consist of all the telescopes manufactured by the same process and at the same plant location and submitted for Government acceptance at any one time.

4.3 Sampling. -

4.3.1 For preproduction inspection. - Unless otherwise specified (see 4.3.1.1), one preproduction sample telescope shall be supplied by the contractor as specified in 3.2. The sample shall be submitted to the Government inspector for preproduction inspection (see 4.4.3.1) at an activity designated in the contract or order (see 6.2) or by the Bureau of Ordnance. Further production of the telescopes by the contractor prior to the approval of the procuring activity or completion of inspection of the preproduction sample shall be at the contractor's risk.

4.3.1.1 Preproduction sample and inspection for a subsequent contract. - If a contractor has previously delivered telescopes in accordance with the requirements of this specification and his product has been found to be

Source: https://assist.dla.mil -- Downloaded: 20260-19T11:27Z
Check the source to verify that this is the current version before use.

satisfactory, the preproduction sample and inspection for any subsequent contract or order may be waived at the discretion of the procuring activity. (See 6.2)

4.3.2 Sampling for periodic tests. - Unless otherwise specified by the procuring activity, sample telescopes shall be randomly selected by the Government inspector, as indicated below, for periodic testing (See 4.4.3.2). The Government inspector shall forward the sample to a testing activity designated in the contract or order (See 6.2) or by the Bureau of Ordnance. The sampling procedure shall be as follows:

a. One telescope from the first twenty-five telescopes or less.
b. One telescope from the next fifty telescopes or less
c. One telescope from the next seventy-five telescopes or less.
d. One telescope from each succeeding quantity of one hundred telescopes or less.

If a sample from any of the above quantities fails the periodic tests, sampling shall be repeated starting with (a) above.

4.3.3 Sampling for lot acceptance. - No provisions are made for sampling for lot acceptance because each telescope shall be inspected (visually and dimensionally examined and tested) in accordance with 4.4.1 through 4.4.3.4.9, as applicable.

4.4 Inspection

4.4.1 General procedure. - General inspection and test procedures shall be in accordance with Publication OP 400. Acceptance inspection shall be conducted at the contractor's plant. Inspection shall be performed at the stage of assembly best suited for performing the examinations and tests specified herein.

4.4.2 Visual and dimensional examination. - Each telescope shall be visually examined for completeness of manufacture, freedom from defects, proper identification, and workmanship. Dimensional and other nondestructive inspections shall be made in accordance with the acceptance inspection instructions provided by the procuring activity.

4.4.2.1 Packaging, packing, and marking. - Telescope containers shall be examined to determine whether or not packaging, packing, and marking are in accordance with Section 5.

4.4.3 Tests and test procedures. -

4.4.3.1 Preproduction tests. - Preproduction telescopes (See 4.3.1) shall be subjected to the environmental tests of 4.4.3.3.1 through 4.4.3.3.5.2 and the acceptance tests of 4.4.3.4.1 through 4.4.3.4.9. Proproduction telescopes that pass the required tests and meet the require-

Source: https://assist.dla.mil -- Downloaded: 20261O-19T11:27Z
Check the source to verify that this is the currentversion before use.

ments specified herein shall be included in the quantity called for in the contract order.

4.4.3.2 Periodic tests. - Periodic tests (See 4.3.2) shall be performed on telescopes that have previously passed the acceptance tests of 4.4.34.1 through 4.4.3.4.9. The periodic tests shall consist of the environmental tests of 4.4.3.3.1 through 4.4.3.3.5.2.

4.4.3.2.1 Failures during periodic tests. - In the event of failure of any telescope during periodic testing, inspection and acceptance of subsequent telescopes shall be suspended until the reasons for failure and consequent rejection have been determined and the cause of failure corrected by the contractor to the satisfaction of the procuring activity. The contractor shall furnish the procuring activity with a written statement properly endorsed by the Government inspector indicating the reasons for failure and the corrective action taken.

4.4.3.3 Environmental tests. -

4.4.3.3.1 Shock. - The telescope shall be secured to the shock test stand shown on Drawing 181117 and tested to determine conformance to 3.4.1. The blows shall be struck, two in each of the three mutually perpendicular directions.

4.4.3.3.2 Shock transportation, storage, and handling. - Telescope packs conforming to 5.3.1, 5.3.2, and 5.3.3 shall be subjected to the applicable rough handling tests of Publication NAVORD OS 8983 to determine conformance to 3.4.2.

4.4.3.3.3 Vibration. - The telescope shall be tested to determine conformance to 3.4.3. The vibrations shall be applied separately in each of the three mutually perpendicular directions. Each test in each direction shall be of at least fifteen minutes duration.

4.4.3.3.4 Vibration-transportation. - Telescope packs conforming to 5.3.1, 5.3.2, and 5.3.3 shall be subjected to the applicable vibration test of Publication NAVORD OS 8983 to determine conformance to 3.4.4.

4.4.3.3.5 Pressure-temperature. - The telescope shall be tested for pressure-temperature to determine conformance to 3.4.5.

4.4.3.3.5.1 Test procedure. - The telescope shall be charged with dry air to a pressure of 4-psi. The exact internal air pressure, ambient temperature, and barometric pressure shall be simultaneously recorded. The air inlet valve shall then be closed to seal the telescope and the time recorded. The telescope shall then be subjected to the following temperatures in the order listed.

a. Room temperature (approximately 72°F) until stabilized.

Source: https://assist.dla.mil -- Downloaded: 202610-19T11:27Z
Check the source to verify that this is the current version before use.

b. Ambient temperature of plus 155°F for at least 5 hours.
c. Room temperature (approximately 72°F) for at least 2 hours.
d. Ambient temperature of minus 20°F for at least 16 hours.
e. Room temperature (approximately 72°F for approximately 24 hours.

During and at the end of the minus 20°F temperature run of (d) above the telescope shall be examined to determine that no condensation or moisture has collected on the internal surfaces of the telescope and on the surfaces of optical components. At the end of the temperature run of (e) above the telescope internal air pressure, ambient temperature, and barometric pressure, shall be simultaneously recorded and the internal air pressure corrected for any change between the ambient temperature and barometric pressure at the end of the test and the ambient temperature pressure at the beginning of the test.

4.4.3.3.5.2 Corrected and interpolated internal pressure. - A check shall be made to determine that the corrected final internal air pressure, as determined in 4.4.3.3.5.1, is not less than the interpolated internal air pressure, computed on the basis of 1-psi loss in 72 hours. The interpolated air pressure shall be computed from the formula,

$$P_t = P_o e^{-.004t}$$

Where: P_t = Interpolated pressure in psi at time t.

P_o = Initial pressure in psi.

e = Base of natural logarithms.

t = Time in hours between initial and final readings of internal air pressure in psi.

4.4.3.3.6 Examination and retests following environmental tests. - Following the environmental tests of 4.4.3.3.1 through 4.4.3.3.5.2 telescopes shall be examined for breakage, loose parts and other defects. Telescopes that pass the environmental tests shall be returned to the contractor for repair and reconditioning if such repair and reconditioning are necessary as a result of environmental testing. The lot acceptance tests of 4.4.3,4.1 through 4.4.3.4.9 shall be repeated as necessary to determine that no changes in mechanical and optical performance have taken place as a result of the environmental tests.

4.4.3.3.7 Waiver of tests. - The tests specified in 4.4.3.3.2 and 4.4.3.3.4 may be waived by the procuring activity for level C packs only, provided the contractor guarantees safe delivery to the using activity.

4.4.3.4 Lot acceptance tests. -

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:27Z
Check the source to verify that this is the current version before use.

4.4.3.4.1 Internal cleanness. - The telescope shall be examined for internal cleanness to determine conformance to 3.3.1. Examination shall be made by looking into the telescope in bright light, both directly and with the aid of an auxiliary lens placed behind the eyepiece, and by looking through the telescope at a uniform field having the brightness of the sky in average daylight.

4.4.3.4.2 Range focus. - The range focusing lens mount shall be tested to determine that it meets the mechanical and optical requirements of 3.3.2. The equipment required for the optical test is a collimator telescope and a target or other object situated 15 feet distant from the test site. With the telescope under test facing the collimator telescope, operate the range focusing control until the image of the collimator telescope reticle is focused free from parallax with respect to the reticle of the telescope under test. Another focusing test shall be conducted using the 15 foot distant target or object instead of the collimator telescope. Operate the range focusing control until the target or object is in focus free from parallax with respect to the telescope reticle.

4.4.3.4.3 Optical cementing. - Cemented optical elements shall be examined to determine conformance to 3.3.3.

4.4.3.4.4 Reticle. - The reticle shall be examined during the test of 4.4.3.4.1 to determine conformance to 3.3.4.

4.4.3.4.5 Stray light. - The telescope shall be tested and examined to determine conformance to 3.3.5. With the telescope directed at a distant natural target silhouetted against a bright sky at least 40 degrees from the direct line of the sun, the exit pupil shall be examined with the aid of a 5-power loupe. Upon placing the eye in the exit pupil, no haze or clouding of the image resulting from superimposed stray light shall be evident as the observer's eye is slowly moved out of the exit pupil in a lateral direction until the image is extinguished.

4.4.3.4.6 Image quality and definition. - The telescope shall be subjected to a star test to determine conformance to 3.3.6.

4.4.3.4.6.1 Test equipment. - The target for the star test shall be situated at least 50 meters from the test site or a miniature target may be contained in a suitable collimator. The target shall consist of three adjacent circular apertures, each 10 second in angular diameter, placed beside one another. All of the apertures shall be brightly illuminated from the rear by means of tungsten lamp or lamps operated at ordinary line voltage. The light from the first, or white star, shall be unfiltered. The light emitted by the second, or red star, shall have a visual spectrum centroid at 656.3 ±10 millimicrons wavelength. The light emitted by the third, or blue star, shall have a visual spectrum centroid at 486.2 ±5 millimicrons wavelength. An auxiliary telescope shall be provided having a magnification of not less than 3, nor more than 6, diameters.

Source: https://assist.dla.mil -- Downloaded: 202610-19T11:27Z
Check the source to verify that this is the current version before use.

4.4.3.4.6.2 Test Procedure. - In all focusing and testing the particular aperture being observed should be centered in the field of view of the telescope under test and the image observed with the aid of the auxiliary telescope. Focus the telescope under test on the white star for best image as seen through the auxiliary telescope. The star image shall appear round with a sharply defined edge and shall be free from points, flares, rays, fog, haze, and halos other than the normal diffraction rings. No difference in coloration between one side of the star and the other shall be seen. Defocus the telescope under test slightly in either direction. The blurred image of the star shall remain round. Focus the telescope under test successively on the red star, adjusting for best focus as seen through the auxiliary telescope and observe whether the blue star is also in focus.

4.4.3.4.7 Resolution. - The telescope shall be tested for resolution to determine conformance to 3.3.7. The target for the resolution test shall be of the Foucault resolving power pattern containing horizontal and vertical black bars on a white field. It shall be brightly illuminated by tungsten light without filters. Variation of target illumination to obtain optimum resolution is permitted. The auxiliary telescope should have a magnification of not less than 3 nor more than 6 diameters. The relescope under test shall be focused on the target for best image as seen through the auxiliary telescope.

4.4.3.4.8 Eyepiece focus. - The eyepiece shall be tested for proper setting to determine conformance to 3.3.8.

4.4.3.4.8.1 Method 1. - The equipment required is a diopterscope of at least four power (see 6.4). Motion of the diopterscope eyepiece away from its objective is considered negative and toward it positive. Focus the diopterscope on a distant target and read the scale. Introduce diffused light into the objective of the telescope under test. With the objective of the diopterscope at the exit pupil of the telescope under test, focus the diopterscope for clearest image of the reticle of the telescope and again read the scale. The eyepiece setting is calculated as the reciprocal of this distance in meters.

4.4.3.4.9 Alignment. - The telescope shall be tested to determine conformance to the alignment requirements of 3.3.9. The equipment required for this test is a collimator telescope, a fixture for supporting the telescope under test, and an aperture cap. The supporting fixture shall have horizontal and vertical bearing surfaces to contact the aligning surfaces of the telescope under test. Prior to the test, the intersection of the bearing surfaces shall be established parallel to the line of sight of the collimator telescope crosslines within 15 seconds of arc in any meridan. The aperture cap, containing a central 0.2-inch diameter aperture, fits over the front of the telescope under test so that the aperture is centered on the axis of the objective lens. Clamp or bolt the telescope on the fixture and see that the aperture cap

Source: https://assist.dla.mil -- Downloaded: 202610-19T11:27Z
Check the source to verify that this is the current version before use.

is removed. Focus the telescope for freedom from parallax between the image of the collimator crosslines and the telescope reticle and note the displacement of the collimator crosslines from the center of the reticle pattern. Three-fifths mil on the reticle pattern corresponds to two minutes of arc. Place the aperture cap over the objective. While observing the field, rotate the range focusing ring throughout its entire range of motion and note the movement of the collimator crosslines from this position at infinity focus by reference to the reticle of the telescope under test. A movement of 0.15 mil on the reticle corresponds to 30 seconds of arc.

4.5 Resubmission. - Telescopes that fail to pass any acceptance test shall be rejected. Rejected telescopes may be resubmitted for retests in accordance with the procedures of Publication OP 400.

5. PREPARATION FOR DELIVERY

5.1 Required levels. - Telescopes shall be preserved, packaged, and packed in accordance with one of the following levels as specified in the contract or oder (see 6.2).

5.2 Preservation and packaging. -

5.2.1 Level A.

5.2.1.1 Cleaning, drying, and preservation. - Not applicable.

5.2.1.2 Unit packaging. - Unit packaging of the telescope shall consist of packaging it in its stowage box in accordance with Drawing 797250 listed on LD 167943.

5.2.1.3 Intermediate package. - Not applicable.

5.2.2 Level B and level C. - Not applicable.

5.3 Packing. -

5.3.1 Level A. - Telescopes packaged as specified in 5.2.1.2 shall be packed one or more in an overseas type box conforming to Specification PPP-B-385, PPP-B-601, or PPP-B-621. Boxes shall be lined with a waterproof case liner conforming to Specification MIL-L-10547, and sealed in accordance with the appendix thereto. Seams and closures shall have a water resistance equal to or better than that of the body material. The gross weight of any pack shall not exceed 150 pounds.

5.3.2 Level B. - Telescopes packages as specified in 5.2.1.2 shall be packed one or more in a domestic type box conforming to Specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:27Z
Check the source to verify that this is the current version before use.

PPP-B-585, PPP-B-601, or PPP-B-621. The gross weight of any pack shall not exceed 150 pounds.

5.3.3 Level C. - Telescopes packaged as specified in 5.1.1.2 shall be packed or otherwise prepared for shipment to insure carrier acceptance and to insure safe delivery to destination at the lowest applicable rate. Containers shall comply with the Consolidated Freight Classification Rules or other carrier regulations applicable to the mode of transportation.

5.3.4 Cushioning. - Each pack shall incorporate sufficient cushioning material, bracing, or other adequate shock absorbing devices to ensure that the telescope will meet all the requirements of Section 3 after being tested in accordance with 4.4.3.3.2 and 4.4.3.3.4. At the time of packing the moisture content of the cushioning material shall be no more than 5 percent. The pH range of the material shall be between 6.0 and 8.0.

5.4 Marking of shipping containers. -

5.4.1 For production telescopes. - In addition to any special marking required by the contract or order (see 6.2), shipping containers shall be marked in accordance with Standard MIL-STD-129.

5.4.2 For preproduction telescopes. - Shipping containers shall be marked as specified in 5.4.1 and with the following information:

Title, number, and date of this specification
Mark and Mod and LD number
Sample for preproduction inspection
Name of manufacturer
Manufacturer's plant address
Reference (contract number)

5.4.3 For telescopes for periodic testing. - Shipping containers shall be marked as specified in 5.4.2 except that containers shall be marked "Sample for periodic tests" instead of "Sample for preproduction inspection." In addition, containers shall be marked with the identification of the lot or quantity from which the sample was taken.

6. NOTES

6.1 Intended use. - The telescope Mark 104 Mod 0 is intended for use as a visual boresight for Gun Director Mark 56, Radar Sets AN/SPW-2 and AN/SPG-51 and Fire Control System Mark 74.

6.2 Ordering data. - Procurement documents should specify the following

a. Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 202640-19T11:27Z
Check the source to verify that this is the currentversion before use.

b. Whether preproduction samples and inspection are required (see 3.2 and 4.3.1.1).

c. Testing activity for preproduction samples or samples for periodic tests if the activity is not designated by the Bureau of Ordnance (see 4.3.1 or 4.3.2).

d. Levels required in preparation for delivery (see 5.1).

e. Special marking when required (see 5.4).

6.3 Preparation for delivery criteria. - Criteria for use of the proper level of preservation, packaging, and packing shall be as indicated below in 6.3.1 through 6.3.3.

6.3.1 Level A. - This level shall be used to afford adequate protection of items during multiple shipment and handling, indeterminate storage, and worldwide redistribution.

6.3.2 Level B. - This level shall be used for protection of items multiple domestic shipment and handling and covered storage. Six month cyclic inspection and any necessary represervation and repackaging is required when this level is used.

6.3.3. Level C. - This level shall be used only when it is definitely known that items are to be shipped to domestic installations for immediate use at the first receiving activity.

6.4 Definition of diopterscope. - A diopterscope is an auxiliary telescope with a calibrated focusing, motion for measuring the convergence or divergence of light pencils. The scale reads directly the reciprocal distance to the focus of the pencil in diopters, the reference point on the diopterscope usually being the front of the objective.

Notice. - When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Preparing activity
Navy - Bureau of Ordnance

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:27Z
Check the source to verify that this is the current version before use.