INCH-POUND

MIL-B-467E
17 November
SUPERSEDING
MIL-B-467D
1 July 1976

MILITARY SPECIFICATION

BREAKERS, PAVING:
PNEUMATIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers manually controlled, pneumatic paving breakers.

1.2 Classification. The pneumatic paving breakers shall be of the following sizes, as specified (see 6.2):

60 pound.
80 pound.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3820

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

WW-C-633	- Coupling Halves, Cap and Wye; Quick Disconnect, Pneumatic Hose, Two-Lug, Universal Type.
PPP-B-636	- Box, Shipping, Fiberboard.
PPP-P-40	- Preservation and Packing of Hand Tools; Tools and Tool Accessories for Power Driven, Metal and Woodworking Machinery.

MILITARY

MIL-T-704	- Treatment and Painting of Materiel.
MIL-O-13417	- Oilers, Air Line, for Pneumatic Tools.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-838	- Lubrication of Military Equipment.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1474	- Noise Limits for Army Materiel.
MIL-STD-1472	- Human Engineering Design Criteria for Military Systems, Equipment, and Facilities.

HANDBOOKS

MILITARY

MIL-HDBK-113	- Guide for the Selection of Lubricants, Functional Fluids, Preservatives and Speciality Products for Use in Ground Equipment Systems.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.2 Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM A 366	- Spec. for Steel, Sheet, Carbon, Cold-Rolled Commercial Quality.
ASTM A 569	- Spec. for Steel, Carbon (0.15 Maximum, Percent), Hot-Rolled Sheet and Strip, Commercial Quality.
ASTM A 686	- Spec. for Tool Steel, Carbon.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

COMPRESSED AIR AND GAS INSTITUTE (CAGI)

Compressed Air and Gas Handbook.

(Application for copies should be addressed to the Compressed Air and Gas Institute, 1230 Keith Building, c/o Thomas Associates, Inc., 1621 Euclid Avenue, Cleveland, OH 44115-2180.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

J833	- USA Human Physical Dimensions

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. Each Pneumatic paving breaker shall consist of: (1) a backhead mode of forged steel, equipped with a T-handle with rubber handgrips and throttle, (2) cylinder assembly made of forged steel or have a surface hardened cylinder liner, and (3) a fronthead equipped with a chuck for collared-shank tools with a latch type retainer, that shall prevent the accessory tool from becoming accidentally disengaged from the breaker. The pneumatic paving breaker (hereinafter referred to as "breaker") shall conform to table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

TABLE I. Physical and performance characteristics.

Size	Weight without accessories min.	Weight without accessories max.	Air consumption total (90 psig at the tool), max.	Piston diameter, min.	Piston stroke, min.	Piston speed, no load, min.	Force of blow (90 psig at the tool), min.
	lb	lb	cfm	inch	inch	blows/ minute	ft-lb/ blow
60	53	68	65	2.000	4.5	1,290	40
80	75	94	78	2.250	5.5	1,200	60

3.1.1 Performance. The breaker shall operate on compressed air at pressures between 70 and 100 pounds per square inch gage (lb/psig). The breaker shall break a 5.00-inch or thicker slab of Portland cement concrete, having a compressive strength of not less than 3,200 (lb/psi), into sections having an approximate top surface area not greater than 35.00 square inches without malfunction, damage, scored parts, wear of piston diameter, or cylinder diameter of more than 0.001 inch, or absence of oil vapor in the exhaust air when tested, as specified in 4.5.2.2.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or deviations of the pneumatic paving breaker from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnish breakers conforming to this specification.

3.3 Materials. Material shall be as specified herein. Material not specified herein shall be selected by the contractor and shall be subject to all provisions of this specification (see 4.1.2).

3.3.1 Material deterioration prevention and control. The breakers shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the breakers may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the breakers may be newly fabricated from recovered materials to the maximum extent practicable, provided the breakers produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the breakers.

3.4 Design.

3.4.1 Interchangeability. All parts having the same manufacturer's part number shall be interchangeable with each other with respect to installation and performance.

3.5 Components.

3.5.1 Backhead assembly. The backhead assembly shall include a housing, T-handle, and throttle lever.

3.5.1.1 Housing. The housing shall be made of forged steel.

3.5.2 Throttle lever. The throttle lever shall be located on the T-handle and shall be operable from either side of the breaker.

3.5.3 Throttle valve. The throttle valve shall be self-closing when the throttle lever is released.

3.5.4 Cylinder assembly. The cylinder assembly shall include a cylinder, piston, and hose connection swivel tube with coupling.

3.5.4.1 Cylinder. The cylinder shall be made of forged steel or have a surface-hardened cylinder liner.

3.5.4.2 Piston. The piston shall be reversible and conform to the physical characteristics of table I.

3.5.5 Hose connection tube. The hose connection tube shall be shaped in a gooseneck and shall be of the swivel type. The tube end thread shall be 0.750-inch, external, American National Pipe Thread.

3.5.5.1 Coupling. A 0.750-inch universal hose coupling conforming to WW-C-633, type II, shall be furnished.

3.5.6 Fronthead assembly. The fronthead shall include a retainer, chuck, and housing for the chuck.

3.5.6.1 Liner. The chuck housing shall contain a replaceable liner.

3.5.6.2 Chuck. The chuck shall be 1.250-inch hexagonal by 6 inch (nominal size), in accordance with Compressed Air and Gas Handbook, standard chuck-gage size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

3.5.6.3 Retainer. The retainer shall be latch type (see 3.10).

3.5.6.4 Air strainer. When an air strainer is furnished (see 6.2), the air strainer or screen (with a minimum mesh of 24 per inch) shall be replaceable and shall not be damaged with the supply hose is connected or disconnected from the air inlet connection.

3.5.6.5 Exhaust port. The exhaust port shall be located to direct exhaust air downward and away from the operator.

3.6 Accessories. Unless otherwise specified (see 6.2), the accessories specified in table II shall be furnished.

TABLE II. Accessories.

Accessory	Nominal length under collar (inches)	Tool end (inches)
a. Chisel	13.5 to 14.5	2.75 to 3.25 wide
b. Moil point	13.5 to 14.5	point
c. Tamping rod	8 to 9	1.640 diameter
d. Tamping pad	not applicable	not less than 6 inch round or not less than 6 inch square

3.6.1 Chisel and moil point. The chisel and moil point shall be made of forged steel conforming to ASTM A 686.

3.6.1.1 Heat treatment. After forging, the chisel and moil point shall be normalized, hardened, and tempered to a hardness of 54 to 60 Rockwell C.

3.6.2 Tamping rod. The tamping rod shall be made of forged steel conforming to ASTM A 686. The rod shall have a 3/4-inch per foot taper up to a diameter of 2-1/4 inch.

3.6.3 Tamping pad. The tamping pad shall be made of malleable iron or forged steel. The tamping pad shall attach to the tamping rod (see 3.6.2) having a 3/4-inch per foot taper.

3.7 Attachments. Unless otherwise specified (see 6.2), a spike driver and a sheeting driver (for 80-pound breaker) shall be furnished.

3.7.1 Spike driver. The breaker shall be convertible to use as a spike driver by replacement of the standard fronthead or cylinder with a fronthead or cylinder constructed specifically for driving railroad spikes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

3.7.1.2 Sheeting driver. The 80-pound breaker shall be convertible to use a sheeting driver by replacement of the standard fronthead or cylinder, with a fronthead or cylinder constructed specifically for driving sheeting and planks. The sheeting driver shall be adjustable for driving 2.00- to 3.00-inch planks.

3.7.2 Driving tools. Unless otherwise specified (see 6.2), a spike driving tool and a sheeting driver shall be furnished.

3.7.2.1 Spike driving tool. The spike driving tool shall have a 1.25-inch hexagonal shank and shall have a lower end designed specifically for driving railroad spikes.

3.7.2.2 Sheeting driver. The sheeting driver tool shall have a 1.25-inch hexagonal shank and shall be designed specifically for driving 2.00- to 3.00-inch thick planks.

3.7.3 Oil reservoir. When specified (see 6.2), an oil reservoir shall be furnished. The oil reservoir shall have capacity for not less than 25 minutes of continuous operation while operating at 90 psig at the tool. The oil reservoir shall be built in the backhead or cylinder. The type and quantity of the oil shall be labeled near the oil reservoir fill port.

3.7.3.1 Leader hose. When an oil reservoir is not furnished, a 10-foot long, 0.750-inch inside-diameter hose shall be furnished, with an external NPT connector on one end and a universal hose coupling (conforming to WW-C-633) on the other.

3.8 Lubrication. All surfaces requiring lubrication shall be provided with a means for lubricating using either an internal oil reservoir (see 3.7.3) or an air-line oiler conforming to MIL-O-13417. The air-line oiler shall not be furnished under this specification. The breakers shall operate as specified herein when lubricated with military lubricants (see 6.4).

3.8.1 Lubricants. The procedure for the selection of lubricants shall be in accordance with MIL-STD-838, section 5. Lubricants selected shall be in accordance with MIL-HDBK-113, chapter 2. When the specification of the lubricant selected includes a requirement for a qualified products list (QPL), the lubricant supplied shall be from a source that is listed on the applicable QPL.

3.9 Chest. When specified (see 6.2), one or both types of chests made of steel of not less than 0.071-inch thickness shall be provided. The steel shall conform to ASTM A 366 or A 569. One chest, hereafter referred to as the "accessory chest", shall be of a size to hold the maintenance tools, leader hose, repair parts, and accessories furnished with each breaker. The other chest, hereafter referred to as the "breaker chest", shall be of a size to hold the breaker. The chests shall have an overlapping hinge lid that prevents the entry of rain and dirt, with not less than two tension-type hook latches. The chests lid shall open at least 90 degrees from the closed position and shall remain in the open position either by its own weight or by a holding device. A clasp that will accommodate a padlock with a 0.375-inch shackle shall be provided to secure the lid to the chests. The breaker chest shall be labeled "BREAKER". The breaker chest shall be labeled "2 SOLDIER LIFT" for the 60 pound breaker and

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

"4 SOLDIER LIFT" for the 80 pound breaker. The accessory chest shall be labeled "BREAKER ACCESSORIES" and "2 SOLDIER LIFT". Chests that are labeled "@ SOLDIER LIFT" shall be provided with four handles, two located at each end of the chest. Chests that are labeled "4 SOLDIER LIFT" shall be provided with eight handles, two on each corner. The handles shall be sized to accommodate 95th percentile male, gloved hands.

3.10 Safety. Each breaker shall be provided with a retainer that will prevent the accessory tool from becoming accidentally disengaged from the breaker. All sharp edges, shall be rounded or beveled. All surfaces that are subject to high temperatures shall be covered or protected.

3.11 Noise limits. The noise produced by the paving breakers shall conform to MIL-STD-1474 requirements, with the exception of MIL-STD-1474, 5.2 and 5.4, when tested in accordance with 4.5.2.7. The provisions of MIL-STD-1474, 4.3 and 4.4 shall apply if and only if MIL-STD-1474, 5.1.1.2 procedures have been pursued and documented to the satisfaction of the procuring activity and written permission to exceed the 85 dB(A) limit is obtained from the contracting officer. Hazard signs shall conform to MIL-STD-1474, 4.3, except the sign will state "HEARING PROTECTION REQUIRED WITHIN (specify) FEET". The sign shall be readable at the distance indicated on the sign.

3.12 Human factors engineering. The breakers shall conform to accepted human factors engineering design criteria and practice. The breakers shall be operable and maintainable by soldiers ranging from the small man, clothed, through the large man, arctic and MOPP IV clothed, in accordance with SAE J833, and MIL-STD-1472.

3.13 Identification marking. The breaker shall be identified in accordance with MIL-STD-130 and as specified herein.

3.14 Treatment and painting. The portions of the breaker and its components normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type A, color as specified (see 6.2).

3.15 Workmanship. The breaker shall be free of defects such as galvanic action resulting from contact of dissimilar metals, rust, cracks, and other defects that could impair its operation or serviceability.

3.15.1 Surfaces. All parts, components, and assemblies of the breaker including castings, forgings, molded parts, stampings, bearings, seals, and machined surfaces shall be clean and free from sand, dirt, fins, pits, sprues, scale, and other harmful or extraneous materials.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications and standards as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The breaker shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The breaker shall be tested as specified in 4.5.2 through 4.5.2.7. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling shall be in accordance with MIL-STD-105, inspection level S-1. The sample unit shall be one completely finished breaker.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. Acceptable quality level (AQL) shall be 1.0 percent defective for major defects and 2.5 percent defective for minor defects.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.3, 4.5.2.5, and 4.5.2.6. AQL shall be 1.0 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The breakers shall be examined as specified in 4.4.2 for defects listed in table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

TABLE III. Examination schedule.

Number	Defects	Requirement paragraph
Major		
101.	Weight not as specified.	3.1, table I
102.	Dimensions not as specified.	3.1, table I
103.	Material not as specified.	3.3
104.	Interchangeability of parts not as specified.	3.4.1
105.	Components not as specified.	3.5
106.	Location of throttle lever not as specified.	3.5.2
107.	Throttle valve not of the self-closing, lever-operated type.	3.5.3
108.	Cylinder assembly not as specified.	3.5.4.1
109.	Hose connection tube not as specified.	3.5.5
110.	Coupling not furnished or not as specified.	3.5.5.1
111.	Housing not as specified.	3.5.6.1
112.	Replaceable liner not furnished with 80-pound breaker.	3.5.6.1.1
113.	Chuck not suitable for accessories.	3.5.6.2
114.	Retainer not as specified.	3.5.6.3, 3.10
115.	Air strainer not as specified.	3.5.6.4
116.	Exhaust port not as specified.	3.5.6.5
117.	Accessories not as specified.	3.6
118.	Tamping pad taper not compatible with tamping rod taper.	3.6.3
119.	Attachments not as specified.	3.7
120.	Driving tools not as specified.	3.7.2
121.	Oil reservoir not as specified.	3.7.3
122.	Leader hose not furnished or not as specified.	3.7.3.1
123.	Lubrication and lubricants not as specified.	3.8, 3.8.1
124.	Human factor engineering not as specified.	3.12
Minor		
201.	Chest not as specified.	3.9
202.	Identification markings not as specified.	3.13
203.	Treatment and painting not as specified.	3.14
204.	Workmanship not as specified.	3.15, 3.15.1

4.5.2 Tests.

4.5.2.1 Test conditions. Unless otherwise specified, tests shall be performed without shelter and at the climatic conditions existing at the test site. The breaker shall operate as specified herein without maintenance other than the contractor's recommended normally scheduled maintenance as established by a maintenance schedule prepared and submitted by the contractor prior to test. Prior to test, the breaker shall be lubricated with military oils (see 3.8.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

Oils shall be those designated for use in the ambient temperatures at which the test is being performed. A slab of Portland cement concrete having a compressive strength of 3,200 psi, 5.00 inches thick (127 mm) or thicker with a top surface area of 100 square feet shall be made available for testing.

4.5.2.2 Performance. Using the chisel or moil point accessories, operate the breaker for 25 hours each at compressed air pressures at the tool of 70 and 100 psig, breaking the concrete slab into sections with top areas not greater than 35 square inches. At 5-hour intervals during the test, examine the exhaust for oil in the exhausted air. At the completion of 50 hours of operation, take the following action:

a. Examine all external parts of the breaker.
b. Disassemble the breaker and examine the parts for damage, wearing, or scoring.

Evidence of mechanical failure, permanent deformation, or damaged or scored parts; evidence of wearing of the piston diameter or cylinder diameter of more than 0.001 inch; or absence of oil vapor in the exhaust air shall constitute failure of this test.

4.5.2.3 Force of blow. Attach a steel ball with a Brinell hardness of not less than 200 and a 0.499 to 0.500 inch spherical diameter to the end of an accessory bar. Make twenty impressions with the steel ball in a 0.250-inch-thick strip of 1020 steel that has a Brinell hardness between 163 and 179. Measure in millimeters the mean diameter of the impressions. Convert to foot-pounds using table IV. Force of blow less than that specified in table I shall constitute failure of this test.

4.5.2.4 Air-consumption test. Measure the total air consumption (cubic feet per minute of free air) at 90 psig with the throttle valve fully open during the operational test. A water displacement meter or airflow meter shall be used in accordance with procedures outlined in the Compressed Air and Gas Handbook to determine air consumption. Air consumption exceeding that specified in table I shall constitute failure of this test.

4.5.2.5 Piston speed test. Determine the piston speed (blows per minute at no load). Piston speed less than that specified in table I at no load shall constitute failure of this test.

4.5.2.6 Individual operation test. Operate each breaker for 10 minutes at 100 psi. Any operational difficulties, breakage, or permanent deformation shall constitute failure of this test.

4.5.2.7 Noise level test. Noise levels shall be measured in accordance with MIL-STD-1474 requirements and reported in the format indicated by MIL-STD-1474, figure 7. As a minimum, noise levels shall be measured when equipment is operating under full load. MIL-STD-1474, 5.1.2.1.4 contours shall be taken at

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

not fewer than twelve equal (horizontal) arc increments; one increment shall include data from the noisiest position. Additionally, the noise level at the typical operating position shall be provided as dB(A) level. Failure to comply with MIL-STD-1474 provisions shall constitute failure of this test (see 3.11).

4.6 Inspection of packaging. The preservation, packing, and marking for level A, B, and C shall be examined to determine compliance with the applicable quality assurance provisions of PPP-P-40 and any additional requirements specified herein.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Breakers, accessories, repair parts, tools and publications. The breakers, accessories, repair parts, tools, and publications shall be preserved and packaged in accordance with level A requirements of PPP-P-40.

5.2 Packing. Packing of the breakers and their components shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A and B. The breakers and their components, preserved as specified in 5.1 shall be packed in accordance with level A or B requirements of PPP-P-40.

5.2.2 Level C. The breakers and their components, preserved as specified in 5.1, shall be packed in boxes conforming to PPP-B-636, domestic class. The weight of the contents shall not exceed 150 pounds. Box closure shall be in accordance with the appendix to the box specification.

5.3 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2), shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The breakers covered by this specification are intended for use in breaking up concrete, brick, asphalt, and macadam and for performing similar demolition work.

6.2 Acquisition requirements. Acquisition documents shall specify the following:

a. Title, number, and date of this specification.
b. Size required (see 1.2).
c. Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 3.1.1 and 2.2).
d. Timeframe required for submission of the first article (see 3.2).
e. When a first article is required for inspection and approval and the number of units required (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

f. When an air strainer is to be furnished (see 3.5.6.4).
g. Accessories required (see 3.6).
h. When attachments are not required (see 3.7).
i. When driving tools are not required (see 3.7.2).
j. When an oil reservoir is to be furnished (see 3.7.3).
k. When an accessory chest is required (see 3.9).
l. When a breaker chest is required (see 3.9).
m. Color required (see 3.13).
n. Level of packing required (see 5.2).
o. Any special marking required (see 5.3).

6.3 First article. When a first article inspection is required, the item should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instruction in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the first article.

6.4 Lubricants. MIL-STD-838, Lubrication of Military Equipment, prescribes the policy for using specification-type products wherever possible and provides specific requirements for potential use of non-standard proprietary products. MIL-STD-838 is implemented by MIL-HDBK-113, Guide for the Selection of Lubricants, Functional Fluids, Preservatives and Specialty Products for Use in Ground Equipment Systems. The contracting officer should note that unless otherwise authorized by the US Army Belvoir Research, Development and Engineering Center (ATTN: STRBE-VF), Fort Belvoir, VA 22060-5606, lubricants, fluids, and greases for ground equipment systems must be restricted to those listed under MIL-HDBK-113, chapter 2.

6.5 Subject term (key word) listing.

Breakers, paving: pneumatic
Paving breakers, pneumatic
Pneumatic paving breakers

6.6 Changes from previous issue. The margins of this specification are marked with asterisks (or vertical lines) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in theses notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review activities:
Army - AT
DLA - CS
Air Force - 84

User activities:
Navy - MC

Preparing activity:
Army - ME

Project 3820-0187

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

Table IV. Force of blow conversion table.

Impression diameter	Force of blow-ft/lb									
	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09
6.0	23.9	24.07	24.24	24.41	24.58	24.75	25.92	25.09	25.26	25.43
6.1	25.6	25.77	25.94	26.11	26.28	26.45	26.62	26.79	29.96	27.13
6.2	27.3	27.49	27.69	27.88	28.08	28.27	28.47	28.66	28.86	29.05
6.3	29.25	29.46	29.67	29.88	30.09	30.30	30.51	30.72	30.93	31.14
6.4	31.35	31.59	31.85	32.09	32.34	32.58	32.83	33.07	33.32	33.56
6.5	33.80	34.05	34.30	34.55	34.80	35.05	35.30	35.55	35.80	36.05
6.6	36.3	36.57	36.83	37.11	37.38	37.65	37.92	38.19	38.46	38.73
6.7	39.0	39.3	39.6	39.9	40.2	40.5	40.8	41.1	41.4	41.70
6.8	42.0	42.33	42.66	42.99	43.32	43.65	43.98	44.31	44.64	44.97
6.9	45.3	45.64	45.99	46.33	46.68	47.02	47.37	47.71	48.06	48.40
7.0	48.75	49.10	49.46	49.81	50.17	50.52	50.88	51.23	51.59	52.94
7.1	52.3	52.70	53.10	53.50	53.90	54.30	54.70	55.10	55.50	55.90
7.2	56.3	56.67	57.04	57.41	57.78	58.15	58.52	58.89	59.26	59.63
7.3	60.0	60.37	60.74	61.11	61.48	61.85	62.22	62.59	62.96	63.33
7.4	63.7	64.08	64.46	64.84	65.22	65.60	65.98	66.36	66.74	67.12
7.5	67.5	67.87	68.24	68.61	68.98	69.35	69.72	70.09	70.46	70.83
7.6	71.2									

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-467E	Breakers, Paving: Pheumatic

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.