INCH-POUND

MIL-B-467E
AMENDMENT 1
20 May 1991

MILITARY SPECIFICATION

BREAKERS, PAVING: PNEUMATIC

This amendment forms a part of MIL-B-467E, dated 17 November 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.1, line 2, delete "mode" and substitute "made".
line 3, after "forged", insert "or hardened".

PAGE 4

3.1.1, delete in its entirety and substitute:

"3.1.1 Performance. Each size breaker shall operate on compressed air pressures of 70 and 100 pounds per square inch gage (lb/psig). The size 60 breaker shall break a 5.00-inch or thicker slab of portland cement concrete and the size 80 breaker shall break a 6.00-inch or thicker slab of portland cement concrete with each slab having a compressive strength of not less than 5000 (lb/psi). Each concrete slab shall be broken into sections having a top surface area not greater than 35.00 square inches without breaker malfunction, damage, scored parts, wear of piston or cylinder diameter of more than 0.001 inch, or absence of oil vapor in exhaust air when tested as specified in 4.5.2.2."

PAGE 5

3.4.1, line 2, delete "with each other".

3.5.1, delete and substitute:

"3.5.1 Backhead assembly. The backhead assembly shall include a housing, T-handle with throttle lever and hose connection swivel tube with coupling."

3.5.1.1, after "forged", insert "or hardened".

3.5.4, delete in its entirety and substitute:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

"3.5.4 Cylinder assembly. The cylinder assembly shall consist of a cylinder and piston."

3.5.4.1, line 1, after "forged", insert "or hardened".

3.5.4.2, line 1, delete "be reversible and".

3.5.6, delete in its entirety and substitute:

"3.5.6 Fronthead assembly. The fronthead assembly shall consist of a chuck housing with retainer."

3.5.6.1, delete in its entirety and substitute:

"3.5.6.1 Liner. When a nonreplaceable chuck housing is furnished, the housing shall be equipped with a replaceable liner."

PAGE 6

3.5.6.4, delete in its entirety and substitute:

"3.5.6.4 Air strainer. When an air strainer is furnished (see 6.2), the air strainer or screen shall be replaceable and shall not be subjected to damage when the air supply line is connected or disconnected from the air inlet connection."

3.7.1, delete in its entirety and substitute:

"3.7.1 Spike driver. The breaker shall have the capability for use as a railroad spike driver using the standard fronthead and spike driving tool with detachable shank, or converting to a fronthead specifically intended for driving railroad spikes."

PAGE 7

3.7.1.2, delete in its entirety and substitute:

"3.7.1.2 Sheeting driver. The 80-pound breaker shall be capable of driving 2.00- and 3.00-inch planks using a sheeting driving tool with detachable shank, or shall be convertible for use as a sheeting driver with a fronthead replacement unit constructed specifically for driving sheeting and planks."

3.7.3, second sentence, delete and substitute: "The oil reservoir shall have a capacity for not less than 2 hours of continuous operation while operating at 90 psig at the tool."

PAGE 8

3.11, delete in its entirety and substitute:

"3.11 Noise limits. The noise produced by the paving breakers shall conform to MIL-STD-1474 requirements, with the exception of MIL-STD-1474, 5.2, 5.3, and 5.4, when tested in accordance with 4.5.2.7. The provisionos MIL-STD-1474, 4.2 and 4.3 shall apply if and only if MIL-STD-1474, 5.1.1.2 procedures have been

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

"pursued and documented to the satisfaction of the procuring activity and written permission to exceed the 85 dB(A) limit is obtained from the contracting officer. Hazard signs shall conform to MIL-STD-1474, 4.2, except the sign will state "HEARING PROTECTION REQUIRED WITHIN (specify) FEET". The sign shall be readable at the distance indicated on the sign."

PAGE 9

4.4.1, 4.4.2, and 4.4.3, delete in their entirety and substitute:

"4.4.1 Sampling. Sampling shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and IIa. The sample unit shall be one completely finished breaker."

"4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. Presence on one or more defects shall be cause for rejection.

"4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.6."

PAGE 10

Table III, delete "Major" and "Minor".

112, delete and substitute:

"112. Replaceable liner not furnished, when required. 3.5.6.1"

PAGE 11

4.5.2.1, lines 8 thru 10, delete last sentence and substitute: "A slab of portland cement concrete having a compressive strength of 5000 psi, not less than 5.00- or 6.00-inches thick as applicable (see 3.1.1), and each having sufficient surface area, shall be made available for testing (see 4.5.2.2)."

4.5.2.2, line 4, after "35 square inches.", add: "Check capacity of oil reservoir for compliance with 3.7.3."

4.5.2.2.1 Attachments. When furnished, the spike driver and sheeting driver shall be operated for not less than 10 hours each. The spike driver shall drive railroad spikes and the sheeting driver shall drive planks of 2- and 3-inch thickness. Failure of the breaker to convert to and operate as a spike driver and a sheeting driver shall constitute failure of this test."

4.5.2.6, line 1, after "breaker", add "(see 3.1.1)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review activities:
Army - AT
Air Force - 84
DLA - CS

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 3820-0195

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:31Z
Check the source to verify that this is the current version before use.