MIL-E-463B
INTERIM AMD. 2 (AR)
15 APRIL 1977
SUPERSEDES
INTERIM AMD. 1 (MU)
22 MARCH 1967

INTERIM AMENDMENT

MILITARY SPECIFICATION

ETHYL ALCOHOL (FOR ORDNANCE USE)

This Interim Amendment is issued for use by the U. S. Army Armament Research and Development Command with Military Specification MIL-E-463B dated 14 May 1962.

Page 1, paragraph 1.2 Classification. - Add the following:

"Grade 3 Delete "Benzene", substitute "Toluene"

"Grade 5 - 95.0 percent by volume (see 3.1.5)

Grade 6 - 88.3 percent by volume (see 3.1.6)".

Page 1, paragraph 2. APPLICABLE DOCUMENTS. - Add the following:

"2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials

ASTM D 1364	Water in Volatile Solvents (Fischer Reagent Titration Method)

(Application for copies should be addressed to the American Society for Testing, 1916 Race Street, Philadelphia, Pennsylvania, 19103)."

Page 2, 3.1 Material, Table 1 Delete "Benzene", substitute "Toluene"

Page 2. - Add new paragraphs as follows:

"3.1.5 Applicable to Grade 5. Grade 5 shall be made by mixing 100 gallons of anhydrous ethyl alcohol with 5 gallons of anhydrous methyl alcohol.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/4224

FSC 6810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:30Z
Check the source to verify that this is the current version before use.

"3.1.6 Applicable to Grade 6. Grade 6 shall be made by mixing 100 gallons of either anhydrous SD3A Alcohol or Grade 5 Alcohol with 5 gallons of ethyl acetate and 1 gallon of methyl isobutyl ketone."

Page 2, Table I, Chemical and Physical Properties. - Add Grade 5 and 6 as follows:

	Grade 5	Grade 6
Ethyl alcohol by volume, min. percent	95.0	88.3
Acidity, grams per 100 ml as acetic acid, max.	0.01	0.01
Water, percent by weight, max.	0.3	0.3
Methyl alcohol, percent by volume, max.	5.0	4.5
Ethyl acetate, percent, by volume, max.	...	5.4
Methyl isobutyl ketone, percent by volume, max.	...	1.5

Page 5, 4.3.2, Delete "Benzene" wherever it appears and substitute "toluene".

Line 4, Delete "5" substitute "3".

Page 6, 4.3.2.1, Delete "Benzene" wherever it appears and substitute "toluene".

4.3.2.2, Delete "Benzene" and substitute "toluene"

4.3.2.2.2, Delete "Benzene" wherever it appears and substitute "toluene".

4.3.2.2.3, Delete "Benzene" wherever it appears and substitute "toluene".

4.3.2.3, Delete "Benzene" wherever it appears and substitute "toluene".

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:30Z
Check the source to verify that this is the current version before use.

Page 7, - Add 4 new paragraphs as follows:

"4.3.7 Water. The percent by weight of water present shall be determined in accordance with ASTM Method D1364, Part 20.

4.3.8 Methyl alcohol. The methyl alcohol content shall be determined using a suitable method that has been approved by the contracting officer.

4.3.9 Ethyl acetate. The ethyl acetate content shall be determined by using a suitable method that has been approved by the contracting officer.

4.3.10 Methyl isobutyl ketone. The methyl isobutyl ketone content shall be determined using a suitable method that has been approved by the contracting officer".

Custodian:
Army - AR

Preparing Activity:
Army - AR

Project Number 6810 - AA78

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:30Z
Check the source to verify that this is the current version before use.