INCH-POUND

MIL-E-463B
INTERIM AMENDMENT 3 (AR)
15 February 1994
SUPERSEDING
INTERIM AMENDMENT 2 (AR)
15 APRIL 1977

MILITARY SPECIFICATION

ETHYL ALCOHOL (FOR ORDNANCE USE)

This interim amendment is approved for use within the US Army Armament, Munitions and Chemical Command, with Military Specification MIL-E-463B dated 14 May 1962.

PAGE 1

1.2 Classification. Add the following:

"Grade 3 Delete "Benzene", and substitute "Toluene"

"Grade 5 - 95.0 percent by volume (see 3.1.5)

Grade 6 - 88.3 percent by volume (see 3.1.6)".

2. APPLICABLE DOCUMENTS: Add the following:

"2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials

ASTM D 1364	Water in Volatile Solvents (Fischer Reagent Titration Method)

(Application for copies should be addressed to the American Society for Testing, 1916 Race Street, Philadelphia, Pennsylvania, 19103)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:30Z
Check the source to verify that this is the current version before use.

PAGE 2

3.1 Material. Table 1, Delete "Benzene", substitute "Toluene"

* 3.1.2 Delete "the addition of benzene", substitute "the addition of toluene".

* 3.1.3 Delete "the addition of benzene", substitute "the addition of toluene".

Add new paragraph as follows:

"3.1.5 Applicable to Grade 5. Grade 5 shall be made by mixing 100 gallons of anhydrous ethyl alcohol with 5 gallons of anhydrous methyl alcohol."

"3.1.6 Applicable to Grade 6. Grade 6 shall be made by mixing 100 gallons of either anhydrous SD3A Alcohol or Grade 5 Alcohol with 5 gallons of ethyl acetate and 1 gallon of methyl isobutyl ketone."

Table I. Chemical and Physical Properties - Add Grade 5 and 6 as follows:

	Grade 5	Grade 6
Ethyl alcohol by volume, min. percent	95.0	88.3
Acidity, grams per 100 ml as acetic acid, max.	0.01	0.01
Water, percent by weight, max.	0.3	0.3
Methyl alcohol, percent by volume, max.	5.0	4.5
Ethyl acetate, percent by volume, max.	...	5.4
Methyl isobutyl ketone, percent by volume, max.	...	1.5

PAGE 5

4.3.2 Delete "Benzene" wherever it appears and substitute "toluene".

Line 4, Delete "5" and substitute "3".

PAGE 6

4.3.2.1 Delete "Benzene" wherever it appears and substitute "toluene".

4.3.2.2 Delete "Benzene" and substitute "toluene".

4.3.2.2.2 Delete "Benzene" wherever it appears and substitute "toluene".

Source: https://assist.dla.mil -- Downloaded: 20261O-16T07:30Z
Check the source to verify that this is the current version before use.

4.3.2.2.3 Delete "Benzene" wherever it appears and substitute "toluene".

4.3.2.3 Delete "Benzene" wherever it appears and substitute "toluene".

PAGE 7

4.3 Test methods and procedures. Add 4 new paragraphs as follows:

"4.3.7 Water. The percent by weight of water present shall be determined in accordance with ASTM Method D1364, Part 20.

4.3.8 Methyl alcohol. The methyl alcohol content shall be determined by using a suitable method that has been approved by the contracting officer.

4.3.9 Ethyl acetate. The ethyl acetate content shall be determined by using a suitable method that has been approved by the contracting officer.

4.3.10 Methyl isobutyl ketone. The methyl isobutyl ketone content shall be determined by using a suitable method that has been approved by the contracting officer."

The margins of this amendment are marked with asterisks to indicate where the changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 6810-A089)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:30Z
Check the source to verify that this is the current version before use.