INCH-POUND

MIL-N-00494B (AR)
AMENDMENT 2
30 June 1992

SUPERSEDING
AMENDMENT 1
22 June 1990

MILITARY SPECIFICATION

NITROGUANIDINE

This Amendment forms a part of Military Specification MIL-N-00494B (AR) dated 26 October 1984 and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.2: Add the following method: "ASTM D1125 - Test Methods for Electrical Conductivity and Resistivity of Water".

PAGE 11

4.4.3: Delete "and one shift's production of nitroguanidine" and substitute "and one half shift's production of nitroguanidine".

4.4.3.2: Delete 4.4.3.2 in its entirety and substitute the following:

"4.4.3.2 Sampling from units of product. A single drum shall be selected at random from each unit of product selected for sampling. A single sample of about one pound of nitroguanidine shall be taken from the drum in accordance with the sampling procedure for solids in ASTM E300. The sample of nitroguanidine shall be analyzed in duplicate by the methods given in section 4.5 of this specification to ascertain conformance with the requirements given in section 3 of this specification."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:35Z
Check the source to verify that this is the current version before use.

PAGE 15

4.5.3:

Delete "A 200 milliliter portion... shall be added" and substitute "A 200 milliliter portion of distilled or deionized water shall be added. The deionized water shall be passed through a carbon column first to remove dissolved organics. The distilled or deionized water shall have an electrical conductivity of 1.0 micro mho/cm or less when determined IAW ASTM D1125."

* Delete "buffer solution at pH 8.0." and substitute "buffer solutions at pH 4.0 and 7.0."

PAGE 16

4.5.4: Delete "distilled water" and substitute "distilled or deionized water".

4.5.6:

Delete "The solution shall then be allowed to stand for at least 10 hours" and substitute "The solution shall then be allowed to stand for at least 1 hour".

Delete "warm distilled water" and substitute "warm distilled or deionized water".

PAGE 18

5.1.1.1: Delete "capacity approximately eighteen gallons" and substitute "with a maximum capacity of twenty gallons".

5.1.1.1.a: Delete "14 inches in diameter and 27 inches in height" and substitute "15.5 inches in diameter and 24.4 inches in height".

5.1.1.1.c: Delete "minimum thickness of 0.108 inch" and substitute "minimum thickness of 0.120 inch".

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:35Z
Check the source to verify that this is the currentversion before use.

5.1.1.1.h: Delete paragraph 5.1.1.1.h in its entirety.

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1376-A432)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:35Z
Check the source to verify that this is the current version before use.