INCH-POUND

MIL-S-0027178H(84)
10 January 1989

USED IN LIEU OF
MIL-S-27178G
17 DECEMBER 1982

MILITARY SPECIFICATION

SNOW SWEEPER, TOWED, ROTARY, AIRBLAST

This military specification has been prepared by WR-ALC/MMVRG based upon currently available technical information but it has not been approved for promulgation as a coordinated revision of MIL-S-27178G. It is subject to modification. However, pending its promulgation as a coordinated military specification, it may be used in acquisition.

1. SCOPE.

1.1 Scope. This specification covers a towed, rotary, snow airblast sweeper for removing snow and slush from runways, taxiways and aircraft parking ramps.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

W-B-131	Battery, Storage (Vehicular, Ignition, Lighting and Starting)
VV-F-800	Fuel Oil, Diesel

MILITARY

MIL-P-514	Plates, Identification, Instructions and Marking, Blank

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMVRG, Robins AFB, GA 31098-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 3825

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

MIL-STD-12	Abbreviations for Use on Drawings, and on Specifications, Standards and Technical Documents
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-143	Standards and Specifications, Order of Precedence, for the Selection of
MIL-STD-209	Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment
MIL-STD-461	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462	Electromagnetic Interference Characteristics, Measurements of
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-831	Test Reports, Preparation of
MIL-STD-889	Dissimilar Metals
MIL-STD-1223	Nontactical Wheeled Vehicle Treatment, Painting, Identification Marking, and Data Plate Standards

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DOT)

Federal Motor Carrier Safety Regulations

(Applications for copies should be addressed to the Department of Transportation, Federal Highway Administration, Washington DC 20591.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

J293	Vehicle Grade Parking Performance Requirements
J318	Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers-Trucks, Truck-Tractors, and Trailers
J360	Motor Vehicle Grade Parking Performance Test Code
J534	Lubrication Fittings
J560	Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable
J786	Brake System Road Test Code-Truck, Bus and Combination of Vehicles
J845	360 Degree Warning Lamp for Authorized Emergency, Maintenance and Service Vehicles
J992	Brake System Performance Requirements-Truck, Bus and Combination of Vehicles
J1077	Measurement of Exterior Sound Level of Trucks with Auxiliary Equipment
J1292	Automobile, Truck, Truck-Tractor, Trailer and Motor Coach Wiring
J1349	Engine Power Test Code-Spark Ignition and Diesel

Source: https://assist.dla.mil -- Downloaded: 20260-20T11:04Z
Check the source to verify that this is the current version before use.

(Application for Copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale PA 15096.)

THE TIRE AND RIM ASSOCIATION

Year Book

(Application for copies should be addressed to The Tire and Rim Association Incorporated, 3200 West Market Street, Akron OH 44313.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

3.1 Design.

3.1.1 Selection of specifications and standards. Specifications and standards, necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.1.2 Materials. Materials shall be as specified herein. Materials not specifically covered by this specification or referenced document shall be suitable in every respect for this type equipment. Except as otherwise specified, wood shall not be used.

3.1.2.1 Protective treatment. Materials that are subject to deterioration shall be protected in such a manner that shall in no way prevent compliance with the performance requirements of this specification. Protective coatings that will chip, crack or scale with age or extremes of climatic conditions shall not be used.

3.1.2.2 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.1.3 Design and construction. Except as specified herein, the sweeper, components, assemblies and accessories to be delivered under contract shall be standard or optional items which meet or exceed the requirements of this specification. In addition to the manufacturer's standard sweeping unit, the sweeper shall be supplied with equipment as specified herein and shall conform to the requirements of this specification. The sweeper shall be constructed so that parts do not work loose in service and shall withstand the loads, shocks, vibrations and other conditions incident to operation, shipping and storage with minimum loss of time for maintenance, repair and servicing. The design of the sweeper shall ensure safe, efficient and economical operation. All assemblies, controls and installed equipment shall be located so that there is no adverse interference with each other, or with the operation, and shall be readily accessible for maintenance, operation, removal and replacement.

3.1.3.1 Reliability. The sweeper, including all components, shall have a Mean-Time-Between-Failures (MTBF) of not less than 250 hours demonstrated at an 0.9 confidence level. The sweeper shall be designed for a life expectancy of at least 10 years.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

3.1.3.2 Maintainability. The sweeper shall be designed and constructed to provide the following:

a. A minimum number of parts consistent with the performance required herein.

b. A minimum amount of time for assembling, disassembling, locating trouble sources and maintaining the sweeper. Where practical, components shall be located for rapid inspection and recognition of potential failure.

c. Ease of adjusting, servicing and replacing parts and components.

d. Use of readily available standard tools and equipment for maintenance.

e. Maintenance with a minimum number of tools.

f. Mean corrective maintenance downtime of no greater than one hour.

g. Maximum corrective maintenance downtime of no greater than four hours.

h. Maximum total downtime to perform all daily scheduled maintenance and servicing tasks of no greater than 35 minutes.

The sweeper shall be designed so that one mechanic, using common hand tools, can perform the following maintenance operations within the time specified:

(1) Remove, replace and adjust all engine drive belts, with the exception of power take-off (PTO) belts - 3/4 hour.

(2) Remove and replace alternator - 1/2 hour.

(3) Remove and replace all filters, screens and strainers in all hydraulic systems - one hour.

(4) Drain engine coolant system, remove and replace engine coolant system hoses, and refill system - 3/4 hour.

(5) Drain engine lubricating oil, remove and replace oil filter element(s) and refill crankcase - one hour.

(6) Remove and replace fuel filter element(s) - 1/2 hour.

(7) Disconnect battery cables, remove and replace batteries and reconnect battery cables - 1/2 hour.

(8) Remove and replace starter - one hour.

(9) Remove broom core (if required), remove and replace all broom bristles, and replace core - 1 hour.

(10) Adjust broom pattern - 1/6 hour.

3.1.3.3 Foolproofness. Where improper installation of an item could cause a malfunction, an asymmetric mounting system shall be provided, where practical, to ensure proper mounting of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

3.1.3.4 Fastening devices. All screws, bolts, nuts, pins and other fastening devices shall be properly designed, manufactured and installed with adequate means of preventing loss of torque or adjustment. Tapped aluminum threads shall have a minimum thread engagement of at least two times the nominal fastener diameter.

3.1.3.5 Servicing provisions. Drains, grease fittings, lines and check points for all components shall be so located that they are readily accessible and do not require special tools for proper servicing. All drain plugs shall be located, or shall be fitted with extensions as necessary, so that the fluid being drained does not strike structural members and/or adjacent components.

3.1.3.6 Lubrication. All parts normally requiring grease for lubrication shall be provided with lubrication fittings in accordance with SAE J534. Where the use of high lubrication pressures may damage grease seals, a pressure relief device shall be provided. Extended fittings shall be provided to lubricate parts or assemblies which are not readily accessible for direct lubrication or which are likely to be overlooked because of inaccessibility.

3.1.3.7 Component protection. All space in which work is performed during operation, service and maintenance of the sweeper shall be free of hazardous protrusions, sharp edges or other features which may cause injury to personnel. All rotating and reciprocating parts and all parts subject to high operational temperatures or subject to being electrically energized, that are of such nature or so located as to be hazardous to personnel, shall be guarded or insulated to the extent necessary to eliminate the hazard.

3.1.3.8 Foreign object damage. All loose metal parts, such as pins and valve caps, shall be securely attached so they cannot become separated from the sweeper.

3.1.4 Environmental conditions. The sweeper shall be capable of satisfactory storage and operation under the following environmental conditions:

a. Full-time exposure to temperatures ranging from -40°F to +125°F for operation: -60°F to +160°F for storage.

b. Full-time exposure to relative humidities up to 100 percent.

3.1.5 Weight distribution. The weight distribution of the sweeper in any loading condition shall not be unbalanced or improperly distributed. The difference in load between the left and right wheels of any axle shall not exceed 2.5 percent of the total load on the axle.

3.1.6 Electromagnetic interference. The sweeper shall comply with the requirements of MIL-STD-461, Class C1, Group II for electromagnetic interference, except that the limits for UM03 (Figure 8-1) shall be relaxed by 20dB.

3.1.7 Sound levels.

3.1.7.1 Equipment operation sound level. The maximum sound level produced by the sweeper shall not exceed 85dBA when measured in accordance with the moving test procedure of SAE J1077. In addition, a microphone shall be positioned in the cab at approximately the level of and six inches away from the operator's ear. The sound level measured in the cab shall not exceed 85 dBA when the equipment is operated as described in the moving test procedure.

3.1.8 Lifting and tiedown attachments. When specified (see 6.2), lifting and tiedown attachments in accordance with MIL-STD-209, Type III shall be provided to enable the sweeper, without the broom, to be lifted in its normal position without damage to the sweeper or its components. The attachments shall be so located that adequate clearance will be provided between lifting slings and all exterior parts of the sweeper when hoisting. Spreader bars will be permitted. Each attachment shall be of sufficient strength to carry

Source: https://assist.dla.mil -- Downloaded: 202640-20T11:04Z
Check the source to verify that this is the currentversion before use.

the total weight of the sweeper. Markings shall clearly indicate that the attachments are intended for lifting, tying down, or lifting and tying down the sweeper.

3.2 Performance.

3.2.1 Mobility. The fully loaded and equipped sweeper shall:

a. Effectively remove, down to the bare pavement, two inches of fresh fallen snow having a density of approximately 5 pounds per cubit foot, or a reduced depth of proportionately higher density snow, at a rate of 693 tons per hour minimum. The unit shall also be capable of sweeping at speeds of up to 35 mph.

b. Remove 90 percent of loose dry sand spread on a level paved surface at a density of 0.83 pounds per square foot while operating at a minimum speed of 20 mph.

c. Be capable of being towed in the travel configuration (broom and air nozzle(s) raised) at not less than 50 mph.

d. Be capable of performing as describe in subparagraph a. for not less than 100 hours without requiring any maintenance operations other than lubrication, as recommended by the manufacturer, and broom adjustments.

e. Comply with all service brake performance requirements of SAE J992 when the service brakes are used in conjunction with the prime mover brakes.

f. Comply with all parking brake performance requirements of SAE J293, when the parking brakes are used in conjunction with the prime mover parking brakes and also when the sweeper is standing alone and facing either up or downgrade.

3.3 Chassis.

3.3.1 Engine. The sweeper shall be equipped with a commercial liquid cooled diesel engine (see 6.3.1). The total power output required by all items driven by the engine shall not exceed its net power output rating at 2,000 feet elevation, determined in accordance with SAE J1349. The engine shall demonstrate the performance characteristics specified herein when using diesel fuel in accordance with VV-F-800.

3.3.1.1 Engine housing. The engine and blower system shall be completely enclosed by a housing constructed of not less than 16-gauge steel or fiberglass of strength equal to 16-gauge steel. The housing shall have a canopy hinged at the rear and lifted by hydraulic cylinders. The cylinders shall be actuated by an electrically operated pump such that it shall not be necessary to operate the engine in order to lift the canopy. A positive means of locking the canopy in the raised position shall be furnished. It shall be possible to lift the canopy manually in the event of power assist failure. When the canopy is in the raised position, it shall be possible for a person standing on the ground to service the engine and all systems and components contained in the housing. If it is necessary for a person to enter the housing to perform maintenance tasks, steps shall be provided inside the housing to allow ease of entry and exit. The housing shall be insulated to reduce noise produced by the engine and blower system.

3.3.1.2 Engine cooling system. The engine shall be equipped with a cooling system capable of satisfactory performance under the environmental conditions specified herein; coolant temperature shall not exceed the engine manufacturer's recommended maximum. Expansion tanks of sufficient capacity for expansion of all coolant in the system shall be provided. Devices to provide automatic engine shutoff in the event of high coolant temperature or low coolant level shall be furnished and installed on the engine.

Source: https://assist.dla.mil -- Downloaded: 20261-20T11:04Z
Check the source to verify that this is the current version before use.

3.3.1.3 Engine starting system. The engine shall start within 15 seconds in any ambient temperature within the required operating range of the sweeper. Installed glow plugs, fluid starting aids and heat from the winterization system may be used to facilitate engine starting under the following conditions:

TEMPERATURE RANGE (DEGREES F)	STARTING AIDS PERMITTED
40 through 125	None
1 through 39	Glow plugs and fluid starting aids
-40 through 0	Glow plugs, fluid starting aids and heat from the winterization system

The starting system shall be equipped with an interlock device to prevent starter engagement when the engine is running. Either a 12 or 24 volt starting system shall be furnished. If a fluid starting aid system is furnished, it shall be the measured shot type having a reservoir of not less than 12 fluid ounces and shall be inoperative with the engine warm. The control for the ether injection shall be located on the fixed control panel (see 3.3.8).

3.3.1.4 Air cleaner. The engine air inlet shall be provided with an air cleaner of design and capacity as recommended by the engine manufacturer for the operating conditions as specified herein. The engine intake air shall be drawn from outside the engine housing. A precleaner shall be furnished to remove snow and debris from the air before it is drawn into the engine air cleaner. The precleaner/air intake shall be located, as much as practical, to avoid the direct intake of snow.

3.3.2.1 Service brakes. The sweeper shall be equipped with full air brakes on all rear wheels. Brakes shall be either drum or disc type and shall conform to Federal Motor Carrier Safety Regulations 393.40, 393.41, 393.43(d), 393.43(e), 393.46, 393.47 and 393.52. The brake system shall include piping, hose connections, gladhands in accordance with SAE J318, dummy gladhands equipped with security chains, air reservoirs, automatic slack adjusters, relay emergency valves with "no-bleed-back" feature and all other parts and connections required for a complete air brake system. A drain shall be provided on each reservoir and shall be readily accessible for service. The gladhands shall be located at the forward end of the frame in a protected location.

3.3.2.2 Parking brakes. The sweeper shall be equipped with parking brakes of the spring applied type on each rear wheel.

3.3.3 Frame. The frame shall be the manufacturer's standard commercial (see 6.3.1) type for the sweeper model furnished and shall be of adequate strength to support the sweeper and all components when fully equipped for operation. The frame shall be the tricycle type, supported by one wheel at the front end and by at least two wheels at the rear.

3.3.3.1 Towbar. A towbar, designed for towing by vehicles having a pintle hook height between 30 and 40 inches above ground level, shall be furnished. The towbar shall have a lunette eye with an inside diameter of 3 inches ± 1/32 inch. The lunette eye and towbar shall be designed to withstand a vertical force of 9,000 pounds minimum and shall be capable of towing a minimum gross trailer weight of 45,000 pounds.

3.3.4 Broom system.

3.3.4.1 Broom drive system. The broom assembly shall be driven by the manufacturer's standard commercial (see 6.3.1) closed loop hydrostatic system for the sweeper model furnished. The system shall, as a minimum, include a hydraulic pump powered by the engine, hydrostatic motor(s) to drive the broom core, a reservoir with fluid level indicator, an oil cooler and all necessary hoses and fittings. The pump

Source: https://assist.dla.mil -- Downloaded: 202610-20T11:04Z
Check the source to verify that this is the current version before use.

shall be the variable displacement type and a clutch mechanism shall be provided to disengage the pump from the engine to allow ease of engine startup and warmup operations in cold weather. The minimum size of the reservoir shall be equal to one minute of total system flow. The motor(s) shall be installed on the sweeping assembly such that torsional forces on the assembly do not result in differing sweeping patterns at either end when the broom is in operation. A pressure relief device shall be provided to relieve the system in the event of operating pressures above the manufacturer's recommended maximum. The system shall not lose fluid as a result of the actuation of the pressure relief. Devices shall also be provided to prevent the spillage of fluid in the event of hose failure. The reservoir shall be provided with a drain valve at the lowest point of the tank. The system shall be provided with safety devices for automatic shutdown in the event of high oil temperature or low oil level. A minimum 10 micron full flow by-pass type filter shall be installed on both the pressure and return sides of the loop. A minimum 10 micron no by-pass type filter shall be installed in the charge pump circuit. All filters shall incorporate restrictions gauges or devices to indicate when replacement is necessary. It shall be possible to replace the filters without draining the system. The broom speed shall be infinitely variable within the range of 0-675 revolutions per minute (rpm).

3.3.4.2 Clutch mechanism. A clutch shall be provided to disengage the broom drive system from the engine. The clutch shall be the manufacturer's standard commercial (see 6.3.1) type for the sweeper model furnished and shall be readily accessible for maintenance. The control for engaging and disengaging the clutch shall be manually operated and shall be located adjacent to the fixed control panel.

3.3.4.3 Broom assembly. The broom assembly shall consist of steel wire fillers together with all necessary mounting devices on a power driven core assembly. The diameter of the core shall be maintained for the full length around the true center within a tolerance of plus or minus 1/64-inch. The core shall be balanced to assure vibration free operation under all operating conditions specified herein. The diameter of the broom shall be 36 inches plus or minus 1/2-inch. The broom fillers shall be the manufacturer's standard commercial (see 6.3.1) type for sweeper model furnished. Provisions shall be made for removing one or both of the broom core endplates.

3.3.4.4 Broom mounting and positioning. The entire broom assembly shall be mounted to the frame such that the broom may be pivoted to the right or left side of the sweeper. The broom assembly shall pivot not less than 40 degrees left or right of the longitudinal axis of the sweeper. Complete swinging of the broom from 40 degrees right to 40 degrees left or vice versa shall take not less than 15 seconds nor more than 30 seconds at any ambient temperature within the range specified in 3.1.4.a. The cleared path perpendicular to the direction of travel of the sweeper shall be not less than 10.5 feet when the broom assembly is angled 40 degrees to the right or left. Means shall be provided to adjust the broom contact with the paved surface to compensate for broom wear and establish sweeping patterns. The broom adjustment shall allow vertical motion of the broom core with respect to the paved surface over a minimum range of 9 inches in increments such that the sweeping pattern does not change by more than 1/2-inch at any one adjustment. A system shall be provided whereby the broom assembly may be brought from any operating position to a "park" position in which the longitudinal axis of the broom is parallel to the longitudinal axis of the sweeper. When in this position, the entire broom assembly shall be automatically lifted to provide not less than 5 inches of ground clearance. The unit shall be capable of being towed at 50 mph while the broom assembly is in this position. A positive means of locking the broom assembly in the park position shall be provided. When the broom assembly is in the parked position, the width of the sweeper shall not be more than 9 feet. Placing the broom in and removing the broom from the park position shall not change the preset sweeping pattern. All broom assembly positioning operations shall be controlled by electrohydraulics in the same manner as the lifting of the engine canopy so that the assembly may be pivoted, placed in the parked configuration or manipulated to adjust the sweeping pattern while the engine is not operating. It shall also be possible to control the positioning of the broom assembly manually in the event of power assist failure. The controls for the parking and adjusting operations shall be located on the fixed control panel. The control for angling the broom shall be located on the portable control panel in the cab of the prime mover.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

3.3.4.5 Broom shroud. A shroud or cover shall be provided over the broom to prevent snow and debris picked up by the broom from being thrown back on the sweeper and the swept area. The shroud shall be constructed of steel of a thickness suitable for this purpose and shall be designed to prevent snow from adhering to the upper or lower surfaces. The distance from the under surface of the shroud to the surface of the broom shall be adjustable to provide uniform broom clearance and prevent snow from being carried over the broom during high speed sweeping operations.

3.3.4.6 Casters. When required by the manufacturer's standard commercial (see 6.3.1) design, the broom assembly shall be supported by heavy duty casters mounted at each end. The casters shall be mounted such that they will always travel in the swept path of the broom. The vertical centerline of the caster kingpins shall remain perpendicular to the ground during sweeping pattern adjustment. The casters shall be free to swivel through horizontal angles of 360 degrees without interference or tire scuffing. The casters shall have pneumatic tires suitable for this application under all operating conditions specified herein, and the complete caster assemblies shall be easily removable for replacement.

3.3.4.7 Broom filler replacement. Means shall be provided to replace worn broom filler elements. Replacement shall be accomplished with ordinary hand tools and shall not require disconnection or removal of the broom shroud or hydraulic lines. Replacement procedures requiring the use of dial meters or runout indicators to assure alignment shall not be acceptable. It shall be possible for one person to replace an entire brush of water type fillers in not more than 1 hour. It shall be possible to replace an entire brush of cassette type fillers in not more than 30 minutes.

3.3.5 Blower system. The blower system shall, as a minimum, include a high volume fan, and all necessary ducting to provide a suitable air intake and discharge system.

3.3.5.1 High volume fan. The fan shall be driven by the diesel engine through a suitable clutch or coupling that shall allow the engine to be started without load from the fan and shall allow fan over-run after the engine has been shut down. The fan shall be completely enclosed within the engine housing and shall be the noiseless type. The fan shall deliver a minimum of 15,500 cubic feet per minute (cfm) of air at a minimum velocity of 250 mph.

3.3.5.2 Air intake and discharge system. The fan intake ducting shall be located to avoid direct intake of snow during operation. The minimum ground clearance of the ducting shall be 5 inches. The fan output ducting and discharge nozzle(s) shall be designed and sized to allow the passage of air at the conditions specified in 3.3.5.1. The direction of air discharge shall be perpendicular to the direction of travel of the sweeper and shall be toward the side to which the broom assembly is angled. When the broom assembly angle is changed from right to left or vice versa, the direction of the air blast shall automatically correspond to the direction of the broom. It shall also be possible to position the air discharge nozzle(s) or direct the air stream independently of the broom to permit the clearance of snow from runway lights. Control of this feature shall be possible from the cab of the prime mover. When the broom assembly is placed in the parked position, the air discharge nozzle(s) shall be automatically lifted to a transport position providing not less than 5 inches of ground clearance. A positive means of locking the discharge nozzle(s) in the transport position shall be furnished. The positioning of the discharge nozzle(s) shall be controlled by electrohydraulics in the manner of the broom and engine housing so that it shall not be necessary to operate the diesel engine while positioning the nozzle(s). It shall be possible to manually position the nozzle(s) in the event of power assist failure.

3.3.6 Wheels and tires. The sweeper shall be equipped with at least three wheels (exclusive of casters), one front and two rear. The front wheel assembly shall be attached to the towbar and swivel mounted in a manner that will allow the wheel to be changed without exposing the wheel bearings. Wheel bearings shall be sealed to prevent loss of lubricant and entrance of moisture and abrasives. The front wheel shall be positioned such that debris from sweeping is not thrown onto the wheel during sweeping operations to either side. The tires shall be pneumatic, either tube or tubeless type, with manufacturer's standard

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

commercial (see 6.3.1) tread. The rims, tires, and tubes, if used, shall be in accordance with Tire and Rim Association recommendations for this application.

3.3.7 Fuel system.

3.3.7.1 Fuel tank. A fuel tank shall be provided with a capacity sufficient for 8 hours of operation of the sweeper at maximum capacity. The tank shall have a fill opening of three inches minimum readily accessible to personnel standing on the ground. It shall be located and mounted so as to provide maximum protection from damage.

3.3.7.2 Fuel filter. At least one filter of the fuel-water separator type shall be located in the fuel line between the fuel tank and the engine. It shall be installed so that the element can be readily serviced without removing surrounding equipment. Unless the filter is mounted higher than the fuel tank, a shutoff valve shall be included in the inlet line to the filter.

3.3.8 Instruments and controls. A fixed control panel mounted on the sweeper and a portable control panel in the cab of the prime mover shall be furnished.

3.3.8.1 Fixed control panel. The fixed control panel shall be mounted on the exterior of the engine housing. The panel shall be weatherproof and shall contain at least the following instruments and controls:

a. Engine start/run/stop switch.

b. Ether injection control (if required).

c. Engine throttle control.

d. Engine tachometer.

e. Engine hourmeter, having a totalizing mechanism not less than 9,999 hours.

f. Engine coolant temperature gauge.

g. Engine oil pressure gauge.

h. Voltmeter or charging indicator.

i. Fuel level gauge.

j. Hydraulic fluid temperature gauge.

k. Actuator switch for lifting of engine housing.

l. Actuator switches for floodlights and engine housing light.

m. Control for sweeping pattern adjustment.

n. Control for placing the broom in the park position.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T11:04Z
Check the source to verify that this is the current version before use.

3.3.8.2 Portable control panel. A portable control panel suitable for location in the cab of the prime mover shall be furnished. All cables connecting the control panel to the sweeper shall be enclosed in a single flexible rubber or neoprene conduit and shall extend at least 25 feet forward of the leading edge of the towbar. A weatherproof multipin type plug shall be provided in the cables. The plug shall be designed so that the female section may be connected to the rear cab wall of the prime mover. The male section shall then plug into the female section through the rear cab wall of the prime mover so that it shall not be necessary to route the cables for the control panel through a cab window. The plug shall be located such that there is a sufficient length of cable between the sweeper and the plug to reach the cab of the prime mover. The control panel shall contain the following minimum equipment:

a. Voltmeter or charging indicator.

b. Broom speed control.

c. Broom speed indicator.

d. Joystick-type control for angling the broom assembly.

e. Air stream/air discharge nozzle(s) direction control.

f. Actuator switches for flood lights and warning beacon.

3.3.9 Electrical system. The sweeper shall be equipped with a 12 or 24 volt electrical system. Wiring shall be weatherproof and color coded or numbered for easy identification. All circuits shall be protected by circuit breakers located in the engine housing so as to be readily accessible to a mechanic. A master switch shall be provided to disconnect the batteries from the electrical system.

3.3.9.1 Alternator. The engine shall be equipped with an alternator sufficient for operating all sweeper electrical components simultaneously. Minimum capacity of the alternator shall be 60 amperes.

3.3.9.2 Batteries. The sweeper shall be equipped with at least two 12 volt batteries, rated at a total of 1,800 CCA minimum. The batteries shall comply with the maintenance free characteristics of W-B-131. Batteries shall be so arranged and connected to provide sufficient capacity for engine starting in all conditions specified herein. The batteries shall be mounted in an acid resistant tray; a sliding carriage shall be provided if the batteries must be moved sideways to permit access for servicing or replacement.

3.3.9.3 Lighting. The sweeper shall be equipped with tail lights, parking lights, clearance lights, brake lights, turn signal lights and reflectors in accordance with Federal Motor Carrier Safety Regulations. The wiring for the lighting system shall be in accordance with SAE J1292 and shall terminate in a receptacle in accordance with SAE J560 for the connection of a truck-trailer jumper cable. The receptacle shall be located in a protected position at the forward end of the frame. The sweeper lights shall be activated by the prime mover.

3.3.9.3.1 Floodlights. Two floodlights shall be furnished and located in a protected position at the forward end of the frame. The lights shall completely illuminate the sweeper and the swept path during nighttime operation. The floodlights shall be activated by a switch on the fixed control panel and also by a switch on the portable control panel.

3.3.9.3.2 Warning beacon. At least one warning beacon shall be installed on top of the sweeper. The beacon shall be a yellow, Class 2, flashing type in accordance with SAE J845. The warning beacon shall be activated by a switch located on the portable control panel.

Source: https://assist.dla.mil -- Downloaded: 202640-20T11:04Z
Check the source to verify that this is the currentversion before use.

3.3.9.3.3 Engine housing light. A light shall be furnished inside the engine housing to facilitate nighttime maintenance and servicing. The light shall be activated by a switch located on the fixed control panel.

3.4 Winterization system. The sweeper shall be equipped with a winterization system to permit storage and operation in ambient temperatures as low as -40°F. Heaters shall operate on 110 volt alternating current (AC) and shall be wired through a junction block to a single three pronged (male) weatherproof slave receptacle for receiving external power and grounding the sweeper. A three wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the sweeper end and a standard weatherproof three pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77 (c) (7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperature without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with sweeper component operation and without loose excess wire. Provisions for storage of the cable shall be provided on the sweeper. Heaters shall be furnished as follows:

a. Coolant heater, 1,500 watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose. Engine thermostat, with an operating range of 170°F to 195°F, shall be installed.

b. Immersion type engine oil heater, 300 watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening.

c. Battery heater, having a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during sweeper exposure in ambient air temperatures as low as -40°F, and having a thermostat to limit the temperature of the electrolyte to not more than 80°F.

d. A fuel warmer or preheater shall be provided to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of -40°F to an outlet temperature of +9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.5 Finish and protective coatings.

3.5.1 Cleaning, painting, plating, anodic films and chemical treatments. Cleaning, painting, plating, anodic films and chemical treatments shall be in accordance with the manufacturer's standard commercial (see 6.3.1) practice. Lead and chromate free paint shall be utilized.

3.5.2 Finish. The exterior paint finish shall show no evidence of uneven application, curtains, runs, sags, orange peel, lack of adhesion or other defects.

3.5.2.1 Forest green. Unless otherwise specified (see 6.2), the color of the exterior finish shall be Forest Green, Color Number 24052 of FED-STD-595.

3.5.3 Rustproofing. Unless otherwise specified (see 6.2), the sweeper shall be rustproofed in accordance with the contractor's standard commercial (see 6.3.1) practice. The first article units shall not be rustproofed until after approval of the first article test report.

3.6 Markings. Markings for sweepers painted Forest Green shall be applied with black paint, Color Number 37038 of FED-STD-595.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

3.6.1 Identification markings. Unless otherwise specified (see 6.2), the sweeper shall be marked for the appropriate service in accordance with MIL-STD-1223.

3.7 Identification plates and data plates. All identification plates, instruction plates, data plates, etc., shall conform to MIL-P-514 and be of a size and shape consistent with the information required thereon. Abbreviations shall be in accordance with MIL-STD-12.

3.7.1 Identification plate. An identification plate, permanently marked in accordance with MIL-STD-130, shall be securely attached to the sweeper in a readily accessible location. The identification plate shall contain the following information:

NOMENCLATURE

MANUFACTURER'S MODEL NUMBER

MANUFACTURER'S SERIAL NUMBER

MANUFACTURER'S NAME

MANUFACTURER'S ADDRESS

MANUFACTURER'S SERVICE PHONE NUMBER

DATE OF MANUFACTURE

CONTRACT NUMBER

NATIONAL STOCK NUMBER

3.7.2 Control markings. All controls, valves, gauges and indicators used in the operation of the sweeper shall be identified by securely attached nameplates.

3.7.3 Operating instructions. Brief operating and precautionary instructions shall be permanently affixed near the appropriate controls in accordance with the manufacturer's standard commercial (see 6.3.1) practice. The instructions shall be clear, concise and adequate to enable operation of the sweeper without damage to the equipment or injury to personnel and shall refer to the components as identified by nameplates.

3.7.4 Lubrication plate. A lubrication plate shall be provided directing attention to all lubrication fittings and components which require lubrication. The plate shall identify the type and grade of lubricant required for all operational temperatures.

3.7.5 Transportation data plate. A transportation data plate shall be provided. The plate shall contain at least the following information:

a. Side and rear silhouette views of the sweeper.

b. Horizontal and vertical location of the center of gravity of the sweeper in transport condition.

c. Shipping weight.

d. Loading cubage.

e. Overall length, width and height.

Source: https://assist.dla.mil -- Downloaded: 202610-20T11:04Z
Check the source to verify that this is the current version before use.

3.8 Part numbering of interchangeable parts. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable.

3.9 Dimensions. The sweeper in the transport condition, including all equipment and accessories, shall not exceed the following dimensions:

a. Length: 38 feet

b. Width: 9 feet

c. Height: 8.5 feet

3.10 Welders. All welders employed in the fabrication of the sweeper shall be certified in accordance with the applicable requirements of the American Welding Society, or the American Society of Mechanical Engineers.

3.11 Welding. The surface parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall transmit stress without cracking or permanent distortion when the parts connected by the welds are subjected to test, proof and service loadings.

3.12 Screw assemblies. Unless torque is specified, threaded fasteners shall be tight and shall not work loose during testing or service usage.

3.13 Riveting. Riveting operations shall be performed to ensure tight fit and complete heading of the rivets.

3.14 Gear and lever assemblies. Gear and lever assemblies shall be properly aligned and meshed and shall be operable without interference, tight spots, loose spots or other irregularities. Where required for accurate adjustment, gear assemblies shall be free of backlash.

3.15 Cleaning. The sweeper shall be thoroughly cleaned. Loose, spattered or excess solder, welding slag, stray bolts, nuts and washers, rust, metal particles, pipe compound and other foreign matter shall be removed during and after final assembly.

3.16 Workmanship. The sweeper, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs and sharp corners and edges; accuracy of dimensions, surface finish and radii of fillets; thoroughness of soldering, welding, brazing, painting, wiring and riveting, marking of parts and assemblies; alignment of parts and tightness of assembly fasteners; etc.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for

Source: https://assist.dla.mil -- Downloaded: 202640-20T11:04Z
Check the source to verify that this is the currentversion before use.

acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of Tests. The inspection and testing of the sweeper shall be classified as follows:

a. First Article Testing (see 4.4).

b. Acceptance Testing (see 4.5).

4.3 Test conditions.

4.3.1 Apparatus. Apparatus used in conjunction with the testing specified herein shall be of laboratory precision type and shall be calibrated at proper intervals to ensure laboratory accuracy.

4.3.2 Data. During all testing specified herein, at least the following data, unless not applicable, shall be recorded at intervals not to exceed 30 minutes. Additional data and/or shorter intervals shall be provided as appropriate for any specific test.

a. Date.

b. Time started.

c. Time finished.

d. Ambient temperature.

e. Engine speed.

f. Engine oil pressure.

g. Engine coolant temperature.

h. Transmission oil temperature.

i. Engine hourmeter reading at the start and finish of each test.

j. Hydraulic fluid pressure at the pump outlet.

k. Hydraulic fluid temperature in the reservoir.

4.3.3 Preparation for tests. The sweeper, equipped with all specified equipment, shall be fully serviced and all equipment shall be prepared for immediate operation.

4.3.4 Test rejection criteria. Throughout all tests specified herein, the sweeper shall be closely observed for the following conditions, which shall be cause for rejection:

a. Failure to conform to design or performance requirements specified herein.

b. Spillage or leakage of any liquid, including fuel, coolant, lubrication or hydraulic fluid, under any operating condition, except as allowed herein.

c. Structural failure of any component, including permanent deformation, or evidence of impeding failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

d. Evidence of excessive wear.

e. Interference between the sweeper components or between the sweeper and the ground with the exception of normal contact by the tires and broom.

f. Misalignment of components.

g. Evidence of undesirable roadability characteristics, including instability in handling during cornering and braking.

h. Conditions which present a safety hazard to personnel during operation, service or maintenance.

i. Overheating of the engine or any other sweeper component.

4.4 First article testing.

4.4.1 First article test sample. The sample shall be identical to the items procured under the terms of the contract. Approval of the first article sample shall not constitute a waiver by the Government of its rights under the provisions of the contract. Unless otherwise specified (see 6.2), a single first article test sample shall be furnished and tested according to 4.4.2.1. When specified, two first article samples shall be produced and tested as follows:

a. Contractor Test Sample (see 4.4.2.1).

b. Operational Test Sample (see 4.4.2.2).

4.4.2 First article tests.

4.4.2.1 Contractor test sample. The contractor test sample shall be subjected to the tests described in 4.6.1 through 4.6.8.

4.4.2.2 Operational test sample. The operational test sample shall be subjected to the tests in 4.6.1, 4.6.2, and 4.6.9. The tests described in 4.6.1 and 4.6.2 shall be completed prior to the test described in 4.6.9.

4.4.3 Test report. Upon completion of the first article tests, a first article test report shall be prepared in accordance with MIL-STD-831. An authorized Government representative shall countersign all data sheets and the report. The following shall be incorporated as a part of the test report:

a. All failures, maintenance performed and other events recorded shall be identified by accumulated operation time, miles, cycles or position of the test procedure, as appropriate. Test conditions at the time of failures or irregular operations identified shall be recorded.

b. Summary of the engineering reasoning and of any tests conducted to determine assignable causes for all failures and irregular operations identified.

c. Summary of the engineering reasoning behind any corrections made, to be made or proposed to be made, and the predicted effectiveness of those corrections.

d. Test activity and/or contractor comments on item features or requirements, that if modified, should improve the item.

e. Test activity and/or contractor comments on field conditions or operating procedures to be avoided or cultivated to increase the reliability and useful life of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

f. Plan for testing production units.

4.5 Acceptance testing. Acceptance testing shall be classified as follows:

a. Individual Testing (see 4.5.1).

b. Random Sample Testing (see 4.5.2).

4.5.1 Individual testing. Each sweeper shall be subjected to the tests specified in 4.6.1 and 4.6.2.

4.5.2 Random sample testing. Any production sweeper may be selected by the procuring activity at any time to be subjected to the tests describe in 4.6.3.1, 4.6.3.2 and 4.6.4.1. Upon completion of the random sample testing, the contractor shall prepare a test report in accordance with MIL-STD-831. An authorized Government representative shall countersign all data sheets and the report.

4.5.2.1 Rejection and retest. When a sweeper fails to meet the requirements of this specification, sweepers to be delivered pursuant to the contract may not be accepted until the cause of the failure is determined, corrective action is taken by the contractor and the component that failed is successfully retested to assure compliance with this specification. Tests not involving the failed component may be continued pending the investigation of the test failure.

4.6 Test methods.

4.6.1 Examination of product. The sweeper shall be inspected to determine compliance with the requirements specified herein. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and their application, welding and riveting, and markings. For the first article and random sample sweepers, this examination shall be accomplished by use of a checklist which lists each requirement, of section 3 of this specification, not validated by a test and the results of the examination.

4.6.2 Preliminary operation. The sweeping unit shall be subjected to a run-in test in accordance with the manufacturer's recommendations. The duration of the test shall be sufficient to ensure that all components and assemblies operate as intended.

4.6.3 Mobility tests.

4.6.3.1 Road test. The sweeper, with the broom and blower nozzle(s) in the raised position, shall be towed at speeds up to 50 mph over improved roads and/or runways not less than 250 miles without damage.

4.6.3.2 Endurance test. The sweeper shall be towed in a sweeping position (i.e. both broom and blower operating) for a minimum of 100 hours. The sweeping pattern shall be set at the manufacturer's recommended maximum. During this test only refueling and adjustment of the sweeping pattern to compensate for wear shall be permitted. At least 75 percent of the total test time shall be for periods of not less than 4 hours continuous operation at an average forward speed of not less than 25 mph.

4.6.3.3 Service brake tests. The prime mover-sweeper combination shall be tested in accordance with SAE J786 to demonstrate compliance with 3.2.1.e.

4.6.3.4 Parking brake tests. The sweeper shall be tested in accordance with SAE J360 to demonstrate compliance with 3.2.1.f.

4.6.4 Capacity testing.

Source: https://assist.dla.mil -- Downloaded: 202640-20T11:04Z
Check the source to verify that this is the current version before use.

4.6.4.1 Sweeping test. The sweeper shall make at least 2 passes in snow having an average depth of 2 inches and average density of 5 pounds per cubic foot. The depth may be proportionately reduced for higher density snow. The sweeper shall clear a path not less than 1500 feet in length. Snow depth and density shall be determined in at least 5 intermediate locations and average values calculated. The time of each pass shall be measured with a stop watch and the length and width of each pass measured. From this information the snow removal rate shall be calculated to determine conformance to 3.2.1.a. The broom shall be angled 40 degrees right on one pass and 40 degrees left on the other. The sweeping pattern shall not be set larger than the manufacturer's recommended maximum setting.

4.6.4.2 Alternate sweeping test. In lieu of testing the sweeper in snow, as described in 4.6.4.1, the sweeping performance may be tested utilizing sand. If this method is used, the sweeper shall make 2 passes not less than 250 feet in length by 10.5 feet in width. The sand shall be spread over the test area at an average density of 0.83 pounds per square foot. The broom shall be angled 40 degrees right on one pass and 40 degrees left on the other. The sweeper shall remove not less than 90 percent of the sand while sweeping at an average speed of not less than 20 miles per hour. The sweeping pattern shall not be set larger than the manufacturer's recommended maximum setting.

4.6.4.3 Air system test. The air blower system shall be tested to verify conformance to 3.3.5.1. The air volume and velocity shall be measured at the opening of the discharge nozzle(s).

4.6.5 Design verification.

4.6.5.1 Weight and towing. The weight on each wheel of each axle shall be weighed to demonstrate compliance with 3.1.5.

4.6.5.2 Electromagnetic interference measurement. The sweeper and all electrical components shall be tested in accordance with MIL-STD-462 to demonstrate compliance with 3.1.6.

4.6.5.3 Sound level testing. The sweeper shall be tested in accordance with SAE J1077 to demonstrate compliance with 3.1.7.1.

4.6.6 Environmental tests.

4.6.6.1 Low temperature storage and operation. The complete sweeper including all accessories, shall be tested in accordance with Test Method 502.1, Procedures I and II, of MIL-STD-810 to demonstrate compliance to 3.1.4.a. Temperature sensor locations shall be approved by the procuring activity. Operational checkouts shall be performed in accordance with paragraph 4.6.6.2. Engine starting aids may be used (see 3.3.1.3). "Standard ambient" and "controlled ambient" shall be defined as the ambient condition of the test site. For Procedure I, the sweeper shall be exposed to the minimum required cold storage temperature of 3.1.4.a in a steady-state condition for 24 hours. For Procedure II, the sweeper shall be exposed to the minimum required cold operational temperature 3.1.4.a in a steady-state condition.

4.6.6.2 Operational checkout. All controls, levers and mechanisms shall be actuated a sufficient number of times to ensure consistency of operation and to determine whether the test exposure produced system degradation. These actions are to result in the operation of the following systems, but will not be limited to:

a. Engine starting, operation and accessories.

b. Lift mechanisms, all attitudes.

c. Pumps; auxiliary pumps.

d. Lights.

Source: https://assist.dla.mil -- Downloaded: 202640-20T11:04Z
Check the source to verify that this is the currentversion before use.

e. Brakes, stationary (i.e. service, parking and emergency).

f. Hydraulic hoses/electrical lines/connectors.

g. Equipment/compartment covers/doors.

h. Miscellaneous equipment.

4.6.7 Lifting and tiedown attachment test. When required, the lifting and tiedown attachments shall be tested to demonstrate compliance with 3.1.8.

4.6.8 Maintainability demonstration. Compliance with the maintenance downtime requirements shall be demonstrated by task performance. All daily scheduled maintenance tasks and all tasks listed in 3.1.3.2 shall be performed.

4.6.9 Omitted.

4.7 Refurbishment. After successful completion of all required testing, each sweeper shall be restored to like new condition. This restoration shall consist of touch up of the exterior finish or repainting as necessary, replacement of broom fillers, and servicing of all components (i.e. engine, hydraulic system, clutches, bearings, etc.) in accordance with the manufacturer's maintenance schedule for the amount of operational time accumulated during testing. The sweeper(s) used during testing shall be warranted the same as all other units delivered on contract.

5. PREPARATION FOR DELIVERY.

5.1 Preparation for delivery shall be in accordance with the instructions of the procuring activity.

6. NOTES.

6.1 Intended use. The sweeper described by this specification is intended for use in the removal of new fallen snow, ice or slush from runways, taxiways, ramps and other airfield paved areas.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. If lifting and tiedown attachments are required (see 3.1.8).

c. Finish color required, if not Forest Green, Color Number 24052 of FED-STD-595 (see 3.5.2.1).

d. Rustproofing, if other than the manufacturer's standard commercial practice, is required (see 3.5.3).

e. If identification markings other than in accordance with MIL-STD-1223 are required (see 3.6.1).

f. If two first article test samples are required (see 4.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.

6.3 Definitions.

6.3.1 Commercial. A manufacturer's standard product, practice, or process, having been marketed, in production and sold in substantial quantities to the general public for a minimum of one year prior to the date of invitation for bid or request for proposal. An item is "sold in substantial quantities" only when the quantities regularly sold are sufficient to constitute a real commercial market. Nominal quantities, such as models, samples, prototypes or experimental units, do not meet this requirement. The "general public" is a significant number of buyers other than the Government or affiliates of the offeror; the item involved must not be for Government end use. For the purpose of this specification, items acquired for "Government end use" include items acquired for foreign military sales.

6.4 Subject term (Key Word) listing.

Air Blast
Rotary
Snow plow
Towed

Custodian:

Air Force - 99

Preparing Activity:

Air Force - 84

Project No: 3825-F182

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:04Z
Check the source to verify that this is the current version before use.